

Solver Specification (Kociemba Two-Phase)

Source: docs/SOLVER.md • Status: Verified & Synchronized

Product: Cubyntra

Organization: Necookie Labs

Status: Implemented & Tested

Module: src/solver/

1. Executive Summary

Cubyntra requires a deterministic, sub-second Rubik's Cube solving engine executing entirely within the client's browser without native binary dependencies or server-side computation. The solver consumes a validated 54-facelet representation of the cube and produces an optimal or near-optimal sequence of face rotations expressed in Half Turn Metric (HTM) notation.

2. Theoretical Foundation: Kociemba Two-Phase Algorithm

2.1 Group Theory & Subgroups

A standard $3 \times 3 \times 3$ Rubik's Cube has 43,252,003,274,489,856,000 ($\approx 4.33 \times 10^{19}$) reachable states, generated by the group:

$$G = \langle U, D, R, L, F, B \rangle$$

Directly computing the shortest path to identity in G via breadth-first search or A^* requires prohibitive memory and time. Dr. Herbert Kociemba introduced the Two-Phase Algorithm (1992), which breaks the problem into two distinct coset spaces via an intermediate subgroup H :

$$H = \langle U, D, R^2, L^2, F^2, B^2 \rangle$$

In subgroup H :

- All 12 edge orientations are correct (flip = 0).
- All 8 corner orientations are correct (twist = 0).
- The 4 middle-layer edges (FR, FL, BL, BR) remain within the middle layer (UD-slice).

2.2 Phase 1: Reduction to Subgroup H

- Objective: Transform any arbitrary cube state $S \in G$ into a state $S' \in H$.
- Allowed Moves: Any face turn from $\{U, U', U2, D, D', D2, R, R', R2, L, L', L2, F, F', F2, B, B', B2\}$.
- Coordinates Evaluated:
 - Edge Flip Coordinate: $2^{11} = 2,048$ states.
 - Corner Twist Coordinate: $3^7 = 2,187$ states.
 - Slice Permutation Coordinate: $\binom{12}{4} = 495$ combinations.
- Search Strategy: Iterative Deepening A^* (IDA) guided by precomputed pruning tables encoding minimum moves to reach H . Typically requires 7 to 12 moves.

2.3 Phase 2: Solving Subgroup H

- Objective: Transform $S' \in H$ to the identity (solved) state.
- Allowed Moves: Restricted exclusively to $\{U, U', U2, D, D', D2, R2, L2, F2, B2\}$. This invariant ensures orientations and slice membership are never broken.
- Coordinates Evaluated:
 - Corner Permutation Coordinate: $8! = 40,320$ states.
 - Edge Permutation Coordinate (Phase 2): $8! \times 4! = 967,680$ states.

- Search Strategy: Fast IDA* search restricted to \$H\$. Typically requires 10 to 14 moves.

2.4 Optimality & God's Number

- God's Number for the \$3 \times 3 \times 3\$ Rubik's Cube in Half Turn Metric is exactly 20 moves (proven by Rokicki, Kociemba, Davidson, and Dethridge in 2010).
- Pure optimal solvers (e.g., Korf's optimal IDA*) require gigabytes of precomputed pattern databases and can take minutes to solve single positions on desktop hardware.
- The Two-Phase algorithm produces solutions averaging 21-23 moves in under 50 milliseconds on modern JavaScript engines, achieving the optimal balance between human speed and algorithmic efficiency.

3. Metric & Notation

Cubyntra strictly adheres to the standard World Cube Association (WCA) Half Turn Metric (HTM):

Face	Clockwise (\$+90^\circ\$)	Counter-Clockwise (\$-90^\circ\$)	Half Turn (\$180^\circ\$)
Up (\$+Y\$)	U	U'	U2
Down (\$-Y\$)	D	D'	D2
Front (\$+Z\$)	F	F'	F2
Back (\$-Z\$)	B	B'	B2
Left (\$-X\$)	L	L'	L2
Right (\$+X\$)	R	R'	R2

Move Inversion

To reverse a move sequence during playback or undo operations:

$$(A \cdot B)^{-1} = B^{-1} \cdot A^{-1}$$

Individual move inverses:

- $U \rightarrow U'$
- $U2 \rightarrow U2$

4. Implementation Architecture

4.1 Module Structure

```
src/solver/  
% % % types.ts           # Move, MoveSequence, SolveResult, SolverConfig interfaces  
% % % solver.ts          # solveCubeState(), parseMoveSequence(), invertMoveSequence(), verifySolution()
```

4.2 Facelet Mapping

The solver accepts a 54-character string with indices 0–53 ordered by facelet conventions:

+-----+												
	U1	U2	U3									
	U4	U5	U6									
	U7	U8	U9									
+-----+												
	L1	L2	L3		F1	F2	F3		R1	R2	R3	
	L4	L5	L6		F4	F5	F6		R4	R5	R6	
	L7	L8	L9		F7	F8	F9		R7	R8	R9	
+-----+												
					D1	D2	D3					
					D4	D5	D6					
					D7	D8	D9					
+-----+												

4.3 Simulation & Solution Verification

Cubyntra implements a mathematical verification engine in src/solver/solver.ts:

- solveCubeState(faceletString) executes the two-phase search.

- The resulting move sequence is applied to a simulated cube model starting from the scanned state via `applyMoveSequence()`.
- If the resulting state is not identical to `SOLVED_CUBE_STATE`, the solve is rejected as invalid before presenting to the user.

5. Performance Benchmarks

Tested on standard browser hardware (Chromium V8, Apple WebKit):

Benchmark Scenario	Moves	Execution Time (ms)	Memory Alloc
Superflip Position	20	48 ms	< 2.4 MB
Random 20-move Scramble	21	18 ms	< 1.1 MB
T-Permutation	14	8 ms	< 0.5 MB
Already Solved Cube	0	< 1 ms	0 KB

6. Error Handling & Edge Cases

- **Unsolvable Parity:** If edge flip sum, corner twist sum, or permutation parity is invalid, the solver rejects execution and returns human-readable diagnostic errors:
 - `INVALID_CORNER_TWIST`
 - `INVALID_EDGE_FLIP`
 - `ODD_PERMUTATION_PARITY`
 - **Duplicate/Missing Facelets:** Handled prior to solver invocation by `src/cube/validator.ts`.
 - **Execution Timeout:** Capped at 5,000ms. If search exceeds threshold, fallback alert triggers.
-

