

StockNetwork API

Integration Reference

Consolidated from API v1 and v2 documentation
Document Version: 1.0 | June 2026

Document Changelog

Version	Date	Author	Description
1.0	June 2026	Consolidated	Initial consolidated reference. Merges StockNetwork API v1 (doc v0.10) and v2 into a single flow-based document. Full professional rewrite.
—	2023-05-31	Jeffrey Hiscox	v1 doc v0.10 — Added ResortTypeID to search and booking request objects
—	2023-03-01	Jeffrey Hiscox	v1 doc v0.9 — Added MealPlan rates to AdditionalInfo response
—	2023-02-06	Jeffrey Hiscox	v1 doc v0.8 — Added ChildAges and MealPlanRateId to booking request
—	2023-02-04	Jeffrey Hiscox	v1 doc v0.7 — Additional information requirements for external stock sources
—	2023-02-03	Jeffrey Hiscox	v1 doc v0.6 — JSON notation fixes
—	2023-01-18	Jeffrey Hiscox	v1 doc v0.5 — Reservation return objects (success and error responses)
—	2022-12-22	Jeffrey Hiscox	v1 doc v0.4 — Fetch member/voucher by code
—	2022-12-07	Jeffrey Hiscox	v1 doc v0.3 — Initial search filter calls
—	2022-10-01	Jeffrey Hiscox	v1 doc v0.2 — Separated voucher/member import calls
—	2022-09-10	Jeffrey Hiscox	v1 doc v0.1 — First draft: authentication, voucher and member imports

Table of Contents

- 1. Overview
 - 1.1 API Versions
 - 1.2 Integration Flow
 - 1.3 Required HTTP Headers

1.4 Sandbox Environment

2. Authentication

2.1 Obtain an Access Token

2.2 Using the Token

3. Search Filter Options

3.1 Request

3.2 Response

4. Search for Available Stock

4.1 Request

4.2 Response

5. Additional Information

5.1 Request

5.2 Response

6. Book Stock

6.1 Request

6.2 Response

7. Members and Vouchers

7.1 Validate a Member

7.2 Validate a Voucher

7.3 Upload Members

7.4 Upload Vouchers

8. Reference

8.1 Response Status

8.2 Reservation Status

8.3 Membership Type

8.4 Bank Name

8.5 Bank Account Type

8.6 Contact

1. Overview

The StockNetwork API enables third-party platforms to search for available accommodation stock, retrieve pricing and availability, and make reservations on behalf of customers. The API follows RESTful conventions and uses JSON for all request and response payloads.

1.1 API Versions

Two API versions are in active use. They share the same authentication mechanism and can be used together within a single integration.

Version	Base URL	Purpose
v1	https://api.stocknetwo	Authentication, additional info, booking, member/voucher management

Version	Base URL	Purpose
	rk.co.za/api/1.0/	
v2	https://api.stocknetwork.co.za/api/2/	Search and availability (supersedes v1 search)

Note: All requests must use HTTPS. HTTP is not supported in production.

1.2 Integration Flow

A complete integration follows this sequence:

- Authenticate and obtain a Bearer token (once, valid for 30 days).
- Retrieve search filter options (regions, amenities, unit sizes) to populate your UI.
- Search for available stock using date range and filter criteria.
- For any unit where `requiresAdditionalInformation` is `true`, call the Additional Information endpoint before booking.
- Submit a booking request with the selected unit(s) and customer details.
- Optionally validate member or voucher codes before or during booking.

1.3 Required HTTP Headers

All requests must include the following headers:

Header	Value
Content-Type	application/json
Accept	application/json
Authorization	Bearer {access_token} (required on authenticated endpoints)

1.4 Sandbox Environment

The sandbox base URL is `https://testapi.stocknetwork.co.za`. Use this environment for development and testing. Request sandbox credentials by emailing `onboarding@stocknetwork.co.za` with your company name, contact person details, and reason for access.

2. Authentication

The StockNetwork API uses Bearer token authentication. You must obtain an access token before making any authenticated requests. Tokens are valid for 30 days and must be stored securely — treat them as passwords.

2.1 Obtain an Access Token

POST <https://api.stocknetwork.co.za/api/1.0/token>

Send the following JSON body:

```
{
  "username": "your_username",
  "clientId": "your-client-id-guid",
  "clientSecret": "your-client-secret-guid"
}
```

Request Parameters

Parameter	Type	Required	Description
username	string(20)	Yes	Your integration's unique username
clientId	string(36)	Yes	Your integration's client ID (UUID)
clientSecret	string(36)	Yes	Your integration's client secret (UUID)

Success Response — HTTP 201

```
{
  "accessToken": "eyJhbGciOi...",
  "expiryDt": 1234567890,
  "clientId": "your-client-id-guid",
  "siteId": "site-uuid",
  "site": 4851
}
```

Field	Type	Description
accessToken	string	JWT bearer token — include in all subsequent requests
expiryDt	int64 (Unix)	Timestamp when the token expires (30 days from issue)
clientId	string(36)	Your client ID, echoed back for confirmation
siteId	string(36)	The unique site UUID your credentials are scoped to
site	int	Human-readable site number (used in stock source references)

Error Response — HTTP 401

Returned when credentials are missing, invalid, or the username is incorrect.

```
{
  "error_message": "Invalid credentials"
}
```

2.2 Using the Token

Include the token as a Bearer token in the Authorization header of every authenticated request:

```
Authorization: Bearer eyJhbGciOiJIUzUxMiIsInR5cCI6IkpXVCJ9...
```

⚠ Warning: Tokens may be revoked by StockNetwork at any time. Implement token refresh logic to re-authenticate when a 401 is received on a previously valid token. Never expose tokens in client-side code or logs.

3. Search Filter Options

GET <https://api.stocknetwork.co.za/api/1.0/search/options>

Retrieve the available filter options for your site — regions, amenities, activities, experiences, unit sizes, and resort types. Use this data to populate search UI filters before submitting a search request.

Note: Fetch this data on application startup. Do not cache it long-term as filter options may change (new regions, new amenities, etc.).

3.1 Request

No request body or query parameters are required. The API identifies your site from the Authorization header.

3.2 Response

Field	Type	Description
siteId	string(36)	Your site's unique UUID
siteCode	int	Your site's human-readable numeric ID
countries	Country[]	Countries and their nested regions accessible to your site
amenities	Amenity[]	Amenities found across resorts your site has access to
experiences	Amenity[]	Experiences available at accessible resorts
activities	Amenity[]	Activities available at accessible resorts
unitSizes	UnitSize[]	Available unit/room size options
resortTypes	SystemType[]	Available resort type classifications

Country

Field	Type	Description
name	string(100)	Country name

Field	Type	Description
regions	Region[]	Regions within this country

Region

Field	Type	Description
regionId	string(36)	Unique region UUID
name	string(100)	Region name
country	string(100)	Parent country name
countryId	string(36)	Parent country UUID
isRciRegion	bool	Whether stock in this region comes from RCI
regionCode	string(3)	Short region code (e.g. CE for Cape Eastern)

Amenity / Experience / Activity

Field	Type	Description
amenityTypeId	string(36)	Unique amenity UUID — use this in search requests
name	string(100)	Display name
description	string(500)	Optional description
groupId	string(36)	UUID of the group this amenity belongs to

UnitSize

Field	Type	Description
unitSizeId	string(36)	Unique unit size UUID — use this in search requests
name	string	Display name (e.g. 2 Sleeper, 4 Sleeper)
description	string(500)	Optional description

SystemType (Resort Type)

Field	Type	Description
systemTypeId	string(36)	Unique resort type UUID
name	string	Display name (e.g. Guest House, Hotel)
description	string(500)	Optional description

4. Search for Available Stock

POST <https://api.stocknetwork.co.za/api/2.0/search>

Searches for available accommodation matching the supplied criteria. Returns a paginated list of resorts with unit types, rates, and availability details. This is the v2 search endpoint and supersedes the v1 search endpoint for all new integrations.

4.1 Request

Query Parameters (Pagination)

Parameter	Type	Description
Offset	int	Zero-based pagination offset
Limit	int	Number of records to return per page
Date_From	datetime	Optional date filter — lower bound
Date_To	datetime	Optional date filter — upper bound
OrderBy	string	Field name to sort results by
Filter	string	Custom filter expression

Request Body

Field	Type	Required	Description
searchRequestId	UUID	Yes	Caller-generated UUID for this search session. Must be the same UUID on all paging calls for this search. If omitted on paged requests, nothing is returned.
checkInDate	datetime	Yes	Requested check-in date
checkOutDate	datetime	Yes	Requested check-out date
searchText	string(100)	No	Free-text search against resort name, area, city, or district
region	Region	No	Region to restrict search to (see Section 3 for Region object)
amenities	Amenity[]	No	Filter by amenities (use amenityTypeId values from Section 3)
activities	Amenity[]	No	Filter by activities
experiences	Amenity[]	No	Filter by experiences
unitSizes	UnitSize[]	No	Filter by unit sizes (use unitSizeId values from Section 3)
pricing	PriceDTO	No	Min/max price range filter
geocoordinates	GeoCoordinateDTO	No	Latitude/longitude radius filter (reserved for future use)

PriceDTO

Field	Type	Description
minPrice	decimal	Minimum price. Default: 0

Field	Type	Description
maxPrice	decimal	Maximum price. Default: 1,000,000

Example Request Body

```
{
  "searchRequestId": "3fa85f64-5717-4562-b3fc-2c963f66afa6",
  "checkInDate": "2026-08-01T00:00:00.000Z",
  "checkOutDate": "2026-08-04T00:00:00.000Z",
  "searchText": "Brooklyn Pretoria",
  "region": null,
  "amenities": null,
  "unitSizes": null,
  "pricing": {
    "minPrice": 0,
    "maxPrice": 5000
  }
}
```

4.2 Response

Field	Type	Description
searchRequestId	string(36)	Echoed back — use for subsequent paging calls
stockAvailability	Resort[]	List of matching resorts with unit types and rates
pageNumber	int	Current page number
totalPages	int	Total number of pages available
pageSize	int	Records per page
totalRowCount	int	Total matching results
checkInDate	datetime	Check-in date from the request, echoed back
checkOutDate	datetime	Check-out date from the request, echoed back
referenceUrl	string	A URL representing this search that can be bookmarked or reused
isSuccess	bool	Whether the request succeeded
error	Error	Error code and message if isSuccess is false

Resort Object

Field	Type	Description
resortId	string(36)	Unique resort UUID
name	string	Resort name
description	string	Resort description
location	string	Human-readable location (e.g. Brooklyn, Pretoria, Gauteng)
area	string	Area/province
resortCode	string(10)	Short resort code
resortType	string	Resort type classification (e.g. Guest House, Hotel)
currency	string	Currency code (e.g. ZAR)

Field	Type	Description
cheapestRate	decimal	Lowest available rate across all unit types
latitude	float	Resort latitude
longitude	float	Resort longitude
imageLinks	ImageLink[]	Resort images
amenities	Amenity[]	Amenities available at this resort
experiences	Amenity[]	Experiences available
activities	Amenity[]	Activities available
unitTypes	UnitType[]	Available room/unit types with rates
referenceUrl	string	Direct URL to this resort's availability
resortInfoUrl	string	URL to the resort information page

UnitType Object

Field	Type	Description
resortUnitTypeid	string(36)	Unique unit type UUID
name	string	Unit type name (e.g. Deluxe Inside Room)
description	string	Unit description
code	string	Unit code
sleeper	string	Sleeper capacity description (e.g. 2 Sleeper)
unitSize	string	Unit size label
unitSizeTypeid	string(36)	UUID of the unit size type
roomCount	int	Number of this room type at the resort
unitsAvailable	int	Number of units currently available
rate	Rate	Pricing details for this unit type
checkInDate	datetime	Check-in date for this availability
checkOutDate	datetime	Check-out date for this availability
nights	int	Number of nights
requiresAdditionalInformation	bool	If true, call Section 5 before booking this unit
source	string	Stock source identifier
url	string	Direct URL for this unit type

Rate Object

Field	Type	Description
uniqueId	string(36)	Rate UUID — required when booking this unit
rate	decimal	Selling price for this unit and stay
normalRate	decimal	Standard rack rate (before any discount)
currency	string	Currency code
currencySymbol	string	Currency symbol (e.g. R)

Field	Type	Description
maximumDiscountAllowed	decimal	Maximum discount permitted on this rate

□ **Note:** When `requiresAdditionalInformation` is true on a unit type, you must call the Additional Information endpoint (Section 5) before submitting a booking for that unit. Failure to do so will result in a booking failure.

5. Additional Information

POST <https://api.stocknetwork.co.za/api/1.0/request/additionalinformation>

Some unit types are sourced from external providers who impose specific requirements or restrictions. When a unit type has `requiresAdditionalInformation: true` in the search response, this endpoint must be called before submitting a booking for that unit.

⚠ **Warning:** Repeated booking failures caused by not calling this endpoint may result in suspension of API access.

5.1 Request

Field	Type	Required	Description
resortId	string(36)	Yes	Resort UUID from the search response
roomId	string(36)	Yes	Unit type UUID (resortUnitTypeId from search response)
checkInDate	datetime	Yes	Check-in date
checkOutDate	datetime	Yes	Check-out date

Example Request

```
{
  "resortId": "1e872343-1720-4211-90d0-a77c864176de",
  "roomId": "a9865f4d-890b-4278-b009-aeefe32746621",
  "checkInDate": "2026-08-01T00:00:00",
  "checkOutDate": "2026-08-04T00:00:00"
}
```

5.2 Response

Field	Type	Description
reservationCanContinue	bool	Whether the booking can proceed. Check this before continuing.
maxOccupancy	int	Maximum total occupants (adults + children)

Field	Type	Description
maxAdults	int	Maximum number of adults
minLOS	int	Minimum length of stay in nights (defaults to 1)
childPolicy	ChildPolicy	Child age restrictions for this unit
cancellationPolicy	CancellationPolicy	Cancellation terms for this unit
mealPlans	MealPlan[]	Available meal plan options, if any
errorMessage	string(200)	Reason booking cannot proceed, if reservationCanContinue is false

ChildPolicy

Field	Type	Description
childrenAllowed	bool	Whether children are permitted at this resort/unit
child1AgeLimit	string(50)	Lower age bracket (e.g. 0–12)
child1AgeLimitAllowed	bool	Whether children in the child1 age range are allowed
child2AgeLimit	string(50)	Upper age bracket (e.g. 13–18)
child2AgeLimitAllowed	bool	Whether children in the child2 age range are allowed

Occupancy Validation Rules

Your application must enforce these checks before submitting a booking:

- Total adults + children must not exceed maxOccupancy.
- Number of adults must not exceed maxAdults.
- If `childrenAllowed` is false, no children may be included in the booking.
- If `child1AgeLimitAllowed` is false, no children within the child1 age range are allowed.
- If `child2AgeLimitAllowed` is false, no children within the child2 age range are allowed.
- If `child1AgeLimitAllowed` is true, children must fall within the child1 age range.
- The stay duration must be equal to or greater than minLOS.

MealPlan

Field	Type	Description
mealPlanRateId	string(36)	Meal plan UUID — pass this in the booking request if selected
description	string	Description of the meal plan
isDefaultMealPlan	bool	Whether this is the resort's default meal plan for this unit
hasAdditionalCharge	bool	Whether selecting this plan incurs an extra charge
additionalCharge	decimal	Additional cost if hasAdditionalCharge is true (defaults to 0)

□ **Note:** Always display meal plan options and any additional charges to the customer before they confirm the booking. StockNetwork will automatically add the additional meal plan rate to the reservation total when a mealRatePlanId is submitted.

CancellationPolicy

Field	Type	Description
description	string(1000)	Full cancellation policy text for this unit at this resort

6. Book Stock

POST <https://api.stocknetwork.co.za/api/1.0/request>

Submits a reservation request for one or more units. StockNetwork will attempt to book each line item. If stock is no longer available for any item, that item is returned in the errorItems array with a reason, while any successfully booked items are returned in successfullItems.

6.1 Request

Top-Level Fields

Field	Type	Required	Description
fullName	string(100)	Yes	Customer's full name
emailAddress	string(100)	Yes	Customer's email address
cellphone	string(20)	Yes	Customer's cellphone number (include country code, e.g. +27)
currency	string	Yes	Currency code (e.g. ZAR)
currencySymbol	string(3)	Yes	Currency symbol (e.g. R)
amountIncl	decimal	Yes	Total amount for all items — informational; StockNetwork calculates its own total
items	StayItem[]	Yes	One or more units to reserve
personId	string(36)	No	Existing customer UUID, if known
customerReferenceNo	string(36)	No	Your own reference number for this booking
notes	string(500)	No	Additional notes from the customer
membershipNo	string(20)	No	Member or voucher code, if applicable
preferredContactMethod	string	No	Email (default) or other contact preference
discount	decimal	No	Total discount amount — informational only
isRequestAndPay	bool	No	True if the customer is paying immediately. Determined by hidePayForReservation in search response. Defaults to false.
deleteCustomerInfoAfterCheckout	bool	No	If true, customer personal data is deleted after checkout. Defaults to false.

StayItem

Field	Type	Required	Description
uniqueStockId	string(36)	Yes	The rate uniqueId from the search response UnitType.rate.uniqueId
reservationRateId	string(36)	Yes	The rate UUID from the search response
resortName	string(100)	Yes	Resort name
unitSize	string(100)	Yes	Unit size label
checkInDate	datetime	Yes	Check-in date
checkOutDate	datetime	Yes	Check-out date
numberOfNights	int	Yes	Number of nights
noOfUnits	int	Yes	Number of units to reserve
adultOccupancy	int	Yes	Number of adults
childOccupancy	int	Yes	Number of children (defaults to 0)
amountIncl	decimal	Yes	Unit rate × noOfUnits
source	string(100)	Yes	Source field from the search response UnitType.source
resortId	string(36)	No	Resort UUID
unitSizeTypeId	string(36)	No	Unit size type UUID
unitNameId	string(36)	No	Unit type UUID
unitName	string(100)	No	Unit type name
sharingStockSourceId	int	No	Site ID where this stock originated
mealRatePlanId	int	No	Meal plan ID from the Additional Information response, if a plan was selected
childAges	int[]	No	Age of each child — array length must equal childOccupancy

Example Request

```
{
  "amountIncl": 975.00,
  "fullName": "Jane Smith",
  "emailAddress": "jane@example.com",
  "cellphone": "+27831234567",
  "currency": "ZAR",
  "currencySymbol": "R",
  "isRequestAndPay": false,
  "items": [
    {
      "uniqueStockId": "8a05f230-4542-4a5e-a33f-f8791367de7f",
      "reservationRateId": "8a05f230-4542-4a5e-a33f-f8791367de7f",
      "resortId": "1e872343-1720-4211-90d0-a77c864176de",
      "resortName": "37 On Anderson",
      "unitSize": "2 Sleeper",
      "unitName": "Deluxe Inside Room",
      "checkInDate": "2026-08-01T00:00:00",
      "checkOutDate": "2026-08-04T00:00:00",
      "numberOfNights": 3,
      "noOfUnits": 1,
      "adultOccupancy": 2,
      "childOccupancy": 0,
      "amountIncl": 975.00,
      "source": "ManualStock - Site: 4851"
    }
  ]
}
```

```

    }
  ]
}
```

6.2 Response

Field	Type	Description
reservationId	string(36)	StockNetwork's unique reservation UUID
reservationRefNo	string(20)	Human-readable reference number
status	ResponseStatus	Endpoint result: Success, Error, or PartialSuccess
reservationStatus	ReservationStatus	Booking state: Request, Booked, Paid, Confirmed, Cancelled
totalAmountExcl	decimal	Total amount excluding VAT
vatAmount	decimal	VAT amount
totalAmountIncl	decimal	Total including VAT (before discount)
discountReceived	decimal	Discount applied
totalAmountInclAfterDiscount	decimal	Final total after discount — this is the true payable amount
amountPaid	decimal	Amount already paid
successfulItems	ReservationItem[]	Items that were successfully booked
errorItems	ReservationItem[]	Items that could not be booked, with reasons
paymentUrl	URI	URL to direct the customer to for payment
reservationInformationUrl	URI	URL for full reservation details and status
customerReference	string	Your reference, echoed back
siteId	string(36)	Site this reservation belongs to

ReservationItem

Field	Type	Description
id	string(36)	Unique ID for this reservation line
uniqueReference	string(20)	Human-readable reference for this line item
resortName	string	Resort name
unitName	string	Unit type name
unitSize	string	Unit size
checkInDate	datetime	Check-in date
checkOutDate	datetime	Check-out date
nights	int	Number of nights
noOfUnits	int	Units booked
maxOccupancy	int	Maximum occupancy for this unit
adultOccupancy	int	Adults booked

Field	Type	Description
childOccupancy	int	Children booked
totalAmountIncl	decimal	Total for this line item including VAT
minimumDepositRequired	decimal	Minimum deposit to confirm this booking
reservationRateId	string(36)	Rate reference for this booking
bookingAgentEmail	string	Email to contact the booking agent
bookingAgentPhone	string	Phone number for the booking agent
resortAgentEmail	string	Email to contact the resort directly
resortAgentPhone	string	Phone for the resort
resortInformationUrl	URI	Resort information page
resortImageUrl	URI	Default resort image
unitImageUrl	URI	Default unit image
errorReason	string(200)	If in errorItems, the reason this line could not be booked

7. Members and Vouchers

StockNetwork supports optional member and voucher validation. When your site is configured to require a membership or voucher code, the API will reject booking requests that do not supply a valid code. Use the endpoints in this section to validate codes before submitting bookings, and to import your own member and voucher lists.

7.1 Validate a Member

GET <https://api.stocknetwork.co.za/api/1.0/person/membership/{membershipNo}>

Validates whether a membership number is active and permitted to make reservations.

Response

Field	Type	Description
personid	string(36)	StockNetwork's unique person UUID
membershipnumber	string(36)	The membership number
fullname	string(100)	Member's full name
emailaddress	string(100)	Member's email address
cellphone	string(20)	Member's cellphone
isactive	bool	Whether the membership is active. If false, the code cannot be used.
membershiptype	MembershipType	Standard or Wealth
expirydt	string(30)	Expiry date of the membership, if applicable
username	string(100)	Member's login username

Field	Type	Description
referrermembershipcode	string(30)	Membership code of the referring member, if any
bankdetail	BankDetail	Member's banking details, if stored

7.2 Validate a Voucher

GET <https://api.stocknetwork.co.za/api/1.0/persondiscount/voucher/{voucherCode}>

Validates a voucher code. A previously redeemed voucher is still returned, but with an amount of 0 — this allows the customer to continue making reservations without a discount.

Response

Field	Type	Description
persondiscountid	string(36)	StockNetwork's unique voucher UUID
personid	string(36)	UUID of the person this voucher belongs to
code	string(50)	The voucher code
amount	decimal	Value of the voucher. Will be 0 if previously redeemed.
fullname	string(100)	Voucher holder's full name
emailaddress	string(100)	Voucher holder's email
cellphone	string(20)	Voucher holder's cellphone
isredeemedpreviously	bool	Whether this voucher has been used before
redeemdt	string	Date the voucher was redeemed, if applicable

7.3 Upload Members

POST <https://api.stocknetwork.co.za/api/1.0/persondiscount/member>

Bulk upload member records. The request body is a JSON array — even for a single member. If a member with the same membershipNumber already exists, their record will be updated.

Member Object

Field	Type	Required	Description
membershipNumber	string(36)	Yes	Unique member identifier. Existing records are updated on match.
fullName	string(100)	Yes	Member's full name
emailAddress	string(100)	Yes	Member's email address
cellphone	string(20)	Yes	Member's cellphone
isActive	bool	No	Whether the member is active. Defaults to true.

Field	Type	Required	Description
username	string(100)	No	Login username
password	string(50)	No	Login password
membershipType	Membership Type	No	Standard (default) or Wealth
expiryDt	datetime	No	Membership expiry date
referrerMembershipCode	string(100)	No	Membership code of the referrer
bankDetails	BankDetail	No	Member's bank account details

BankDetail

Field	Type	Description
bankName	BankName	Bank name enum (see Section 8.4)
accountName	string(100)	Account holder name
accountType	BankAccountType	Account type enum (see Section 8.5)
accountNumber	string(50)	Bank account number
branchCode	string(10)	Branch code

7.4 Upload Vouchers

POST <https://api.stocknetwork.co.za/api/1.0/persondiscount/voucher>

Bulk upload voucher codes. The request body is a JSON array. Voucher codes must be unique — duplicate codes will be rejected. Vouchers are single-use; a redeemed voucher can still be submitted but will apply a discount of zero.

Voucher Object

Field	Type	Required	Description
code	string(36)	Yes	Unique voucher code. Duplicates are rejected.
amount	decimal	Yes	Discount value. Use 0 for member-linked vouchers with no monetary value.
fullName	string(100)	Yes	Voucher holder's full name
emailAddress	string(100)	Yes	Voucher holder's email
cellphone	string(100)	Yes	Voucher holder's cellphone
isActive	bool	No	Whether the voucher is active. Defaults to true.

8. Reference

8.1 Response Status (ResponseStatus)

Value	Description
Success	All requested items were successfully booked
Error	All items failed — no bookings were made
PartialSuccess	At least one item was booked, but one or more failed
ReservationFound	Returned when a reservation lookup found no matching record
NoReservationLineItems	Booking rejected — no items were included in the request

8.2 Reservation Status (ReservationStatus)

Value	Description
Request	Reservation received and being processed
Booked	Stays confirmed at the resort(s)
Paid	Payment received (may be partial — check amountPaid)
Confirmed	Fully booked and fully paid
Cancelled	Reservation has been cancelled

8.3 Membership Type (MembershipType)

Value	Description
Standard	Standard membership tier
Wealth	Wealth/premium membership tier

8.4 Bank Name (BankName)

Valid values for the bankName field in BankDetail:

- ABSA
- AfricaBank
- BankZero
- BidvestBank
- CapitecBank
- DiscoveryBank
- FNB
- Investec

- Nedbank
- StandardBank
- TymeBank
- Chips
- NedbankCash

8.5 Bank Account Type (BankAccountType)

Value	Description
Cheque	Cheque account
Savings	Savings account
CreditCard	Credit card account
Current	Current account
Chips	Chips account
AccountBank	Bank account
Wallet	Digital wallet

8.6 Contact

For API support, email support@stocknetwork.co.za.

To request sandbox access, email onboarding@stocknetwork.co.za.