

SOFTWARE REQUIREMENTS SPECIFICATION

CyberShield

Multi-Modal Phishing Detection Platform

SRS Report

Version 2.0

Prepared for Academic Project Documentation

CyberShield analyzes suspicious URLs, SMS/email text, and screenshots to help users identify phishing attempts before they act.

Document Control

This Software Requirements Specification (SRS) defines the functional, quality, interface, data, security, and validation requirements for CyberShield. It is intended to guide design, development, testing, review, and future maintenance.

Table 1: Revision History

Version	Date	Owner	Description
1.0	Initial project phase	CyberShield Team	URL analysis requirements established.
2.0	Current revision	CyberShield Team	Adds SMS/email NLP analysis and screenshot phishing detection requirements.

Document Status

Baseline draft for implementation and academic review. Requirements marked mandatory are necessary for the proposed release; optional enhancements are planned only after the core workflow is stable.

Approval Roles

- Project guide: validates academic scope and documentation quality.
- Development team: confirms technical feasibility and estimates.
- Test reviewer: confirms that acceptance criteria are measurable.
- Product owner: accepts the requirements baseline and priorities.

Acknowledgement

The CyberShield team gratefully acknowledges the guidance of its project mentor, faculty members, peers, and families whose feedback and encouragement support this work. The project is shaped by the practical need to make phishing warnings understandable and available before a user clicks a link, replies to a message, or shares sensitive information.

The team also recognizes the security research community, standards bodies, and open-source contributors whose work in secure systems, natural-language processing, image analysis, and threat intelligence informs the proposed design.

Abstract

CyberShield is a multi-modal phishing detection platform. Its existing URL analysis capability is extended by two complementary services: text analysis for SMS and email content, and screenshot analysis for visual phishing indicators. The platform combines cybersecurity intelligence with natural-language processing (NLP) and image processing (IP) to provide a consistent, evidence-based risk assessment.

A user can submit a URL, paste a message, or upload a screenshot. CyberShield normalizes the input, performs modality-specific analysis, generates a risk score and explanations, preserves a privacy-aware audit record, and provides safe next actions. The proposed system is web-based, role-aware, scalable, and designed to minimize the risk of overconfident or harmful automated advice.

Table of Contents

1. Introduction	1
2. Overall Description	4
3. Specific Requirements	9
4. System Models	22
5. Verification and Acceptance	26
6. Deployment and Operations	28
7. Appendices and References	30

List of Tables

Table 1 Revision History; Table 2 User Classes; Table 3 Functional Requirements; Table 4 Non-functional Requirements; Table 5 Data Entities; Table 6 Traceability Matrix.

List of Figures

Figure 1 Platform Context; Figure 2 Processing Pipeline; Figure 3 Data Flow; Figure 4 Entity Relationship View; Figure 5 Sequence View.

1. Introduction

CyberShield addresses the growing variety of phishing channels. A link-only tool is useful but incomplete: attackers also rely on persuasive SMS messages, email bodies, and images that imitate legitimate brands. CyberShield unifies these signals into a single user-facing risk assessment while preserving the evidence needed for later review.

1.1 Purpose

The purpose of this SRS is to define what CyberShield must do, its boundaries, interfaces, data behavior, and quality attributes. It is written for developers, testers, project reviewers, and future maintainers.

1.2 Scope

The system shall allow a registered or guest user to analyze a URL, text message, email content, or screenshot. It shall identify suspicious indicators, assign a transparent risk level, give safety guidance, retain records according to policy, and support administrative oversight. It does not guarantee that every threat is detected or replace organizational incident response.

1.3 Goals

- Detect common phishing indicators across web, text, and image inputs.
- Explain findings in plain language without encouraging unsafe actions.
- Protect submitted content, especially personally identifiable information.
- Support continuous model and rule improvement using approved feedback.

1.4 Definitions, Acronyms, and Abbreviations

Phishing: a deceptive attempt to obtain credentials, money, or sensitive information. URL: a web address. NLP: computational processing of natural-language text. IP: image processing. OCR: optical character recognition. IOC: indicator of compromise. Risk score: a normalized estimate used to classify an input as low, medium, high, or critical risk.


1.5 References

- IEEE 830, recommended practice for software requirements specifications.
- OWASP guidance on phishing, secure application design, and logging.
- NIST SP 800-53 security and privacy controls; NIST guidance on incident response.
- Project references: EXPIROCHAIN report structure and supplied SRS Formatting Guide.

1.6 Document Overview

Section 2 describes the product context and users. Section 3 contains requirements for each analysis mode, interfaces, quality attributes, and data. Section 4 provides system models. The final sections define verification, operations, appendices, and references.

Figure 1: CyberShield Platform Context



2. Overall Description

2.1 Product Perspective

CyberShield is a web platform that coordinates a client interface, an application API, a URL intelligence service, an NLP service, an image/OCR service, a risk-scoring engine, and a protected data store. It can consume configurable reputation feeds and may later integrate an organization's security operations workflow.

The product is a new multi-modal layer rather than a browser replacement, mail gateway, or antivirus tool. It performs pre-action triage: it helps a user decide whether to avoid, verify, report, or safely continue.

2.2 Product Functions

- Submit and normalize URLs for lexical, DNS/reputation, redirect, and certificate-related checks.
- Extract semantic and structural phishing cues from pasted SMS and email content.
- Extract visible text and visual cues from screenshots using OCR and image analysis.
- Fuse modality signals into an explainable classification and record an audit trail.
- Present recommendations, feedback controls, administrative configuration, and reports.

2.3 User Classes

Table 2: User Classes and Access

Class	Description	Primary permissions
Guest user	Unregistered visitor	Submit limited analyses; view current result only.
Registered user	Individual account holder	Analyze, view history, submit feedback, manage privacy settings.
Analyst	Authorized security reviewer	Review flagged cases and feedback; annotate disposition.
Administrator	Platform operator	Manage users, policies, integrations, and model/rule releases.
Auditor	Read-only oversight role	View security-relevant logs and compliance reports.

2.4 Operating Environment

The client shall support current desktop and mobile versions of major browsers. The server shall run in a hardened cloud or institutional environment using HTTPS. Processing services may use containerized Python/ML workloads and a relational database; object storage may retain approved screenshot artifacts.

2.5 Design and Implementation Constraints

- All data in transit shall use TLS; insecure HTTP callbacks are prohibited.
- The UI shall never render a submitted URL as an automatically clickable link before warning the user.
- Analysis models must expose a version identifier with each result.
- Image size, file type, retention, and throughput shall be constrained to reduce abuse.

2.6 Assumptions and Dependencies

CyberShield assumes that users submit content they are authorized to inspect and that external reputation sources can be unavailable, stale, or incomplete. A network connection is required for intelligence lookups. OCR accuracy depends on screenshot resolution, language, compression, and visual complexity.

Dependencies include an authentication provider, URL/domain reputation feeds, an OCR engine, an NLP classifier or ruleset, secure object storage, database backups, and operational monitoring. A failed dependency shall degrade a result with a visible limitation instead of silently producing certainty.

2.7 Out of Scope

- Automatic clicking, visiting, or credential submission to suspicious websites.
- Forensic compromise confirmation on the user device.
- Blocking messages at a telecom carrier or enterprise email gateway.
- Legal adjudication or irreversible account actions based solely on a model score.

2.8 Business Rules

The system shall classify results as Low, Medium, High, or Critical. High and Critical results must display a prominent safety warning. A result can be “Inconclusive” when evidence is insufficient or a dependency is unavailable. Users may delete their history subject to legal and institutional retention requirements.

3. Specific Requirements

3.1 Requirement Conventions

Each mandatory requirement uses the form FR (functional requirement) or NFR (non-functional requirement). “Shall” indicates a required behavior. Priority labels are Must, Should, or Could. Acceptance statements are intentionally testable.

3.2 URL Analysis Requirements

FR-URL-01 (Must): The system shall accept a single URL as text and reject malformed, empty, or oversize input with a clear message.

FR-URL-02 (Must): The system shall normalize the URL, parse hostname and path components, and display the normalized value used for analysis.


FR-URL-03 (Must): The system shall evaluate lexical indicators including misleading subdomains, IP-address hosts, excessive length, encoded characters, suspicious keywords, and homoglyph risk.

FR-URL-04 (Must): The system shall query configured reputation and threat-intelligence sources without opening the target in the user’s browser.

FR-URL-05 (Should): The system shall assess redirect-chain evidence through a sandboxed service where approved by policy.

FR-URL-06 (Must): The result shall show risk level, confidence band, indicators, limitations, and safe next actions.

Figure 2: URL Processing Pipeline



3.3 SMS and Email Text Analysis Requirements

FR-TXT-01 (Must): The system shall accept pasted SMS text, email subject/body text, or structured email fields when available.

FR-TXT-02 (Must): The system shall remove or mask configured personally sensitive fields before persistent storage while preserving sufficient evidence for scoring.

FR-TXT-03 (Must): The NLP pipeline shall identify urgency, threats, reward promises, impersonation cues, credential/payment requests, suspicious links, and grammar or formatting anomalies.

FR-TXT-04 (Must): The system shall extract embedded URLs, phone numbers, email addresses, currency/payment references, and named brands when present.

FR-TXT-05 (Must): The system shall compare claimed sender identity with content claims and flag apparent brand impersonation when confidence exceeds the configured threshold.

FR-TXT-06 (Should): The system shall support English initially and return a limitation notice for unsupported or mixed-language input.

FR-TXT-07 (Must): The result shall quote only minimal, safely masked evidence snippets and shall not expose secrets detected in the submission.

3.4 Screenshot Phishing Detection Requirements

FR-IMG-01 (Must): The system shall accept PNG, JPEG, and WEBP screenshots within configured size and resolution limits.

FR-IMG-02 (Must): The system shall validate file signature and decode image pixels before analysis; files that fail validation shall be rejected.

FR-IMG-03 (Must): The image pipeline shall run OCR to obtain visible text and route that text through the same text-analysis service where applicable.

FR-IMG-04 (Must): The pipeline shall detect visual phishing signals including login forms, password/OTP prompts, payment prompts, brand-like logos, shortened/obscured links, QR codes, and urgency banners.

FR-IMG-05 (Should): The system shall compare extracted domain/brand clues with known legitimate domain patterns and identify likely lookalikes.

FR-IMG-06 (Must): The result shall identify which evidence originated from OCR, visual analysis, or linked text analysis, and shall state OCR confidence.

FR-IMG-07 (Must): The system shall strip executable metadata and never execute embedded content.

3.5 Cross-Modal Scoring and Results

FR-SCR-01 (Must): The scoring engine shall combine applicable indicators using configurable, versioned weights or an approved model.

FR-SCR-02 (Must): The engine shall avoid double-counting the same extracted URL or claim across modalities.

FR-SCR-03 (Must): Each result shall include a score from 0 to 100, risk label, confidence band, reasons, model/rule version, and analysis timestamp.

FR-SCR-04 (Must): A Critical result shall recommend that the user avoid interacting with the content, verify through an independently known channel, and report according to local policy.

FR-SCR-05 (Must): An Inconclusive result shall identify unavailable sources or low-quality evidence and recommend a safer verification path.

FR-SCR-06 (Should): An authorized analyst may override a classification with an explanation; overrides shall be immutable audit events.

Risk Interpretation

0-24 Low: no strong known indicators. 25-49 Medium: caution warranted. 50-74 High: likely suspicious. 75-100 Critical: strong indicators or known malicious evidence. Scores are decision support, not proof of fraud.

3.6 Account, History, and Feedback Requirements

FR-ACC-01 (Must): Registered users shall be able to create an account, sign in, sign out, reset credentials through the approved identity mechanism, and manage consent preferences.

FR-ACC-02 (Must): The system shall display analysis history only to its owner or an authorized role.

FR-ACC-03 (Must): A user shall be able to delete an individual history item or request deletion of eligible history records.

FR-FDB-01 (Must): Users shall be able to mark a result as helpful, unhelpful, suspected false positive, or suspected false negative.

FR-FDB-02 (Should): Feedback intended for learning shall be reviewed or de-identified before it is used to tune a model or rule.

FR-RPT-01 (Must): The system shall generate a shareable incident summary containing safe, masked indicators and no raw credentials.

FR-RPT-02 (Should): The system shall export authorized summaries in PDF or CSV format with an export audit event.

3.7 Administration and Governance Requirements

FR-ADM-01 (Must): Administrators shall manage user roles, retention periods, permitted file types, maximum file sizes, and enabled intelligence sources.

FR-ADM-02 (Must): Administrators shall manage scoring thresholds and model/rule releases through a change-controlled configuration process.

FR-ADM-03 (Must): The system shall preserve a versioned audit event for administrative changes, analyst overrides, exports, deletion actions, and sign-in failures.

FR-ADM-04 (Should): Administrators shall view aggregated metrics for volume, risk distribution, processing failures, feedback trend, and service latency.

FR-ADM-05 (Must): Only authorized administrators shall access raw retained screenshots, and all such access shall be logged.

FR-ADM-06 (Must): The administrative interface shall provide a health view that distinguishes service failure, rate limiting, model unavailability, and intelligence-feed degradation.

3.8 External Interface Requirements

User Interface

The interface shall offer clearly separated Analyze URL, Analyze Text, and Analyze Screenshot actions. Upload and submit buttons shall state what data will be processed. The result shall show a risk badge, an evidence list, limitations, and safe actions. Color shall not be the only way a risk level is conveyed.

Software Interfaces

The API shall expose authenticated endpoints for submission, result retrieval, history, feedback, and administration. It shall use JSON over HTTPS. External feeds shall be accessed through server-side adapters so credentials and provider-specific behavior are not exposed to clients.

Hardware Interfaces

No special client hardware is required. Camera capture is outside the baseline; users upload existing images. Servers may use CPU or approved GPU workers for OCR and image models.

Communications Interfaces

The service shall use HTTPS with modern TLS. SMTP is not required in the baseline. Notifications, if added, shall use a vetted provider and never include raw suspicious content in a notification preview.

3.9 Performance Requirements

NFR-PERF-01 (Must): For a typical URL or text submission, the system shall return an initial result within 5 seconds at the 95th percentile under the defined baseline load.

NFR-PERF-02 (Must): For a screenshot up to the configured maximum, the system shall return a result within 15 seconds at the 95th percentile, excluding a displayed external-feed timeout.

NFR-PERF-03 (Must): The system shall support at least 50 concurrent interactive analyses in the academic deployment baseline without data cross-contamination.

NFR-PERF-04 (Should): Long-running tasks shall be queued and expose a request status rather than holding a browser connection indefinitely.

NFR-PERF-05 (Must): A result page shall render with accessible core content before optional charts or enrichment complete.

Capacity and Limits

Initial limits are: URL 4,096 characters; text 25,000 characters; screenshot 10 MB; history retention configurable from 0 to 180 days. Limits are configurable administrative controls and must be visible in the UI.

3.10 Security and Privacy Requirements

NFR-SEC-01 (Must): The system shall enforce role-based access control using least privilege.

NFR-SEC-02 (Must): The system shall encrypt data in transit and encrypt stored sensitive data using approved platform controls.

NFR-SEC-03 (Must): The system shall protect against common web threats including injection, cross-site scripting, request forgery, insecure file upload, and broken authorization.

NFR-SEC-04 (Must): Credentials, API keys, session tokens, and detected secrets shall not appear in application logs or result pages.

NFR-SEC-05 (Must): Screenshot uploads shall be malware-scanned where infrastructure permits, stored outside the web root, and accessed through time-limited authorization.

NFR-PRV-01 (Must): The system shall minimize collection, explain retention at submission, and honor approved deletion requests.

NFR-PRV-02 (Must): Analytics shall use aggregated or de-identified data where practical.

NFR-SEC-06 (Should): High-risk administrator actions shall require re-authentication or multi-factor authentication.

3.11 Reliability, Usability, and Accessibility

NFR-REL-01 (Must): The service shall fail safely. When a dependency fails, it shall identify the limitation and not label content safe solely because a lookup failed.

NFR-REL-02 (Must): Daily backups of required structured data shall be verifiable, and restoration shall be tested at least once per release cycle.

NFR-USE-01 (Must): The result explanation shall use concise, non-technical wording with expandable technical detail.

NFR-USE-02 (Must): The system shall not use fear-inducing or absolute language such as “guaranteed safe.”

NFR-ACC-01 (Must): Keyboard navigation, visible focus, text alternatives, sufficient contrast, and readable risk labels shall be supported.

NFR-MNT-01 (Must): Rules, model artifacts, and integrations shall be versioned and traceable to a release record.

NFR-LOC-01 (Could): Future releases may support additional languages, locale-aware phishing examples, and right-to-left layouts.

3.12 Data Requirements

Table 5: Core Data Entities

Entity	Key fields	Purpose
User	user_id, role, consent, created_at	Identity and authorization.
AnalysisRequest	request_id, modality, submitted_at, status	Tracks an analysis job.
AnalysisResult	result_id, score, label, version, created_at	Stores outcome and evidence summary.
Indicator	indicator_id, type, value_hash, severity	Stores a normalized signal safely.
ScreenshotAsset	asset_id, object_ref, hash, OCR_confidence	Controlled image metadata.
Feedback	feedback_id, result_id, category, note	Captures user feedback.
AuditEvent	event_id, actor, action, timestamp	Immutable governance evidence.

Data Lifecycle


Raw input is accepted, validated, analyzed, and either discarded or retained according to consent and policy. Derived indicators are preferred over raw content for analytical history. Screenshot storage uses a separate protected object reference; the database stores only the minimum link and integrity hash.

4. System Models

4.1 Use Case Model

Primary actor: User. Supporting actors: Analyst, Administrator, External Intelligence Provider, OCR Service. The user submits one of the three supported modalities and receives a result; the analyst reviews flagged cases; the administrator configures policy and inspects operational health.

Figure 3: High-Level Use Case Flow



4.2 Model Assumptions

Models identify information flow and responsibility; they do not prescribe a specific framework or database vendor. All inter-service calls are authenticated and observable.

4.3 Data Flow Model

The client sends input to the API gateway. The gateway validates identity, rate limits, and input type. It routes URL, text, and image requests to the relevant processor. The score engine aggregates normalized indicators; the result service stores an approved record and returns an explanation. External feeds provide enrichments but never receive unnecessary user identity data.

Figure 4: Data Flow




4.4 Trust Boundaries

The browser, application tier, worker tier, external feeds, and storage tier are distinct trust zones. Input validation occurs at the boundary. Secrets remain server-side. Raw assets never cross into public static hosting.

4.5 Entity Relationship View

A User owns zero or more AnalysisRequests. Each request produces zero or one AnalysisResult during processing; a result contains one or more Indicators and can receive zero or more Feedback records. ScreenshotAsset is optional and linked only for image modality. AuditEvent references an actor and a protected action target.

Figure 5: Entity Relationship View



4.6 Sequence View

The submit sequence is: user submits input; client receives a request identifier; gateway validates and dispatches; processors produce evidence; scoring creates the decision; the result is persisted; the client displays the explanation. If a source times out, the processor returns an explicit unavailable signal and scoring applies the uncertainty policy.

4.7 State Model

AnalysisRequest states are Created, Validating, Queued, Processing, Completed, Inconclusive, Failed, and Deleted. A request may transition to Inconclusive after permitted enrichment timeouts; it may transition to Failed only for technical or invalid-input reasons. Completed results remain immutable except for an authorized analyst disposition or user feedback, each recorded separately.

4.8 Error Handling Model

Invalid input yields a client-safe validation error. A temporary service failure yields a retryable response with a correlation identifier. A policy violation yields a clear explanation without disclosing security-control internals. Security events are logged in a protected audit channel.

4.9 Risk Decision Model

The decision model uses evidence quality, severity, corroboration, and source reliability. It must distinguish absent evidence from unavailable evidence. A high score from one reliable malicious-domain source may be sufficient, whereas weak linguistic signals alone should yield cautious wording and appropriate confidence.

5. Verification and Acceptance

5.1 Requirements Validation

Validation shall combine review, automated tests, integration tests, security tests, usability checks, and controlled test datasets. Test data shall not include live malicious payloads, active credentials, or unauthorized personal information.

Table 6: Sample Traceability Matrix

Requirement	Verification method	Acceptance evidence
FR-URL-03	Unit and integration tests	Indicators returned for curated URLs.
FR-TXT-03	NLP test corpus and review	Urgency and credential-request cues identified.
FR-IMG-03	OCR fixture tests	Expected text and confidence recorded.
FR-SCR-03	API contract test	Score, label, reasons, version returned.
NFR-SEC-05	Security review and test	Rejected unsafe upload; protected asset path.
NFR-PERF-02	Load test	95th percentile screenshot latency report.

5.2 Acceptance Criteria

- All Must requirements have passing verification evidence or an approved, documented exception.
- No Critical or High result displays a clickable suspicious link by default.
- No test reveals raw credentials or secrets in UI, logs, or export.
- The final demo can analyze representative URL, text, and screenshot cases end to end.

5.3 Test Strategy

Unit tests cover parsers, normalizers, score calculations, masking, authorization rules, and storage adapters. Integration tests cover API-to-worker flow, feed timeouts, OCR handoff, and audit events. End-to-end tests use approved benign and synthetic phishing examples. Performance tests measure concurrent submissions and queue behavior.

5.4 Security Testing

Security testing includes dependency review, authentication and authorization tests, upload validation, API schema validation, rate-limit tests, logging inspection, and a review against relevant OWASP risks. Testing must be authorized and confined to owned systems.

5.5 Model Evaluation

The project shall record precision, recall, false-positive rate, false-negative rate, and latency for representative labeled datasets. Scores must be interpreted with dataset limitations. Model updates require regression testing against a held-out approved set and review of changed error patterns.

5.6 Usability Evaluation

At least a small representative user review shall verify that users can submit each modality, understand the risk label, find the evidence, and identify a safe next step. Feedback must not be used to claim statistical validity unless the study design supports it.

6. Deployment and Operations

6.1 Deployment Architecture

A recommended deployment separates the browser client, application API, asynchronous worker queue, URL/NLP/image processors, database, protected object storage, and monitoring stack. Environment-specific configuration and secrets are injected securely; they are never committed to source control.

6.2 Monitoring and Logging

Operational metrics include request count by modality, success/error rate, latency percentiles, queue depth, dependency status, model version distribution, and storage growth. Security logs include authentication failures, authorization denials, administrative changes, sensitive exports, and protected asset access. Logs must be integrity protected and retention limited.

6.3 Incident Handling

When CyberShield itself is suspected of compromise, administrators shall contain access, preserve authorized evidence, rotate relevant credentials, assess affected data, restore service safely, and document the event. Users should be informed through approved channels when disclosure is required.

6.4 Maintenance

Routine maintenance covers dependency patches, threat-feed health, model drift checks, backup verification, capacity review, and periodic access review. A rollback path is required for scoring rules and model releases.

7. Appendices

Appendix A: Sample Result Structure

A result contains: request identifier; modality; normalized input summary; risk score and label; confidence; detected indicators with severity and evidence source; safe recommendations; limitations; created time; rule/model version; and retention/deletion controls.

Appendix B: Safe User Guidance

- Do not click or reply when a message demands urgent credential, OTP, or payment action.
- Verify using a trusted official app, bookmarked site, or independently known phone number.
- Do not share passwords, one-time codes, recovery codes, or card details.
- Report suspicious content through the appropriate organization or service channel.

Appendix C: Future Enhancements

Potential future work includes multilingual NLP, QR-code destination analysis, email-header parsing, explainability improvements, organization-specific brand profiles, browser extension integration, and SOC/ticketing integration. Each enhancement requires a separate privacy and security assessment.

Appendix D: Functional Requirement Summary

Table 7: Requirement Groups

Group	Purpose	Priority
URL analysis	Detect technical and reputation-based URL risk indicators.	Must
Text analysis	Identify phishing intent and entities in SMS/email text.	Must
Screenshot analysis	Combine OCR and visual cues to assess phishing screenshots.	Must
Scoring	Produce an explainable, calibrated risk decision.	Must
Governance	Control roles, configuration, audit, and retention.	Must
Reporting	Provide safe summaries, exports, and user feedback.	Should

Interpretation Note

The requirements are deliberately layered: validation and safe storage are prerequisites for analysis; modality-specific evidence is normalized before it reaches scoring; the result experience then explains uncertainty and recommends a safe action. This approach makes each component testable without treating any one signal as definitive.

Configuration Baseline

Thresholds, enabled feeds, retention duration, supported languages, maximum inputs, and model versions are configuration values. They must be change controlled and recorded with each analysis result so the behavior can be reproduced during review.

Appendix E: Example Indicators

URL Indicators

- Domain contains a suspicious lookalike of a known brand.
- Hostname is a raw IP address or uses misleading nested subdomains.
- URL includes excessive encoding, unusual path structure, or credential/payment terms.
- Configured intelligence source reports a malicious or suspicious reputation.

Text Indicators

- Artificial urgency, account threat, prize, refund, or unexpected payment language.
- Request for password, OTP, recovery code, card detail, or remote-access action.
- Impersonation claim that conflicts with sender clues or embedded domain.
- Obscured link, unusual contact channel, or abrupt instruction to move conversation.

Image Indicators

- OCR extracts a login form, password/OTP request, or payment prompt.
- Visual structure imitates a brand while domains or text show mismatches.
- QR code or shortened link attempts to conceal destination information.
- Low image quality reduces OCR confidence and must reduce certainty.

Appendix F: Risk Communication Examples

Low Risk

“No strong phishing indicators were found in this analysis. This does not confirm that the content is safe. Continue only if you expected it and can verify the sender or website independently.”

Medium Risk

“This content includes signals often used in scams, such as urgency or an unfamiliar link. Do not provide credentials or payment information. Verify through an official channel before taking action.”

High / Critical Risk

“Multiple strong phishing indicators were detected. Avoid clicking, replying, scanning a QR code, or sharing information. Use a known official website or contact method to verify the request and report it if appropriate.”

Inconclusive

“The analysis could not use one or more evidence sources, or the image/text quality was limited. Treat the content cautiously and verify through an independently trusted channel.”

These examples are guidance templates, not legal or incident-response instructions. The final user interface shall show the specific reasons behind each classification.

References

1. IEEE Computer Society, IEEE 830: Recommended Practice for Software Requirements Specifications.
2. OWASP Foundation, OWASP Application Security Verification Standard and OWASP web application security guidance.
3. National Institute of Standards and Technology, Security and Privacy Controls for Information Systems and Organizations (SP 800-53).
4. National Institute of Standards and Technology, Computer Security Incident Handling Guide (SP 800-61).
5. Anti-Phishing Working Group, phishing activity reports and educational resources.
6. Project reference: EXPIROCHAIN report, supplied as a structural reference for academic documentation.
7. Project reference: SRS Report Formatting Guide, supplied for A4 layout, typography, headings, captions, and IEEE-based structure.

End of Document