



These are your bread and butter for handling those `..` and `/` paths.

2. File & Folder Management

Window cmd most known being a window users

Command	Action	Example
<code>mkdir</code>	M ake K edirectory (Create a folder)	<code>mkdir css</code>
<code>type nul ></code>	Create a new empty file (CMD)	<code>type nul > index.html</code>
<code>ni</code>	N ew I tem (Create file in PowerShell)	<code>ni style.css</code>
<code>copy</code>	Copy a file to a new location	<code>copy file.txt ../backup/</code>
<code>move</code>	Move or rename a file	<code>move old.js new.js</code>
<code>del</code>	D ele t e a file	<code>del temp.txt</code>
<code>rmdir /s</code>	Remove a folder and everything inside	<code>rmdir /s old_project</code>

3. System & Network Essentials

Useful when you need to check if your environment is set up correctly.

- `cls` : **C**lear **S**creen (Cleans up your messy terminal window).
- `ipconfig` : Shows your network info (useful for finding your IP address).
- `systeminfo` : Displays detailed specs of your computer.
- `where` : Finds where a program is installed.
 - *Example:* `where node` will show you exactly where Node.js is located on your path.
- `exit` : Closes the terminal.

4. Searching & Finding (Crucial for Debugging)

When you have 100 files, you can't open them all to find a specific word.

Command	Action	Why it's important
---------	--------	--------------------

<code>findstr</code>	Search for a string inside files	Find which file contains a specific variable name.
<code>type</code>	Display file content in terminal	Read a config file without opening an editor.
<code>echo</code>	Print text or write to a file	Quickly check an environment variable (\$180°C\$ or \$10\%\$ not needed here, just plain text).

5. Environment & Tools

You need to know if your computer actually "sees" the tools you installed.

- `-version`: This isn't a command itself, but a flag. Use it on everything: `node --version`, `python --version`, `git --version`.
- `code .`: If you use VS Code, typing this in your terminal opens the **current folder** as a project in VS Code immediately.

6. Forced Deletion

Sometimes a file is "Read-Only," and the terminal will refuse to delete it.

- **CMD:** `del /f <filename>` (The `/f` stands for Force).
- **PowerShell:** `rm -Force <filename>`