Udacity – Path Planning Project

Submitted by: Neeraj Gulia

Date: May-11-2018

Objective

The objective of this project is to run the car in simulator to follow lane lines and to not collide with other cars. Also to switch the lanes safely if there is a slow moving vehicle ahead of our car.

Rubric Points

Compilation

The code compiles correctly.

I used spline.h library and added in the source folder. The code compiled without any errors.

Valid trajectories

Description	Result
The car is able to drive at least 4.32 miles without incident.	Car drove more than 12 miles without any incident
The car drives according to the speed limit.	Car never crossed the speed limit
Max Acceleration and Jerk are not Exceeded.	Within given limit
Car does not have collisions.	No collisions
The car stays in its lane, except for the time between changing lanes.	Car stays in the lane
The car is able to change lanes	Car successfully changed lanes when it's safe to change



Figure 1 Screenshot of the successfull run

Reflection

Model description:

The main.cpp file listens to the message sent from the simulator (using web sockets). The simulator sends the data related to car, like Car's location, velocity, yaw rate, speed and Frenet coordinates (longitudinal and lateral displacement). It also sends the data from the sensor fusion which contains data for other cars in vicinity.

The working of the model can be broken down in following three parts:

Prediction

The data from the sensor fusion and simulator is used to generate the predictions about the likely behavior of moving objects. Like if there is a car in front of us, what it will do in future and based on that we will decide the behavior of our car.

Behavior Planning

Based on the prediction of the other moving objects we decide the behavior of our car. There can be following behaviors which our car can do based on the other moving cars:

Prediction	Behavior of our car
Car ahead us is too close	Slow down our car
Car ahead us is driving slow	See if we can change lane safely
Car ahead us is slow and there	Change the lane to left lane (but see first if it is safe to change
is no car on left lane	the lane and we are not in the left most lane)
Car ahead us is slow and there	Change the lane to right (but see first if it is safe to change the
is another car in left lane	lane and we are not in the right most lane)
There is no car ahead of us or	Increase the speed of the car to approx. speed limit and
car is too far away	maintain the lane

The buffer distance between our car and car ahead is set as 30 meters.

We try to change the lane if there is no vehicle in the side lane in front of us for 30 meters and there is no car too close to us which is coming from behind (there might be a car coming too fast from side lanes while we plan to change the lane).

Trajectory Generation

Our car calculates the trajectory based on the speed, other vehicles position - velocity and lane, current lane, car coordinates and past path points. To make the trajectory smooth we adds the last two points from the previous trajectory path. If there are no previous paths we calculate the previous point from the current yaw rate and the current car coordinates.

Also we add three way points in next 30 meters, 60 meters and 90 meters to the trajectory. All these points are then shifted to the car reference angle (local car coordinates) – this is done to simplify the calculations.

We then use spline library to get the remaining points of the trajectory based on the current path (we are adding total of 50 points to the trajectory). All these points are then again moved to the global coordinates (so that these can be sent to the simulator to generate the trajectory and to drive the car based on this trajectory)

Final Thoughts

This project helps us to visualize the Path planning and helps us to understand why it is one of the most crucial parts of the autonomous vehicle. Safety is one of the most important point in the path planning.