



EMV®

Secure Remote Commerce

Specification – API

Version 1.3

December 2022

Legal Notice

The EMV® Specifications are provided “AS IS” without warranties of any kind, and EMVCo neither assumes nor accepts any liability for any errors or omissions contained in these Specifications. EMVCO DISCLAIMS ALL REPRESENTATIONS AND WARRANTIES, EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, TITLE AND NON-INFRINGEMENT, AS TO THESE SPECIFICATIONS.

EMVCo makes no representations or warranties with respect to intellectual property rights of any third parties in or in relation to the Specifications. EMVCo undertakes no responsibility to determine whether any implementation of the EMV® Specifications may violate, infringe, or otherwise exercise the patent, copyright, trademark, trade secret, know-how, or other intellectual property rights of third parties, and thus any person who implements any part of the EMV® Specifications should consult an intellectual property attorney before any such implementation.

Without limiting the foregoing, the Specifications may provide for the use of public key encryption and other technology, which may be the subject matter of patents in several countries. Any party seeking to implement these Specifications is solely responsible for determining whether its activities require a license to any such technology, including for patents on public key encryption technology. EMVCo shall not be liable under any theory for any party’s infringement of any intellectual property rights in connection with the EMV® Specifications.

Revision Log – Version 1.3

The following changes have been made to the document since the publication of version 1.2:

- Minor editorial changes throughout the document, with sections and tables renumbered where necessary
- Edits to account for the deprecation of the SRC Data Dictionary
- Section 2.1 Complex Data Objects has been reorganised so that it is in alphabetical order, with the following complex data objects added:
 - AccountReference (Section 2.1.3)
 - AuthenticationContext (Section 2.1.8)
 - AuthenticationMethod (Section 2.1.9)
 - BusinessIdentification (Section 2.1.10)
 - ComplianceResource (Section 2.1.14)
 - RecognitionData (Section 2.1.43)
 - UriData (Section 2.1.47)
- Section 2.1 Complex Data Objects, the following has been deprecated:
 - Consent (Section 2.1.18)
- Section 2.1 Complex Data Objects, the following have been modified:
 - Address (Section 2.1.5): updated description to data element `state`
 - AssuranceData (Section 2.1.7): new data element `eci` added
 - ComplianceSettings (Section 2.1.15): individual data elements replaced with a list of ComplianceResources
 - DigitalCardData (Section 2.1.24): new data element `authenticationMethods` added
 - DpaData (Section 2.1.27): `dpaUri` made conditional (from optional) and seven new data elements (`merchantCountryCode`, `businessId`, `merchantName`, `merchantCategoryCode`, `acquirerId`, `acquirerBin`, `dpaPanDataRequested`) added
 - DpaTransactionOptions (Section 2.1.28): two new data elements (`cardholderNameRequested`, `consumerNationalIdentifierRequested`) added
 - MaskedAddress (Section 2.1.35): updated description to data element `state`

- MaskedCard (Section 2.1.36): four new data elements (`enrollmentReferenceData`, `cofEligible`, `maskedCardholderFullName`, `maskedCardholderFirstName`, `maskedCardholderLastName`, `complianceSettings`) added
- MaskedConsumer (Section 2.1.37): new data element `pendingEvents` added
- Payload (Section 2.1.39): new data element `consumerNationalIdentifier` added
- VerificationData (Section 2.1.46): new data element `methodResults` added
- Section 2.2 Individual Attributes has been deleted. Following the introduction of the new table structure for the individual APIs in version 1.2, descriptions for individual data elements are included within the APIs themselves. Therefore Section 2.2 is no longer required, since the information can be found elsewhere.
- Section 2.2 JSON Attributes has been added to describe the attributes of specific JSON objects
- Section 2.3 Enumerations, the following have been added or modified:
 - Action
 - AuthenticationReason
 - AuthenticationMethodType
 - AuthenticationSubject
 - AuthenticationStatus
 - AuthenticationResult
 - BindingStatus
 - CardPendingEvent: the `PENDING_SCA` value has been deprecated and replaced with the `PENDING_CARDHOLDER_AUTHENTICATION` value and the `PENDING_CSC` value has been added
 - ComplianceType: the `ComplianceType` enumeration replaces the individual data elements within the complex data object `ComplianceSettings` (Section 2.1.15), with the addition of `REMEMBER_ME`, which supersedes the `cookie` data element in `ComplianceSettings`
 - ConsumerPendingEvent
 - DcfActionCode: the `PENDING_AUTHENTICATION` value has been added
 - EnrollmentReferenceType: the `COF_REFERENCE_ID` value has been added
 - UriType
- Section 3.1.2 Token Claims, an additional value `merchant_rememberme` has been added to the `amr` claim

- Section 5.1 API Principles, the following subsections have been added:
 - Section 5.1.5.1 Recognition Token JWT
 - Section 5.1.7 API Tables
- Section 5 Server-Side API (Sections 5.2 to 5.11) and Section 6 Notification Service (Sections 6.2 to 6.5), each API has had the existing table structure replaced, where applicable, with individual tables for:
 - HTTP Verb, Path and Parameters
 - Query Parameters
 - Request Body
 - Response Body
 - HTTP Status Codes
- Section 5 Server-Side API, the following Services and their APIs have been added:
 - Authentication Facilitation Service (Section 5.8)
 - Retrieve Latest Compliance Resources Service (Section 5.10)
 - Management Service (Section 5.11)
- Section 5 Server-Side API, the following Services and their APIs have been changed:
 - Card Enrolment Response Body (Section 5.2.1) `appInstanceId` deprecated and replaced by `recognitionToken`
 - Add Consumer Identities Request Body (Section 5.4.2) `encryptedConsumer` added
 - Add Consumer Identities Response Body (Section 5.4.2) `appInstanceId` deprecated and replaced by `recognitionToken`
 - Unbind App Instance Query Parameters (Section 5.4.3) `appInstanceId` deprecated and replaced by `recognitionToken`
 - Confirmation Request Body (Section 5.6.1) `assuranceData` deprecated
 - Identity Lookup Body (Section 5.7.1) `lastUsedCardTimestamp` added
 - Initiate Identity Validation Response Body (Section 5.7.2) `authenticationAppUri` added
 - Complete Identity Validation Response Body (Section 5.7.3) `maskedCard` added
 - Is Recognized Query Parameters (Section 5.7.4) `appInstanceId` deprecated and replaced by `recognitionTokens`
 - Is Recognized Response Body (Section 5.7.4) `appInstanceId` deprecated and replaced by `recognitionToken`, `recognitionDomainName` added
- Section 6 Notification Service, the following Services and their APIs have been added:

- Authentication Event Notification (Section 6.4)
- The following Annex has been added:
 - Annex B 3DS Data

Contents

Legal Notice	i
Revision Log – Version 1.3.....	ii
Contents	vi
Tables	x
1 Introduction	1
1.1 Scope	1
1.2 Constraints	1
1.3 Audience	1
1.4 References	2
1.4.1 Normative References	2
1.4.2 Published EMVCo Documents	2
1.5 Definitions.....	3
1.6 Notational Conventions.....	4
1.6.1 Abbreviations	4
1.6.2 Terminology and Conventions.....	4
2 Data Dictionary	5
2.1 Complex Data Objects.....	5
2.1.1 AcceptanceChannelData	5
2.1.2 AcceptanceChannelRelatedData	6
2.1.3 AccountReference	6
2.1.4 AdditionalAmount.....	7
2.1.5 Address	7
2.1.6 ApplInstance.....	9
2.1.7 AssuranceData	10
2.1.8 AuthenticationContext.....	17
2.1.9 AuthenticationMethod	18
2.1.10 BusinessIdentification	19
2.1.11 Card.....	20
2.1.12 CardholderData	21
2.1.13 CommunicationsConsent.....	22
2.1.14 ComplianceResource.....	23
2.1.15 ComplianceSettings	23
2.1.16 ConfirmationData DEPRECATED	24
2.1.17 ConfirmationData2	26
2.1.18 Consent DEPRECATED	28
2.1.19 Consumer	29

2.1.20 ConsumerIdentity	30
2.1.21 Dcf	30
2.1.22 DeliveryContactDetails.....	31
2.1.23 DeviceData	32
2.1.24 DigitalCardData	32
2.1.25 DigitalCardFeature.....	34
2.1.26 DigitalCardUpdateNotification	34
2.1.27 DpaData	35
2.1.28 DpaTransactionOptions	38
2.1.29 DynamicData	41
2.1.30 EnrollmentReferenceData.....	42
2.1.31 Error.....	42
2.1.32 ErrorDetail.....	43
2.1.33 EventHistory	43
2.1.34 IdentityValidationChannel	44
2.1.35 MaskedAddress	45
2.1.36 MaskedCard	46
2.1.37 MaskedConsumer.....	50
2.1.38 MaskedConsumerIdentity	52
2.1.39 Payload.....	53
2.1.40 PaymentOptions	59
2.1.41 PaymentToken.....	59
2.1.42 PhoneNumber.....	60
2.1.43 RecognitionData	60
2.1.44 SrcProfile	61
2.1.45 TransactionAmount.....	62
2.1.46 VerificationData	63
2.1.47 UriData	69
2.2 JSON Attributes.....	69
2.2.1 Authentication Facilitation	69
2.3 Enumerations	72
2.4 Signed Checkout Objects	76
2.4.1 Checkout Request JWS.....	76
2.4.2 Checkout Payload Response.....	79
2.4.3 JWS JOSE Header	83
2.5 Masking Rule.....	84
3 Federated Identity	85
3.1 Authorisation Token.....	85
3.1.1 Token Header	85
3.1.2 Token Claims.....	86

3.1.3	Notes on Authentication	90
4	SRCI – DCF Interaction	92
4.1	Interaction Mechanisms	92
4.2	Launch The DCF	93
4.3	Redirect back to SRCI	93
5	Server-Side API	96
5.1	API Principles	96
5.1.1	Common HTTP Status Codes	96
5.1.2	Error Handling	97
5.1.3	Conditionality of Data	97
5.1.4	Authorisation	97
5.1.5	Recognition	97
5.1.6	API Access Control	99
5.1.7	API Tables	99
5.2	Card Service	99
5.2.1	Card Enrolment	99
5.2.2	Delete Card	103
5.2.3	Add Billing Address	105
5.2.4	Get Card Data	107
5.3	Address Service	108
5.3.1	Add Shipping Address	108
5.3.2	Delete Shipping Address	110
5.4	SRC Profile Service	111
5.4.1	Prepare SRC Profile	111
5.4.2	Add Consumer Identities	114
5.4.3	Unbind App Instance	117
5.5	Checkout Service	118
5.5.1	Prepare Checkout Data	118
5.5.2	Checkout	121
5.5.3	Get Payload	126
5.5.4	Make Payment	128
5.6	Confirmation Service	129
5.6.1	Confirmation	129
5.7	Identity Service	131
5.7.1	Identity Lookup	131
5.7.2	Initiate Identity Validation	132
5.7.3	Complete Identity Validation	134

5.7.4	Is Recognized	136
5.8	Authentication Facilitation Service	138
5.8.1	Authentication Methods Lookup	138
5.8.2	Authenticate	140
5.9	Public Keys Retrieval Service	142
5.9.1	Public Key Retrieval	143
5.10	Retrieve Latest Compliance Resources Service	144
5.10.1	Latest Compliance Resources Retrieval	145
5.11	Management Service	146
5.11.1	DPA Registration	146
6	Notification Service	148
6.1	Notifications Principles	148
6.1.1	Data Delivery Modes	148
6.1.2	Standard HTTP Status Codes	148
6.2	Card Update Event Notification	149
6.3	Identity Validation Completion Event Notification	150
6.4	Authentication Event Notification	153
6.5	Payment Notification	154
Annex A	EMVCo Specification Mapping	156
A.1	Merchant-Presented Mode – QR Code Payload	156
A.1.1	SRC Data Elements	156
A.1.2	QR Code specific Data Elements for Seller Data	157
A.1.3	QR Code specific Data Elements for Consumer Data	158
A.1.4	QR Code Specific Data Elements for Additional Amounts	162
Annex B	3DS Data	165
B.1	3DS Input Data	165
B.2	3DS Output Data	166

Tables

Table 1.1: Normative References.....	2
Table 1.2: EMVCo References.....	2
Table 2.1: AcceptanceChannelData.....	5
Table 2.2: AcceptanceChannelRelatedData.....	6
Table 2.3: AccountReference.....	6
Table 2.4: AdditionalAmount.....	7
Table 2.5: Address.....	7
Table 2.6: AppInstance.....	9
Table 2.7: AssuranceData.....	10
Table 2.8: AuthenticationContext.....	17
Table 2.9: AuthenticationMethod.....	18
Table 2.10: BusinessIdentification.....	19
Table 2.11: Card.....	20
Table 2.12: CardholderData.....	21
Table 2.13: CommunicationsConsent.....	22
Table 2.14: ComplianceResource.....	23
Table 2.15: ComplianceSettings.....	23
Table 2.16: ConfirmationData DEPRECATED.....	24
Table 2.17: ConfirmationData2.....	26
Table 2.18: Consent DEPRECATED.....	28
Table 2.19: Consumer.....	29
Table 2.20: ConsumerIdentity.....	30
Table 2.21: Dcf.....	30
Table 2.22: DeliveryContactDetails.....	31
Table 2.23: DeviceData.....	32
Table 2.24: DigitalCardData.....	32
Table 2.25: DigitalCardFeature.....	34
Table 2.26: DigitalCardUpdateNotification.....	34
Table 2.27: DpaData.....	35
Table 2.28: DpaTransactionOptions.....	38
Table 2.29: DynamicData.....	41
Table 2.30: EnrollmentReferenceData.....	42
Table 2.31: Error.....	42
Table 2.32: ErrorDetail.....	43
Table 2.33: EventHistory.....	43
Table 2.34: IdentityValidationChannel.....	44
Table 2.35: MaskedAddress.....	45
Table 2.36: MaskedCard.....	46
Table 2.37: MaskedConsumer.....	50
Table 2.38: MaskedConsumerIdentity.....	52

Table 2.39: Payload	53
Table 2.40: PaymentOptions	59
Table 2.41: PaymentToken	59
Table 2.42: PhoneNumber	60
Table 2.43: RecognitionData	60
Table 2.44: SrcProfile	61
Table 2.45: TransactionAmount	62
Table 2.46: VerificationData	63
Table 2.47: VerificationData Values	64
Table 2.48: UriData	69
Table 2.49: JSON Attributes for CSC_VALIDATION	70
Table 2.50: JSON Attributes for SMS_OTP, EMAIL_OTP, APP_OTP	70
Table 2.51: JSON Attributes for ADDRESS_VERFICATION	70
Table 2.52: JSON Attributes for SPC (Authenticate response)	71
Table 2.53: JSON Attributes for SPC (Authenticate request)	71
Table 2.54: JSON Attributes for 3DS	71
Table 2.55: JSON Attributes for Consumer Authentication	72
Table 2.56: Enumerations	72
Table 2.57: Checkout Request JOSE Header	76
Table 2.58: Checkout Request Claim Set	77
Table 2.59: Checkout Payload Response	79
Table 2.60: JWS JOSE Header	83
Table 3.1: JOSE Header	85
Table 3.2: Federated ID Token Claim Set	86
Table 4.1: Error Codes	94
Table 5.1: Recognition Token Claim Set	98
Table 5.2.1: Card Enrolment Definition – HTTP Verb, Path and Parameters	100
Table 5.2.2: Card Enrolment Definition – Request Body	100
Table 5.2.3: Card Enrolment Definition – Response Body	102
Table 5.2.4: Card Enrolment Definition – HTTP Status Codes	103
Table 5.2.5: Delete Card Definition – HTTP Verb, Path and Parameters	103
Table 5.2.6: Delete Card Definition – Query Parameters	103
Table 5.2.7: Delete Card Definition – Response Body	104
Table 5.2.8: Delete Card Definition – HTTP Status Codes	104
Table 5.2.9: Add Billing Address Definition – HTTP Verb, Path and Parameters ...	105
Table 5.2.10: Add Billing Address Definition – Request Body	105
Table 5.2.11: Add Billing Address Definition – Response Body	106
Table 5.2.12: Add Billing Address Definition – HTTP Status Codes	106
Table 5.2.13: Get Card Data Definition – HTTP Verb, Path and Parameters	107
Table 5.2.14: Get Card Data Definition – Query Parameters	107
Table 5.2.15: Get Card Data Definition – Response Body	108
Table 5.2.16: Get Card Data Definition – HTTP Status Codes	108

Table 5.3.1: Add Shipping Address Definition – HTTP Verb, Path and Parameters	108
Table 5.3.2: Add Shipping Address Definition – Request Body	109
Table 5.3.3: Add Shipping Address Definition – Response Body	109
Table 5.3.4: Add Shipping Address Definition – HTTP Status Codes	110
Table 5.3.5: Delete Shipping Address Definition – HTTP Verb, Path and Parameters	110
Table 5.3.6: Delete Shipping Address Definition – Query Parameters	110
Table 5.3.7: Delete Shipping Address Definition – Response Body	111
Table 5.3.8: Delete Shipping Address Definition – HTTP Status Codes	111
Table 5.4.1: Prepare SRC Profile Definition – HTTP Verb, Path and Parameters .	112
Table 5.4.2: Prepare SRC Profile Definition – Request Body	112
Table 5.4.3: Prepare SRC Profile Definition – Response Body	113
Table 5.4.4: Prepare SRC Profile Definition – HTTP Status Codes	114
Table 5.4.5: Add Consumer Identities Definition – HTTP Verb, Path and Parameters	114
Table 5.4.6: Add Consumer Identities Definition – Request Body	115
Table 5.4.7: Add Consumer Identities Definition – Response Body	116
Table 5.4.8: Add Consumer Identities Definition – HTTP Status Codes	116
Table 5.4.9: Unbind App Instance Definition – HTTP Verb, Path and Parameters.	117
Table 5.4.10: Unbind App Instance Definition – Query Parameters	117
Table 5.4.11: Unbind App Instance Definition – Response Body	118
Table 5.4.12: Unbind App Instance Definition – HTTP Status Codes	118
Table 5.5.1: Prepare Checkout Data Definition – HTTP Verb, Path and Parameters	119
Table 5.5.2: Prepare Checkout Data Definition – Request Body	119
Table 5.5.3: Prepare Checkout Data Definition – Response Body	121
Table 5.5.4: Prepare Checkout Data Definition – HTTP Status Codes	121
Table 5.5.5: Checkout Definition – HTTP Verb, Path and Parameters	122
Table 5.5.6: Checkout Definition – Request Body	122
Table 5.5.7: Checkout Definition – Request Body	123
Table 5.5.8: Checkout Definition – Response Body	125
Table 5.5.9: Checkout Definition – HTTP Status Codes	126
Table 5.5.10: Get Payload Definition – HTTP Verb, Path and Parameters	126
Table 5.5.11: Get Payload Definition – Query Parameters	126
Table 5.5.12: Get Payload Definition – Response Body	128
Table 5.5.13: Get Payload Definition – HTTP Status Codes	128
Table 5.5.14: Make Payment Definition – HTTP Verb, Path and Parameters	128
Table 5.5.15: Make Payment Definition – Request Body	128
Table 5.5.16: Make Payment Definition – HTTP Status Codes	129
Table 5.6.1: Confirmation Definition – HTTP Verb, Path and Parameters	129
Table 5.6.2: Confirmation Definition – Request Body	129
Table 5.6.3: Confirmation Definition – HTTP Status Codes	130
Table 5.7.1: Identity Lookup Definition – HTTP Verb, Path and Parameters	131
Table 5.7.2: Identity Lookup Definition – Request Body	131
Table 5.7.3: Identity Lookup Definition – Response Body	132

Table 5.7.4: Identity Lookup Definition – HTTP Status Codes	132
Table 5.7.5: Initiate Identity Validation Definition – HTTP Verb, Path and Parameters	133
Table 5.7.6: Initiate Identity Validation Definition – Request Body	133
Table 5.7.7: Initiate Identity Validation Definition – Response Body	133
Table 5.7.8: Initiate Identity Validation Definition – HTTP Status Codes.....	134
Table 5.7.9: Complete Identity Validation Definition – HTTP Verb, Path and Parameters	134
Table 5.7.10: Complete Identity Validation Definition – Request Body	135
Table 5.7.11: Complete Identity Validation Definition – Response Headers	135
Table 5.7.12: Complete Identity Validation Definition – Response Body	135
Table 5.7.13: Complete Identity Validation Definition – HTTP Status Codes	136
Table 5.7.14: Is Recognized Definition – HTTP Verb, Path and Parameters	136
Table 5.7.15: Is Recognized Definition – Query Parameters	136
Table 5.7.16: Is Recognized Definition – Response Body	137
Table 5.7.17: Is Recognized Definition – HTTP Status Codes.....	138
Table 5.8.1: Authentication Methods Lookup Definition – HTTP Verb, Path and Parameters	138
Table 5.8.2: Authentication Methods Lookup Definition – Request Body.....	139
Table 5.8.3: Authentication Methods Lookup Definition – Response Body	139
Table 5.8.4: Authentication Methods Lookup Definition – HTTP Status Codes	140
Table 5.8.5: Authenticate Definition – HTTP Verb, Path and Parameters.....	140
Table 5.8.6: Authenticate Definition – Request Body	140
Table 5.8.7: Authenticate Definition – Response Body.....	141
Table 5.8.8: Authenticate Definition – Response Headers	142
Table 5.8.9: Authenticate Definition – HTTP Status Codes	142
Table 5.9.1: Public Key Retrieval Definition – HTTP Verb, Path and Parameters..	143
Table 5.9.2: Public Key Retrieval Definition – Response Body.....	144
Table 5.9.3: Public Key Retrieval Definition – HTTP Status Codes	144
Table 5.10.1: Latest Compliance Resources Retrieval Definition – HTTP Verb, Path and Parameters.....	145
Table 5.10.2: Latest Compliance Resources Retrieval Definition – Request Body	145
Table 5.10.3: Latest Compliance Resources Retrieval Definition – Response Body	145
Table 5.10.4: Latest Compliance Resources Retrieval Definition – HTTP Status Codes	146
Table 5.11.1: DPA Registration Definition – HTTP Verb, Path and Parameters	146
Table 5.11.2: DPA Registration Definition – Request Body	146
Table 5.11.3: DPA Registration Definition – Response Body	147
Table 5.11.4: DPA Registration Definition – HTTP Status Codes.....	147
Table 6.1: Standard HTTP Status Codes	149
Table 6.2.1: Card Update Event Notification Definition – HTTP Verb, Path and Parameters	150
Table 6.2.2: Card Update Event Notification Definition – Request Body.....	150
Table 6.2.3: Card Update Event Notification Definition – HTTP Status Codes.....	150
Table 6.3.1: Identity Validation Completion Event Notification Definition – HTTP Verb, Path and Parameters.....	151

Table 6.3.2: Identity Validation Completion Event Notification Definition – Request Body	151
Table 6.3.3: Identity Validation Completion Event Notification Definition – HTTP Status Codes.....	151
Table 6.4.1: Authentication Event Notification Definition – HTTP Verb, Path and Parameters	153
Table 6.4.2: Authentication Completion Event Notification Definition – Request Body	153
Table 6.4.3: Authentication Completion Event Notification Definition – HTTP Status Codes	154
Table 6.5.1: Payment Notification Definition – HTTP Verb, Path and Parameters .	154
Table 6.5.2: Payment Notification Definition – Request Body	154
Table 6.5.3: Payment Notification Definition – HTTP Status Codes.....	155
Table A.1: SRC API Usage for QR Code Payload.....	158
Table A.2: SRC API Usage for Bill Number	158
Table A.3: SRC API Usage for Mobile Number	159
Table A.4: SRC API Usage for Store Label	159
Table A.5: SRC API Usage for Loyalty Number	159
Table A.6: SRC API Usage for Reference Label	160
Table A.7: SRC API Usage for Customer Label	160
Table A.8: SRC API Usage for Terminal Label.....	160
Table A.9: SRC API Usage for Purpose of Transaction.....	161
Table A.10: SRC API Usage for Email	161
Table A.11: SRC API Usage for Phone Number	162
Table A.12: SRC API Usage for Address	162
Table A.13: SRC API Usage for Tip	163
Table A.14: SRC API Usage for Convenience Fee	163
Table A.15: SRC API Usage for Sub Total.....	164
Table B.1: 3DS Input Data	165
Table B.2: 3DS Output Data.....	166

1 Introduction

Secure Remote Commerce (SRC) is an evolution of remote commerce that provides for secure and interoperable card acceptance established through a standard specification.

This document, the EMV® Secure Remote Commerce Specification – API, (hereafter the “SRC API Specification”), contains server-based APIs which can be used to securely build interfaces between SRC Systems and SRC System Participants. It is intended to be used in conjunction with the SRC Specifications (see Section 1.4.2 Published EMVCo Documents).

1.1 Scope

The SRC API Specification describes APIs to be used for the transmission of data between SRC Systems and SRC System Participants. These APIs are based on the following assumptions:

- The server-based APIs provide a toolkit for SRC System Participants
- They are not intended to provide context for all scenarios or use cases, and individual SRC Systems are responsible for creating implementation instructions for their SRC System Participants
- They do not preclude an SRC System from providing additional technical components to support their implementations
- The EMV SRC API specification offers levels of optionality for implementers of the specifications to add security layers based on the SRC solution provider’s own security requirements and risk controls

1.2 Constraints

The SRC API Specification is designed to work within the constraints described in the SRC Core Specification. In particular, the SRC API Specification or any implementation of the SRC API Specification is not intended to replace or interfere with any international, regional, national or local laws and regulations; those governing requirements supersede any industry standards.

1.3 Audience

This document is intended for use by SRC Systems and SRC System Participants.

1.4 References

The latest version of any reference, including all published amendments, shall apply unless a publication date is explicitly stated.

1.4.1 Normative References

The standards in Table 1.1 may be associated with the SRC API Specification.

Table 1.1: Normative References

Reference	Publication Name
ISO 3166	Country Codes — ISO 3166
ISO 4217	Currency Codes — ISO 4217
ISO/IEC 7812	Identification cards — Identification of issuers
RFC 3447	Public-Key Cryptography Standards (https://tools.ietf.org/html/rfc3447)
RFC 7515	JSON Web Signature (https://tools.ietf.org/html/rfc7515)
RFC 7516	JSON Web Encryption (https://tools.ietf.org/html/rfc7516)
RFC 7517	JSON Web Key (https://tools.ietf.org/html/rfc7517)
RFC 7518	JSON Web Algorithms (https://tools.ietf.org/html/rfc7518)
RFC 7519	JSON Web Token (https://tools.ietf.org/html/rfc7519)

1.4.2 Published EMVCo Documents

The documents in Table 1.2 are related to or are associated with SRC and are located at www.emvco.com.

Table 1.2: EMVCo References

Reference	Publication Name
EMV 3-D Secure Specification	EMV® 3-D Secure – Protocol and Core Functions Specification

Reference	Publication Name
Merchant-Presented Mode	EMV® QR Code Specification for Payment Systems (EMV QRCPS) – Merchant-Presented Mode
Payment Tokenisation	EMV® Payment Tokenisation Specification – Technical Framework
SRC Core Specification	EMV® Secure Remote Commerce Specification
SRC Reproduction Requirements	EMV® Secure Remote Commerce (SRC): Click to Pay Icon Reproduction Requirements
SRC UI Guidelines and Requirements	EMV® Secure Remote Commerce Specification – User Interface Guidelines and Requirements
SRC JavaScript SDK	EMV® Secure Remote Commerce Specification – JavaScript SDK
SRC Version Management	EMV® Secure Remote Commerce Version Management for SRC API and SRC JavaScript SDK Specifications
SRC Use Cases	EMV® Secure Remote Commerce Use Cases

Collectively, the term SRC Specifications refers to:

- SRC Core Specification
- SRC Reproduction Requirements
- SRC UI Guidelines and Requirements
- SRC API (this document)
- SRC JavaScript SDK
- SRC Version Management

1.5 Definitions

For the definition of the terms used in the SRC API Specification, refer to Table 1.3: Definitions in the SRC Core Specification. For definitions of data elements refer to Section 2 Data Dictionary.

1.6 Notational Conventions

1.6.1 Abbreviations

For the definition of the abbreviations used in the SRC API Specification, refer to Section 1.9.1 Abbreviations in the SRC Core Specification.

1.6.2 Terminology and Conventions

For the definition of the terminology and conventions used in the SRC API Specification, refer to Section 1.9.2 Terminology and Conventions in the SRC Core Specification.

2 Data Dictionary

2.1 Complex Data Objects

Table 2.1 to Table 2.48 introduce the common data objects used across the APIs defined in the SRC API Specification. Each table defines a single data object.

The column headed R/C/O in each table refers to whether the data element is required, conditional or optional. The following notation is used:

- R = Required – always present
- C = Conditional – present under certain conditions (as specified in the description)
- O = Optional – can be present

2.1.1 AcceptanceChannelData

Table 2.1: AcceptanceChannelData

Data Element	R/C/O	Constraints	Description
consumerData Type: JSONObject	C	Acceptance channel specific	Consumer supplied data, either manually entered (or supplied by other means, e.g. voice, camera etc.) or previously stored Conditionality: At least one of <code>consumerData</code> or <code>sellerData</code> is required
sellerData Type: JSONObject	C	Acceptance channel specific	Seller supplied data supplied over the acceptance channel technology, or other means Conditionality: At least one of <code>consumerData</code> or <code>sellerData</code> is required

2.1.2 AcceptanceChannelRelatedData

Table 2.2: AcceptanceChannelRelatedData

Data Element	R/C/O	Constraints	Description
acceptanceChannelType Type: AcceptanceChannelType	R	See AcceptanceChan nelType	Type of acceptance channel
acceptanceChannelTechnol ogy Type: AcceptanceChannelTechnolog y	O	See AcceptanceChan nelTechnology	Technology used to transmit/receive the acceptance channel data
acceptanceChannelData Type: AcceptanceChannelData	R	See AcceptanceChan nelData	Acceptance channel data

2.1.3 AccountReference

Table 2.3: AccountReference

Data Element	R/C/O	Constraints	Description
srcDigitalCardId Type: String	C	Max Length = 36	Reference identifier to the Digital Card representing the PAN or Payment Token Conditionality: Required when <code>consumerIdentity</code> is not present
consumerIdentity Type: ConsumerIdentity	C	See ConsumerIdentity	Primary verifiable Consumer Identity within an SRC Profile (e.g. an email address or a mobile phone number) Conditionality: Required when <code>srcDigitalCardId</code> is not present

2.1.4 AdditionalAmount

Table 2.4: AdditionalAmount

Data Element	R/C/O	Constraints	Description
additionalAmountType Type: AdditionalAmountType	R	See AdditionalAmount Type	Type of additional amount
additionalAmountValue Type: String	R		Value of the additional amount

2.1.5 Address

Table 2.5: Address

Data Element	R/C/O	Constraints	Description
addressId Type: String	O	UUID	Reference identifier of the address
name Type: String	O	Max Length = 100	Name of the Consumer
line1 Type: String	C	Max Length = 75	Address line 1 Conditionality: Required when used with the DPA Registration operation in the Management Service APIs
line2 Type: String	O	Max Length = 75	Address line 2
line3 Type: String	O	Max Length = 75	Address line 3

Data Element	R/C/O	Constraints	Description
city Type: String	C	Max Length = 50	Address city Conditionality: When used with the DPA Registration operation in the Management Service APIs at least one of the following is required: <ul style="list-style-type: none">• both <code>city</code> and <code>state</code>• <code>zip</code>
state Type: String	C	Max Length = 30	Address state Recommendation to support ISO 3166-2 format i.e. made up of ISO 3166-1 alpha 2 country code, followed by an alphanumeric string of 3 characters representing the state or sub-division Conditionality: When used with the DPA Registration operation in the Management Service APIs at least one of the following is required: <ul style="list-style-type: none">• both <code>city</code> and <code>state</code>• <code>zip</code>
zip Type: String	C	Max Length = 16	Address zip/postal code Conditionality: When used with the DPA Registration operation in the Management Service APIs at least one of the following is required: <ul style="list-style-type: none">• both <code>city</code> and <code>state</code>• <code>zip</code>

Data Element	R/C/O	Constraints	Description
countryCode Type: String	C	ISO 3166-1 alpha-2 country code	Address country code Conditionality: Required when used with the DPA Registration operation in the Management Service APIs
deliveryContactDetails Type: DeliveryContactDetails	O	See DeliveryContactDetails	Delivery contact details
createTime Type: String (Numeric)	O	UTC time in Unix epoch format	Date and time the address was created
lastUsedTime Type: String (Numeric)	O	UTC time in Unix epoch format	Date and time the address was last used

2.1.6 AppInstance

Table 2.6: AppInstance

Data Element	R/C/O	Constraints	Description
userAgent Type: String	C	N/A	User agent string of the connecting client application Conditionality: <ul style="list-style-type: none"> • Required for browsers • Optional for non-browsers
applicationName Type: String	O	Max Length = 255	Name of the connecting client application
countryCode Type: String	O	ISO 3166-1 alpha-2 country code	The country where the Consumer is accessing the service from
deviceData Type: DeviceData	O	See DeviceData	Device specific data

2.1.7 AssuranceData

Table 2.7: AssuranceData

Data Element	R/C/O	Constraints	Description
verificationData Type: List<VerificationData>	R	See VerificationData	Set of verification data structures relating to different types of assurance
eci Type: String	O	Max Length = 2	Payment System-specific value to indicate the results of the attempt to authenticate the Cardholder
cardVerificationEntity Type: String (Numeric) DEPRECATED	⊖	Length = 2	Entity performing card verification. Valid values are: <ul style="list-style-type: none">• 01 SRC Initiator• 02 SRC System• 03 SRCPI• 04 DCF• 05 DPA• 06 – 99 Others
cardVerificationMethod Type: String (Numeric) DEPRECATED	⊖	Length = 2	Card verification check to validate that the PAN is active and valid at the Card Issuer. Valid values are: <ul style="list-style-type: none">• 01 \$0 authorisation, or single unit of currency authorisation• 02 Card Verification Number validation• 03 Postal code and address verification, where supported• 04 – 20 EMVCo future use• 21 – 99 SRC System specific

Data Element	R/C/O	Constraints	Description
cardVerificationResults Type: String (Numeric) DEPRECATED	⊖	Length = 2	Verification status of the PAN. Valid values are: <ul style="list-style-type: none"> • 01 Verified • 02 Not Verified • 03 Not performed • 04 – 20 EMVCo future use • 21 – 99 SRC System specific
cardVerificationTimestamp Type: String (Numeric) DEPRECATED	⊖	UTC time in Unix epoch format	Date and time when the card verification was conducted
cardAssuranceData Type: String DEPRECATED	⊖		Data collected that is associated with the PAN and presented to the SRC System
cardholderAuthenticationEntity Type: String DEPRECATED	⊖	Max Length = 64	Entity performing Cardholder authentication

Data Element	R/C/O	Constraints	Description
cardholderAuthenticationMethod Type: String (Numeric) DEPRECATED	⊖	Length = 2	Card Issuer verification of the Cardholder. Valid values are: <ul style="list-style-type: none"> • 01 Use of a 3-D Secure ACS • 02 Mobile banking verification of the Cardholder with an authentication code • 03 Federated login systems • 04 A shared secret between the Card Issuer and the Cardholder such as One Time Passcode (OTP), activation code • 05 – 20 EMVCo future use • 21 – 99 SRC System specific
cardholderAuthenticationResults Type: String (Numeric) DEPRECATED	⊖	Length = 2	Indicates whether the Cardholder was verified or not, and what the results are when verified. <ul style="list-style-type: none"> • 01 Verified • 02 Not Verified • 03 Not performed • 04 – 20 EMVCo future use • 21 – 99 SRC System specific
cardholderAuthenticationTimestamp Type: String (Numeric) DEPRECATED	⊖	UTC time in Unix epoch format	Date and time when the Cardholder authentication was conducted

Data Element	R/C/O	Constraints	Description
cardholderAssuranceData Type: String DEPRECATED	⊖		Data collected that is associated with the Cardholder and presented to the SRC System
consumerVerificationEntity Type: String DEPRECATED	⊖	Max Length = 64	Entity performing Consumer verification
consumerVerificationMethod Type: String (Numeric) DEPRECATED	⊖	Length = 2	The verification method used to verify Consumer credential. Valid values are: <ul style="list-style-type: none"> • 01 Static Passcode • 02 SMS One Time Passcode (OTP) • 03 Keyfob or EMV cardreader One Time Passcode (OTP) • 04 Application One Time Passcode (OTP) • 05 One Time Passcode (OTP) Other • 06 Knowledge Based Authentication (KBA) • 07 Out of Band Biometrics • 08 Out of Band Login • 09 Out of Band Other • 10 Risk-Based • 11 Other • 12 - 99 EMVCo future use

Data Element	R/C/O	Constraints	Description
consumerVerificationResult Type: String (Numeric) DEPRECATED	○	Length = 2	Indicates whether the Consumer was verified or not, and what the results are when verified. Valid values are: <ul style="list-style-type: none"> 01 Verified 02 Not Verified 03 Not performed 04 – 20 EMVCo future use 21 – 99 SRC System specific
consumerVerificationTimestamp Type: String (Numeric) DEPRECATED	○	UTC time in Unix epoch format	Date and time when the Consumer verification was conducted
consumerAssuranceData Type: String DEPRECATED	○		Data collected that is associated with the Consumer for assurance purposes
deviceVerificationEntity Type: String (Numeric) DEPRECATED	○	Length = 2	Entity performing device verification. The valid values are: <ul style="list-style-type: none"> 01 SRC Initiator 02 SRC System 03 SRCPI 04 DCF 05 DPA 06 – 99 Others

Data Element	R/C/O	Constraints	Description
deviceVerificationMethod Type: String (Numeric) DEPRECATED	○	Length = 2	Verification method used to verify Consumer Device information. Valid values are: <ul style="list-style-type: none"> • 01 – 20 EMVCo future use • 21 – 99 SRC System specific
deviceVerificationResults Type: String (Numeric) DEPRECATED	○	Length = 2	Indicates whether the device was verified or not, and what the results are when verified. Valid values are: <ul style="list-style-type: none"> • 01 Verified • 02 Not Verified • 03 Not performed • 04 – 20 EMVCo future use • 21 – 99 SRC System specific
deviceVerificationTimestamp Type: String (Numeric) DEPRECATED	○	UTC time in Unix epoch format	Date and time when the device verification was conducted
deviceAssuranceData Type: String DEPRECATED	○		Data collected that is associated with the device for assurance purposes

Data Element	R/C/O	Constraints	Description
relationshipVerificationEntity Type: String (Numeric) DEPRECATED	○	Length = 2	Entity performing relationship verification of a combination of data. The valid values are: <ul style="list-style-type: none">• 01 SRC Initiator• 02 SRC System• 03 SRCPI• 04 DCF• 05 DPA• 06 – 99 Others
relationshipVerificationMethod Type: String (Numeric) DEPRECATED	○	Max Length = 2	Verification method used to verify information associated with the relationship
relationshipVerificationResults Type: String (Numeric) DEPRECATED	○	Max Length = 2	Results of the verification of the relationship of a combination of data
relationshipVerificationTimestamp Type: String (Numeric) DEPRECATED	○	UTC time in Unix epoch format	Date and time when the relationship verification was conducted
relationshipAssuranceData Type: String DEPRECATED	○		Data collected that is associated with the binding relationship for assurance purposes

2.1.8 AuthenticationContext

Table 2.8: AuthenticationContext

Data Element	R/C/O	Constraints	Description
authenticationReasons Type: List<AuthenticationReason>	R	See AuthenticationReason	
srcDpaId Type: String	C	Max length = 255	Conditionality: When authenticationReasons contains TRANSACTION_AUTHENTICATION exactly one of srcDpaId or dpaData must be provided
dpaData Type: DpaData	C		
dpaTransactionOptions Type: DpaTransactionOptions	C	See DpaTransactionOptions	Conditionality: Required when authenticationReasons contains TRANSACTION_AUTHENTICATION. In this case, dpaTransactionOptions must contain the same data that is supplied in Checkout
acquirerMerchantId Type: String	O	Max Length = 35	Acquirer-assigned Merchant identifier
acquirerBIN Type: String	O	Max Length = 11	Acquirer identification code as assigned by the Directory Server receiving the AReq message
merchantName Type: String	O		Merchant name assigned by the Acquirer or Payment System

2.1.9 AuthenticationMethod

Table 2.9: AuthenticationMethod

Data Element	R/C/O	Constraints	Description
authenticationMethodType Type: AuthenticationMethodType	R	See AuthenticationMethodType	
authenticationSubject Type: AuthenticationSubject	R	See AuthenticationSubject	
uriData Type: UriData	O	See UriData	<p>URI associated with the authentication method (only valid in the Authentication Method Lookup response)</p> <p>When authentication is invoked by launching the URI then AssuranceData, AuthenticationStatus, AuthenticationResult and any relevant session ids should be provided back asynchronously when authentication completes.</p> <p>It can be achieved by cross origin post message between the windows i.e. the caller and the authenticator.</p>

Data Element	R/C/O	Constraints	Description
authenticationCredentialReference Type: String	O	Max Length = 255	May be provided by the identity provider once an authentication is initiated to qualify the nature of the authentication method (e.g. for SMS_OTP, this may include the masked mobile number "***-***-1234", which can be displayed to the Consumer to aid method selection)
methodAttributes Type: JSONObject	O		Attributes associated with the authenticationMethod Type (see Section 2.2.1 Authentication Facilitation)

2.1.10 BusinessIdentification

Table 2.10: BusinessIdentification

Data Element	R/C/O	Constraints	Description
businessIdentificationType Type: String	C	Max Length = 50	Conditionality: Required when acquirerMerchantId is not present or when businessIdentificationValue is present
businessIdentificationValue Type: String	C	Max Length = 30	Conditionality: Required when acquirerMerchantId is not present or when businessIdentificationType is present
acquirerMerchantId Type: String	O	Max Length = 35	Acquirer-assigned merchant identifier.

2.1.11 Card

Table 2.11: Card

Data Element	R/C/O	Constraints	Description
primaryAccountNumber Type: String (Numeric)	R	Min Length = 9 Max Length = 19	Primary Account Number. A variable length, ISO/IEC 7812-compliant account number that is generated within account ranges associated with a BIN by a Card Issuer
panExpirationMonth Type: String (Numeric)	C	Length = 2	Expiration month expressed as a two-digit month (MM) Conditionality: Required when specified for the Card (PAN)
panExpirationYear Type: String (Numeric)	C	Length = 4	Expiration year expressed as a four-digit calendar year (YYYY) Conditionality: Required when specified for the Card (PAN)
cardSecurityCode Type: String (Numeric)	O	Length = 3 or 4	Card security code
cardholderFullName Type: String	O	Max Length = 100	Cardholder name
cardholderFirstName Type: String	O	Max Length = 50	Cardholder first name
cardholderLastName Type: String	O	Max Length = 50	Cardholder last name
billingAddress Type: Address	O	See Address	Billing address

Data Element	R/C/O	Constraints	Description
paymentAccountReference Type: String	O	Max Length = 29	A non-financial reference assigned to each unique PAN and used to link a payment account represented by that PAN to affiliated Payment Tokens
customerServiceEmailAddress Type: String	O	Max Length = 255	Customer service email address
customerServicePhoneNumber Type: PhoneNumber	O	See PhoneNumber	Customer service phone number
customerServiceUri Type: String	O	Max Length = 1024	Customer service webpage URI

2.1.12 CardholderData

Table 2.12: CardholderData

Data Element	R/C/O	Constraints	Description
fullName Type: String	O	Max Length = 100	Cardholder name
firstName Type: String	O	Max Length = 50	Cardholder first name
lastName Type: String	O	Max Length = 50	Cardholder last name

Data Element	R/C/O	Constraints	Description
issuerIdentity Type: String	O	Max Length = 64	Cardholder identity as known by the Card Issuer. This generally enables access to an application, website or other. Examples include username/email address/mobile number
emailAddress Type: String	O	Max Length = 255	Cardholder email address. This is Cardholder generated and represents contact or notification data
mobileNumber Type: PhoneNumber	O	See PhoneNumber	Cardholder mobile phone number
billingPhoneNumber Type: PhoneNumber	O	See PhoneNumber	Cardholder billing phone number

2.1.13 CommunicationsConsent

Table 2.13: CommunicationsConsent

Data Element	R/C/O	Constraints	Description
communicationsOptIn Type: Boolean	O	Boolean	Consumer's communications opt in preference.
affiliateCommunicationsOptIn Type: Boolean	O	Boolean	Consumer's affiliate communications opt in preference
allowEmail Type: Boolean	O	Boolean	Consumer's preference for receiving communications via email
allowText Type: Boolean	O	Boolean	Consumer's preference for receiving communications via SMS

Data Element	R/C/O	Constraints	Description
allowCall Type: Boolean	O	Boolean	Consumer's preference for receiving communications via voice calls
allowPush Type: Boolean	O	Boolean	Consumer's preference for receiving communications via a notification channel

2.1.14 ComplianceResource

Table 2.14: ComplianceResource

Data Element	R/C/O	Constraints	Description
complianceType Type: ComplianceType	R	See ComplianceType	
uri Type: String	R	Max Length = 1024	URI
version Type: String	O	Max Length = 10	Version
datePublished Type: String	O	UTC time in Unix epoch format	Date resource was published

2.1.15 ComplianceSettings

Table 2.15: ComplianceSettings

Data Element	R/C/O	Constraints	Description
complianceResources Type: List<ComplianceResource>	R	See ComplianceResource	
privacy Type: Consent DEPRECATED	O	See Consent	Consent wording for privacy policy

Data Element	R/C/O	Constraints	Description
tn Type: Consent DEPRECATED	⊖	See Consent	Consent wording for T&Cs policy
cookie Type: Consent DEPRECATED	⊖	See Consent	Consent wording for cookie policy
geoLocation Type: Consent DEPRECATED	⊖	See Consent	Consent wording for geolocation policy
communications Type: CommunicationsConsent	O	See Communications Consent	Indicates the Consumer's consent to receive communications

2.1.16 ConfirmationData DEPRECATED

Replaced by ConfirmationData2 (Section 2.1.17)

Table 2.16: ConfirmationData DEPRECATED

Data Element	R/C/O	Constraints	Description
checkoutEventType Type: String (Numeric) DEPRECATED	⊖	Length = 2	Event type associated with the update. Valid values are: <ul style="list-style-type: none"> • 01 Authorise • 02 Capture • 03 Refund • 04 Cancel • 05 Fraud • 06 Chargeback • 07 Other

Data Element	R/C/O	Constraints	Description
checkoutEventStatus Type: String (Numeric) DEPRECATED	○	Length = 2	Event type associated with the order. Valid values are: <ul style="list-style-type: none"> • 01 Created • 02 Confirmed • 03 Cancelled • 04 Fraud Cancelled • 05 Others • 06 - 50 EMVCo future use • 51 - 99 SRC System specific
confirmationStatus Type: String (Numeric) DEPRECATED	○	Length = 2	Status of the event as provided by the SRC Initiator in the Confirmation message. Valid values are: <ul style="list-style-type: none"> • 01 Success • 02 Failure • 03 Other
confirmationReason Type: String DEPRECATED	○	Max Length = 64	Description of the reason for the event associated with the order
confirmationTimestamp Type: String (Numeric) DEPRECATED	○	UTC time in Unix epoch format	Date and time of the event completion corresponding to the Confirmation event by the SRC Initiator
networkAuthorizationCode Type: String DEPRECATED	○	Max Length = 25	Authorisation code associated with an approved transaction
networkTransactionIdentifier Type: String DEPRECATED	○	Max Length = 25	Unique authorisation-related tracing value assigned by a Payment Network and provided in an authorisation response

Data Element	R/C/O	Constraints	Description
paymentNetworkReference Type: String DEPRECATED	⊖	Max Length = 25	Transaction identifier as provided by a Payment Network after authorisation has been complete
assuranceData Type: AssuranceData DEPRECATED	⊖	See AssuranceData	Assurance data
transactionAmount Type: TransactionAmount DEPRECATED	⊖	See TransactionAmount	Amount of the transaction

2.1.17 ConfirmationData2

Table 2.17: ConfirmationData2

Data Element	R/C/O	Constraints	Description
checkoutEventType Type: String (Numeric)	R	Length = 2	Event type associated with the confirmation. Valid values are: <ul style="list-style-type: none"> • 00 Place Order • 01 Authorise • 02 Capture • 03 Refund • 04 Cancel (Auth Reversal) • 05 Fraud • 06 Chargeback • 07 Cancel before Auth • 08 Auth for account validation • 09 – 50 EMVCo future use • 51 – 99 SRC System specific

Data Element	R/C/O	Constraints	Description
checkoutEventStatus Type: String (Numeric)	O	Length = 2	Event status associated with the order. Valid values are: <ul style="list-style-type: none"> • 01 Created • 02 Confirmed • 03 Cancelled • 04 Fraud Cancelled • 05 Others • 06 – 50 EMVCo future use • 51 – 99 SRC System specific
confirmationStatus Type: String (Numeric)	R	Length = 2	Status related to the <code>checkoutEventType</code> as provided by the SRC Initiator. Valid values are: <ul style="list-style-type: none"> • 01 Success • 02 Failure • 03 Other • 04 Timeout
confirmationReason Type: String	O	Max Length = 64	Description of the reason for the event associated with the order
confirmationTimestamp Type: String (Numeric)	R	UTC time in Unix epoch format	Date and time of the event set by the SRC Initiator
networkAuthorizationCode Type: String	C	Max Length = 25	Authorisation code associated with an approved transaction Conditionality: Required when the value of: <ul style="list-style-type: none"> • <code>checkoutEventType</code> is set to 01 (Authorize) or 03 (Refund); <i>and</i> • <code>confirmationStatus</code> is set to 01 (Success)

Data Element	R/C/O	Constraints	Description
networkTransactionIdentifier Type: String	O	Max Length = 25	Unique authorisation related tracing identifier assigned by a Payment Network and provided in an payment authorisation response
paymentNetworkReference Type: String	O	Max Length = 25	Transaction identifier as provided by a Payment Network payment authorisation has been completed
assuranceData Type: AssuranceData	O	See AssuranceData	Assurance data
transactionAmount Type: TransactionAmount	C	See TransactionAmount	Amount of the transaction Conditionality: Required when the value of: <ul style="list-style-type: none"> • <code>checkoutEventType</code> is set to 01 (Authorize) or 03 (Refund); <i>and</i> • <code>confirmationStatus</code> is set to 01 (Success)

2.1.18 Consent-DEPRECATED

Table 2.18: ~~Consent~~ DEPRECATED

Data Element	R/C/O	Constraints	Description
acceptedVersion Type: String DEPRECATED	O	Max Length = 10	Version accepted by the Consumer
latestVersion Type: String DEPRECATED	O	Max Length = 10	Latest version

Data Element	R/C/O	Constraints	Description
latestVersionUri Type: String DEPRECATED	○	Max Length = 1024	URI of the latest version

2.1.19 Consumer

Table 2.19: Consumer

Data Element	R/C/O	Constraints	Description
consumerIdentity Type: ConsumerIdentity	R	See ConsumerIdentity	Primary verifiable Consumer Identity within an SRC Profile (e.g. an email address or a mobile phone number)
emailAddress Type: String	○	Max Length = 255	Consumer-provided email address
mobileNumber Type: PhoneNumber	○	See PhoneNumber	Consumer-provided mobile number
nationalIdentifier Type: String	○	Max Length = 20	Geographic-specific, nationally-provided identifier for the Consumer
countryCode Type: String	○	ISO 3166-1 alpha-2 country code	Consumer-provided country code
languageCode Type: String	○	ISO 639-1 Code	Consumer-provided language choice
firstName Type: String	○	Max Length = 50	Consumer-provided first name
lastName Type: String	○	Max Length = 50	Consumer-provided last name

Data Element	R/C/O	Constraints	Description
fullName Type: String	O	Max Length = 100	Consumer-provided full name

2.1.20 ConsumerIdentity

Table 2.20: ConsumerIdentity

Data Element	R/C/O	Constraints	Description
identityProvider Type: IdentityProvider	O	See IdentityProvider	Entity or organisation that collected and verified the Consumer Identity
identityType Type: ConsumerIdentityType	R	See ConsumerIdentity Type	Type of Consumer Identity transmitted or collected
identityValue Type: String	R	Max Length = 255	Consumer Identity value that corresponds to the Consumer Identity Type

2.1.21 Dcf

Table 2.21: Dcf

Data Element	R/C/O	Constraints	Description
applicationType Type: ApplicationType	O	See ApplicationType	Type of the environment of the DCF
uri Type: String	O	Max Length = 1024	DCF URI as provided by DCF
logoUri Type: String	O	Max Length = 1024	Logo image URI provided by the DCF to support presentation

Data Element	R/C/O	Constraints	Description
name Type: String	O	Max Length = 60	Legal Name of DCF Onboarded to the SRC System

2.1.22 DeliveryContactDetails

Table 2.22: DeliveryContactDetails

Data Element	R/C/O	Constraints	Description
contactFullName Type: String	O	Max Length = 100	Consumer-provided name of the contact person
contactPhoneNumber Type: PhoneNumber	O	See PhoneNumber	Consumer-provided phone number of the contact person
numberIsVoiceOnly Type: Boolean	C		Indicates that the phone number provided is not capable of receiving text messages. Conditionality: Required when <code>contactPhoneNumber</code> is provided
contactEmailAddress Type: email	O	See Email	Consumer-provided email address of the contact person
instructions Type: String	O	Max Length = 1024	Consumer-provided delivery instructions

2.1.23 DeviceData

Table 2.23: DeviceData

Data Element	R/C/O	Constraints	Description
type Type: String	O	Max Length = 255	Type of device being used. Example values are: <ul style="list-style-type: none">• Mobile Phone• Tablet• Laptop• Personal Assistant• Connected Auto• Home Appliance• Wearable• Stationary Computer• E-Reader• Handheld Gaming Devices• Other
manufacturer Type: String	O	Max Length = 255	Manufacturer of the device
brand Type: String	O	Max Length = 255	Brand name of the device
model Type: String	O	Max Length = 255	Specific model of the device

2.1.24 DigitalCardData

Table 2.24: DigitalCardData

Data Element	R/C/O	Constraints	Description
status Type: DigitalCardStatus	R	See DigitalCardStatus	State of the Digital Card

Data Element	R/C/O	Constraints	Description
presentationName Type: String	O	Max Length = 64	Presentation text created by the Consumer to enable recognition of the PAN. This value is defined by the Consumer (e.g. nickname)
descriptorName Type: String	R	Max Length = 64	Presentation text defined by the SRC Programme that describes the PAN presented as a Digital Card
artUri Type: String	R	Max Length = 1024	URI that hosts the Card Art image to be used for presentation purposes. Can be provided by SRCPI
artHeight Type: String (Numeric)	O		Height of the card art in pixels
artWidth Type: String (Numeric)	O		Width of the card art in pixels
pendingEvents Type: List<CardPendingEvent>	C	See CardPendingEvent	Set of events that are pending completion Conditionality: Required when the value of <code>status</code> is set to PENDING
authenticationMethods List<AuthenticationMethod>	O	See AuthenticationMethod	List of available authentication methods May be provided when SRC System identifies a need to perform verification

2.1.25 DigitalCardFeature

Table 2.25: DigitalCardFeature

Data Element	R/C/O	Constraints	Description
content Type: String	R	Max Length = 1024	Content of the Digital Card Feature. The value is specific for the <code>contentType</code>
contentType Type: DigitalCardFeatureContentType	R	See DigitalCardFeatureContentType	Type of the content of the Digital Card Feature
style Type: String	O	Max Length = 1024	URI of a CSS style sheet that describes how to present a Digital Card Feature
width Type: String (Numeric)	O		Width to be applied to display of a Digital Card Feature image
height Type: String (Numeric)	O		Height to be applied to display of a Digital Card Feature image

2.1.26 DigitalCardUpdateNotification

Table 2.26: DigitalCardUpdateNotification

Data Element	R/C/O	Constraints	Description
serviceld Type: String	O	Max Length = 255	Service identifier associated to an SRC System specific configuration
srcDigitalCardId Type: String	C	Max Length = 36	Identifier of the updated card Conditionality: Required when <code>maskedCard</code> is not present

Data Element	R/C/O	Constraints	Description
authorization Type: String	O		First Party Token that may be provided if the <code>maskedCard</code> is not present
maskedCard Type: MaskedCard	C	See MaskedCard	Updated masked card data Conditionality: Required when <code>srcDigitalCardId</code> is not present
eventTimestamp Type: String (Numeric)	R	UTC time in Unix epoch format	Date and time of the card update event
srcCorrelationId Type: String	O	Max Length = 256	SRC Correlation Id corresponding to this SRC checkout transaction. May be provided if the notification occurs during checkout
reason Type: String	O	Max length = 255	Reason for the update of the card

2.1.27 DpaData

Table 2.27: DpaData

Data Element	R/C/O	Constraints	Description
dpaPresentationName Type: String	O	Max Length = 60	Merchant company name associated with the DPA to be used for presentation purposes within the user experience
dpaAddress Type: Address	O	See Address	DPA business address
dpaName Type: String	R	Max Length = 60	Legal name of registered DPA
dpaEmailAddress Type: String	O	Max Length = 255	DPA contact email address

Data Element	R/C/O	Constraints	Description
dpaPhoneNumber Type: PhoneNumber	O	See PhoneNumber	DPA contact phone number
dpaLogoUri Type: String	O	Max Length = 1024	URI of the logo of the DPA
dpaSupportEmailAddress Type: String	O	Max Length = 255	DPA support contact email address
dpaSupportPhoneNumber Type: PhoneNumber	O	See PhoneNumber	DPA support contact phone number
dpaSupportUri Type: String	O	Max Length = 1024	DPA's support URI
dpaUri Type: String	C	Max Length = 1024	A suitable unique DPA identifier. May contain the DPA business website URI or mobile application identifier in reversed domain notation or any other suitable unique DPA identifier Conditionality: Required when used with the DPA Registration operation in the Management Service APIs
applicationType Type: ApplicationType	O	See ApplicationType	Type of DPA
merchantAccountInformation Type: String	O	Max Length = 1024	Implementation specific account information for an alternative acceptance channel

Data Element	R/C/O	Constraints	Description
merchantCountryCode Type: String	C	ISO 3166-1 alpha-2 country code	The country code associated with the site or application that implements SRC Conditionality: Required when used with the DPA Registration operation in the Management Service APIs
businessId Type: BusinessIdentification	C	See BusinessIdentificat ion	Conditionality: Required when used with the DPA Registration operation in the Management Service APIs
merchantName Type: String	O	Max Length = 40	Merchant name assigned by the Acquirer or Payment System, for 3DS usage only; may be different from dpaName
merchantCategoryCode Type: String	O	Max Length = 10	
acquirerId Type: String	O	Max Length = 50	
acquirerBin Type: String	O	Max Length = 11	Acquiring institution identification code as assigned by the 3DS Directory Server receiving the AReq message, for 3DS usage only
dpaPanDataRequested Type: Boolean	O		Indicates that the merchant requests PAN-based data in the payload. Valid values are: <ul style="list-style-type: none">• true• false (default)

2.1.28 DpaTransactionOptions

Table 2.28: DpaTransactionOptions

Data Element	R/C/O	Constraints	Description
transactionAmount Type: TransactionAmount	C	See TransactionAmount	The amount of the transaction Conditionality: Required when 3DS is to be performed by SRC System (i.e. the value of <code>threeDsPreference</code> is set to ONBEHALF)
transactionType Type: TransactionType	O	See TransactionType	Type of transaction
deliveryMethod Type: DeliveryMethod	O	See DeliveryMethod	An indication of the manner in which the purchased goods are to be delivered, independent of the <code>dpaBillingPreference</code> or <code>dpaShippingPreference</code> data elements
dpaBillingPreference Type: AddressPreference	O	See AddressPreference	Type of billing address required
dpaAcceptedBillingCountries Type: List<String>	O	Array of country codes in ISO 3166-1 alpha-2 format	Billing restrictions. Payments from all the listed billing countries are accepted For example: ["US", "CA", "AU"] An empty list or the absence of this data element means that all countries are accepted.

Data Element	R/C/O	Constraints	Description
dpaShippingPreference Type: AddressPreference	O	See AddressPreference	Type of shipping address required
dpaAcceptedShippingCountries Type: List<String>	O	Array of country codes in ISO 3166-1 alpha-2 format	Shipping restrictions. Shipping region country codes that limits the selection of eligible shipping addresses For example: ["US", "CA", "AU"] An empty list or the absence of this data element means that all countries are accepted.
consumerEmailAddressRequested Type: Boolean	O		Indicates whether the DPA expects the Consumer email address to be returned in the SRC Payload
consumerNameRequested Type: Boolean	O		Indicates whether the DPA expects the Consumer name to be returned in the SRC Payload
consumerPhoneNumberRequested Type: Boolean	O		Indicates whether the DPA expects the Consumer phone number to be returned in the SRC Payload
cardholderNameRequested Type: Boolean	O		Indicates whether the DPA expects the Cardholder name to be returned in the SRC Payload

Data Element	R/C/O	Constraints	Description
consumerNationalIdentifierRequested Type: Boolean	O		Indicates whether the DPA expects the Consumer National Identifier to be returned in the SRC Payload
merchantCategoryCode Type: String	O	Length = 4	Describes the merchant's type of business, product or service
merchantCountryCode Type: String	O	ISO 3166-1alpha-2 country code	Country code of the merchant
merchantOrderId Type: String	O	UUID	Digital Payment Application generated order/invoice number corresponding to a Consumer purchase
threeDsPreference Type: ThreeDsPreference	R	See ThreeDsPreference	Merchant's 3DS preferences. This data element is not related to the Authentication Facilitation Service API operations and SDK methods
threeDsInputData Type: JSONObject	C		Merchant's 3DS input data Conditionality: Required when 3DS is to be performed by SRC System (i.e. the value of <code>threeDsPreference</code> is set to ONBEHALF)
srcTokenRequestData Type: JSONObject	O		Token specific data provided by the merchant
paymentOptions Type: List<PaymentOptions>	O	See PaymentOptions	Specifies the Dynamic Data requirement for the payload creation

Data Element	R/C/O	Constraints	Description
dpaLocale Type: String	O	ISO language country pair. [ISO 639-1 Code] [ISO 3166-1 alpha-2 country code]	Merchant's preferred locale. For example: ["en_US", "fr_CA"]
customInputData Type: JSONObject	O		Extensible container that allows DPA to pass SRC System-specific data to the SRC System
orderType Type: String	O	Length = 255	Type of the order
confirmPayment Type: Boolean	O		Default value: <code>false</code> <ul style="list-style-type: none"> DCF is expected to prompt the Consumer to confirm payment when value is set to <code>true</code> DPA is expected to prompt the Consumer to confirm payment when value is set to <code>false</code>

2.1.29 DynamicData

Table 2.29: DynamicData

Data Element	R/C/O	Constraints	Description
dynamicDataValue Type: String	C		Value of the dynamic data Conditionality: Required when the value of <code>dynamicDataType</code> is not set to NONE

Data Element	R/C/O	Constraints	Description
dynamicDataType Type: DynamicDataType	R	See DynamicDataTyp e	Type of the Dynamic Data
dynamicDataExpiration Type: String (Numeric)	O	UTC time in Unix epoch format	Date and time at which the Dynamic Data expires

2.1.30 EnrollmentReferenceData

Table 2.30: EnrollmentReferenceData

Data Element	R/C/O	Constraints	Description
enrollmentReferenceId Type: String	R	Max Length = 256	Identifier of the enrolment reference
enrollmentReferenceType Type: EnrollmentReferenceType	R	See EnrollmentRefere nceType	Type of the enrolment reference
enrollmentReferenceProvider Type: String	O	Max Length = 256	Provider of the enrolment reference

2.1.31 Error

Table 2.31: Error

Data Element	R/C/O	Constraints	Description
status Type: Numeric	R	Length = 3	HTTP status code to categorise the errors
reason Type: String	R	Max Length = 32	Error reason as associated with the HTTP status code
message Type: String	R	Max Length = 255	Error message as associated with the HTTP status code

Data Element	R/C/O	Constraints	Description
errorDetail Type: List<ErrorDetail>	O	See ErrorDetail	Error details

2.1.32 ErrorDetail

Table 2.32: ErrorDetail

Data Element	R/C/O	Constraints	Description
reason Type: String	O	Max Length = 32	Error reason
source Type: String	O	Max Length = 255	Name of the source which generated this error
message Type: String	O	Max Length = 255	Error message
sourceType Type: String	O	Max Length = 32	Type of the source

2.1.33 EventHistory

Table 2.33: EventHistory

Data Element	R/C/O	Constraints	Description
ageOfSrcPanEnrolmentSinceCreated Type: String (Numeric)	O	Max Length = 5	Age, in days, since the PAN was enrolled in the SRC System
srcAgeSinceLastSuccessfulTransaction Type: String (Numeric)	O	Max Length = 5	Age, in days, since the PAN/Digital Card/SRC Profile was successfully used for a transaction
ageOfSrcRelationship Type: String (Numeric)	O	Max Length = 5	Age, in days, of the SRC Profile in the SRC System

Data Element	R/C/O	Constraints	Description
ageOfConsumerRelationship Type: String (Numeric)	O	Max Length = 5	Age, in days, since the Consumer profile binding event occurred at the SRC Profile
billingAndShippingRelationship Type: String	O	Length = 2	Relationship between the Cardholder billing and shipping information. Valid values are: <ul style="list-style-type: none"> • 01 Same as Cardholder's billing address • 02 Consumer's preferred shipping address • 03 Consumer other address
shippingAddressUsageNew Type: String (Numeric)	O	UTC time in Unix epoch format	Date when the shipping address used for this transaction was first used with the SRC Initiator
ageOfShippingAddressUsage Type: String (Numeric)	O	Max Length = 5	Age, in days, since shipping address used for this transaction was first used by the SRC Initiator

2.1.34 IdentityValidationChannel

Table 2.34: IdentityValidationChannel

Data Element	R/C/O	Constraints	Description
validationChannelId Type: String	R	Max Length = 36	Reference identifier of the validation channel
identityProvider Type: IdentityProvider	O	See IdentityProvider	Entity or organisation that can validate the identity

Data Element	R/C/O	Constraints	Description
identityType Type: IdentityValidationChannelType	R	See IdentityValidationChannelType	Type of the identity validation channel (e.g. email, SMS)
maskedValidationChannel Type: String	O	Max Length = 255	Masked identity validation channel (e.g. masked email, masked mobile number)

2.1.35 MaskedAddress

Table 2.35: MaskedAddress

Data Element	R/C/O	Constraints	Description
addressId Type: String	R	UUID	Identifier used to point to the address
name Type: String	O	Max Length = 100	Name of the individual receiving the delivered goods or service. Only applicable for the shipping address
line1 Type: String	O	Max Length = 75	Address line 1
line2 Type: String	O	Max Length = 75	Address line 2
line3 Type: String	O	Max Length = 75	Address line 3
city Type: String	O	Max Length = 50	Address city

Data Element	R/C/O	Constraints	Description
state Type: String	O	Max Length = 30	Address state Recommendation to support ISO 3166-2 format i.e. made up of ISO 3166-1 alpha 2 country code, followed by an alphanumeric string of 3 characters representing the state or sub-division
countryCode Type: String	O	ISO 3166-1 alpha-2 country code	Address country code
zip Type: String	O	Max Length = 16	Address zip/postal code
createTime Type: String (Numeric)	O	UTC time in Unix epoch format	Date and time the address was created
lastUsedTime Type: String (Numeric)	O	UTC time in Unix epoch format	Date and time the address was last used

2.1.36 MaskedCard

Table 2.36: MaskedCard

Data Element	R/C/O	Constraints	Description
srcDigitalCardId Type: String	C	Max Length = 36	Reference identifier to the Digital Card representing the PAN or Payment Token Conditionality: <ul style="list-style-type: none"> • Required when returned to an SRCI or DCF • Optional when returned to an SRCPI

Data Element	R/C/O	Constraints	Description
enrollmentReferenceData Type: EnrollmentReferenceData	O	See EnrollmentReferenceData	Contains enrolment reference identifier as per the enrolment reference type
cofEligible Type: Boolean	O		Indicates that the card is eligible for the Merchant Digital Card-on-File use case
srcPaymentCardId Type: String	C	Max Length = 36	Reference identifier to the PAN that enables the SRC System to communicate with the SRCPI without transmitting the actual PAN. It is associated with the SRC Profile to which the Payment Card belongs and is unique within an SRC System Conditionality: Required when returned to the SRCPI
panBin Type: String (Numeric)	R	Max Length = PAN Length - 10	First significant digits of the PAN in an unmasked form
panLastFour Type: String (Numeric)	R	Length = 4	Last four digits of the PAN in an unmasked form
tokenBinRange Type: String (Numeric)	C	Max Length = Payment Token Length - 10	Specific BIN range or subset of the BIN Range that has been designated only for the purpose of issuing Payment Tokens in an unmasked form Conditionality: Required when a Payment Token is used

Data Element	R/C/O	Constraints	Description
tokenLastFour Type: String (Numeric)	C	Length = 4	Last four digits of the Payment Token in an unmasked form Conditionality: Required when a Payment Token is used
digitalCardData Type: DigitalCardData	R	See DigitalCardData	Contains Digital Card information that is used in the acceptance environment and user interface. It refers to the actual PAN or Payment Token without disclosing either
maskedCardholderFullName Type: String	O	Max Length = 100	Masked Cardholder name
maskedCardholderFirstName Type: String	O	Max Length = 50	Masked Cardholder first name
maskedCardholderLastName Type: String	O	Max Length = 50	Masked Cardholder last name
panExpirationMonth Type: String (Numeric)	C	Length = 2	Expiration month expressed as a two-digit month (MM) used for presentation purposes Conditionality: Required when specified for the card (PAN)

Data Element	R/C/O	Constraints	Description
panExpirationYear Type: String (Numeric)	C	Length = 4	Expiration year expressed as four-digit calendar year (YYYY), used for presentation purposes Conditionality: Required when specified for the card (PAN)
paymentCardDescriptor Type: String	O	Max Length = 32	Conveys the card brand, and will be a free-form string, to be defined within an SRC Programme
paymentCardType Type: String	O	Max Length = 32	Conveys the card type
digitalCardFeatures Type: List<DigitalCardFeature>	O	See DigitalCardFeature	Attributes related to the Digital Card Features that should be displayed to the Consumer
countryCode Type: String	O	ISO 3166-1 alpha-2 country code	Country code of issuance associated with the Card Issuer's BIN license
maskedBillingAddress Type: MaskedAddress	O	See MaskedAddress	Masked billing address associated with the card
complianceSettings Type: ComplianceSettings	O	See ComplianceSettings	Consumer compliance settings
dcf Type: Dcf	O	See Dcf	Digital Card Facilitator associated with the card
serviceld Type: String	O	Max Length = 255	Service identifier associated to an SRC System specific configuration

Data Element	R/C/O	Constraints	Description
paymentAccountReference Type: String	O	Max Length = 29	A non-financial reference assigned to each unique PAN and used to link a payment account represented by that PAN to affiliated Payment Tokens
customerServiceEmailAddress Type: String	O	Max Length = 255	Customer service email address
customerServicePhoneNumber Type: PhoneNumber	O	See PhoneNumber	Customer service phone number
customerServiceUri Type: String	O	Max Length = 1024	Customer service webpage URI
dateOfCardCreated Type: String (Numeric)	R	UTC time in Unix epoch format	Date when card was enrolled into the SRC System
dateOfCardLastUsed Type: String (Numeric)	O	UTC time in Unix epoch format	Date when card was last used for an SRC transaction

2.1.37 MaskedConsumer

Table 2.37: MaskedConsumer

Data Element	R/C/O	Constraints	Description
srcConsumerId Type: String	O	UUID	Reference identifier generated by the SRC System
pendingEvents Type: List<ConsumerPendingEvent>	O	See ConsumerPendingEvent	Set of events that are pending completion (e.g. re-acceptance of consent)

Data Element	R/C/O	Constraints	Description
maskedConsumerIdentity Type: MaskedConsumerIdentity	R	See MaskedConsumerIdentity	Masked value of the primary verifiable Consumer Identity within an SRC Profile (e.g. an email address or a mobile phone number)
maskedEmailAddress Type: String	O	Max Length = 255	Masked Consumer email address
maskedMobileNumber Type: PhoneNumber	O	See PhoneNumber	Masked Consumer mobile phone number
maskedNationalIdentifier Type: String	O	Max Length = 20	Masked Consumer national identifier
complianceSettings Type: ComplianceSettings	O	See ComplianceSettings	Consumer compliance settings
countryCode Type: String	O	ISO 3166-1 alpha-2 country code	Consumer-provided country code
languageCode Type: String	O	ISO 639-1 Code	Consumer-provided language choice
status Type: ConsumerStatus	R	See ConsumerStatus	Current status of the Consumer
maskedFirstName Type: String	O	Max Length = 50	Masked Consumer first name
maskedLastName Type: String	O	Max Length = 50	Masked Consumer last name
maskedFullname Type: String	O	Max Length = 100	Masked Consumer name

Data Element	R/C/O	Constraints	Description
dateConsumerAdded Type: String (Numeric)	R	UTC time in Unix epoch format	Date Consumer was added to the SRC System
dateConsumerLastUsed Type: String (Numeric)	O	UTC time in Unix epoch format	Date Consumer last transacted as determined by the SRC System

2.1.38 MaskedConsumerIdentity

Table 2.38: MaskedConsumerIdentity

Data Element	R/C/O	Constraints	Description
identityProvider Type: IdentityProvider	O	See IdentityProvider	Entity or organisation that collected and verifies the Consumer Identity
identityType Type: ConsumerIdentityType	R	See ConsumerIdentity Type	Type of Consumer Identity transmitted or collected
maskedIdentityValue Type: String	R	Max Length = 255	Masked Consumer Identity value (e.g. masked email address or masked mobile phone number)

2.1.39 Payload

Table 2.39: Payload

Data Element	R/C/O	Constraints	Description
card Type: Card	C	See Card	<p>Card data associated with the PAN used for the purchase</p> <p>Conditionality: Required when the:</p> <ul style="list-style-type: none">• value of the relevant data element of type <code>PayloadTypeIndicator</code> was set to FULL or PAYMENT; <i>and</i>• SRC System determines that a PAN-based payload must be returned. <p>A <code>card</code> is required if a <code>token</code> is not present. <code>card</code> and <code>token</code> are mutually exclusive</p>

Data Element	R/C/O	Constraints	Description
token Type: PaymentToken	C	See PaymentToken	<p>Payment Token data associated with the PAN used for the purchase</p> <p>Conditionality: Required when the:</p> <ul style="list-style-type: none">• Value of the relevant data element of type <code>PayloadTypeIndicator</code> or was set to FULL or PAYMENT; <i>and</i>• SRC System determines that a Payment Token-based payload must be returned <p>A <code>token</code> is required if a <code>card</code> is not present. <code>card</code> and <code>token</code> are mutually exclusive</p>
shippingAddress Type: Address	C	See Address	<p>Shipping address as required for the delivery of the goods/services being purchased</p> <p>Conditionality: Required when:</p> <ul style="list-style-type: none">• The value of the relevant data element of type <code>PayloadTypeIndicator</code> or was set to FULL or NON_PAYMENT; <i>and</i>• Identified shipping address is available in the SRC Profile; <i>and</i>• Shipping address was requested (based on <code>dpaShippingPreference</code>)

Data Element	R/C/O	Constraints	Description
consumerEmailAddress Type: String	C	Max Length = 255	Consumer-provided email address Conditionality: Required when: <ul style="list-style-type: none">• The value of the relevant data element of type <code>PayloadTypeIndicator</code> or was set to FULL or NON_PAYMENT; <i>and</i>• Email address is available in the SRC Profile; <i>and</i>• Email address was requested (<code>consumerEmailAddressRequested</code> set to true)
consumerFirstName Type: String	C	Max Length = 50	Consumer-provided first name Conditionality: Required when: <ul style="list-style-type: none">• The value of the relevant data element of type <code>PayloadTypeIndicator</code> or was set to FULL or NON_PAYMENT; <i>and</i>• Consumer first name is available in the SRC Profile; <i>and</i>• Consumer name was requested (<code>consumerNameRequested</code> set to true)

Data Element	R/C/O	Constraints	Description
consumerLastName Type: String	C	Max Length = 50	Consumer-provided last name Conditionality: Required when: <ul style="list-style-type: none">• The value of the relevant data element of type <code>PayloadTypeIndicator</code> or was set to FULL or NON_PAYMENT; <i>and</i>• Consumer last name is available in the SRC Profile; <i>and</i>• Consumer name was requested (<code>consumerNameRequested</code> set to true)
consumerFullName Type: String	C	Max Length = 100	Consumer-provided name Conditionality: Required when: <ul style="list-style-type: none">• The value of the relevant data element of type <code>PayloadTypeIndicator</code> or was set to FULL or NON_PAYMENT; <i>and</i>• Consumer name is available in the SRC Profile; <i>and</i>• Consumer name was requested (<code>consumerNameRequested</code> set to true)

Data Element	R/C/O	Constraints	Description
consumerMobileNumber Type: PhoneNumber	C	See Phonenumber	Consumer-provided mobile number Conditionality: Required when: <ul style="list-style-type: none">• The value of the relevant data element of type <code>PayloadTypeIndicator</code> was set to FULL or NON_PAYMENT; and• Consumer mobile number is available in the SRC Profile; and• Consumer mobile number is requested (<code>consumerPhoneNumberRequested</code> set to true)
consumerNationalIdentifier Type: String	O	Max Length = 20	Consumer National Identifier as available in SRC Profile
srcTokenResultsData Type: JSONObject	O		SRC System specific Token data
dynamicData Type: List<DynamicData>	R	See DynamicData	Dynamic data, generated using the <code>dynamicDataType</code> preference indicated in <code>paymentOptions</code>

Data Element	R/C/O	Constraints	Description
billingAddress Type: Address	C	See Address	Billing address associated with the card used for the purchase Conditionality: Required when: <ul style="list-style-type: none">• The value of the relevant data element of type <code>PayloadTypeIndicator</code> or was set to FULL or NON_PAYMENT; <i>and</i>• Billing address is available in the SRC Profile; <i>and</i>• Billing address was requested (based on <code>dpaBillingPreference</code> or statically derived using the default configured during DPA Registration)
threeDsOutputData Type: JSONObject	C		Result of 3DS payment authentication Conditionality: Required when: <ul style="list-style-type: none">• the value for <code>threeDsPreference</code> was set to ONBEHALF; <i>and</i>• 3DS authentication has been performed

2.1.40 PaymentOptions

Table 2.40: PaymentOptions

Data Element	R/C/O	Constraints	Description
dpaDynamicDataTtlMinutes Type: String (Numeric)	O		Requested “Time to Live” (expiry period) of the Dynamic Data, specified in minutes
dynamicDataType Type: DynamicDataType	O	See DynamicDataTy e	Type of Dynamic Data required in the payload

2.1.41 PaymentToken

Table 2.41: PaymentToken

Data Element	R/C/O	Constraints	Description
paymentToken Type: String	R	ISO/IEC 7812 format	Payment Token
tokenExpirationMonth Type: String (Numeric)	C	Length = 2	Expiration month expressed as a two-digit month (MM) Conditionality: Required when specified for the Payment Token
tokenExpirationYear Type: String (Numeric)	C	Length = 4	Expiration year expressed as a four-digit calendar year (YYYY) Conditionality: Required when specified for the Payment Token
cardholderFullName Type: String	O	Max Length = 100	Cardholder name

Data Element	R/C/O	Constraints	Description
cardholderFirstName Type: String	O	Max Length = 50	Cardholder first name
cardholderLastName Type: String	O	Max Length = 50	Cardholder last name
paymentAccountReference Type: String	O	Max Length = 29	A non-financial reference assigned to each unique PAN and used to link a payment account represented by that PAN to affiliated Payment Tokens

2.1.42 PhoneNumber

Table 2.42: PhoneNumber

Data Element	R/C/O	Constraints	Description
countryCode Type: String	R	Min Length = 1 Max Length = 4	Phone number country code as defined by the International Telecommunication Union
phoneNumber Type: String	R	Min Length = 4 Max Length = 14	Phone number without country code

2.1.43 RecognitionData

Table 2.43: RecognitionData

Data Element	R/C/O	Constraints	Description
srcCorrelationId Type: String	O	Max Length = 256	Unique identifier generated by an SRC System

idTokens Type: List<JWT>	C		List of the Federated ID Tokens issued by the SRC System based on the successful recognition of the instance of the returning Consumer's web browser. Conditionality: If the instance of the web browser has been recognised, at least a single Federated ID Token shall be provided in the list
srcSystemUri Type: String	C	Case sensitive URI using the https scheme that contains scheme and full qualified domain name of the host only	SRC System URI to identify the SRC System that generates the srcCorrelationId Conditionality: Required when srcCorrelationId is provided and idTokens is not provided

2.1.44 SrcProfile

Table 2.44: SrcProfile

Data Element	R/C/O	Constraints	Description
maskedCards Type: List<MaskedCard>	O	See MaskedCard	Masked card data associated with the SRC Profile
maskedShippingAddresses Type: List<MaskedAddress>	O	See MaskedAddress	Masked shipping address data associated with the SRC Profile

Data Element	R/C/O	Constraints	Description
maskedConsumer Type: MaskedConsumer	C	See MaskedConsumer	Masked Consumer data associated with the SRC Profile Conditionality: Required for non-device bound SRC Profiles
authorization Type: String	R		First party authorisation token as defined in Section 5.1.4 Authorisation

2.1.45 TransactionAmount

Table 2.45: TransactionAmount

Data Element	R/C/O	Constraints	Description
transactionAmount Type: Number	R	Max Length = 18	Amount of the transaction represented as a floating-point number
transactionCurrencyCode Type: String	R	ISO 4217 currency code	Currency in which the transaction amount is expressed. It is up to the SRC Programme to determine whether the currency code is: <ul style="list-style-type: none">• Alphabetic• Numeric• Both
additionalAmounts Type: List<AdditionalAmount>	O		A list of additional amounts related to the transaction

2.1.46 VerificationData

Table 2.46: VerificationData

Data Element	R/C/O	Constraints	Description
verificationType Type: VerificationType	R	See VerificationType	Type of the verification data
verificationEntity Type: String (Numeric)	R	Length = 2	Entity performing the verification See Table 2.47
verificationEvents Type: List<String (Numeric)>	O	Array of two digit codes as defined in Table 2.47	Event where the verification occurred See Table 2.47
verificationMethod Type: String (Numeric)	R	Length = 2	Method of the verification See Table 2.47
verificationResults Type: String (Numeric)	R	Length = 2	Result of the verification See Table 2.47
verificationTimestamp Type: String (Numeric)	R	UTC time in Unix epoch format	Date and time when the verification was conducted
methodResults Type: JSONObject	O		Attributes associated with the authentication method (see Section 2.2.1 Authentication Facilitation)
additionalData Type: String	O		Data collected during the verification process

The `VerificationData` structure can contain data relating to various entities within the SRC Specifications. Table 2.47 provides valid values for individual attributes of the structure, depending on the type of the verification.

Table 2.47: VerificationData Values

Verification Type	Verification Entity	Verification Event	Verification Method	Verification Results
CARD	<p>Entity performing or initiating card verification. Valid values are:</p> <ul style="list-style-type: none"> • 01 SRC Initiator • 02 SRC System • 03 SRCPI • 04 DCF • 05 DPA • 06– 20 EMVCo future use • 21 – 99 SRC System specific 	<p>Event where the verification occurred. Valid values are:</p> <ul style="list-style-type: none"> • 01 – 20 EMVCo future use • 21 – 99 SRC System specific 	<p>Validates that the PAN is active and valid at the Card Issuer. Valid values are:</p> <ul style="list-style-type: none"> • 01 \$0 authorisation, or single unit of currency authorisation • 02 Card Verification Number validation • 03 Postal code and address verification, where supported • 04 – 09 EMVCo future use • 10 Card Issuer Account Verification • 11 Card Issuer Interactive Cardholder Authentication – 1 Factor • 12 Card Issuer Interactive Cardholder Authentication – 2 Factor • 13 Card Issuer Risk Oriented Non-Interactive Cardholder Authentication • 14 Card Issuer Asserted Authentication • 15 – 20 EMVCo future use • 21 – 99 SRC System specific 	<p>Verification status of the PAN. Valid values are:</p> <ul style="list-style-type: none"> • 01 Verified • 02 Not Verified • 03 Not performed • 04 Not Required • 05 – 20 EMVCo future use • 21 – 99 SRC System specific

Verification Type	Verification Entity	Verification Event	Verification Method	Verification Results
CARDHOLDER	<p>Entity performing or initiating Cardholder authentication. Valid values are:</p> <ul style="list-style-type: none"> • 01 SRC Initiator • 02 SRC System • 03 SRCPI • 04 DCF • 05 DPA • 06– 20 EMVCo future use • 21 – 99 SRC System specific 	<p>Event where the verification occurred. Valid values are:</p> <ul style="list-style-type: none"> • 01 Payment transaction • 02 Add card/Card enrolment • 03 SRC Profile Access • 04 Account Verification • 05 – 20 EMVCo future use • 21 – 99 SRC System specific 	<p>Card Issuer verification of the Cardholder. Valid values are:</p> <ul style="list-style-type: none"> • 01 Use of an EMV 3-D Secure ACS • 02 App based authentication • 03 Federated login systems • 04 A shared secret between the Card Issuer and the Cardholder such as One Time Passcode (OTP), activation code • 05 No authentication • 06 Proprietary method of authentication • 07 FIDO2 • 08 SPC • 09 – 20 EMVCo future use • 21 – 99 SRC System specific 	<p>Indicates whether the Cardholder was verified or not, and what the results are when verified. Valid values are:</p> <ul style="list-style-type: none"> • 01 Verified • 02 Not Verified • 03 Not performed • 04 Not required • 05 – 20 EMVCo future use • 21 – 99 SRC System specific

Verification Type	Verification Entity	Verification Event	Verification Method	Verification Results
CONSUMER	<p>Entity performing or initiating Consumer verification. Valid values are:</p> <ul style="list-style-type: none"> • 01 SRC Initiator • 02 SRC System • 03 SRCPI • 04 DCF • 05 DPA • 06– 20 EMVCo future use • 21 – 99 SRC System specific 	<p>Event where the verification occurred. Valid values are:</p> <ul style="list-style-type: none"> • 01 – 20 EMVCo future use • 21 – 99 SRC System specific 	<p>Verification method used to verify the Consumer credential. Valid values are:</p> <ul style="list-style-type: none"> • 01 Static Passcode • 02 SMS One Time Passcode (OTP) • 03 Keyfob or EMV cardreader One Time Passcode (OTP) • 04 Application One Time Passcode (OTP) • 05 One Time Passcode (OTP) Other • 06 Knowledge Based Authentication (KBA) • 07 Out of Band Biometrics • 08 Out of Band Login • 09 Out of Band Other • 10 Risk-Based • 11 Other • 12 FIDO2 • 13 – 20 EMVCo future use • 21 – 99 SRC System specific 	<p>Indicates whether the Consumer was verified or not, and what the results are when verified. Valid values are:</p> <ul style="list-style-type: none"> • 01 Verified • 02 Not Verified • 03 Not performed • 04 Not Required • 05 – 20 EMVCo future use • 21 – 99 SRC System specific

Verification Type	Verification Entity	Verification Event	Verification Method	Verification Results
DEVICE	Entity performing or initiating Device verification. Valid values are: <ul style="list-style-type: none">• 01 SRC Initiator• 02 SRC System• 03 SRCPI• 04 DCF• 05 DPA• 06– 20 EMVCo future use• 21 – 99 SRC System specific	Event where the verification occurred. Valid values are: <ul style="list-style-type: none">• 01 – 20 EMVCo future use• 21 – 99 SRC System specific	Verification method used to verify Consumer Device information. Valid values are: <ul style="list-style-type: none">• 01 App Binding (App Instance ID)• 02 – 20 EMVCo future use• 21 – 99 SRC System specific	Indicates whether the device was verified or not, and what the results are when verified. Valid values are: <ul style="list-style-type: none">• 01 Verified• 02 Not Verified• 03 Not performed• 04 Not Required• 05 – 20 EMVCo future use• 21 – 99 SRC System specific

Verification Type	Verification Entity	Verification Event	Verification Method	Verification Results
RELATIONSHIP	Entity performing or initiating relationship verification of a combination of data. Valid values are: <ul style="list-style-type: none">• 01 SRC Initiator• 02 SRC System• 03 SRCPI• 04 DCF• 05 DPA• 06– 20 EMVCo future use• 21 – 99 SRC System specific	Event where the verification occurred. Valid values are: <ul style="list-style-type: none">• 01 – 20 EMVCo future use• 21 – 99 SRC System specific	Verification method used to verify information associated with the relationship.	Results of the verification of the relationship of a combination of data.

2.1.47 UriData

Table 2.48: UriData

Data Element	R/C/O	Constraints	Description
uri Type: String	R	Max Length = 2048	URI
uriType Type: UriType	R	See UriType	

2.2 JSON Attributes

2.2.1 Authentication Facilitation

This section describes the JSON attributes used with the `methodAttributes` and `methodResults` data structures for the Authentication Facilitation Service (Section 5.8) and equivalent SDK methods (see SRC JavaScript SDK). Optionally, they may be used in other API services and equivalent SDK methods where authentication is required.

The contents of `methodAttributes` / `methodResults` depends on the value of `authenticationMethodType` and on the API operation / SDK method being called.

`methodAttributes` is included as follows:

- Within the Authenticate response
- As part of AuthenticationMethod within the:
 - Authentication Methods Lookup response
 - Authenticate request

`methodResults` is part of `VerificationData` which is part of `AssuranceData`, which is returned in the following:

- Authentication Methods Lookup response
- Authenticate response

When the `authenticationMethodType` is `CSC_VALIDATION` then `methodAttributes` in the Authenticate request is given in Table 2.49.

Table 2.49: JSON Attributes for CSC_VALIDATION

Data Element	R/C/O	Constraints	Description
cardSecurityCode Type: String	R	Length = 3 or 4	Card Security Code

When the `authenticationMethodType` is one of:

- SMS_OTP
- EMAIL_OTP
- APP_OTP

then `methodAttributes` in the Authenticate request is given in Table 2.50.

Table 2.50: JSON Attributes for SMS_OTP, EMAIL_OTP, APP_OTP

Data Element	R/C/O	Constraints	Description
otpValue Type: String	R	Max Length = 16	OTP value

When the `authenticationMethodType` is ADDRESS_VERFICATION then `methodAttributes` in the Authenticate request is given in Table 2.51.

Table 2.51: JSON Attributes for ADDRESS_VERFICATION

Data Element	R/C/O	Constraints	Description
billingAddress Type: Address	R	See Address	Billing address data

When the `authenticationMethodType` is SPC then `methodAttributes` is as follows:

- Table 2.52: Authenticate response
- Table 2.53: Authenticate request

The JSON objects in Table 2.52 and Table 2.53 are defined in the W3C specification Secure Payment Confirmation (see <https://www.w3.org/TR/secure-payment-confirmation/> for more details).

Table 2.52: JSON Attributes for SPC (Authenticate response)

Data Element	R/C/O	Constraints	Description
spcRequest Type: JSONObject	R		See W3C specification Secure Payment Confirmation

Table 2.53: JSON Attributes for SPC (Authenticate request)

Data Element	R/C/O	Constraints	Description
spcResponse Type: JSONObject	R		See W3C specification Secure Payment Confirmation

When the `authenticationMethodType` is 3DS, then `methodAttributes` / `methodResults` contains `threeDsData` as shown in Table 2.54. Examples of the contents of `threeDsData` for various API operations / SDK methods are given below, but `threeDsData` may contain other data as specified in the EMV 3-D Secure Specification.

Within `methodAttributes`, `threeDsData` may contain:

- Authentication Methods Lookup response: 3DS method related data (e.g. `threeDsMethodUrl`¹)
- Authenticate response: ACS related data if step-up is required (e.g. `acsSignedContent`¹)

Within `methodResults`, `threeDsData` may contain data such as `tranStatus` and `tranStatusReason` when 3DS is completed:

- Authenticate response

Table 2.54: JSON Attributes for 3DS

Data Element	R/C/O	Constraints	Description
threeDsData Type: JSONObject	R		See EMV 3-D Secure Specification for detailed data objects

¹ These data elements are defined in EMV 3DS

When authentication is successfully completed for an authenticationsubject of CONSUMER, then methodResults in AssuranceData includes the federated identity token as shown in Table 2.55.

Table 2.55: JSON Attributes for Consumer Authentication

Data Element	R/C/O	Constraints	Description
idtoken Type: JWT	R	See Section 3 Federated Identity	Federated identity token

2.3 Enumerations

Note: the enumeration values set out below are not exhaustive. Other values may be added in future versions of this SRC API Specification, or may be defined within the scope of a specific implementation.

Table 2.56: Enumerations

Name	Valid Values
AcceptanceChannelType	<ul style="list-style-type: none">• EMV_MERCHANT_PRESENTED_MODE
AcceptanceChannelTechnology	<ul style="list-style-type: none">• QR_CODE
Action	<ul style="list-style-type: none">• ACTIVATION• DEACTIVATION• REGISTRATION• UPDATE
AdditionalAmountType	<ul style="list-style-type: none">• TIP• CONVENIENCE_FEE• SUB_TOTAL
AddressPreference	<ul style="list-style-type: none">• NONE• FULL• POSTAL_COUNTRY

Name	Valid Values
ApplicationType	<ul style="list-style-type: none">• IOT_DEVICE• MOBILE_APP• WEB_BROWSER• OTHER
AuthenticationReason	<ul style="list-style-type: none">• CARD_VERIFICATION• CONSUMER_IDENTITY_VALIDATION• ENROL_FINANCIAL_INSTRUMENT• TRANSACTION_AUTHENTICATION
AuthenticationMethodType	<ul style="list-style-type: none">• SMS_OTP• EMAIL_OTP• APP_OTP• 3DS• CSC_VALIDATION• APP_AUTHENTICATON• ADDRESS_VERIFICATION• FIDO2• SPC• MANAGED_AUTHENTICATION
AuthenticationSubject	<ul style="list-style-type: none">• CARDHOLDER• CONSUMER• CARD
AuthenticationStatus	<ul style="list-style-type: none">• COMPLETE• PENDING• PENDING_CHALLENGE• CANCELLED• EXPIRED• NOT_SUPPORTED
AuthenticationResult	<ul style="list-style-type: none">• AUTHENTICATED• NOT_AUTHENTICATED
BindingStatus	<ul style="list-style-type: none">• BIND• UNBIND
CardDeletionReason	<ul style="list-style-type: none">• SUSPECTED_FRAUD• ACCOUNT_CLOSED

Name	Valid Values
CardPendingEvent	<ul style="list-style-type: none">• PENDING_AVS• PENDING_CSC• PENDING_CONSUMER_IDV• PENDING_SCA (DEPRECATED) <i>replaced by</i>• PENDING_CARDHOLDER_AUTHENTICATION
ComplianceType	<ul style="list-style-type: none">• PRIVACY_POLICY• REMEMBER_ME• TERMS_AND_CONDITIONS• COOKIE• GEOLOCATION
ConsumerIdentityType	<ul style="list-style-type: none">• EMAIL_ADDRESS• MOBILE_PHONE_NUMBER
ConsumerPendingEvent	<ul style="list-style-type: none">• PENDING_RE_CONSENT
ConsumerStatus	<ul style="list-style-type: none">• ACTIVE• SUSPENDED• LOCKED
DcfActionCode	<ul style="list-style-type: none">• COMPLETE• PENDING_AUTHENTICATION• CHANGE_CARD• ADD_CARD• SWITCH_CONSUMER• CANCEL• ERROR
DeliveryMethod	<ul style="list-style-type: none">• NO_DELIVERY• ADDRESS_BILLING• ADDRESS_ON_FILE• ADDRESS_OTHER• PICKUP• ELECTRONIC
DigitalCardFeatureContent Type	<ul style="list-style-type: none">• TEXT_STRING• IMAGE_URL• CONTENT_URL• LINK_URL

Name	Valid Values
DigitalCardStatus	<ul style="list-style-type: none">• ACTIVE• SUSPENDED• EXPIRED• PENDING• CANCELLED
DynamicDataType	<ul style="list-style-type: none">• CARD_APPLICATION_CRYPTOGram_SHORT_FORM• CARD_APPLICATION_CRYPTOGram_LONG_FORM• DYNAMIC_CARD_SECURITY_CODE• CARDHOLDER_AUTHENTICATION_CRYPTOGram• NONE
EnrollmentReferenceType	<ul style="list-style-type: none">• SRC_DIGITAL_CARD_ID• SRC_PAYMENT_CARD_ID• COF_REFERENCE_ID
IdentityProvider	<ul style="list-style-type: none">• SRC
IdentityValidationChannel Type	<ul style="list-style-type: none">• EMAIL• SMS• OUT_OF_BAND
Origin	<ul style="list-style-type: none">• CARDHOLDER• MERCHANT• ISSUER
PayloadTypeIndicator	<ul style="list-style-type: none">• SUMMARY• FULL• PAYMENT• NON_PAYMENT
SrciActionCode	<ul style="list-style-type: none">• NEW_USER• AUTH_FAILED• AUTH_SKIPPED
ThreeDsPreference	<ul style="list-style-type: none">• NONE• SELF• ONBEHALF

Name	Valid Values
TransactionType	<ul style="list-style-type: none">• PURCHASE• BILL_PAYMENT• MONEY_TRANSFER• DISBURSEMENT• P2P
UriType	<ul style="list-style-type: none">• APP_URI• WEB_URI
VerificationType	<ul style="list-style-type: none">• CARD• CARDHOLDER• CONSUMER• DEVICE• RELATIONSHIP

2.4 Signed Checkout Objects

2.4.1 Checkout Request JWS

The Checkout Request JWS is a signed object generated by the SRC System for the SRCI front-end to pass to the DCF front-end. The SRC System can subsequently recognise/verify this JWS when it is provided by the DCF front-end in the Checkout operation.

Note: The language within the descriptions in Table 2.57 and Table 2.58 is taken directly from the relevant RFC.

Table 2.57: Checkout Request JOSE Header

Parameter Name	R/C/O	Description
alg	R	Algorithm used to digitally sign the payload according to RFC 7518 Section 3.1: <ul style="list-style-type: none">• 'None' is not supported.• 'PS256' is preferred to 'RS256' following the recommendation in RFC 3447
kid	R	Key ID of the cryptographic public key of the signing SRC System.

		<p>Relying party SHOULD use the key ID to select the appropriate key to verify the signature.</p> <p>The key type of the public key identified by the key ID MUST match the type of the signing algorithm.</p>
--	--	--

Table 2.58: Checkout Request Claim Set

Claim Name	Cardinality	Notes
iss	1	<p>Value has to be URI or other identifier of the SRC System that generated this JWS. The format of the identifier is specific to SRC Programme.</p> <p>Sample value of the URI: https://srcsystem1.com</p>
exp	1	<p>Expiration time in UTC and unix/epoch format. This is useful for the cases where the transaction is abandoned and the JWS can be used for one-time attack, where jti cannot help.</p>
iat	1	<p>Issuance time in UTC and unix/epoch format</p> <p>Time at which the JWS was issued. This should not be before the current date/time.</p>
jti	0..1	<p>Provides a unique identifier for the JWS. The value is a case-sensitive string. This helps against replay attacks</p>
jti_IDToken	0..1	<p>Populated from the <code>idToken_JWT.jti</code>, if the authorisation is the <code>idToken</code></p>
srcInitiatorId	1	<p>Identifier of the SRCI assigned during Onboarding</p> <p>Type: String</p>
maskedCard	1	<p>Masked Digital Card information</p> <p>Type: <code>MaskedCard</code></p>
maskedConsumer	0..1	<p>Masked Consumer information</p> <p>Type: <code>MaskedConsumer</code></p>
maskedShippingAddresses	0..n	<p>Array of masked shipping addresses</p> <p>Type: <code>List<MaskedAddress></code></p>

Claim Name	Cardinality	Notes
authorization	0..1	First Party Token Type: String
srcCorrelationId	1	Unique identifier corresponding to the present checkout session. A new one is generated by the SRC System if not provided in the input Type: String
srciTransactionId	0..1	Transactional identifier provided by the SRCI. Populated if provided in the input Type: String
srcDpaId	0..1	Identifier of the DPA. Populated if provided in the input Type: String
dpaData	0..1	Data associated with the DPA Type: DpaData
dpaTransactionOptions	1	Transaction options as provided by the DPA Type: DpaTransactionOptions
assuranceData	0..1	Assurance data related to the checkout flow. Populated if provided in the input Type: AssuranceData
checkoutRequestUri	1	The URI that the SRCI will use to invoke the DCF. This can be same as or derived from the <code>checkoutRequestUri</code> in the request body Type: String
checkoutResponseUri	1	The URI that the DCF will use to redirect back to the SRCI after the transaction is completed or cancelled or failed. Provided by SRCI during Onboarding Type: String
serviceId	0..1	Service identifier Type: String

Claim Name	Cardinality	Notes
payloadTypeIndicatorCheckout	0..1	Type of encrypted payload to be returned in the Checkout operation response Type: <code>PayloadTypeIndicator</code>
payloadTypeIndicatorPayload	0..1	Type of encrypted payload to be created for the retrieval by the Get Payload operation Type: <code>PayloadTypeIndicator</code>
recipientIdCheckout	0..1	Recipient identifier of the encrypted payload known to the SRC System (as provided in the Checkout operation response) for the intended recipient Type: <code>String</code>
recipientIdPayload	0..1	Recipient identifier of the encrypted payload known to the SRC System (as retrieved by the Get Payload operation) for the intended recipient Type: <code>String</code>

2.4.2 Checkout Payload Response

Table 2.59 defines a data type of `CheckoutPayloadResponse`.

Table 2.59: Checkout Payload Response

Data Element	R/C/O	Constraints	Description
srcCorrelationId Type: <code>String</code>	C	Max Length = 256	Unique identifier generated by an SRC System Conditionality: <ul style="list-style-type: none">• Required for the Checkout and Make Payment operations• Optional for the Get Payload operation

Data Element	R/C/O	Constraints	Description
srciTransactionId Type: String	C	Max Length = 255	Transactional identifier provided by the SRCI Conditionality: Required when received in the request
srcDpaId Type: String	O	Max Length = 255	Identifier of the DPA generated by SRC System based on the previously provided <code>dpaData</code> or generated during the DPA Registration process
dpaData Type: DpaData	C	See DpaData	Data associated with the DPA Conditionality: <ul style="list-style-type: none">• Required for the Make Payment operation• Optional for the Checkout and Get Payload operations
maskedConsumer Type: MaskedConsumer	C	See MaskedConsumer	Masked Consumer data associated with the SRC Profile Conditionality: <ul style="list-style-type: none">• Required for the Checkout and Get Payload operations if the associated SRC Profile contains Consumer data• Optional for the Make Payment operation

Data Element	R/C/O	Constraints	Description
maskedCard Type: MaskedCard	C	See MaskedCard	Masked card data Conditionality: <ul style="list-style-type: none"> • Required for the Checkout and Get Payload operations • Optional for the Make Payment operation
shippingAddressZip Type: String	C	Max Length = 16	Zip or postal code of selected shipping address Conditionality: Required, depending on the <code>dpaShippingPreference</code> option in the <code>dpaTransactionOptions</code> structure and if either a <code>shippingAddressId</code> or <code>shippingAddress</code> object was present in the Checkout operation request
shippingAddressCountryCode Type: String	C	ISO 3166-1 alpha-2 country code	Country code of selected shipping address Conditionality: Required, depending on the <code>dpaShippingPreference</code> option in the <code>dpaTransactionOptions</code> structure and if either a <code>shippingAddressId</code> or <code>shippingAddress</code> object was present in the Checkout operation request
customOutputData Type: JSONObject	O		SRC System-specific data
assuranceData Type: AssuranceData	O	See AssuranceData	Assurance data related to the checkout flow

Data Element	R/C/O	Constraints	Description
eventHistory Type: EventHistory	O	See EventHistory	Event history related to the checkout flow
payload Type: JWE<JWS<Payload>> DEPRECATED	C	See Payload	SRC Payload. Signed by prior to being encrypted for the specific recipient Conditionality: Refer to the response definitions for the Checkout operation (see Section 5.5.2 Checkout) and the Get Payload operation (see Section 5.5.3 Get Payload)
encryptedSignedPayload Type: JWE<JWS<Payload>>	C	See Payload	SRC Payload. Signed by prior to being encrypted for the specific recipient Conditionality: Refer to the response definitions for the Checkout operation (see Section 5.5.2 Checkout) and the Get Payload operation (see Section 5.5.3 Get Payload) encryptedSignedPayload and encryptedPayload are mutually exclusive

Data Element	R/C/O	Constraints	Description
encryptedPayload Type: JWE<Payload>	C	See Payload	SRC Payload. Encrypted for the specific recipient Conditionality: Refer to the response definitions for the Checkout operation (see Section 5.5.2 Checkout) and the Get Payload operation (see Section 5.5.3 Get Payload) encryptedSignedPayload and encryptedPayload are mutually exclusive
dpaTransactionOptions Type: DpaTransactionOption	O	See DpaTransactionOptions	Transaction options as provided by the DPA
acceptanceChannelRelatedData Type: AcceptanceChannelRelatedData	O	See AcceptanceChannelRelatedData	Data related to the acceptance channel

2.4.3 JWS JOSE Header

The JWS structure for the signed data elements of type CheckoutPayloadResponse and Payload contains the protected JOSE header as specified in Table 2.60.

Note: The language within the descriptions in Table 2.60 is taken directly from the relevant RFC.

Table 2.60: JWS JOSE Header

Parameter Name	R/C/O	Description
alg	R	Algorithm used to digitally sign the payload according to RFC 7518 Section 3.1:

Parameter Name	R/C/O	Description
		<ul style="list-style-type: none">• 'None' is not supported.• 'PS256' is preferred to 'RS256' following the recommendation in RFC 3447
kid	R	Key ID of the cryptographic public key of the signing SRC System. Relying party SHOULD use the key ID to select the appropriate key to verify the signature. The key type of the public key identified by the key ID MUST match the type of the signing algorithm
iss	R	Issuer identifier. The value is a case sensitive URI using the https scheme that contains scheme and full qualified domain name of the host only. Sample value of the URI: https://srcsystem1.com
jti	R	A pseudo-random value used as nonce. The value is a case-sensitive string
iat	R	Issuance timestamp in UTC and Unix/epoch format

2.5 Masking Rule

All masked objects should follow the masking rules as defined in the SRC Core Specification.

3 Federated Identity

The concept of federated identity enables collaborating SRC Systems to reduce friction by sharing the results of a successfully validated Consumer Identity. This Section describes a federated token that supports the notion of federated digital identity and authorisation. A Federated ID Token is issued by the SRC System as a digitally signed attestation that the identity of the requestor has been validated.

3.1 Authorisation Token

By default, the digital authorisation is a JSON Web Token (JWT) in line with RFC 7519 and compatible with OpenID Connect ID Token.

Each token needs to be digitally signed by the SRC System that issued the token. Relying parties (e.g. other SRC Systems) need to be able to validate this token using the issuing SRC System's public key. Signature has to be compliant with JSON Web Signature (JWS) specification RFC 7515.

3.1.1 Token Header

The header of the JWT has to be compliant with the JOSE Header as specified by RFC 7519. Table 3.1 describes the JOSE Header.

Table 3.1: JOSE Header

Parameter Name	R/C/O	Description
alg	R	Algorithm used to digitally sign the payload according to RFC 7518 Section 3.1: <ul style="list-style-type: none">• 'None' is not supported• 'PS256' is preferred to 'RS256' following the recommendation in RFC 3447
kid	R	Key ID for the SRC System public key to be used to verify the signature. Relying party SHOULD use the Key ID to select the appropriate key to verify the signature. The key type of the public key identified by the Key ID MUST match the type of the signing algorithm

Parameter Name	R/C/O	Description
typ	R	Media type of the token. For JWT tokens the value should be <code>JWT+ext.id_token</code>

3.1.2 Token Claims

The Federated ID Token represents digitally signed attestation that a Consumer has been identified by an SRC System. The token contains Consumer Identities that allow other SRC Systems to identify the corresponding SRC Profile.

Table 3.2: Federated ID Token Claim Set

Claim Name	Cardinality	Notes
Public Claims		
iss	1	Issuer identifier for the Issuer of the response. Identifiers MUST BE in the form of case sensitive URI using the https scheme that contains scheme and full qualified domain name of the host only. Sample value of the URI: https://srcsystem1.com
sub	1	Subject Identifier. A locally unique and never reassigned identifier within the Issuer for the end user (Consumer), which is intended to be consumed by the Client, e.g., 24400320 or AitOawyewNvutrJUqsvl6qs7A4. It MUST NOT exceed 255 ASCII characters in length. The sub value is a case sensitive string. SRC System-specific primary identifier of the Consumer that MAY BE used to locate Consumer's SRC Profile.
aud	1..n	JSON Array of the audience(s) that this ID Token is intended for.

Claim Name	Cardinality	Notes
		<p>It MUST contain the identifier of the requestor (SRCI or DCF) as the first element of the array. It MUST also contain identifiers for participating SRC Systems as audiences.</p> <p>Identifiers MUST BE in the form of case sensitive URIs using the https scheme that contains scheme and full qualified domain name of the host only.</p> <p>Sample value of the array: ["https://srci.com", "https://srcsystem1.com", "https://srcsystem2.com", "https://srcsystem3.com"]</p>
exp	1	<p>Expiration time on or after which the ID Token SHOULD NOT be accepted for processing. The processing of this parameter requires that the current date/time MUST be before the expiration date/time listed in the value.</p> <p>Implementers MAY provide for some small leeway, usually no more than a few minutes, to account for clock skew.</p> <p>Its value is a JSON number representing the number of seconds from 1970-01-01T0:0:0Z as measured in UTC until the date/time. See RFC 3339 [RFC3339] for details regarding date/times in general and UTC in particular.</p> <p>Minimum expiration timestamp SHOULD BE 15 minutes from the issued-at timestamp.</p>
iat	1	<p>Time at which the ID Token was issued. Its value is a JSON number representing the number of seconds from 1970-01-01T0:0:0Z as measured in UTC until the date/time.</p> <p>This MAY BE before current date/time, i.e., an SRC System may cache tokens up to close to the expiration time of the token.</p>
jti	0..1	<p>The "jti" (JWT ID) claim provides a unique identifier for the JWT. The value is a case-sensitive string.</p>

Claim Name	Cardinality	Notes
auth_time	0..1	<p>Time when the end user authentication occurred. Its value is a JSON number representing the number of seconds from 1970-01-01T0:0:0Z as measured in UTC until the date/time.</p> <p>Value of the claim reflects the time when the user actually provided the credentials for authentication on this specific browser or app instance: A validated token MUST be issued if and only if a channel was validated on this specific browser or app instance.</p>
amr	0..n	<p>List of methods end user was authenticated with.</p> <p>JSON array of strings that are identifiers for authentication methods used in the authentication. For instance, values might indicate that both password and OTP authentication methods were used. The amr value is an array of case sensitive strings.</p> <p>The authentication method used when the user actually provided the credentials for authentication on this specific browser or app instance: A validated token MUST be issued if and only if a channel was validated on this specific browser or app instance.</p> <p>For the specific details of each of the values, see:</p> <p>https://tools.ietf.org/html/draft-ietf-oauth-amr-values-04#page-3</p> <p>Additional values for SRC are:</p> <ul style="list-style-type: none">• sms_otp• email_otp• merchant_rememberme

Claim Name	Cardinality	Notes
Standard ID Token Claims		
phone_number	0..1	<p>Obfuscated end user's preferred mobile phone number. Underlying phone number value MUST conform with E.164 [E.164] format except that the leading “+” special character MUST be excluded.</p> <p>Used by Relying Party to help to identify a matching SRC Profile.</p> <p>The Relying Party MUST NOT rely upon this value being unique.</p>
phone_number_verified	0..1	<p><code>true</code> if the end user's phone number has been verified; otherwise <code>false</code>.</p> <p>When this claim value is <code>true</code>, this means that the OP (OpenID Provider) took affirmative steps to ensure that this phone number was controlled by the end user at the time the verification was performed. The means by which a phone number is verified is context-specific, and dependent upon the trust framework or contractual agreements within which the parties are operating.</p> <p>The Relying Party MUST NOT rely upon this value being unique.</p> <p>For SRC, this value MUST be <code>true</code> only if the OP can deterministically confirm that the phone number was verified by the user authenticated on this specific browser or app instance.</p>
email	0..1	<p>Obfuscated end user's preferred e-mail address. Underlying email address value MUST conform to the RFC 5322 addr-spec syntax simplified to all lowercase characters.</p> <p>Used by Relying Party to help to identify a matching SRC Profile.</p> <p>The Relying Party MUST NOT rely upon this value being unique.</p>

Claim Name	Cardinality	Notes
email_verified	0..1	<p>true if the end user's e-mail address has been verified; otherwise false.</p> <p>When this claim value is true, this means that the OP took affirmative steps to ensure that this e-mail address was controlled by the end user at the time the verification was performed. The means by which an e-mail address is verified is context-specific, and dependent upon the trust framework or contractual agreements within which the parties are operating.</p> <p>For SRC, this value MUST be true only if the OP can deterministically confirm that the email address was verified by the user authenticated on this specific browser or app instance.</p>
Private Claims		
src_phone_number_mask	0..1	<p>Masked Consumer mobile phone number. This MUST use E.164 format with SRC-specific masking rules.</p> <p>Used by the Relying Party to properly render the UI and allow a frictionless user experience.</p>
src_email_mask	0..1	<p>Masked Consumer e-mail address in RFC 5322 format with SRC-specific masking rules.</p> <p>Used by the Relying Party to properly render the UI and allow a frictionless user experience.</p>

3.1.3 Notes on Authentication

Note that:

- The `auth_time` claim is not correlated with the `iat` claim
- The `amr` claim is optional. If value is not specified, the end user cannot be assumed as authenticated
- The `auth_time` claim SHOULD BE present only if the `amr` claim is present
- The `auth_time` claim MUST always represent the time at which a consumer-interactive authentication method was performed (e.g. `email_otp` or `sms_otp`)

- The `auth_time` claim MUST NOT represent a consumer-transparent authentication method (e.g. `swk` or `rbd`)
- The `amr` claim array MUST present authentication methods in order from oldest to most recent
- When the `amr` claim contains a list of different authentication methods the `auth_time` claim shall correspond to the most recent interactive authentication method from the `amr` list

4 SRCI – DCF Interaction

As part of a checkout flow, an SRCI may be required to invoke the DCF to support necessary aspects of the checkout user experience. Upon completion of these steps, the DCF can return control back to the SRCI.

The SRCI and DCF will not know each other directly, however. The URIs will be provided by the SRC System to the SRCI and the DCF to invoke each other for native or browser environments.

The following are the use cases to be addressed here:

- The recognized Consumer (with an `idToken`), card list is presented by the SRCI and the Consumer chooses a card. The appropriate DCF for that Digital Card is invoked by the SRCI using the URI provided by the SRC System
- The recognized Consumer (with an `idToken`), card list is presented by the SRCI and the Consumer chooses to add a new card. The appropriate default DCF for that SRC System is invoked by the SRCI using the URI provided by the SRC System
- The unrecognized Consumer (no `idToken`) adds a new card. The appropriate default DCF for that SRC System is invoked by the SRCI using the URI provided by the SRC System

All the above use cases should be addressed for the following:

- Browser and native (iOS/Android) use cases
- Support the following action/result scenarios from DCF to SRCI:
 - Change Consumer
 - Change Card
 - Add Card
 - Cancel Checkout
 - Successful Checkout
 - Error

4.1 Interaction Mechanisms

There can be various possible technical implementation approaches to support these interactions. The example flow is illustrative only to help the reader understand the concept, however actual implementations will differ due to security principles and policies.

The sequence of calls are as follows:

- SRCI front end (e.g. JavaScript from the SRCI that executes in the Consumer's browser) calls the SRC System back end to create the Checkout Request JWS and get the DCF URI
- The SRCI front end launches the DCF front end (e.g. JavaScript from the DCF that executes in the Consumer's browser) using the `checkoutRequestUri`
- After the transaction is completed, the DCF front end sends control to the SRCI using the `checkoutResponseUri` obtained from the Checkout Request JWS

4.2 Launch The DCF

This is the mechanism for the SRCI to launch a DCF from the given DCF URI using the Checkout Request JWS.

```
{checkoutRequestUri}?action={actionCode}&IDToken={idToken}#{checkoutRequestJws}
```

The `actionCode`, if passed from the SRCI to the DCF, is expected to be one of the following:

- `NEW_USER`: if specified, will advise the DCF that the Consumer entered the flow for Enrolment
- `AUTH_FAILED`: if specified, will advise the DCF that the Consumer failed identity validation with no attempts remaining
- `AUTH_SKIPPED`: if specified, will advise the DCF that the Consumer chose to skip identity validation

The DCF application would need to read the Checkout Request JWS from the URI fragment using `document.location` (in case of the browser) or using native code (in case of a native mobile app). Note that the `idToken` might not be present in scenarios such as an unrecognised Consumer adding a new card.

The usage of fragment has the benefit of not having to pass the contents of Checkout Request JWS through the network.

There can be more suitable methods like Android Intents to launch the DCF for certain native environments like Android. In those cases, the implementer can choose to use those platform-specific methods.

4.3 Redirect back to SRCI

After the transaction is processed, the control needs to be handed back to the SRCI from the DCF.

This is done using the `checkoutResponseUri` derived from the above-mentioned JWS.

For non-error scenarios:

```
{checkoutRequestJws.checkoutResponseUri}?action={actionCode}&  
IDToken={idToken}#{checkoutResponse}
```

The `checkoutResponse` is the signed data element of type `CheckoutPayloadResponse` as returned by the Checkout operation. Note that `checkoutResponse` will be present only when the content of `actionCode` has a value of `COMPLETE`.

The `idToken` is conditional in the response URI fragment and is present only when the Consumer successfully completes identity validation and the Consumer chooses to add/change card.

There might be more suitable methods like Android Intents to redirect back to the SRCI for certain native environments like Android. In those cases, the implementer can choose to use those platform-specific methods.

The valid values of `actionCode` are as follows:

- `COMPLETE`: DCF processing completed normally
- `CHANGE_CARD`: Consumer wishes to select an alternative card
- `ADD_CARD`: Consumer wishes to add a new card
- `SWITCH_CONSUMER`: Consumer wishes to change account profile / identity
- `CANCEL`: Consumer wishes to cancel the flow
- `ERROR`: an error was detected and the DCF processing cannot continue

For error scenarios:

```
{checkoutRequestJws.checkoutResponseUri}?action=ERROR&error={errorCode}&errorDescription={errorDescription}
```

The error codes and description values are defined in Table 4.1.

Table 4.1: Error Codes

Name	R/C/O	Description	
errorCode Type: string	R	Code for the error. Used by the API client for error handling.	
		Error	Comments
		TERMS_AND_CONDITIONS _NOT_ACCEPTED	Terms and Conditions are not accepted

		ACCT_INACCESSIBLE	User account is disabled or locked out
		AUTH_INVALID	Client is not authorised to make this request
		AUTH_ERROR	Unrecognised client
		SERVICE_ERROR	Unexpected server error
		INVALID_REQUEST	This error can result when the <code>checkoutRequestJws</code> format or contents are invalid (due to invalid signature, etc.)
errorDescription Type: string	O	Description of the error message. Should not be used for display purposes since this message is not localised. However, it could be used for logging and debugging purposes.	

5 Server-Side API

5.1 API Principles

- The server-side API is designed as a set of web services where each API endpoint represents an operation to be performed
- All request and response data elements are sent in the JSON (JavaScript Object Notation) data-interchange format
- Each endpoint in the API specifies the HTTP Method used to perform the required operation
- All data elements or parameters of type String in requests and responses, or within complex data objects are UTF-8 encoded
- All actionable fields MUST be provided as part of the request parameters (path, query or body). Only meta data must be carried in the headers. This ensures that the SDK and API spec have similar function signatures and that actionable fields can be included as part of cryptographic signatures to control against data tampering as well as repudiation claims

5.1.1 Common HTTP Status Codes

The following common HTTP status codes are defined:

- 200: OK, the request was successful; details are included in the response body
- 202: Accepted, e.g. card details have been accepted by Enrolment service, but enrolment is outstanding, dependent upon further checks, identified by response data
- 204: No content, the service completed successfully and there is no content to be returned
- 400: Bad request, see `Error` object for details, e.g. identifies a malformed or invalid request
- 401: Unauthorised, see `Error` object for details, e.g. authorisation token validation failure
- 403: Forbidden, see `Error` object for details, e.g. client identity (origin) not validated
- 404: Not found, see `Error` object for details, e.g. the reference to the SRC Profile in the request data was not found
- 409: Conflict, see `Error` object for details, e.g. the submitted Consumer Identity(s) are already bound to an established SRC Profile
- 500: Internal server error, see `Error` object for details

5.1.2 Error Handling

In case an API service call response contains an HTTP error status code (4xx, 5xx), then the response body contains only an `Error` object that includes details about the error.

5.1.3 Conditionality of Data

Definitions of data conditionality for the APIs are provided based on successful outcomes for those APIs. In case of error outcomes, only an `error` object is returned.

5.1.4 Authorisation

The SRC System uses an authorisation object provided by the API client to identify if there is an existing SRC Profile on which to perform the API operation and determine whether identity validation must occur.

The SRC System supports two categories of authorisation objects:

- **Federated ID Token:** A Federated ID Token is a digitally signed attestation that the identity of the requestor has been validated by an SRC System. A Federated ID Token issued by one SRC System may be sent by the client to any other participating SRC System
- **First Party Token:** An opaque first party token issued and recognised by the same SRC System. The content and structure of these tokens is out of scope of the specification

The authorisation objects may be provided by the API client as HTTP header value, e.g. `Authorisation`, or in the body of HTTP request as explicitly defined by the respective operation, or through other mechanism depending on the integration model and specificity of the individual operation.

5.1.5 Recognition

The SRC System binds device/app identifiers to an SRC Profile to enable the relevant SRC Profile to be determined when device/app identifiers are provided in an API request. Once the relevant SRC Profile has been determined, the SRC System performs additional identity verification if necessary. An SRC System that recognises, and can validate, the associated Consumer Identity, returns a Federated ID Token that may be sent by the client to any other participating SRC System.

The `Is Recognized` API (Section 5.7.4) provides two mechanisms for recognising the device and/or app depending on the specific calling client:

- **Implicit cookie-based recognition:** the HTTP client (e.g. web browser) may provide a secure HTTP cookie (containing a First Party Token) in the HTTP header that enables the SRC System to identify an SRC Profile

- Explicit token-based recognition: the SRC Initiator may provide one or more `recognitionToken` JWTs explicitly in the request body.

The SRC System issues a Federated ID Token after successful verification of the tokens described above, and after any necessary additional identity validation.

5.1.5.1 Recognition Token JWT

The recognition token JWT represents the Device Identity bound to the specific SRC Profile. It is a first party token issued by the SRC System and is intended to be sent to the same SRC System as the explicit recognition token.

The recognition token JWT should be structured as JSON Web Token (JWT) in line with RFC 7519 and should contain at least the claim as described in Table 5.1.

Note: The language within the notes in Table 5.1 is taken directly from the relevant RFC.

Table 5.1: Recognition Token Claim Set

Claim Name	Cardinality	Notes
iss	1	Issuer of the recognition token JWT. Identifiers MUST BE in the form of case sensitive URI using the https scheme that contains scheme and full qualified domain name of the host only. Sample value of the URI: https://srcsystem1.com
exp	1	Expiration time of the recognition token JWT.
sub	1	Subject Identifier. A locally unique and never reassigned identifier within the Issuer for the end user (Consumer), which is intended to be consumed by the Client, e.g., 24400320 or AitOawyewNvutrJUqsvl6qs7A4. It MUST NOT exceed 255 ASCII characters in length. The sub value is a case sensitive string.

In addition to the claim required by this SRC API Specification, each SRC System may specify its own claims.

5.1.6 API Access Control

Access to all APIs must be protected using an authorisation mechanism defined by the SRC System. For server-to-server API access, mutually authenticated TLS connections are generally recommended. For browser-to-server APIs, besides the server authenticated TLS connection, SRC Systems may choose to implement additional access protection models, in order to authenticate that all incoming requests are generated by Onboarded SRC System Participants.

Refer to Annex A Security Guidelines of the SRC Core Specification for more details on the various security credentials used in TLS connections, along with different versions and cipher suites.

5.1.7 API Tables

In the following sections, API tables are only shown for the elements of the API which have content. For example, if an API does not have a response body, no response body table will be shown.

5.2 Card Service

Card Service supports Payment Card digitisation. It covers operations to enrol a card, delete a card, to add a billing address card to a previously enrolled card and to retrieve a Digital Card and related masked card data.

5.2.1 Card Enrolment

The Card Enrolment operation enrolls a Consumer and Digital Card (associated with an underlying PAN) to a new SRC Profile, or adds a Digital Card to an existing SRC Profile. Note that the Digital Card maybe associated with a specific merchant for certain use cases.

If an existing SRC Profile is identified, a Digital Card (associated with an underlying PAN) will be added to that SRC Profile. In the case that an SRC Profile cannot be identified, the SRC System will either create a new SRC Profile based on the Consumer Identity provided, or the Digital Card will be enrolled in an unbounded state. An unbound Digital Card can be bound to an SRC Profile in a subsequent Add Consumer Identities operation, leveraging a first party opaque authorisation token provided in response to this operation.

The `serviceId` can be used for extended functionality as defined by the SRC System (e.g. to indicate to the SRC System that this Digital Card is the merchant Digital Card-on-file for the merchant associated with `srcDpaId`).

Table 5.2.1: Card Enrolment Definition – HTTP Verb, Path and Parameters

HTTP Verb	POST
Path	/cards
Parameters	None

Table 5.2.2: Card Enrolment Definition – Request Body

Data Element	R/C/O	Notes
srcClientId Type: String	R	Reference identifier of the connecting client (Max length = 255)
srcDpaId Type: String	C	Reference identifier of the DPA (Max length = 255) Must be provided if the calling client is an SRCI
srcCorrelationId Type: String	C	Unique identifier generated by an SRC System (Max length = 256) Must be provided if available within the present checkout session (e.g. received in an earlier response during the present session), otherwise a new checkout session will be initiated
serviceId Type: String	O	Service identifier associated to an SRC System specific configuration (Max length = 255)
srciTransactionId Type: String	O	Transactional identifier provided by the SRCI (Max length = 255)
srcTokenRequestData Type: JSONObject	O	
threeDsInputData Type: JSONObject	O	Input data for 3DS processing

Data Element	R/C/O	Notes
assuranceData Type: AssuranceData	O	
consumer Type: Consumer	C	Either none or one of <code>consumer</code> or <code>encryptedConsumer</code> must be provided
encryptedConsumer Type: JWE<Consumer>	C	
applInstance Type: ApplInstance	O	
digitalCardData Type: DigitalCardData	O	
cardholderData Type: CardholderData	C	Either none or one of <code>cardholderData</code> or <code>encryptedCardholderData</code> must be provided
encryptedCardholderData Type: JWE<CardholderData>	C	
complianceSettings Type: ComplianceSettings	O	
cardSource Type: Origin	O	Indicates the entity performing the Enrolment
card Type: Card	C	<p>Exactly one of “card”, “srcDigitalCardId”, or “encryptedCard” must be provided</p> <p>Conditionality changed to</p> <p>Exactly one of <code>card</code>, <code>encryptedCard</code> or <code>enrollmentReferenceData</code> must be provided</p>
encryptedCard Type: JWE<Card>	C	
srcDigitalCardId Type: String DEPRECATED Replaced by	C	
enrollmentReferenceData Type: EnrollmentReferenceData	C	

If the operation is processed successfully, the response body in Table 5.2.3 will be returned.

Table 5.2.3: Card Enrolment Definition – Response Body

Data Element	R/C/O	Notes
srcCorrelationId Type: String	O	Unique identifier generated by an SRC System (Max length = 256)
maskedCard Type: MaskedCard	R	
maskedConsumer Type: MaskedConsumer	C	Must be provided if <code>consumer</code> was provided in the request
authorization Type: String	C	Must be provided if no <code>authorization</code> was provided in the request
appInstanceId Type: String DEPRECATED	C	Must be provided if <code>appInstance</code> was provided in the request
recognitionToken Type: JWT	C	Long-lived First Party Token representing a device or app bound to the SRC Profile (Max length = 1024) Must be provided if <code>appInstance</code> was provided in the request

Table 5.2.4: Card Enrolment Definition – HTTP Status Codes

Code	Description
200	The operation is processed successfully and the card is enrolled
202	The operation is processed successfully, but the card is pending further checks or authentication which must be performed before Enrolment can be completed
4xx – 5xx	See Common HTTP Status Codes (Section 5.1.1)

5.2.2 Delete Card

The Delete Card operation deletes a Digital Card from an SRC Profile.

If the parameter `cardId` is a Payment Card Identifier provided by the SRCPI, the relationship of that identifier to Digital Cards is SRC System specific.

Table 5.2.5: Delete Card Definition – HTTP Verb, Path and Parameters

HTTP Verb	DELETE
Path	/cards/{cardId}
Parameters	cardId: Value: may be <code>srcDigitalCardId</code> or <code>srcPaymentCardId</code> , Required

Table 5.2.6: Delete Card Definition – Query Parameters

Data Element	R/C/O	Notes
srcClientId Type: String	R	Reference identifier of the connecting client (Max length = 255)
srcDpald Type: String	C	Reference identifier of the DPA (Max length = 255) Must be provided if the calling client is an SRCI

Data Element	R/C/O	Notes
srcCorrelationId Type: String	C	Unique identifier generated by an SRC System (Max length = 256) Must be provided if available within the present checkout session (e.g. received in an earlier response during the present session), otherwise a new checkout session will be initiated
serviceId Type: String	O	Service identifier associated to an SRC System specific configuration (Max length = 255)
srciTransactionId Type: String	O	Transactional identifier provided by the SRCI (Max length = 255)
requestor Type: Origin	O	Indicates the original entity requesting deletion of the card from the SRC Profile. Note: the requestor may be different than the API client identified by the <code>srcClientId</code>
reason Type: CardDeletionReason	O	Reason of the card deletion request

If the operation is processed successfully, the response body in Table 5.2.7 will be returned.

Table 5.2.7: Delete Card Definition – Response Body

Data Element	R/C/O	Notes
srcCorrelationId Type: String	O	Unique identifier generated by an SRC System (Max length = 256)

Table 5.2.8: Delete Card Definition – HTTP Status Codes

Code	Description
200	The operation is processed successfully and the card is deleted

Code	Description
404	Not found, see <code>Error</code> object for details, e.g. content of <code>cardId</code> not recognised
4xx – 5xx	See Common HTTP Status Codes (Section 5.1.1)

5.2.3 Add Billing Address

The Add Billing Address operation adds a billing address to an SRC Profile.

Table 5.2.9: Add Billing Address Definition – HTTP Verb, Path and Parameters

HTTP Verb	POST
Path	/cards/{cardId}/address
Parameters	cardId: Value: <code>srcDigitalCardId</code> or <code>srcPaymentCardId</code> , Required

Table 5.2.10: Add Billing Address Definition – Request Body

Data Element	R/C/O	Notes
srcClientId Type: String	R	Reference identifier of the connecting client (Max length = 255)
srcDpald Type: String	C	Reference identifier of the DPA (Max length = 255) Must be provided if the calling client is an SRCI
srcCorrelationId Type: String	C	Unique identifier generated by an SRC System (Max length = 256) Must be provided if available within the present checkout session (e.g. received in an earlier response during the present session), otherwise a new checkout session will be initiated

Data Element	R/C/O	Notes
serviceld Type: String	O	Service identifier associated to an SRC System specific configuration (Max length = 255)
srciTransactionId Type: String	O	Transactional identifier provided by the SRCI (Max length = 255)
billingAddress Type: Address	R	
setAsShippingAddress Type: Boolean	O	If set to <code>true</code> , the shipping address is also created and is set to the same as the billing address

If the operation is processed successfully, the response body in Table 5.2.11 will be returned.

Table 5.2.11: Add Billing Address Definition – Response Body

Data Element	R/C/O	Notes
srcCorrelationId Type: String	O	Unique identifier generated by an SRC System (Max length = 256)
maskedCard Type: MaskedCard	R	
maskedShippingAddress Type: MaskedAddress	C	Must be provided if <code>setAsShippingAddress</code> in the request was set to <code>true</code>

Table 5.2.12: Add Billing Address Definition – HTTP Status Codes

Code	Description
200	The operation is processed successfully and the masked card details are included in the response body
404	Not found, see <code>error</code> object for details, e.g. the digital card referenced in the request data was not found
4xx – 5xx	See Common HTTP Status Codes (Section 5.1.1)

5.2.4 Get Card Data

The Get Card Data operation allows an SRC Participant to retrieve a Digital Card and related masked card data.

Table 5.2.13: Get Card Data Definition – HTTP Verb, Path and Parameters

HTTP Verb	GET
Path	/cards/{cardId}
Parameters	cardId: Value: srcDigitalCardId, Required

Table 5.2.14: Get Card Data Definition – Query Parameters

Data Element	R/C/O	Notes
srcClientId Type: String	R	Reference identifier of the connecting client (Max length = 255)
srcDpaId Type: String	C	Reference identifier of the DPA (Max length = 255) Must be provided if the calling client is an SRCI
srcCorrelationId Type: String	C	Unique identifier generated by an SRC System (Max length = 256) Must be provided if available within the present checkout session (e.g. received in an earlier response during the present session), otherwise a new checkout session will be initiated
serviceId Type: String	O	Service identifier associated to an SRC System specific configuration (Max length = 255)
srciTransactionId Type: String	O	Transactional identifier provided by the SRCI (Max length = 255)

If the operation is processed successfully, the response body in Table 5.2.15 will be returned.

Table 5.2.15: Get Card Data Definition – Response Body

Data Element	R/C/O	Notes
maskedCard Type: MaskedCard	R	
srcCorrelationId Type: String	O	Unique identifier generated by an SRC System (Max length = 256)

Table 5.2.16: Get Card Data Definition – HTTP Status Codes

Code	Description
200	The operation is processed successfully and the masked card meta-data is included in the response body
4xx – 5xx	See Common HTTP Status Codes (Section 5.1.1)

5.3 Address Service

The Address Service enables the management of shipping addresses.

5.3.1 Add Shipping Address

The Add Shipping Address operation adds a shipping address to an SRC Profile.

Table 5.3.1: Add Shipping Address Definition – HTTP Verb, Path and Parameters

HTTP Verb	POST
Path	/addresses
Parameters	None

Table 5.3.2: Add Shipping Address Definition – Request Body

Data Element	R/C/O	Notes
srcClientId Type: String	R	Reference identifier of the connecting client (Max length = 255)
srcDpald Type: String	C	Reference identifier of the DPA (Max length = 255) Must be provided if the calling client is an SRCI
srcCorrelationId Type: String	C	Unique identifier generated by an SRC System (Max length = 256) Must be provided if available within the present checkout session (e.g. received in an earlier response during the present session), otherwise a new checkout session will be initiated
serviceId Type: String	O	Service identifier associated to an SRC System specific configuration (Max length = 255)
srciTransactionId Type: String	O	Transactional identifier provided by the SRCI (Max length = 255)
shippingAddress Type: Address	R	

If the operation is processed successfully, the response body in Table 5.3.3 will be returned.

Table 5.3.3: Add Shipping Address Definition – Response Body

Data Element	R/C/O	Notes
srcCorrelationId Type: String	O	Unique identifier generated by an SRC System (Max length = 256)
maskedShippingAddress Type: MaskedAddress	R	

Table 5.3.4: Add Shipping Address Definition – HTTP Status Codes

Code	Description
200	The operation is processed successfully and the updated masked card details are included in the response body
4xx – 5xx	See Common HTTP Status Codes (Section 5.1.1)

5.3.2 Delete Shipping Address

The Delete Shipping Address operation deletes a shipping address from an SRC Profile.

Table 5.3.5: Delete Shipping Address Definition – HTTP Verb, Path and Parameters

HTTP Verb	DELETE
Path	/addresses/{addressId}
Parameters	addressId: addressId of shipping address to be deleted, Required

Table 5.3.6: Delete Shipping Address Definition – Query Parameters

Data Element	R/C/O	Notes
srcClientId Type: String	R	Reference identifier of the connecting client (Max length = 255)
srcDpaId Type: String	C	Reference identifier of the DPA (Max length = 255) Must be provided if the calling client is an SRCI
srcCorrelationId Type: String	C	Unique identifier generated by an SRC System (Max length = 256) Must be provided if available within the present checkout session (e.g. received in an earlier response during the present session), otherwise a new checkout session will be initiated

Data Element	R/C/O	Notes
serviceId Type: String	O	Service identifier associated to an SRC System specific configuration (Max length = 255)
srciTransactionId Type: String	O	Transactional identifier provided by the SRCI (Max length = 255)

If the operation is processed successfully, the response body in Table 5.3.7 will be returned.

Table 5.3.7: Delete Shipping Address Definition – Response Body

Data Element	R/C/O	Notes
srcCorrelationId Type: String	O	Unique identifier generated by an SRC System (Max length = 256)

Table 5.3.8: Delete Shipping Address Definition – HTTP Status Codes

Code	Description
200	The operation is processed successfully and the shipping address is deleted
404	Not found, see <code>Error</code> object for details, e.g. <code>addressId</code> not recognised
4xx – 5xx	See Common HTTP Status Codes (Section 5.1.1)

5.4 SRC Profile Service

The SRC Profile Service enables SRC System Participants to retrieve SRC Profiles from SRC Systems and manage binding of identities to SRC Profiles.

5.4.1 Prepare SRC Profile

The Prepare SRC Profile operation requests that an SRC System prepare one or more SRC Profile(s) to be returned.

Table 5.4.1: Prepare SRC Profile Definition – HTTP Verb, Path and Parameters

HTTP Verb	POST
Path	/profiles/prepare
Parameters	None

Table 5.4.2: Prepare SRC Profile Definition – Request Body

Data Element	R/C/O	Notes
srcClientId Type: String	R	Reference identifier of the connecting client (Max length = 255)
srcDpaId Type: String	C	Reference identifier of the DPA (Max length = 255) Must be provided if the calling client is an SRCI
srcCorrelationId Type: String	C	Unique identifier generated by an SRC System (Max length = 256) Must be provided if available within the present checkout session (e.g. received in an earlier response during the present session), otherwise a new checkout session will be initiated
serviceId Type: String	O	Service identifier associated to an SRC System specific configuration (Max length = 255)
srciTransactionId Type: String	O	Transactional identifier provided by the SRCI (Max length = 255)
idTokens Type: List<JWT>	C	

Data Element	R/C/O	Notes
consumerIdentities Type: List<ConsumerIdentity>	C	<p>Either <code>idTokens</code> or <code>consumerIdentities</code> must be provided if:</p> <ul style="list-style-type: none"> The <code>idTokens</code> list carries one or more Federated ID Tokens (used to identify associated SRC Profile(s), and attest that the requester is authorised to access this data) The <code>consumerIdentities</code> list carries one or more Consumer Identities and is used to identify associated SRC Profile(s) (may be used only when the client is trusted and authorised to access the SRC System)
dpaTransactionOptions Type: DpaTransactionOptions	O	
dpaData Type: DpaData	O	

If the operation is processed successfully, the response body in Table 5.4.3 will be returned.

Table 5.4.3: Prepare SRC Profile Definition – Response Body

Data Element	R/C/O	Notes
srcCorrelationId Type: String	O	Unique identifier generated by an SRC System (Max length = 256)
profiles Type: List<SrcProfile>	R	Contains entries if one or more SRC Profiles are found, otherwise an empty list is returned
srcDpald Type: String	C	<p>Reference identifier of the DPA (Max length = 255)</p> <p>Must be provided if the DPA Registration occurred based on the <code>dpaData</code> in the request</p>

Table 5.4.4: Prepare SRC Profile Definition – HTTP Status Codes

Code	Description
200	The operation is processed successfully and the SRC Profile details are included in the response body
400	Bad request, see <code>Error</code> object for details. Identifies a malformed or invalid request, including reporting that the <code>srcCorrelationId</code> provided was invalid or not recognised
4xx – 5xx	See Common HTTP Status Codes (Section 5.1.1)

5.4.2 Add Consumer Identities

The Add Consumer Identities operation binds a Device Identity (an application instance) or Consumer Identity to an SRC Profile.

In the case that the SRC Profile cannot be located, the SRC System may create a new SRC Profile (based on Consumer details provided in the request) if a previously enrolled unbound Digital Card exists.

The Add Consumer Identifiers operation supports Consumer Identities such as e-mail address, phone number and/or application instance information to support a range of use-cases.

When the type of a provided Consumer Identity is considered to be a primary identity for an SRC Profile (e.g. an email address or phone number), then, if the SRC System detects that an SRC Profile already exists with the same primary identity, the SRC System should respond to the request by advising that an SRC Profile with that identity already exists.

Whether or not a provided Consumer Identity is used to replace an existing identity on an existing SRC Profile is an SRC System implementation decision.

Table 5.4.5: Add Consumer Identities Definition – HTTP Verb, Path and Parameters

HTTP Verb	POST
Path	/profiles
Parameters	None

Table 5.4.6: Add Consumer Identities Definition – Request Body

Data Element	R/C/O	Notes
srcClientId Type: String	R	Reference identifier of the connecting client (Max length = 255)
srcDpaId Type: String	C	Reference identifier of the DPA (Max length = 255) Must be provided if the calling client is an SRCI
srcCorrelationId Type: String	C	Unique identifier generated by an SRC System (Max length = 256) Must be provided if available within the present checkout session (e.g. received in an earlier response during the present session), otherwise a new checkout session will be initiated
serviceId Type: String	O	Service identifier associated to an SRC System specific configuration (Max length = 255)
srciTransactionId Type: String	O	Transactional identifier provided by the SRCI (Max length = 255)
consumer Type: Consumer	C	One and only one of the following must be provided: <ul style="list-style-type: none"> • appInstance • consumer • encryptedConsumer • consumer and appInstance • encryptedConsumer and appInstance
encryptedConsumer Type: JWE<Consumer>	C	
appInstance Type: AppInstance	C	
assuranceData Type: AssuranceData	O	
complianceSettings Type: ComplianceSettings	O	

Data Element	R/C/O	Notes
srcDigitalCardId Type: String	C	Must be provided if the request is to establish a new SRC Profile and bind the identifier(s) to a previously enrolled, unbound card

If the operation is processed successfully, the response body in Table 5.4.7 will be returned.

Table 5.4.7: Add Consumer Identities Definition – Response Body

Data Element	R/C/O	Notes
srcCorrelationId Type: String	O	Unique identifier generated by an SRC System (Max length = 256)
authorization Type: String	C	Must be provided if <code>consumer</code> was provided in the request May be provided if <code>appInstance</code> was provided in the request
maskedConsumer Type: MaskedConsumer	C	Must be provided if <code>consumer</code> was provided in the request
appInstanceId Type: String DEPRECATED	C	Must be provided if <code>appInstance</code> was provided in the request
recognitionToken Type: JWT	C	Long-lived First Party Token representing a device or app bound to the SRC Profile (Max length = 1024) Must be provided if <code>appInstance</code> was provided in the request

Table 5.4.8: Add Consumer Identities Definition – HTTP Status Codes

Code	Description
2xx – 5xx	See Common HTTP Status Codes (Section 5.1.1)

5.4.3 Unbind App Instance

The Unbind App Instance operation unbinds a Device Identity (an application instance) from an SRC Profile.

Table 5.4.9: Unbind App Instance Definition – HTTP Verb, Path and Parameters

HTTP Verb	DELETE
Path	/profile/appinstances DEPRECATED Replaced by /profiles/appinstances
Parameters	None

Table 5.4.10: Unbind App Instance Definition – Query Parameters

Data Element	R/C/O	Notes
srcClientId Type: String	R	Reference identifier of the connecting client (Max length = 255)
srcDpaid Type: String	C	Reference identifier of the DPA (Max length = 255) Must be provided if the calling client is an SRCI
srcCorrelationId Type: String	C	Unique identifier generated by an SRC System (Max length = 256) Must be provided if available within the present checkout session (e.g. received in an earlier response during the present session), otherwise a new checkout session will be initiated.
serviceId Type: String	O	Service identifier associated to an SRC System specific configuration (Max length = 255)
srciTransactionId Type: String	O	Transactional identifier provided by the SRCI (Max length = 255)

Data Element	R/C/O	Notes
appInstanceId Type: String DEPRECATED	O	A unique identifier of an app/device issued by the given SRC System. See details in Section 5.1.5 Recognition
recognitionToken Type: JWT	O	The explicit recognition token issued by the SRC System (Max length = 1024). See details in Section 5.1.5 Recognition

If the operation is processed successfully, the response body in Table 5.4.11 will be returned.

Table 5.4.11: Unbind App Instance Definition – Response Body

Data Element	R/C/O	Notes
srcCorrelationId Type: String	O	Unique identifier generated by an SRC System (Max length = 256)

Table 5.4.12: Unbind App Instance Definition – HTTP Status Codes

Code	Description
404	Not found, see <code>Error</code> object for details, e.g. <code>recognitionToken</code> provided in the request does not match the SRC Profile
2xx – 5xx	See Common HTTP Status Codes (Section 5.1.1)

5.5 Checkout Service

The Checkout Service provides Payment Data and payment related data for a specific checkout. It also allows provisioning of transaction credentials and retrieval or delivery of the `encryptedPayload` or `encryptedSignedPayload` to support a wide range of checkout use cases.

5.5.1 Prepare Checkout Data

The Prepare Checkout Data operation allows the SRCI to create a checkout request to fetch the DCF information along with the SRC checkout request JWS for the DCF.

The resulting `checkoutRequestJws` is signed by the SRC System and this structure needs to be passed to the SRC System for Checkout operation.

Table 5.5.1: Prepare Checkout Data Definition – HTTP Verb, Path and Parameters

HTTP Verb	POST
Path	/transaction/preparedata
Parameters	None

Table 5.5.2: Prepare Checkout Data Definition – Request Body

Data Element	R/C/O	Notes
srcClientId Type: String	R	Reference identifier of the connecting client (Max length = 255)
srcDpaid Type: String	C	Reference identifier of the DPA (Max length = 255) Must be provided if the calling client is an SRCI
srcCorrelationId Type: String	C	Unique identifier generated by an SRC System (Max length = 256) Must be provided if available within the present checkout session (e.g. received in an earlier response during the present session), otherwise a new checkout session will be initiated
serviceId Type: String	O	Service identifier associated to an SRC System specific configuration (Max length = 255)
srciTransactionId Type: String	O	Transactional identifier provided by the SRCI (Max length = 255)
srcInitiatorId Type: String	R	Reference identifier of the SRCI (Max length = 255)

Data Element	R/C/O	Notes
payloadTypeIndicatorCheckout Type: PayloadTypeIndicator	O	Type of encrypted payload to be returned in the Checkout operation response
payloadTypeIndicatorPayload Type: PayloadTypeIndicator	O	Type of encrypted payload to be created for the retrieval by the Get Payload operation
recipientIdCheckout Type: String	O	Recipient of the encrypted payload known to the SRC System (as provided in the Checkout operation response) for the intended recipient (Max length = 36)
recipientIdPayload Type: String	O	Recipient of the encrypted payload known to the SRC System (as retrieved by the Get Payload operation) for the intended recipient (Max length = 36)
customInputData Type: JSONObject	O	SRC System-specific input data
srcDigitalCardId Type: String	R	
consumerId Type: String DEPRECATED Replaced by srcConsumerId Type: String	C C	Must be provided if available within the present checkout session (e.g. received in an earlier API response during the present session)
shippingAddressIds Type: List<String>	O	List of shipping address reference identifiers (each with max length = 256)
authorization Type: String	O	
dpaTransactionOptions Type: DpaTransactionOptions	R	

Data Element	R/C/O	Notes
dpaData Type: DpaData	O	
assuranceData Type: AssuranceData	O	
checkoutResponseUri Type: String	O	Redirection URI for the DCF (Max length = 1024)

If the operation is processed successfully, the response body in Table 5.5.3 will be returned.

Table 5.5.3: Prepare Checkout Data Definition – Response Body

Data Element	R/C/O	Notes
srcCorrelationId Type: String	R	Unique identifier generated by an SRC System (Max length = 256)
checkoutRequestJws Type: JWS<CheckoutRequest>	R	The definition of <code>checkoutRequestJws</code> is included in Section 2.4.1 Checkout Request JWS

Table 5.5.4: Prepare Checkout Data Definition – HTTP Status Codes

Code	Description
404	Not Found, see <code>Error</code> object for details. Used to indicate the checkout flow does not require redirection to a DCF and the Checkout operation can be performed instead
2xx – 5xx	See Common HTTP Status Codes (Section 5.1.1)

5.5.2 Checkout

The Checkout operation utilises the Consumer's chosen Digital Card and details of the current transaction to retrieve Payment Data and payment related data.

If present in the `checkoutResponse` attribute, the `encryptedPayload` or `encryptedSignedPayload` encrypted according to JSON Web Encryption (JWE) specification RFC 7516 and the algorithm used for encryption is according to RFC 7518 Section 4.1.

Note that for the Checkout operation, the content of the request body depends on whether it contains:

- The signed `checkoutRequestJws` object (Table 5.5.6)
- Only unsigned checkout request data (Table 5.5.7)

Table 5.5.5: Checkout Definition – HTTP Verb, Path and Parameters

HTTP Verb	POST
Path	/transaction/credentials
Parameters	None

Table 5.5.6: Checkout Definition – Request Body

Table 5.5.6 defines the request body for requests containing the signed `checkoutRequestJws` object.

Data Element	R/C/O	Notes
srcClientId Type: String	R	Reference identifier of the connecting client (Max length = 255)
srcDpald Type: String	C	Reference identifier of the DPA (Max length = 255) Must be provided if the calling client is an SRCI
srcCorrelationId Type: String	C	Unique identifier generated by an SRC System (Max length = 256) Must be provided if available within the present checkout session (e.g. received in an earlier response during the present session), otherwise a new checkout session will be initiated
serviceId Type: String	O	Service identifier associated to an SRC System specific configuration (Max length = 255)

Data Element	R/C/O	Notes
srciTransactionId Type: String	O	Transactional identifier provided by the SRCI (Max length = 255)
shippingAddressId Type: String	O	Shipping address reference identifier (Max length = 256)
shippingAddress Type: Address	O	
acceptanceChannelRelatedData Type: AcceptanceChannelRelatedData	O	
complianceSettings Type: ComplianceSettings	O	
checkoutRequestJws Type: JWS<CheckoutRequest>	R	

Table 5.5.7: Checkout Definition – Request Body

Table 5.5.7 defines the request body for requests containing only unsigned checkout request data.

Data Element	R/C/O	Notes
srcClientId Type: String	R	Reference identifier of the connecting client (Max length = 255)
srcDpaId Type: String	C	Reference identifier of the DPA (Max length = 255)
dpaData Type: DpaData	C	Either <code>srcDpaId</code> or <code>dpaData</code> must be provided by the calling client when it is an SRCI

Data Element	R/C/O	Notes
srcCorrelationId Type: String	C	Unique identifier generated by an SRC System (Max length = 256) Must be provided if available within the present checkout session (e.g. received in an earlier response during the present session), otherwise a new checkout session will be initiated
serviceId Type: String	O	Service identifier associated to an SRC System specific configuration (Max length = 255)
srciTransactionId Type: String	O	Transactional identifier provided by the SRCI (Max length = 255)
payloadTypeIndicatorCheckout Type: PayloadTypeIndicator	O	Type of encrypted payload to be returned in the Checkout operation response
payloadTypeIndicatorPayload Type: PayloadTypeIndicator	O	Type of encrypted payload to be created for the retrieval by the Get Payload operation
recipientIdCheckout Type: String	O	Recipient of the encrypted payload known to the SRC System (as provided in the Checkout operation response) for the intended recipient (Max length = 36)
recipientIdPayload Type: String	O	Recipient of the encrypted payload known to the SRC System (as retrieved by the Get Payload operation) for the intended recipient (Max length = 36)
srcDigitalCardId Type: String	R	
shippingAddressId Type: String	O	Shipping address reference identifier (Max length = 256)
shippingAddress Type: Address	O	

Data Element	R/C/O	Notes
dpaTransactionOptions Type: DpaTransactionOptions	C	Must be provided if: <ul style="list-style-type: none"> • 3DS is to be performed by SRC System; <i>or</i> • Default configuration values are required to be overridden for a given transaction; <i>or</i> The calculation of Dynamic Data is dependent on knowing the transaction amount
acceptanceChannelRelatedData Type: AcceptanceChannelRelatedData	O	
assuranceData Type: AssuranceData	O	
complianceSettings Type: ComplianceSettings	O	

If the operation is processed successfully, the response body in Table 5.5.8 will be returned.

Table 5.5.8: Checkout Definition – Response Body

Data Element	R/C/O	Notes
checkoutResponse Type: JWS<CheckoutPayloadResponse>	R	encryptedPayload <i>or</i> encryptedSignedPayload will be not present within the checkoutResponse (see Table 2.59) when: <ul style="list-style-type: none"> • payloadTypeIndicatorCheckout is set to SUMMARY <i>or</i> • HTTP status code is 202 Note that the value of payloadTypeIndicatorCheckout is either dynamically supplied in the request (query) or statically derived using the default configured during DPA Registration

Table 5.5.9: Checkout Definition – HTTP Status Codes

Code	Description
200	The operation is processed successfully and the transaction credential response details are included in the response body
202	The operation is processed successfully and the SUMMARY payload is included in the response body. Further checks or authentication must be performed before checkout can be complete
409	Conflict, see <code>Error</code> object for details. For example, data supplied in <code>dpaTransactionOptions</code> is different from that supplied in <code>authenticationContext</code> in prior calls
4xx – 5xx	See Common HTTP Status Codes (Section 5.1.1)

5.5.3 Get Payload

The Get Payload operation returns Payment Data and payment related data to be used in payment authorisation.

The Get Payload operation is a server-side API intended for server-based communication.

Table 5.5.10: Get Payload Definition – HTTP Verb, Path and Parameters

HTTP Verb	GET
Path	/transaction/credentials
Parameters	None

Table 5.5.11: Get Payload Definition – Query Parameters

Data Element	R/C/O	Notes
srcClientId Type: String	R	Reference identifier of the connecting client (Max length = 255)

Data Element	R/C/O	Notes
payloadTypeIndicator Type: PayloadTypeIndicator	O	Identifies the type of encrypted payload to be returned. A value of SUMMARY is invalid for the Get Payload operation
recipientId Type: String	O	Recipient of the encrypted payload known to the SRC System (as provided in the Checkout operation response) for the intended recipient (Max length = 36). The SRC System will use this value to determine the key used for encryption of the payload
srcDpaId Type: String	C	Reference identifier of the DPA (Max length = 255) Must be provided if the calling client is an SRCI
srcCorrelationId Type: String	R	Unique identifier generated by an SRC System (Max length = 256)
serviceId Type: String	O	Service identifier associated to an SRC System specific configuration (Max length = 255)
srciTransactionId Type: String	O	Transactional identifier provided by the SRCI (Max length = 255)

If the operation is processed successfully, the response body in Table 5.5.12 will be returned. This request should return an HTTP Status Code of 400 indicating an invalid request when:

- `payloadTypeIndicator` in this request or `payloadTypeIndicatorPayload` in the Checkout operation or `checkout()` method is set to SUMMARY
- The Card has pending events which prevent a payload being returned

Table 5.5.12: Get Payload Definition – Response Body

Data Element	R/C/O	Notes
payloadResponse Type: JWS<CheckoutPayloadResponse>	R	Presence of either the <code>encryptedPayload</code> or <code>encryptedSignedPayload</code> data element within the <code>payloadResponse</code> (see Table 2.59) is always required

Table 5.5.13: Get Payload Definition – HTTP Status Codes

Code	Description
200	The operation is processed successfully and the transaction credential response details are included in the response body
4xx – 5xx	See Common HTTP Status Codes (Section 5.1.1)

5.5.4 Make Payment

The Make Payment operation allows an SRC System to send payload information for authorisation purposes directly to a payment SRCI.

Table 5.5.14: Make Payment Definition – HTTP Verb, Path and Parameters

HTTP Verb	POST
Path	/transaction/credentials
Parameters	None

Table 5.5.15: Make Payment Definition – Request Body

Data Element	R/C/O	Notes
signedTransactionCredentials Type: JWS<CheckoutPayloadResponse>	R	

Table 5.5.16: Make Payment Definition – HTTP Status Codes

Code	Description
2xx – 5xx	See Common HTTP Status Codes (Section 5.1.1)

5.6 Confirmation Service

The Confirmation Service enables SRC Participants to notify the SRC System of the checkout or payment results.

5.6.1 Confirmation

The Confirmation operation enables SRC Participants to provide a notification of the result of a checkout service (checkout or payment authorisation).

The Confirmation operation is server-side API intended for server-based communication.

Table 5.6.1: Confirmation Definition – HTTP Verb, Path and Parameters

HTTP Verb	POST
Path	/confirmations
Parameters	None

Table 5.6.2: Confirmation Definition – Request Body

Data Element	R/C/O	Notes
srcClientId Type: String	R	Reference identifier of the connecting client (Max length = 255)
srcDpald Type: String	C	Reference identifier of the DPA (Max length = 255) Must be provided if the calling client is an SRCI
srcCorrelationId Type: String	R	Unique identifier generated by an SRC System (Max length = 256)

Data Element	R/C/O	Notes
serviceld Type: String	O	Service identifier associated to an SRC System specific configuration (Max length = 255)
srciTransactionId Type: String	O	Transactional identifier provided by the SRCI (Max length = 255)
assuranceData Type: AssuranceData DEPRECATED	Ø	
customData Type: JSONObject	O	
confirmationData Type: ConfirmationData DEPRECATED <i>Replaced by</i> confirmationData2 Type: ConfirmationData2	R R	

Table 5.6.3: Confirmation Definition – HTTP Status Codes

Code	Description
2xx – 5xx	See Common HTTP Status Codes (Section 5.1.1)

5.7 Identity Service

The Identity Service enables operations related to identity recognition, validation of identity and the generation of Federated ID Tokens.

The service allows identity validation to be a two-step process encompassing initiation and completion to allow challenge/response interaction with the Consumer within the SRC experience. It is also possible that an out of band mechanism be used in which case the challenge/response within the SRC experience may not be necessary.

When requested, the SRC System should perform the validation of the identity (to verify possession) regardless of whether the Consumer Identity is associated with an SRC Profile or not.

5.7.1 Identity Lookup

The Identity Lookup operation utilises a provided Consumer Identity (email address or mobile phone number) to determine whether it is associated with an SRC Profile.

Table 5.7.1: Identity Lookup Definition – HTTP Verb, Path and Parameters

HTTP Verb	POST
Path	/identities/lookup
Parameters	None

Table 5.7.2: Identity Lookup Definition – Request Body

Data Element	R/C/O	Notes
srcClientId Type: String	R	Reference identifier of the connecting client (Max length = 255)
serviceId Type: String	O	Service identifier associated to an SRC System specific configuration (Max length = 255)
consumerIdentity Type: ConsumerIdentity	R	

If the operation is processed successfully, the response body in Table 5.7.3 will be returned.

Table 5.7.3: Identity Lookup Definition – Response Body

Data Element	R/C/O	Notes
consumerPresent Type: Boolean DEPRECATED <i>Replaced by</i> consumerPresent1 Type: Boolean	C R	consumerPresent must be provided if the specified Consumer Identity was recognised by the SRC System Indicates whether the Identity Lookup operation was successful or not
idLookupSessionId Type: String	C	Session identifier of format UUID, returned by SRC System following an Identity Lookup operation. Can be used in subsequent Initiate Identity Validation operation
consumerStatus Type: ConsumerStatus	C	consumerStatus, idLookupSessionId and the list of supportedValidationChannels must all be provided if the specified Consumer Identity was recognised by the SRC System
supportedValidationChannels Type: List<IdentityValidationChannel>	C	
lastUsedCardTimestamp Type: String	O	

Table 5.7.4: Identity Lookup Definition – HTTP Status Codes

Code	Description
200	The operation is processed successfully and the lookup result is included in the response body
4xx – 5xx	See Common HTTP Status Codes (Section 5.1.1)

5.7.2 Initiate Identity Validation

The Initiate Identity Validation operation initiates a process to validate that a Consumer is in the possession of, or has access to, the Consumer Identity claimed.

Table 5.7.5: Initiate Identity Validation Definition – HTTP Verb, Path and Parameters

HTTP Verb	POST
Path	/identities/validation/initiate
Parameters	None

Table 5.7.6: Initiate Identity Validation Definition – Request Body

Data Element	R/C/O	Notes
srcClientId Type: String	R	Reference identifier of the connecting client (Max length = 255)
serviceId Type: String	O	Service identifier associated to an SRC System specific configuration (Max length = 255)
idLookupSessionId Type: String	C	Session identifier of format UUID, returned by SRC System following an Identity Lookup operation. Can be used in subsequent Initiate Identity Validation operation
consumerIdentity Type: ConsumerIdentity	C	Exactly one of <code>consumerIdentity</code> or <code>idLookupSessionId</code> must be provided
requestedValidationChannel Type: IdentityValidationChannel	O	

If the operation is processed successfully, the response body in Table 5.7.7 will be returned.

Table 5.7.7: Initiate Identity Validation Definition – Response Body

Data Element	R/C/O	Notes
idValidationSessionId Type: String	R	Session identifier of UUID format, returned by SRC System following an Initiate Identity Validation operation. Used in subsequent Complete Identity Validation operation

Data Element	R/C/O	Notes
maskedValidationChannel Type: IdentityValidationChannel	R	
validationMessage Type: String	O	Validation message that needs to be presented to the Consumer for step up authentication (Max length = 255)
supportedValidationChannels Type: List<IdentityValidationChannel>	O	
uriData Type: UriData	O	URI (e.g. Android App link, IOS universal link)

Table 5.7.8: Initiate Identity Validation Definition – HTTP Status Codes

Code	Description
200	The operation is processed successfully and the verification request results are included in the response body
404	Not Found, see <code>Error</code> object for details. Used to indicate that the identity provided was not recognised
4xx – 5xx	See Common HTTP Status Codes (Section 5.1.1)

5.7.3 Complete Identity Validation

The Complete Identity Validation operation determines whether data, provided by the Consumer as part of a second step of an identity validation process, is valid. It can also be used to check whether an out-of-band service was successful.

Table 5.7.9: Complete Identity Validation Definition – HTTP Verb, Path and Parameters

HTTP Verb	POST
Path	/identities/validation/complete
Parameters	None

Table 5.7.10: Complete Identity Validation Definition – Request Body

Data Element	R/C/O	Notes
srcClientId Type: String	R	Reference identifier of the connecting client (Max length = 255)
serviceId Type: String	O	Service identifier associated to an SRC System specific configuration (Max length = 255)
idValidationSessionId Type: String	R	Session identifier of UUID format, returned by SRC System following an Initiate Identity Validation operation. Used in subsequent Complete Identity Validation operation
validationData Type: String	C	Validation data (e.g. OTP) as entered by the Consumer as a part of the step up authentication (Max length = 255) Must be provided if type of identity validation channel was other than OUT_OF_BAND

Table 5.7.11: Complete Identity Validation Definition – Response Headers

Header	Retry-After: may be specified by the server when HTTP status code is 202.
---------------	---

If the operation is processed successfully, the response body in Table 5.7.12 will be returned.

Table 5.7.12: Complete Identity Validation Definition – Response Body

Data Element	R/C/O	Notes
idToken Type: JWT	R	
maskedCard Type: MaskedCard	O	MaskedCard representing the last used card

Table 5.7.13: Complete Identity Validation Definition – HTTP Status Codes

Code	Description
200	The operation is processed successfully, validation of identity has been successfully completed and the Federated ID Token included in the response body
202	OK, validation still in progress and no result yet available
4xx – 5xx	See Common HTTP Status Codes (Section 5.1.1)

5.7.4 Is Recognized

The Is Recognized operation uses a Device Identity (derived from a First Party Token) to determine whether it is bound to an SRC Profile and, if so, returns a Federated ID Token.

Table 5.7.14: Is Recognized Definition – HTTP Verb, Path and Parameters

HTTP Verb	GET
Path	/identities/recognize
Parameters	None

Table 5.7.15: Is Recognized Definition – Query Parameters

Data Element	R/C/O	Notes
srcClientId Type: String	R	Reference identifier of the connecting client (Max length = 255)
srcDpald Type: String	C	Reference identifier of the DPA (Max length = 255) Must be provided if the calling client is an SRCI
serviceId Type: String	O	Service identifier associated to an SRC System specific configuration (Max length = 255)

Data Element	R/C/O	Notes
srciTransactionId Type: String	O	Transactional identifier provided by the SRCI (Max length = 255)
appInstanceId Type: String DEPRECATED	O	A unique identifier of an app/device issued by the given SRC System. See details in Section 5.1.5 Recognition
recognitionToken Type: JWT	O	An explicit recognition token issued by the SRC System. See details in Section 5.1.5 Recognition

If the operation is processed successfully, the response body in Table 5.7.16 will be returned.

Table 5.7.16: Is Recognized Definition – Response Body

Data Element	R/C/O	Notes
srcCorrelationId Type: String	O	Unique identifier generated by an SRC System (Max length = 256)
idTokens Type: List<JWT>	R	Each idToken in the list should be a Federated ID Token <ul style="list-style-type: none"> If the Consumer Device is recognised, a list of idTokens must be provided, one for each established SRC Profile associated to the recognised Consumer application instance If the Consumer Device is not recognised, the list must be empty
appInstanceId Type: String DEPRECATED	O	Must be supplied if the connecting consumer application instance is recognised by the SRC System
recognitionToken Type: JWT	O	An explicit recognition token issued by the SRC System (Max length = 1024). See details in Section 5.1.5

Data Element	R/C/O	Notes
recognitionDomainName Type: String	O	A redirection to a domain that may facilitate recognition of the Consumer Device (e.g. browser or client application) by the SRC System (Max length = 256)

Table 5.7.17: Is Recognized Definition – HTTP Status Codes

Code	Description
200	The operation is processed successfully, the Consumer application instance was recognised and the recognition data is included in the response body
4xx – 5xx	See Common HTTP Status Codes (Section 5.1.1)

5.8 Authentication Facilitation Service

The Authentication Facilitation Service provides operations to enable Cardholder, Card and Consumer authentication methods to be performed. Examples include:

- OTP (SMS or email)
- 3DS authentication
- Card Security Code (CSC) validation

The Authentication Methods Lookup operation returns a list of methods that are relevant to the criteria specified by the client, which chooses one of the methods to facilitate the authentication process using the Authenticate operation.

5.8.1 Authentication Methods Lookup

The Authentication Methods Lookup operation obtains a proposed list of authentication methods relevant to criteria specified by the client.

Table 5.8.1: Authentication Methods Lookup Definition – HTTP Verb, Path and Parameters

HTTP Verb	POST
Path	/authentications/lookup

Parameters	None
-------------------	------

Table 5.8.2: Authentication Methods Lookup Definition – Request Body

Data Element	R/C/O	Notes
srcClientId Type: String	R	Reference identifier of the connecting client (Max length = 255)
serviceId Type: String	O	Service identifier associated to an SRC System specific configuration (Max length = 255)
srcCorrelationId Type: String	O	Unique identifier generated by an SRC System (Max length = 256)
srciTransactionId Type: String	O	Transactional identifier provided by the SRCI (Max length = 255)
accountReference Type: AccountReference	R	
authenticationContext Type: AuthenticationContext	R	

If the operation is processed successfully, the response body in Table 5.8.3 will be returned.

Table 5.8.3: Authentication Methods Lookup Definition – Response Body

Data Element	R/C/O	Notes
srcCorrelationId Type: String	O	Unique identifier generated by an SRC System (Max length = 256)
srciTransactionId Type: String	O	Transactional identifier provided by the SRCI (Max length = 255)
authenticationSessionId Type: String	O	
assuranceData Type: AssuranceData	O	

Data Element	R/C/O	Notes
authenticationMethods List<AuthenticationMethod>	R	List of available authentication methods

Table 5.8.4: Authentication Methods Lookup Definition – HTTP Status Codes

Code	Description
2xx – 5xx	See Common HTTP Status Codes (Section 5.1.1)

5.8.2 Authenticate

The Authenticate operation can:

- Initiate a multi-step authentication based on specified input criteria
- Complete in-band validation, passing validation data for assessment, e.g. OTP value
- Check progress / status of an on-going out-of-band validation, where validation occurs on another channel

In the final case, validation data is not supplied, but the `authenticationSessionId` provides the context.

Table 5.8.5: Authenticate Definition – HTTP Verb, Path and Parameters

HTTP Verb	POST
Path	/authentications/authenticate
Parameters	None

Table 5.8.6: Authenticate Definition – Request Body

Data Element	R/C/O	Notes
srcClientId Type: String	R	Reference identifier of the connecting client (Max length = 255)
serviceId Type: String	O	Service identifier associated to an SRC System specific configuration (Max length = 255)

Data Element	R/C/O	Notes
srcCorrelationId Type: String	O	Unique identifier generated by an SRC System (Max length = 256)
srciTransactionId Type: String	O	Transactional identifier provided by the SRCI (Max length = 255)
authenticationSessionId Type: String	C	Must be provided if available from a previously initiated authentication event
accountReference Type: AccountReference	C	Must be provided if <code>authenticationSessionId</code> is not available
authenticationContext Type: AuthenticationContext	C	Must be provided if <code>authenticationSessionId</code> is not available
authenticationMethod Type: AuthenticationMethod	R	

If the operation is processed successfully, the response body in Table 5.8.7 will be returned. If authentication is invoked by using `uriData` provided in `authenticationMethod`, then the data elements in the response body need to be returned asynchronously to SRC Initiator via a cross origin Post Message.

Table 5.8.7: Authenticate Definition – Response Body

Data Element	R/C/O	Notes
srcCorrelationId Type: String	O	Unique identifier generated by an SRC System (Max length = 256)
srciTransactionId Type: String	O	Transactional identifier provided by the SRCI (Max length = 255)
authenticationSessionId Type: String	R	
authenticationResult Type: AuthenticationResult	C	Must be provided if <code>authenticationStatus</code> is COMPLETE

Data Element	R/C/O	Notes
authenticationStatus Type: AuthenticationStatus	R	
assuranceData Type: AssuranceData	C	See AssuranceData Must be provided if <code>authenticationStatus</code> is COMPLETE
methodAttributes Type: JSONObject	C	Any relevant attributes supplied by the SRC System Must be provided as specified in Section 2.2.1 Authentication Facilitation

Table 5.8.8: Authenticate Definition – Response Headers

Header	Retry-After: may be specified by the server when HTTP status code is 202.
---------------	---

Table 5.8.9: Authenticate Definition – HTTP Status Codes

Code	Description
202	OK, validation still in progress and no result yet available
409	The supplied authentication method doesn't match the authentication context
2xx – 5xx	See Common HTTP Status Codes (Section 5.1.1)

5.9 Public Keys Retrieval Service

The Public Keys Retrieval service enables retrieval of cryptographic public keys from a well-known URI hosted by an SRC System. The keys retrieved are used by other SRC Participants for Federated ID Token and JWS signature verification.

Each SRC System must host cryptographic public keys for retrieval by other SRC Systems and SRC Participants to allow signature verification and encryption in the following cases:

- Federated ID Token is signed JWT in the form of JWS

- checkoutRequest, checkoutResponse, payloadResponse and (optionally) encryptedSignedPayload are signed in the form of JWS
- Payment Card and Consumer details presented during Enrolment can be encrypted in the form of JWE

Each SRC System must publish the cryptographic public keys on the web in well-known location to allow discovery of the keys by the relying party. Each key must be easily identifiable so it can be selected by the relying party based on the key ID (“kid”) specified in the header of the JWS.

For signature verification, key retrieval and selection process for SRC Systems follows the steps below:

1. The relying party discovers the URI of the signature issuer by examining the JWS content (i.e. “iss”) or using some other method.
2. The relying party retrieves the set of public keys available at the well-known path on issuer host as per issuer URI
3. The relying party examines JWS header to discover the key ID (“kid” member) and cryptographic signature algorithm (“alg” member).
4. The relying party selects the corresponding public key that matched the key ID and performs verification of the signature following the algorithm

For encryption, the recipient party should fetch the key from the well-known path based on a pre-agreed key ID.

Note: *Symmetric Key Retrieval is not defined in this version of the specification.*

5.9.1 Public Key Retrieval

The Public Key Retrieval operation retrieves a set of public keys.

Table 5.9.1: Public Key Retrieval Definition – HTTP Verb, Path and Parameters

HTTP Verb	GET
Path	/keys
Parameters	None

If the operation is processed successfully, the response body in Table 5.9.2 will be returned.

Table 5.9.2: Public Key Retrieval Definition – Response Body

Data Element	R/C/O	Notes
keySet Type: JWKS	R	<p>JSON Web Key Set (JWKS) as specified by JSON Web Key standard (RFC 7517).</p> <p>The keyset must specify at least one valid public key.</p> <p>Each key in the keyset must contain the following details:</p> <ul style="list-style-type: none">• Key ID (“kid”) used for key selection as described in the flow above• Key type (“kty”). <p>It is also recommended to specify Key Operations (“key_ops”) with value “verify” to indicate the public key intended use.</p> <p>The key is specified as an X.509 certificate chain (“x5c”)</p>

Table 5.9.3: Public Key Retrieval Definition – HTTP Status Codes

Code	Description
2xx – 5xx	See Common HTTP Status Codes (Section 5.1.1)

Handling of keys used to encrypt the `encryptedPayload` or the `encryptedSignedPayload` returned by SRC Systems is out the scope of the SRC Specifications. The encryption algorithms and keys should be specified by SRC Programme.

5.10 Retrieve Latest Compliance Resources Service

The Retrieve Latest Compliance Resources service allows the retrieval of latest compliance resource URI for consent from a well-known URI hosted by an SRC System.

5.10.1 Latest Compliance Resources Retrieval

The Latest Compliance Resources Retrieval operation retrieves the latest compliance resource URI for consent from a well-known URI hosted by an SRC System.

Table 5.10.1: Latest Compliance Resources Retrieval Definition – HTTP Verb, Path and Parameters

HTTP Verb	POST
Path	/compliance
Parameters	None

Table 5.10.2: Latest Compliance Resources Retrieval Definition – Request Body

Data Element	R/C/O	Notes
encryptedCard Type: JWE<Card>	C	Either <code>encryptedCard</code> or <code>srcDigitalCardId</code> must be provided, but not both
srcDigitalCardId Type: String (Numeric)	C	
srcClientId Type: String	R	Reference identifier of the connecting client (Max length = 255)
dpaLocale Type: String	O	

If the operation is processed successfully, the response body in Table 5.10.3 will be returned.

Table 5.10.3: Latest Compliance Resources Retrieval Definition – Response Body

Data Element	R/C/O	Notes
complianceResources Type: list<ComplianceResource>	R	

Table 5.10.4: Latest Compliance Resources Retrieval Definition – HTTP Status Codes

Code	Description
2xx – 5xx	See Common HTTP Status Codes (Section 5.1.1)

5.11 Management Service

The Management Service allows an SRC System to provide various management functions to its participants.

5.11.1 DPA Registration

The DPA Registration operation is provided for an SRC Initiator to register a DPA in the SRC System. After successful registration, the `srcDpaId` returned by SRC System can be used by SRC Initiator in future operations.

Table 5.11.1: DPA Registration Definition – HTTP Verb, Path and Parameters

HTTP Verb	POST
Path	/dpas
Parameters	None

Table 5.11.2: DPA Registration Definition – Request Body

Data Element	R/C/O	Notes
srcInitiatorId Type: String	R	Reference identifier of the SRCI (Max length = 255)
serviceId Type: String	O	Service identifier associated to an SRC System specific configuration (Max length = 255)
action Type: Action	R	

Data Element	R/C/O	Notes
srcDpaId Type: String	C	Reference identifier of the DPA (Max length = 255) Must be provided if <code>action</code> is one of: <ul style="list-style-type: none">• ACTIVATION• DEACTIVATION• UPDATE
dpaData Type: DpaData	C	Must be provided only when <code>action</code> is one of: <ul style="list-style-type: none">• REGISTRATION• UPDATE

If the operation is processed successfully, the response body in Table 5.11.3 will be returned.

Table 5.11.3: DPA Registration Definition – Response Body

Data Element	R/C/O	Notes
srcDpaId Type: String	R	Reference identifier of the DPA (Max length = 255)

Table 5.11.4: DPA Registration Definition – HTTP Status Codes

Code	Description
2xx – 5xx	See Common HTTP Status Codes (Section 5.1.1)

6 Notification Service

The Notification service enables outbound messages sent by the SRC System when specific events occur.

6.1 Notifications Principles

The notifications are sent as HTTP POST messages to the specific endpoint. The SRC System must support HTTPS and use it as default.

The SRC System maintains a registry of the SRC Participants (notification subscribers) for any given event. Each notification subscriber must be Onboarded to the SRC System and the base URIL of the notification subscriber's server provided as configuration data. The Onboarding and configuration of the notification subscribers are out of scope of this document.

Each notification defines a specific path that should be appended to the base URIL specified for the notification subscriber.

The "Success" HTTP status code indicates to the SRC System that the notification has been received, acknowledged and understood. In case of an error, client or server, the entity which contains an explanation of the error should be provided.

6.1.1 Data Delivery Modes

Where applicable, the following two data delivery models should be considered:

- Push Model – where the SRC System includes the data in the body of the notification. The notification subscriber receives the full set of data associated with the event that triggered the notification
- Push-Pull Model – where the SRC System only includes a specific entity identifier or session identifier (and optionally a First Party Token) in the request body of the notification. The notification subscriber willing to act on the notification received should refer to the specific API to fetch the data associated with the event that triggered the notification

The SRC System may support either one or both data delivery models.

6.1.2 Standard HTTP Status Codes

For the notifications the standard classes of HTTP status codes should be used by the server hosting subscriber's notification endpoint. These are described in Table 6.1.

Table 6.1: Standard HTTP Status Codes

Code Class	Type	Description
2XX	Success	This class of status codes indicates the notification was received by the subscriber, understood, accepted.
3XX	Redirection	Indicates that further action may be taken by the SRC System in order to fulfil the delivery of notification. SRC System is under no obligation to follow the actions indicated.
4XX	Client Error	Intended for cases in which the SRC System originating the notification seems to have encounter an error and therefore the subscriber's endpoint cannot acknowledge the reception of the notification.
5XX	Server Error	Indicate cases in which the subscriber's server is aware that it has encountered an error or is otherwise incapable of handling the notification.

In case of the error HTTP codes, the subscriber's server should include a standard Error entity containing an explanation of the error situation.

Support for individual HTTP codes for the classes given above is optional for the SRC System.

6.2 Card Update Event Notification

The Card Update Event notification sends a message to subscribers when a Digital Card's information has been modified or updated.

Each notification must specify the timestamp of the event and must contain the reason for the modification or update.

The SRC System may support two notification delivery models:

- The request body may contain the `maskedCard` object representing the updated Digital Card, or
- The request body may only contain the `srcDigitalCardId` along with the optional `authorization` (a First Party Token). The subscriber may then fetch the `maskedCard` object using the Get Card Data operation

Table 6.2.1: Card Update Event Notification Definition – HTTP Verb, Path and Parameters

HTTP Verb	POST
Path	/notifications/cards
Parameters	None

Table 6.2.2: Card Update Event Notification Definition – Request Body

Data Element	R/C/O	Notes
digitalCardUpdateNotifications Type: List<DigitalCardUpdateNotification>	R	

Table 6.2.3: Card Update Event Notification Definition – HTTP Status Codes

Code	Description
204	No Content, the subscriber acknowledges the receipt of the notification
400	Bad Request, the request body has been malformed or otherwise prohibits the subscriber to process the notification
2xx – 5xx	See Standard HTTP Status Codes (Section 6.1.2)

6.3 Identity Validation Completion Event Notification

The Identity Validation Complete Event notification sends a message to subscribers when an SRC System determines, or is itself notified, that an out-of-band identity validation service has completed.

The SRC System may support two notification delivery models:

- The request body may contain a Federated ID Token; *or*
- The request body may contain an `idValidationSessionId` along with the optional `authorization` (a First Party Token). The subscriber may the fetch the Federated ID Token using the Complete Identity Validation operation

Table 6.3.1: Identity Validation Completion Event Notification Definition – HTTP Verb, Path and Parameters

HTTP Verb	POST
Path	/notifications/identities/validation/complete
Parameters	None

Table 6.3.2: Identity Validation Completion Event Notification Definition – Request Body

Data Element	R/C/O	Notes
idValidationSessionId Type: String	R	Session identifier of UUID format, returned by SRC System following an Initiate Identity Validation operation. Used in subsequent Complete Identity Validation operation
idToken Type: JWT	C	Either <code>idToken</code> or <code>error</code> must be provided if the subscriber is configured in the push model
error Type: Error	C	
maskedCard Type: MaskedCard	O	MaskedCard representing the last used card
authorization Type: String	O	

Table 6.3.3: Identity Validation Completion Event Notification Definition – HTTP Status Codes

Code	Description
204	No Content, the subscriber acknowledges the receipt of the notification
400	Bad Request, the request body has been malformed or otherwise prohibits the subscriber to process the notification

Code	Description
2xx – 5xx	See Standard HTTP Status Codes (Section 6.1.2)

6.4 Authentication Event Notification

The Authentication Event Notification sends a message to subscribers when an authentication event is completed (`authenticationStatus` is set to COMPLETE).

Table 6.4.1: Authentication Event Notification Definition – HTTP Verb, Path and Parameters

HTTP Verb	POST
Path	/notifications/authentications
Parameters	None

Table 6.4.2: Authentication Event Notification Definition – Request Body

Data Element	R/C/O	Notes
authenticationSessionId Type: String	R	
srcCorrelationId Type: String	O	Unique identifier generated by an SRC System (Max length = 256)
srciTransactionId Type: String	O	Transactional identifier provided by the SRCI (Max length = 255)
authenticationResult Type: AuthenticationResult	C	Must be provided if <code>authenticationStatus</code> is COMPLETE
authenticationStatus Type: Authenticationstatus	R	
assuranceData Type: AssuranceData	C	See AssuranceData Must be provided if <code>authenticationStatus</code> is COMPLETE

Table 6.4.3: Authentication Event Notification Definition – HTTP Status Codes

Code	Description
204	No Content, the subscriber acknowledges the receipt of the notification
400	Bad Request, the request body has been malformed or otherwise prohibits the subscriber to process the notification
2xx – 5xx	See Standard HTTP Status Codes (Section 6.1.2)

6.5 Payment Notification

The Payment Notification sends a message to subscribers when an SRC System has received a confirmation of payment authorisation.

Each Payment Notification must specify the timestamp of the payment completion event and must contain the status of the payment authorisation.

Table 6.5.1: Payment Notification Definition – HTTP Verb, Path and Parameters

HTTP Verb	POST
Path	/notifications/payment
Parameters	None

Table 6.5.2: Payment Notification Definition – Request Body

Data Element	R/C/O	Notes
srcCorrelationId Type: String	R	Unique identifier generated by an SRC System (Max length = 256)
srciTransactionId Type: String	O	Transactional identifier provided by the SRCI (Max length = 255)
serviceId Type: String	O	Service identifier associated to an SRC System specific configuration (Max length = 255)

Data Element	R/C/O	Notes
srcDigitalCardId Type: String	O	
confirmationData2 Type: ConfirmationData2	R	
customData Type: JSONObject	O	

Table 6.5.3: Payment Notification Definition – HTTP Status Codes

Code	Description
204	No Content, the subscriber acknowledges the receipt of the notification
400	Bad Request, the request body has been malformed or otherwise prohibits the subscriber to process the notification
4xx – 5xx	See Standard HTTP Status Codes (Section 6.1.2)

Annex A EMVCo Specification Mapping

This Annex describes the mapping of data from other EMVCo specifications to these SRC Specifications. It provides a level of interoperability for an implementation using another EMVCo specification to use SRC to process such a transaction.

A.1 Merchant-Presented Mode – QR Code Payload

Annex A.1 describes the mapping of data from the QR Code Payload described in the Merchant-Presented Mode specification (EMV® QR Code Specification for Payment Systems (EMV QRCPS) – Merchant-Presented Mode). As per the Merchant-Presented Mode specification, this describes any conversion of data necessary as well as any additional data needed to process the transaction.

The mapping is described from the perspective of the Mobile Application consuming a QR Code Payload and building the SRC data elements to be populated to SRC API input parameters and SRC JavaScript SDK attributes. The descriptions below all assume that the QR Code Payload complies with the Merchant-Presented Mode specification.

A.1.1 SRC Data Elements

The following SRC data elements, parameters, objects or attributes are populated with Merchant-Presented Mode QR specific data. Based on the mapping described, when processing a Merchant-Presented Mode QR Code payment transaction using SRC, `acceptanceChannelRelatedData` is a required input parameter or attribute in the relevant SRC API operation or SRC JavaScript SDK method.

Transaction Amount

The `transactionAmount` data element of the `TransactionAmount` object is populated with:

- The transaction amount; *or*
- When there is also a tip or convenience fee (see Annex A.1.4 QR Code Specific Data Elements for Additional Amounts), the sum of the transaction amount and the tip or convenience fee

The value of the transaction amount is dependent on the presence of the Transaction Amount (ID “54”) in the QR Code Payload.

- If present, the transaction amount referred to above is the value present in Transaction Amount (ID “54”) in the QR Code Payload

- If not present, the transaction amount referred to above is the Consumer-entered amount

Transaction Currency

The `transactionCurrency` data element of the `TransactionAmount` object is populated with the Transaction Currency (ID “53”) in the QR Code Payload.

Acceptance Channel Type

The `acceptanceChannelType` data element of the `AcceptanceChannelRelatedData` object is populated with the value of `EMV_MERCHANT_PRESENTED_MODE`

Acceptance Channel Technology

The `acceptanceChannelTechnology` data element of the `AcceptanceChannelRelatedData` object is populated with the value of `QR_CODE`.

Digital Payment Application Data

The `merchantAccountInformation` data element of the `DpaData` object is populated with the Merchant Account Information (IDs “02” to “51”) of the QR Code Payload. It is only necessary to populate the content of the ID relevant to the receiving SRC System, which is based on which SRC System maintains the Digital Card selected for the specific transaction:

- ID “02” or “03” for the Visa SRC System
- ID “04” and “05” for the Mastercard SRC System
- ID “09” or “10” for the Discover SRC System
- ID “11” and “12” for the Amex SRC System
- ID “13” or “14” for the JCB SRC System
- ID “15” and “16” for the Union Pay SRC System

A.1.2 QR Code specific Data Elements for Seller Data

The following data element is defined specifically for the `sellerData` object which is a data element of the `AcceptanceChannelData` object (see Table 2.1).

QR Code Payload

Always populated with the full content of the QR Code Payload.

Table A.1: SRC API Usage for QR Code Payload

qrCodePayload	
Type	String
Constraint	Maximum length of 2048
Present in object	<code>sellerData</code>

A.1.3 QR Code specific Data Elements for Consumer Data

The following data elements are defined specifically for the `consumerData` object which is a data element of the `AcceptanceChannelData` object (see Table 2.1). Consumer Data will only be present and populated if one or more of the following data objects are indicated within the QR Code Payload

Bill Number

Populated with a Consumer-entered bill number if the Bill Number (ID “01”), with a value of “***”, is present within the Additional Data Field Template (ID “62”) of the QR Code Payload.

Table A.2: SRC API Usage for Bill Number

billNumber	
Type	String
Constraint	Maximum length of 25
Present in object	<code>consumerData</code>

Mobile Number

Populated with a Consumer-entered mobile number if the Mobile Number (ID “02”), with a value of “****”, is present within the Additional Data Field Template (ID “62”) of the QR Code Payload.

Table A.3: SRC API Usage for Mobile Number

mobileNumber	
Type	String
Constraint	Maximum length of 25
Present in object	consumerData

Store Label

Populated with a Consumer-entered store label if the Store Label (ID “03”), with a value of “***”, is present within the Additional Data Field Template (ID “62”) of the QR Code Payload.

Table A.4: SRC API Usage for Store Label

storeLabel	
Type	String
Constraint	Maximum length of 25
Present in object	consumerData

Loyalty Number

Populated with a Consumer-entered loyalty number if the Loyalty Number (ID “04”), with a value of “****”, is present within the Additional Data Field Template (ID “62”) of the QR Code Payload.

Table A.5: SRC API Usage for Loyalty Number

loyaltyNumber	
Type	String
Constraint	Maximum length of 25
Present in object	consumerData

Reference Label

Populated with a Consumer-entered reference label if the Reference Label (ID “05”), with a value of “****”, is present within the Additional Data Field Template (ID “62”) of the QR Code Payload.

Table A.6: SRC API Usage for Reference Label

referenceLabel	
Type	String
Constraint	Maximum length of 25
Present in object	consumerData

Customer Label

Populated with a Consumer-entered Customer label if the Customer Label (ID “06”), with a value of “****”, is present within the Additional Data Field Template (ID “62”) of the QR Code Payload.

Table A.7: SRC API Usage for Customer Label

customerLabel	
Type	String
Constraint	Maximum length of 25
Present in object	consumerData

Terminal Label

Populated with a Consumer-entered terminal label if the Terminal Label (ID “07”), with a value of “****”, is present within the Additional Data Field Template (ID “62”) of the QR Code Payload.

Table A.8: SRC API Usage for Terminal Label

terminalLabel	
Type	String
Constraint	Maximum length of 25

terminalLabel	
Present in object	consumerData

Purpose of Transaction

Populated with a Consumer-entered transaction purpose if the Purpose of Transaction (ID “08”), with a value of “***”, is present within the Additional Data Field Template (ID “62”) of the QR Code Payload.

Table A.9: SRC API Usage for Purpose of Transaction

purposeOfTransaction	
Type	String
Constraint	Maximum length of 25
Present in object	consumerData

Email

Populated with an email known to the Mobile Application if the Additional Consumer Data Request (ID “09”), with a value containing the character “E”, is present within the Additional Data Field Template (ID “62”) of the QR Code Payload.

Table A.10: SRC API Usage for Email

email	
Type	String
Constraint	Maximum length of 255
Present in object	consumerData

Phone Number

Populated with an mobile number known to the Mobile Application if the Additional Consumer Data Request (ID “09”), with a value containing the character “M”, is present within the Additional Data Field Template (ID “62”) of the QR Code Payload.

Table A.11: SRC API Usage for Phone Number

phoneNumber	
Type	String
Constraint	A length ranging from 4 to 14
Present in object	consumerData

Address

Populated with an address known to the Mobile Application if the Additional Consumer Data Request (ID “09”), with a value containing the character “A”, is present within the Additional Data Field Template (ID “62”) of the QR Code Payload.

Table A.12: SRC API Usage for Address

address	
Type	String
Constraint	Maximum length of 2048
Present in object	consumerData

A.1.4 QR Code Specific Data Elements for Additional Amounts

The following data elements are defined specifically for the `additionalAmounts` list which is a data element the `TransactionAmount` object (see Table 2.45).

Tip

A floating-point number only populated with a Consumer-entered tip value if Tip or Convenience Indicator (ID “55”), containing a value of “01”, is present within the QR Data Payload.

If present with the relevant value, populate an entry of the `additionalAmounts` list with the values in Table A.13.

Table A.13: SRC API Usage for Tip

Data Element	Value
<code>additionalAmountType</code>	TIP
<code>additionalAmountValue</code>	Consumer entered tip value

Convenience Fee

A floating-point number only populated if the Tip or Convenience Indicator (ID “55”), containing a value of “02” or “03”, is present within the QR Data Payload.

If present with the relevant values, populate an entry of the `additionalAmounts` list with the values in Table A.14.

Table A.14: SRC API Usage for Convenience Fee

Data Element	Value
<code>additionalAmountType</code>	CONVENIENCE_FEE
<code>additionalAmountValue</code>	<p>If the value of ID “55” is:</p> <ul style="list-style-type: none">• “02” then populate with the content of the Value of Convenience Fee Fixed (ID “56”) present within the QR Data Payload (converted to a floating-point number)• “03” then populate with a Mobile Application calculated value, equal to a percentage of the Sub Total. The percentage used for the calculation is the Convenience Fee Percentage (ID “57”) value present in the QR Code Payload

Sub Total

A floating-point number only populated if one of the above `tip` or `convenienceFee` data elements is populated.

If a `tip` or `convenienceFee` data elements is populated, then populate an entry of the `additionalAmounts` list with the values in Table A.15.

Table A.15: SRC API Usage for Sub Total

Data Element	Value
additionalAmountType	SUB_TOTAL
additionalAmountValue	Either the: <ul style="list-style-type: none">• Transaction Amount (ID “54”) if present in the QR Code Payload (converted to a floating-point number); <i>or</i>• Consumer-entered amount if the Transaction Amount (ID “54”) is not present in the QR Code Payload

Annex B 3DS Data

This Annex describes the additional data elements required specifically for 3DS Input Data and 3DS Output Data when `threeDsPreference` in `DpaTransactionOptions` is set to `ONBEHALF`.

Note: data elements defined in this Annex may be duplicates of data elements defined elsewhere in this specification.

B.1 3DS Input Data

The `threeDsInputData` object is defined as `JSONObject` type and is populated with the data elements as defined in the 3DS Specification. This includes, but is not necessarily limited to, those data elements shown in Table B.1.

Table B.1: 3DS Input Data

Name	Constraints	Description
acquirerMerchantId Type: String	Max Length = 35	Acquirer-assigned merchant identifier. This may be the same value that is used in authorisation requests sent on behalf of the 3DS Requestor and is represented in ISO 8583 formatting requirements
acquirerBIN Type: String	Max Length = 11	Acquiring institution identification code as assigned by the DS receiving the AReq message
merchantName Type: String	Max Length = 40	Merchant name assigned by the Acquirer or Payment System
merchantCategoryCode Type: String	Length = 4	Describes the merchant's type of business, product or service (mcc)

Name	Constraints	Description
merchantCountryCode Type: String	ISO 3166-1alpha-2 country code	Country code of the merchant

B.2 3DS Output Data

The `threeDsOutputData` object of the `Payload` object is defined as `JSONObject` type and is populated with data elements as defined in the 3DS Specification. This includes, but is not necessarily limited to, the data elements shown in Table B.2.

Table B.2: 3DS Output Data

Name	Constraints	Description
authenticationValue Type: String	Max Length = 28 A 20-byte value that has been BASE64 encoded	Payment System-specific value provided by the ACS or the DS using an algorithm defined by the Payment System. Authentication Value may be used to provide proof of authentication
eci Type: String	Max Length = 2	Payment System-specific value provided by the ACS or the DS to indicate the results of the attempt to authenticate the Cardholder
transStatus Type: String	Max Length = 1 See 3DS Specification for more details	Indicates whether a transaction qualifies as an authenticated transaction or account verification
transStatusReason Type: String	Max Length = 2 See 3DS Specification for more details	Provides information on why the Transaction Status field has the specified value

Name	Constraints	Description
dsTransId Type: String	Max Length = 36	Universally unique transaction identifier assigned by the DS to identify a single transaction
acsTransId Type: String	Max Length = 36	Universally unique transaction identifier assigned by the ACS to identify a single transaction

***** END OF DOCUMENT *****