

EMV – TEST PCD V3.0

This Specification Bulletin describes the specification changes related to the introduction of EMV – TEST PCD V3.0.

Applicability

This Specification Bulletin applies to:

- *EMV Level 1 Specifications for Payment Systems, EMV Contactless Interface Specification, Version 3.1 – December 2020.*

Related Documents

- *None*
-

Description

This Specification Bulletin describes the updates related to the introduction of the new EMV – TEST PCD V3.0.

EMV – TEST PCD V3.0 replaces EMV – TEST PCD V2.1 and is introduced to improve the test conditions for PICCs. Set-up values and limits are adjusted to align to the new PCD antenna characteristics.

Specification Changes

Change [PCD MANUAL] reference in section 1.2:

[PCD MANUAL] EMV ~~Contactless Level 1~~ Specifications for Payment Systems ~~Level 1~~
Contactless Test Equipment Specifications – PCD Manual

Update Figure 2.2 as follows:

Figure 2.2: EMV – TEST PCD



A new set-up $V_{S,OV,INFL}$ value has been introduced to measure influence of the PICC on the Operating Field in section 3.2.3. Change Step 2 in Table 3.5 as follows:

Table 3.5: Measurement of the Influence of the PICC on the Operating Field

Step #	Action
...	
Step 2	Connect input J1 of the EMV – TEST PCD with a signal generator V generating a carrier signal with frequency $f_{s,c}$ within the range specified in Annex A.3. Regulate the signal generator V in such a way that it generates a mean voltage defined by the minimum -value of $V_{S,OV}$ $V_{S,OV,INFL}$ specified in Annex A.3 at J1 of the EMV – TEST PICC 1.
...	

Update maximum V_{PP} value in Table A.2 as follows:

Table A.2: RF Power and Signal Interface

Topic	Parameter	EMV – TEST PICC	Value Min	Max	Units
....					
Load Modulation	V_{pp}		See Table A.3	8092	mV

Update V_{pp} values in Table A.3 as follows:

Table A.3: Minimum Value of V_{pp}

$r \backslash z$		0	1.5	2.5
0		8.8 <u>10.3</u>	4.9 <u>5.7</u>	–
1		7.2 <u>8.4</u>	4.1 <u>4.8</u>	2.5 <u>2.9</u>
2		5.6 <u>6.5</u>	3.3 <u>3.9</u>	2.1 <u>2.5</u>
3		4.0 <u>4.7</u>	2.5 <u>2.9</u>	1.7 <u>2.0</u>
4		2.4 <u>2.7</u>	1.7 <u>1.9</u>	–

Update the linear interpolation example following Table A.3 as follows:

Minimum values of V_{pp} for (z,r) not included in the table are derived through linear interpolation. For example:

V_{pp} (z=2.5, r=1):

$$V_{pp} (z=2.5, r=0) = \underline{5.66.5} - (\underline{5.66.5} - \underline{4.04.7}) \times 0.5 = \underline{4.85.6} \text{ mV}$$

$$V_{pp} (z=2.5, r=1.5) = \underline{3.33.9} - (\underline{3.33.9} - \underline{2.52.9}) \times 0.5 = \underline{2.93.4} \text{ mV}$$

$$V_{pp} (z=2.5, r=1) = \underline{4.85.6} - (\underline{4.85.6} - \underline{2.93.4}) / 1.5 = \underline{3.54.1} \text{ mV}$$

Update set-up values in Table A.4 as follows:

Table A.4: Set-up Values for EMV Contactless Level 1 Test Equipment

Topic	Parameter	EMV – TEST PICC	Min	Max	Unit
PCD Power	V _{S,OV}	1	<u>5.115.22</u>	<u>5.955.57</u>	V
	V _{S,OV,RESET}		0	5.3	mV
	V _{S,OV,LM}	1	<u>5.745.40</u>		V
	<u>V_{S,OV,INFL}</u>		<u>4.57</u>		<u>V</u>
....					
Load Modulation	V _{S1,pp}	1	<u>5.56.5</u>	<u>85.096.0</u>	mV
		2	<u>5.56.5</u>	<u>85.096.0</u>	mV
		3	<u>6.07.0</u>	<u>85.096.0</u>	mV
	V _{S2,pp}	1	<u>3.54.2</u>	<u>40.048.0</u>	mV
		2	<u>3.54.2</u>	<u>40.048.0</u>	mV
		3	<u>4.55.3</u>	<u>33.039.0</u>	mV
	V _{S2,pp,IQ}	IQ	<u>4.04.8</u>		mV

Legal Notice

The EMV® Specifications are provided “AS IS” without warranties of any kind, and EMVCo neither assumes nor accepts any liability for any errors or omissions contained in these Specifications. EMVCO DISCLAIMS ALL REPRESENTATIONS AND WARRANTIES, EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, TITLE AND NON-INFRINGEMENT, AS TO THESE SPECIFICATIONS.

EMVCo makes no representations or warranties with respect to intellectual property rights of any third parties in or in relation to the Specifications. EMVCo undertakes no responsibility to determine whether any implementation of the EMV® Specifications may violate, infringe, or otherwise exercise the patent, copyright, trademark, trade secret, know-how, or other intellectual property rights of third parties, and thus any person who implements any part of the EMV® Specifications should consult an intellectual property attorney before any such implementation.

Without limiting the foregoing, the Specifications may provide for the use of public key encryption and other technology, which may be the subject matter of patents in several countries. Any party seeking to implement these Specifications is solely responsible for determining whether its activities require a license to any such technology, including for patents on public key encryption technology. EMVCo shall not be liable under any theory for any party’s infringement of any intellectual property rights in connection with the EMV® Specifications