


# Racerback Sports Bra

*A sports bra with a one-piece front, in stretch fabric.*

TECHNICAL DRAWING (from the same draft)



## BODY MEASUREMENTS FOR THIS PATTERN

|                                |                          |
|--------------------------------|--------------------------|
| Bust (body)                    | <b>92 cm (36.2 in)</b>   |
| Underbust (body)               | <b>78 cm (30.7 in)</b>   |
| Bust – underbust difference    | <b>14 cm (5.5 in)</b>    |
| Finished underbust band length | <b>68.6 cm (27.0 in)</b> |

## PATTERN PIECES

Front — 1 fabric + 1 lining  
 Back — 1 fabric + 1 lining  
 Underbust band — 1 fabric (folded in half)

## MATERIALS

Fabric: lycra, microfiber, cotton with elastane or lace; lining in tulle or light microfiber.  
 Underbust elastic, 1.2 cm / ½ in (if the band is elastic) and 8 mm (⅜ in) picot elastic for the edges.  
 Sports fabric with elastane (supplex or lycra): 0.6 m (0.7 yd). 3 cm (1¼ in) elastic for the band: 70 cm (27.6 in).

## HOW TO PRINT

A4: print at 100 % (“Actual size”) with “Fit to page” turned off. Follow the assembly map.


Plotter: send the sheet at actual size as it is (the file is already at 1:1 scale).

Before cutting, measure the test square: 10 × 10 cm (3.94 × 3.94 in).


## ORDER OF CONSTRUCTION

1. Cut the pieces with the greatest stretch running across (horizontal on the pattern).
2. If the cup has a dart or seams, close them first in the fabric and in the lining separately; join them right sides together along the top edge.
3. Join the cups to the band (or to the center gore and the wings), matching the notches.
4. Apply the elastic to the edges, 10 % shorter, and attach the closure or the ties.
5. Try it on before finishing: strap length is adjusted while worn.


Pattern drafted with classic pattern-making formulas from the measurements above (one size, wire-free). A 0.6 cm (¼ in) allowance is included. Make a first sample in scrap fabric: on cups, the fine fit is done at the fitting.



Front  
Cut 1 in fabric + 1 in lining  
Seam allowance included: 0.6 cm (0.2 in)  
BRA 019  
Center front



Back  
Cut 1 in fabric + 1 in lining  
Seam allowance included: 0.6 cm (0.2 in)  
BRA 019  
Center back



Underbust band  
Cut 1 in fabric (folded in half)  
Seam allowance included: 0.6 cm (0.2 in)  
BRA 019  
With 3 cm (1 1/4 in) elastic inside

TEST SQUARE  
It must measure 10 x 10 cm  
(3.94 x 3.94 in). If it does not,  
check you printed at 100 %  
("Actual size", no scaling).

BRA 019