

SQL Queries and Relational Algebra answering physical model

1. What user posted this tweet?

Query1:

Select tweets.twitter_handle, user.user_name, tweets.tweet_description
from tweets inner join user on tweets.twitter_handle=user.twitter_handle
where tweet_id = 1596997211048808448;

Relational Notation: $\Pi_{\text{twitter_handle, tweet_text}}(\sigma_{\text{tweet_id} = '1596997211048808448'}(\text{tweets}))$

2. When did the user post this tweet?

Query2:

Select tweets.twitter_handle, user.user_name, tweets.tweet_description,
tweets.created_at from tweets inner join user on
tweets.twitter_handle = user.twitter_handle
where tweet_id = 1596997211048808448;

Relational Notation: $\Pi_{\text{twitter_handle, tweet_text, created_at}}(\sigma_{\text{tweet_id} = '1596997211048808448'}(\text{tweets}))$

3. What tweets have this user posted in the past 24 hours?

Query3:

Select tweets.twitter_handle, tweets.tweet_id, tweets.created_at,
tweets.tweet_description from tweets

where tweets.twitter_handle='Patricia' and created_at between '2022-11-11' and '2022-11-12';

Relational Notation: $\Pi_{\text{tweet_id, tweet_text}}(\sigma_{\text{twitter_handle} = '@smith' \cap \text{created_at between ('2022-11-11) and ('2022-11-12))}$ (Tweets)

4. How many tweets have this user posted in the past 24 hours?

Query4:

Select count(tweet_id) as NoOfTweets from tweets where
twitter_handle= 'Patricia' and created_at between '2022-11-11'
and '2022-11-12';

Relational Notation: $\rho \text{ NoOfTweets } (\Pi \text{ count(tweet_id)} (\sigma_{\text{twitter_handle} = 'Patricia' \cap \text{created_at between (SYSDATE-1) and SYSDATE ()}$ (Tweets))

5. When did this user join twitter?

Query5:

Select u.twitter_handle, u.user_name, u.join_date from tweets t, user u
where u.twitter_handle=t.twitter_handle and u.twitter_handle= 'Patricia';

Relational Notation: $\Pi (u.\text{twitter_handle}, u.\text{join_date}) \sigma (u.\text{twitter_handle} = '@smith')(User \bowtie_{u.\text{twitter_handle} = t.\text{twitter_handle}} \text{Tweets})$

6. What keywords/hashtags are popular?

Query6:

Select hashtags from tweets group by hashtags having count(tweet_id)>2;

Relational Notation: Not possible as Group By function does not exist in relational algebra.

7. What tweets are popular?

Query7:

Select tweet_id from tweets where retweet_count>1;

Relational Notation: Π (tweet_id)(σ retweet > 60) (tweets)

8. What is the followers and following count for this user?

Query8:

Select follower_count, following_count from user where user_name='Patricia';

Relational Notation: Π (tweet_id)(σ retweet > 60) (tweets)

9. Who are the influential users and what are the tweets posted by them?

Query9:

Select distinct t.twitter_handle, t.tweet_description from user u, tweets t where user_type = 'True';

10. List the top 5 locations based on the tweets posted ?

Query10:

Select count(t.tweet_id) as total_tweets , u.location from user u, tweets t
where u.twitter_handle=t.twitter_handle and u.location != "
group by location
order by count(t.tweet_id) desc
limit 5;

Relational Notation: Not possible as Group By function does not exist in relational algebra.

11.List the locations with number of crime incidents reported?

Query11:

Select count(u.location) as total_crime, u.location from user u, tweets t
where u.twitter_handle=t.twitter_handle and t.tweet_description like
'%crime%' and u.location != "
group by location
order by count(u.location) desc;

Relational Notation: Not possible as Group By function does not exist in relational algebra.