

Duke®

DY 3020M



DIRECT DRIVE PROCEDURAL FLORIATION MACHINE

- Use of sewing machine: Flat-seam floriation sewing machine (2-times hook)
- Line: Single-needle flat seam
- Highest sewing speed: 2,700 rpm
- Sewing area (XxY): (Maximum) 300X200 mm
- Cloth feeding device: Intermittent feeding (driven by pulse motor)
- Needle pitch: 0.05-12.7mm
- Maximum needle number: (20,000 needles/1 pattern)
- Presser foot drive: Pneumatic
- Work Clamp Height: (Maximum) 30 mm
- 2-step presser foot: All-in-one presser foot
- Raising amount by intermittent presser foot: 22 mm
- Stroke by intermittent presser foot: 0 or 2 4.5 mm or 4.5-10 mm (Factory defaults 3mm)
- Hook: Two times of shuttle hooks (Standard shuttle hooks are optional components)
- Scavenging device: Standard facility
- Tangent device: Standard facility
- Data storage way: Flash memory (You can sew pattern with CF card) 3.5inch disk 2HD/1.44MB, 2DD (options)
- Motor: AC servomotor 550W
- Weight: Head about 160 kg, Operating panel: about 0.6 kg, control box: 14.2-16.2 kg (according to different export countries)
- Power: Single phase 220V, 3-phase 380V
- Air pressure: 0.5 Mpa 18 l/min

Adopting servo control and textile feed device with enhanced rigidity, thus, high exquisite patterns can be sewed, even while sewing with high speed or sewing thick textiles, bad stitches and deviation problems which often occur to computer floriation machines would not exist.

Function:

- Exquisite Stitches, reliable floriation sewing.
- Highest sewing speed 2,700rpm (Using the stitch length of 3.5mm).
- Strong frame needle Penetrating Power.
- Low power consumption, Economical & Practical.
- Using big presser foot of two steps descending to Easily Position the textiles.

Duke®

DY-9503-D4



Special Features



Stepper Motor



Sealed Oil Tank



Smart Auto Oil Drain



Hand Key for Reverse
Stitch

**Advanced, intelligent direct-drive
single-needle lockstitch sewing machine**

Features :

Innovation with World's leading technology perfect combination of auto-needle positioner mechanical & electrical integrated, beautiful appearance.

Efficient: Servo motor inbuilt direct drive, responsive rapidly, stop needle exactly, without control box and install.

Save energy: 70% energy saving than ordinary clutch Motor.

Convenient: With LED adjustable light suitable for environment, and variable speed.

Low noise: Many spare parts with ergonomic design, low noise, low vibration, easy operation.

Specification :

Needle 11# - 18#
Number of Needle 4
Presser Foot Lift 5 - 13 mm
Speed 5000 spm
Weight 25.5 - 35.5 Kg



HARI CHAND ANAND & CO.

Corporate Head Office:

A-94/1, Okhla Industrial Area Phase II, New Delhi - 110020

+91-8584068564

enquiry@grouphca.com