

KP-ES Auto Cutter




Duke®

Technical Parameters >>>>>>>>

Model.NO	KP-ES1725	KP-ES2025	KP-ES2325	KP-ES1733	KP-ES2033	KP-ES2333
Cutting Area(w*I)	1650*2300mm	1950*2300mm	2230*2300mm	1650*3100mm	1950*3100mm	2250*3100mm
Machine Dimensions	5900*2950*2150mm	5900*3250*2150mm	5900*3550*2150mm	7500*2950*2150mm	7500*3250*2150mm	7500*3550*2150mm
Weight	4.2T	4.5T	4.8T	4.8T	5T	5T
Max Positioning Speed	100m/min			Cooling System	Optional Super Cooling System	
Cutting Thickness	9cm			Sharpen Way	Belts Sharpening System	
Cutting Accuracy	±1mm			Max Speed	6000rpm/min	
Power	16-25kw			Motor & Driver	Yaskawa Servo Motor	
Cutting Style	Straight Knife Cutting			Driving mode	Bilateral Drive	
Software	Cutting Program			Machine Power	AC380V/50Hz	
Control System	CUT V5.0			Air Pressure Supply	0.5MPa 160L/min	

1 Control System



- Cutting control system CutV5.0 by Yinengtech
- Super cooling controller for easy melting materials to reduce the viscous of chemical fiber materials.
- Double-gear sharpening controller increase autocompensation for sharpening loss.
- Arbitrary segmented cutting for multiple sharp graph ensure the cutting accuracy.
- Make Batch Identification to the set segmented process template graphics.

2 Body and Electrical



- One-piece machine body structure milled by 5-axis milling machine.
- Annealing & stress-relieving treatment.
- Electrical system adopts automatic control system.
- Large number of imported components protects the stable operation of the electrical control system.
- Japanese Yaskawa full digital AC servo driver system ensure the high precision cutting.

3 Sharpening System



- Adopt belt sharpening method, high speed sharpening speed.
- Sharper blade, more uniform, ensuring high speed cutting accuracy.

4 Cutting head



- Cutter head adopts the principle of European and American systems.
- Cutter head more stronger strength.
- Greater bearing capacity, less vibration.
- High wear resistance of core components ensuring stable cutting at high speed.

5 Bilateral Drive System



- Dual-motor synchronous drive, stronger stability during high speed operation.
- Faster response speed, smooth running.
- Stronger acceleration and deceleration ability of the whole machine.



Application Industries: clothing, home textiles, medical, inflatables, sofas, shoes and hats, luggage, plush toys, car interiors and other applications.