

Duke®

KP-L

Auto Spreading Machine



Technical Parameters>>>>>>>>

Model.NO	KP-L160S	KP-L190S	KP-L210S
Max Fabric Width	1600mm/63"	1900mm/75"	2100mm/83"
Table Size	1830mm/72"	2130mm/84"	2330mm/92"
Voltage	220V/1P	220V/1P	220V/1P
Motor Power	3KW	3KW	3KW
Working Speed	96m/min	96m/min	96m/min
One Way Spreading(Face Up)	20cm	20cm	20cm
Zigzag Spreading(Face to Face)	18cm	18cm	18cm
Fabric Weight	80KG	80KG	80KG
Diameter of Fabric Roller	55cm	55cm	55cm
Machine Dimensions	2370*1850*950mm	2670*1850*950mm	2870*1850*950mm
Package Size	2516*2000*1250mm	2800*2000*1250mm	2950*2000*1250mm
N.W/G.W	370kg/430kg	420kg/470kg	440kg/490kg



Feeding



Rolled cloth/bolt cloth spreading

Equipped with power bucket

Applicable to all kinds of knitted/woven fabrics, both rolled cloth and bolt cloth



Bolt cloth spreading

Equipped with power bucket

Applicable to bolt clothes of all kinds of knitted/woven fabrics




Rolled cloth spreading

Bucket with support rod

Applicable to woven/composite/non-elastic rolled fabrics



Pulling



- Ordinary one way spreading(face up)
- Configure regular cutter
- Suitable for one way spreading of common knitted fabrics



- One way spreading with front catcher
- Equipped with front pressure cutter
- Suitable for one way spreading of common knitted and woven fabrics

The cutter set is universal with or without pressure, and the inclination angle of the bottom plate of the cutter is the largest inclination angle on the market at present, which can be used for a variety of fabrics.