

KP-LS

Auto Spreading Machine



Technical Parameters>>>>>>>

Model.NO	KP-LS160	KP-LS190	KP-LS210	KP-LS230
Max Fabric Width	1600mm/63"	1900mm/75"	2100mm/83"	2300mm/90"
Table Size	1830mm/72"	2130mm/84"	2330mm/92"	2530mm/100"
Voltage	220V/1P	220V/1P	220V/1P	220V/1P
Motor Power	4KW	4KW	4KW	4KW
Working Speed	120m/min	120m/min	120m/min	120m/min
One Way Spreading(Face Up)	25cm	25cm	25cm	25cm
Zigzag Spreading(Face to Face)	23cm	23cm	23cm	23cm
Fabric Weight	200KG	200KG	200KG	200KG
Diameter of Fabric Roller	70cm	70cm	70cm	70cm
Machine Dimensions	2370*1850*950mm	2670*1850*950mm	2870*1850*950mm	3070*1850*950mm
Package Size	2516*2000*1250mm	2800*2000*1250mm	2950*2000*1250mm	3170*2000*1250mm
N.W/G.W	400kg/460kg	450kg/510kg	500kg/560kg	550kg/610kg

1- Initiate Dual Drive System



- Initiate dual-drive servo travel motor with no error on the left and right.
- With stronger power and highest running speed can reach 120m/min.




2- The big six wheels run independently



- Dual-drive four-wheel walking, stable operation, more precise braking, and the error can be controlled within 1mm.



3- Multi-rod cloth releasing device



- Making the cloth no tension, and truly realizes the replacement of knitted and woven fabrics at any time.
- Solving the problem of frequent adjustment of parameters due to slippage of the fabrics.




4- Autonomous control system



- Independently developed control system.
- Large expansible space.
- Real-time connection to the data on IOT.



5- Intelligent identification system



- Intelligent cutter rise up & down.
- Automatic place down fabric.
- Automatic cloth collection.
- Automatic joint fabric.



This machine is suitable for woven fabrics, milk silk, swimming trunks, underwear, polar fleece, fibers and other fabrics; suitable for sticky fabrics such as bags, down jacket coated fabrics, etc.