

# Duke®

## DY-JZQ-630



## Automatic Conveyor Needle Detector

### Features :

When sensor detects a broken needle pin or over 1.0mm needle chip, buzzer will sound and conveyor belt will stop. After that, detected products will be returned at hand.

This new type needle detector is equipped with select switch for Production mode and Test Card mode.

Monitor of detecting sensitivity helps to adjust sensitivity.

10 pieces of indicator lamp identifies exact location of foreign object so that you can find it easily.

Detecting sensitivity can be adjustable with step less.

Protection cover for control panel can avoid changing sensitivity level and selecting switch for Production and Test Card unconsciously.

### Specification :

**Detection Method:** Magnet Induction

**Detection Ability:**  $\geq 1.0\text{mm}$  steel to small scissors  
(2\$ 1.0mm H125mm, \$ 1.2mm H150mm, \$ 1.5mm H200mm)

**Detection Adjustment:** Adjust with stepless.

**Detection Width:** 600mm, 610mm

**Detection Height:** 100mm, 125mm, 150mm, 200mm

**Alarm Method:** Automatic buzzer and alarm lamp, the conveyor will stop and return.

**Power Supply:** AC200V 50Hz

**Pated Output:** Around 100W

**Dimension:** 1050(w) x 1650(L) x 900(H)

**Weight:** 180 Kg.



## HARI CHAND ANAND & CO.

**Corporate Head Office:**

A-94/1, Okhla Industrial Area Phase II, New Delhi - 110020

+91-8860086712 , 8584068564

enquiry@grouphca.com