

NG-003

Automatic Sponge Gluing Integrated Assembly Line



ADVANTAGES

- 1 The gluing production line consists of an automatic gluing machine, an automatic lifting conveyor, an automatic cotton press, an automatic centering machine, an automatic edge trimming machine, an automatic rotating machine, and an automatic stacking machine.
- 2 The PLC, touch screen, frequency converter, remote module, etc. used in the machinery are all German Siemens brands.
- 3 The Siemens remote control system facilitates the factory's ability to save production capacity and can be accessed through mobile apps at any time. It facilitates the storage of after-sales data and allows for direct remote control and timely handling of accumulated problems and mechanical problems.
- 4 High degree of mechanical automation, capable of automatically detecting product height, automatically trimming according to input data, and automatically stacking multiple products.
- 5 This production line makes the production process more intuitive and can be monitored, greatly improving production efficiency. The training cycle is short, the operation is simple, and it is easy for production personnel to shift.

TECHNICAL PARAMETER

Adhesive width	≤2100mm	Trimming width	<2200mm
Glue height	≤ 400mm	Minimum height of stacker	525mm
Glue passing speed	0-20m/min	Maximum stroke of stacker	1550mm
Cotton pressing plate sizes	2280x2200mm	Voltage	380V/50HZ
Applicable products	Production of sponge	Total power	36.8KW