

Name: Neha Guglot

PRN: 202501050032

1.1 Calculate Momentum

Write a program that accepts the mass of an object (in kilograms) and its velocity (in meters per second), then calculates and displays the momentum of the object. The momentum is calculated using the formula: where: is the mass of the object (in kilograms). is the velocity of the object (in meters per second).

Input Format:

- A single floating-point number representing the mass of the object in kilograms.
- A single floating-point number representing the velocity of the object in meters per second.


Output Format:

- The output will display calculated momentum with appropriate units (kgm/s) (rounded up to 2 decimal places).

Code:

```
mass = float(input()) velocity = float(input())
```

```
momentum = mass*velocity print(f"{momentum:.2f}kgm/s")
```



1.1.2. Conditional Calculation Based on the Number of Digits

Write a Python program that accepts an integer as input. Depending on the number of digits in .

Constraints:

$1 \leq \leq 999$

Input Format:

- The input consists of a single integer .

Output Format:

- If n is a single-digit number, print its square.
- If n is a two-digit number, print its square root (rounded to two decimal places).
- If n is a three-digit number, print its cube root (rounded to two decimal places).
- Else print "Invalid".

Code:

`n=int(input()) if 0<=n and n<=9:`

`print(n*n) elif 10<=n and n<=99:`

`print(f"{n**(1/2):.2f}") elif 100<=n and n<=999:`

`print(f"{n**(1/3):.2f}") else:`

`print("Invalid")`

The screenshot shows the CDE TANTRA IDE interface. At the top, there's a navigation bar with 'Home', 'Learn Anywhere', and a user profile '202501050032@mitaoe.ac.in'. Below this, a summary bar indicates '4 out of 4 shown test case(s) passed' and '3 out of 3 hidden test case(s) passed'. The main area displays four test cases, each with 'Expected output' and 'Actual output' columns. Test case 1: Input 81, Expected 81, Actual 81. Test case 2: Input 100, Expected 10.00, Actual 10.00. Test case 3: Input 24, Expected 2.90, Actual 2.90. Test case 4: Input 3456, Expected Invalid, Actual Invalid.

1.1.3. Days between Two Dates

Write a Python program to calculate number of days between two dates.


Input Format:

- The first line contains the first date in the format YYYY-MM-DD
- The second line contains the second date in the format YYYY-MM-DD

Output Format:

- An integer representing the number of days between the given dates.

Code: from datetime import datetime date1=input().strip() date2=input().strip()
d1=datetime.strptime(date1,"%Y-%m-%d") d2=datetime.strptime(date2,"%Y-%m-%d")
difference = d2-d1 print(difference.days)



1.1.4. Reverse a Number

Write a Python program to reverse the digits of the number and print the reversed number.

Input Format:


- The input is a single integer.

Output Format:

- The output prints a single integer, which is the reversed number.

Code:

```
num = int(input()) reversed_num= int(str(num)[::-1]) print(reversed_num)
```



1.1.5. Multiplication Table

Write a Python program that takes an integer as input and prints the multiplication table for that integer from 1 to 10.

Input Format:


- The first line of input contains an integer that represents the number for which the multiplication table is to be printed.

Output Format:

- Print the multiplication table for the given number in the format: **<number> x <multiplier> = <result>** **Code:**

```
num = int(input()) for i in range(1,11):
```

```
    print(f"{num} x {i} = {num * i}")
```



1.2.1. Pass or Fail

Write a Python program that accepts the number of courses and the marks of a student in those courses.

The grade is determined based on the aggregate percentage:

- If the aggregate percentage is greater than 75, the grade is Distinction.
- If the aggregate percentage is greater than or equal to 60 but less than 75, the grade is First Division.
- If the aggregate percentage is greater than or equal to 50 but less than 60, the grade is Second Division.
- If the aggregate percentage is greater than or equal to 40 but less than 50, the grade is Third Division.

Input Format:

- The first input will be an integer , the number of courses.
- The second input will be integers representing the marks of the student in each of the courses, separated by a space.

Output Format:

If the student passes all courses:

- Print the aggregate percentage (formatted to two decimal places).
- Print the grade based on the aggregate percentage.

If the student fails any course (marks < 40 in any course), print:

- "Fail".

Code:

```
def cal(marks, total_courses):
```

```
    if any(mark < 40 for mark in marks):
```

```
        return "Fail"
```

```
    total_marks = sum(marks)  aggregate_percentage=(total_marks/(total_courses  
*100))*100  if aggregate_percentage >75:        grade="Distinction"  elif
```

```
aggregate_percentage >=60:        grade= "First Division"        elif
```

```
aggregate_percentage >=50:        grade= "Second Division"  elif
```


```
aggregate_percentage >=40:        grade= "Third Division"
```

```
    return (aggregate_percentage,grade) num_courses= int(input()) marks=  
list(map(int,input().split())) result= cal(marks,num_courses) if result == "Fail":
```

```
    print("Fail") else:
```

```
        aggregate_percentage,grade=result        print(f"Aggregate Percentage:  
{aggregate_percentage:.2f}")        print(f"Grade: {grade}")
```

The screenshot shows the CodeTANTRA IDE interface. At the top, there's a navigation bar with 'Home' and 'Learn Anywhere' links, a user profile '202501050032@mitaoe.ac.in', and a 'Logout' button. The main area displays test results for four test cases. Test case 1 (45 ms) passed with expected output '4' and actual output '4'. Test case 2 (32 ms) passed with expected output '5' and actual output '5'. Test case 3 (12 ms) passed with expected output '5' and actual output '5'. Test case 4 (11 ms) passed with expected output 'Fail' and actual output 'Fail'. The bottom bar contains 'Prev', 'Reset', 'Submit', and 'Next' buttons.



1.2.2. Fibonacci Series

Write a Python program that uses recursion to print the first terms of the Fibonacci series.

Input Format:

- A single integer representing the number of terms to generate.

Output Format:

- A single line containing the first terms of the Fibonacci sequence, separated by spaces.

Code:

```
def fibonacci(n):
    if n == 1:
        return 0
    elif n == 2:
        return 1
    else:
        return fibonacci(n - 1) + fibonacci(n - 2)
n = int(input())
for i in range(1, n + 1):
    print(fibonacci(i), end=" ")
```



1.2.3. Pattern -1

Write a Python program to print a pattern of asterisks in the form of a right-angled triangle.

Input Format:


- The input is an integer, representing the number of rows in the pattern. **Output**

Format

- The output should display the pattern of asterisks (*), with each row containing an increasing number of asterisks.

Code:

```
n = int(input())
for i in range(1, n+1):
    print('* ' * i)
```



1.2.4. Pattern -2

Write a Python program to print a right-angled triangle pattern of numbers.

Input Format:

- The input is an integer, representing the number of rows in the pattern.

Output Format:

- The output should display the pattern of numbers separated by space, with each row containing increasing numbers starting from 1 up to the row number.

Code:

```
n = int(input())
for i in range(1, n+1):
    for j in range(1, i+1):
        print(j,end=" ")
    print()
```

The screenshot shows the CODETANTRA online judge interface. At the top, there's a navigation bar with 'Home' and 'Learn Anywhere' links. The user's email '202501050032@mitaoe.ac.in' and a 'Logout' button are visible. The main area displays the results for a problem named 'numberP...'. It shows '2 out of 2 shown test case(s) passed' and '2 out of 2 hidden test case(s) passed'. Below this, two test cases are detailed:

Test Case	Expected output	Actual output
Test case 1 (42 ms)	5 1 1 2 1 2 3 1 2 3 4 1 2 3 4 5	5 1 1 2 1 2 3 1 2 3 4 1 2 3 4 5
Test case 2 (15 ms)	8 1 1 2 1 2 3 1 2 3 4 1 2 3 4 5 1 2 3 4 5 6 1 2 3 4 5 6 7 1 2 3 4 5 6 7 8	8 1 1 2 1 2 3 1 2 3 4 1 2 3 4 5 1 2 3 4 5 6 1 2 3 4 5 6 7 1 2 3 4 5 6 7 8