

❖ MySQL Commands-

1) User Create:

```
create user 'nehal'@'localhost' identified by '12345';
```

```
show databases;
```

```
create database employee;
```

```
GRANT ALL PRIVILEGES ON employee.* TO  
'nehal'@'localhost';
```

```
FLUSH PRIVILEGES;
```

```
Exit;
```

2) Create Table:

```
Use employee;
```

```
create table SALESPeOPLE ( Snum INT(4),Sname  
varchar(10),City varchar(10),Comm float(3,2));
```

3) Insert Data into table:

```
INSERT INTO
```

```
SALESPeOPLE(Snum,Sname,City,Comm) VALUES  
(1001,'Peel','London',.12),(1002,'Serres','San Jose',.13),(1  
004,'Motika','Londan',.11),(1007,'Rifkin','Barcelona',.15),  
(1003,'Axelord','New York',.10);
```

```
INSERT INTO
```

```
ORDERS(Onum,Amt,Odate,Cnum,Snum) VALUES  
(3001,18.96,STR_TO_DATE('03-OCT-1990','%d-%b-  
%Y'),2008,1007),(3003,767.19,STR_TO_DATE('03-  
OCT-1990','%d-%b-  
%Y'),2001,1001),(3002,1900.10,STR_TO_DATE('03-  
OCT-1990','%d-%b-  
%Y'),2007,1004),(3005,5160.45,STR_TO_DATE('03-  
OCT-1990','%d-%b-
```

```
% Y'),2003,1002),(3006,1098.16,STR_TO_DATE('03-  
OCT-1990','%d-%b-% Y'),  
2008,1007),(3009,1713.23,STR_TO_DATE('04-OCT-  
1990','%d-%b-  
% Y'),2002,1003),(3007,75.75,STR_TO_DATE('04-  
OCT-1990','%d-%b-%  
Y'),2004,1002),(3008,4723.00,STR_TO_DATE('05-  
OCT-1990','%d-%b-  
% Y'),2006,1001),(3010,1309.95,STR_TO_DATE('06-  
OCT-1990','%  
d-%b-  
% Y'),2004,1002),(3011,9891.88,STR_TO_DATE('06-  
OCT-1990','%d-%b-% Y'),2006,1001);
```

4) show tables;

5) desc customers;

6) SELECT * FROM customers;