



Incident report analysis

Summary	It was reported that the organization's network services suddenly stopped responding due to a flood of incoming ICMP packets. Normal internal network traffic was unable to access any network resources. The incident response team addressed the situation by blocking incoming ICMP packets, taking all non-critical network services offline, and restoring critical network services. It was discovered that a malicious actor had sent a flood of ICMP pings to the company's network through an improperly configured firewall. This vulnerability allowed the attacker to saturate the company's network via a denial-of-service (DoS) attack.
Identify	The incident response team reacted by blocking incoming ICMP packets, taking all non-critical network services offline, and restoring critical network services. This caused some basic operations to slow down, but resulted in no serious damage.
Protect	A malicious actor or actors targeted the company with an ICMP flood attack. The entire internal network was affected. All critical network resources needed to be secured and restored to a functioning state.
Detect	The cybersecurity team configured source IP address verification on the firewall to check for spoofed IP addresses on incoming ICMP packets and implemented network monitoring software to detect abnormal traffic patterns.
Respond	For future security events, the cybersecurity team will isolate affected systems to prevent further disruption to the network. They will attempt to restore any critical systems and services that were disrupted by the event. Then, the team

	will analyze network logs to check for suspicious and abnormal activity. The team will also report all incidents to upper management and appropriate legal authorities, if applicable.
Recover	To recover from a DDoS attack by ICMP flooding, access to network services need to be restored to a normal functioning state. In the future, external ICMP flood attacks can be blocked at the firewall. Then, all non-critical network services should be stopped to reduce internal network traffic. Next, critical network services should be restored first. Finally, once the flood of ICMP packets have timed out, all non-critical network systems and services can be brought back online.

Reflections/Notes: