J-CAP™ Series

Highest Joules/cc Conductive Polymer Solid Electrolytic Chip Capacitors



FEATURES

- Highest Energy per volume
- Fast DCL drop with Voltage applied after reflow
- Benign failure mode under recommended use conditions
- Low ESR
- Undertab terminations layout:
  - High Volumetric Efficiency
  - Low profile case sizes
  - High capacitance in smaller dimensions
  - Close positioning of several parts for efficient high density PCB layout
- 3x reflow 260°C compatible

LEAD-FREE
LEAD-FREE COMPATIBLE COMPONENT

RoHS COMPLIANT

APPLICATIONS

- Power backup for SSDs (MLC, SLC, EFD, PCIe), battery-powered portable equipment, industrial alarms, smart power meters, and mobile devices.

J-LEAD



UNDERTAB



CASE DIMENSIONS UNDERTAB: millimeters (inches)

Code	EIA Code	EIA Metric	L±0.20 (0.008)	W+0.20 (0.008) -0.10 (0.004)	H max.	W_P±0.10 (0.004)	W_N±0.10 (0.004)	A_P±0.10 (0.004)	A_N±0.10 (0.004)	S Min.
L	1210	3528-10	3.50 (0.138)	2.80 (0.110)	1.00 (0.039)	2.50 (0.098)	2.10 (0.083)	1.15 (0.045)	1.35 (0.053)	1.00 (0.039)
T	1210	3528-12	3.50 (0.138)	2.80 (0.110)	1.20 (0.047)	2.50 (0.098)	2.10 (0.083)	1.15 (0.045)	1.35 (0.053)	1.00 (0.039)
X	2917	7343-15	7.30 (0.287)	4.30 (0.169)	1.50 (0.059)	3.25 (0.128)	3.25 (0.128)	2.00 (0.079)	3.20 (0.126)	2.10 (0.083)
4	2924	7361-20	7.30 (0.287)	6.10 (0.240)	2.00 (0.079)	4.75 (0.187)	4.75 (0.187)	2.00 (0.079)	3.20 (0.126)	2.10 (0.083)

CASE DIMENSIONS J-LEAD: millimeters (inches)

Code	EIA Code	EIA Metric	L±0.20 (0.008)	W+0.20 (0.008) -0.10 (0.004)	H+0.20 (0.008) -0.10 (0.004)	W_1±0.20 (0.008)	A+0.30 (0.012) -0.20 (0.008)	S Min.
C	2312	6032-28	6.00 (0.236)	3.20 (0.126)	2.60 (0.102)	2.20 (0.087)	1.30 (0.051)	2.90 (0.114)
D	2917	7343-31	7.30 (0.287)	4.30 (0.169)	2.90 (0.114)	2.40 (0.094)	1.30 (0.051)	4.40 (0.173)
E	2917	7343-43	7.30 (0.287)	4.30 (0.169)	4.10 (0.162)	2.40 (0.094)	1.30 (0.051)	4.40 (0.173)
H	1210	3528-15	3.50 (0.138)	2.80 (0.110)	1.50 (0.059) max.	2.20 (0.087)	0.80 (0.031)	1.40 (0.055)
5	2917	7343-40	7.30 (0.287)	4.30 (0.169)	3.80 (0.150)	2.40 (0.094)	1.30 (0.051)	4.40 (0.173)

W_1 dimension applies to the termination width for A dimensional area only.

MAXIMUM ENERGY PER CASE SIZE

Case Size	H Max (mm)	Max Energy (mJ)
C	2.8	5.8
D	3.1	21.8
E	4.3	11.9
H	1.5	3.3
L	1.0	1.8
T	1.2	6.5
X	1.5	18.2
4	2.0	43.0
5	4.0	46.6

MARKING

C, D, E, H, L, T, X, 5 CASE



4 CASE



HOW TO ORDER

TCN	4	158	M	006	R	0055	E
Type TCJ TCN	**Case Size** See table above	**Capacitance Code** pF code: 1st two digits represent significant figures, 3rd digit represents multiplier	**Tolerance** M = ±20%	**Rated DC Voltage** 006 = 6.3Vdc 010 = 10Vdc 016 = 16Vdc 020 = 20Vdc 025 = 25Vdc 035 = 35Vdc	**Packaging** R = Pure Tin 7" Reel S = Pure Tin 13" Reel (J-Lead)	**ESR in mΩ**	**Additional Character** E = Black resin

Part Numbers already changed to an "E" suffix will continue to be supplied with only black resin.
Those Part Numbers currently produced with gold resin will eventually change to black before July, 2020.

J-CAP™ Series

Highest Joules/cc Conductive Polymer Solid Electrolytic Chip Capacitors

TECHNICAL SPECIFICATIONS

Technical Data:	All technical data relate to an ambient temperature of +25°C							
Capacitance Range:	4.7 µF to 1500 µF							
Capacitance Tolerance:	±20%							
Leakage Current DCL:	0.1CV							
Rated Voltage DC (V_R)	≤ +85°C:	6.3	10	16	20	25	35	50
Surge Voltage (V_S)	≤ +85ºC:	8	13	21	26	33	46	65
Temperature Range:	-55°C up to +125°C							
Reliability:	1% per 1000 hours at 85°C, V_R with 0.1Ω/V series impedance 60% confidence level							

NOTE: Conductive Polymer Capacitors are designed to operate within the limits of the environmental conditions specified for each series. If operated continuously at their maximum temperature and / or humidity limit, or beyond these limits, capacitors may exhibit a parametric shift in capacitance and increases in ESR. These changes may occur earlier if the specified environmental conditions are exceeded. Similarly, their normal operational time period will be significantly extended if their general duty cycle includes operation below maximum temperature within humidity controlled environments. Careful attention should be paid to maximum temperature with associated high humidity environments as well as voltage derating, ripple current and current surges. Please reference the AVX Conductive Polymer Capacitor Guidelines for more information or contact factory for application assistance.

CAPACITANCE AND RATED VOLTAGE RANGE (LETTER DENOTES CASE SIZE)

Capacitance		Rated Voltage DC to 85°C, [mJ]						
µF	Code	6.3V (J)	10V (A)	16V (C)	20V (D)	25V (E)	35V (V)	50V (T)
4.7	475						L(300E) [1.8] T(200E)	
6.8	685							C(200E) [5.4]
10	106						T(200E) [3.9]	D(120E) [8.0]
15	156						C(200E) [5.8]	E(70E) [11.9]
22	226					T(200E) [4.3]	D(100E) [8.5]	
33	336			H(150E) [3.3] T(200E)		T(250E) [6.5]	D(70E) [12.8]	
47	476		C(100E) [1.7] H(100E)	T(200) [4.7] T(150E)		X(100E) [9.2]	X(150E) [18.2]	
68	686	H(100E) [0.8]	D(45E) [2.5]	D(50E) [6.7]	D(55E) [8.4]	D(70E) [13.3]		
100	107		D(45E) [3.6]	D(50E) [9.9]	D(55E) [12.4]	D(70E) [19.6] 4(100E)	4(100E) [38.8]	
150	157	T(200E) [1.7]	D(45E) [5.4]	X(100E) [14.9]		4(70E) [29.3]		
220	227	H(170E) [2.6]	D(40E) [7.9]	D(50E) [21.8] 4(70E)	4(100E) [27.2]	4(100E) [43.0]		
330	337	D(40E) [3.8]	5(100E) [11.9]	4(70E) [32.7] 5(100E)				
470	477	X(50E) [5.4]		5(100E) [46.6]				
1000	108	4(55E) [11.6]						
1500	158	4(55E) [17.4]						

Note for designers - for the highlighted ratings, higher voltage options are now available in the same case size and are recommended for new designs.
Released ratings, (ESR ratings in mOhms in parentheses) [Energy in mJ]
Note: Voltage ratings are minimum values. AVX reserves the right to supply higher voltage ratings in the same case size, to the same reliability standards.

RATINGS & PART NUMBER REFERENCE

AVX Part No.	Case Size	Capacitance (µF)	Rated Voltage (V)	Maximum Operating Temperature (°C)	DCL Max. (µA)	DF Max. (%)	ESR Max. @ 100kHz (mΩ)	1000kHz RMS Current (mA) 45°C	Product Category	MSL	ENERGY		
											Energy (mJ)	Energy/volume (mJ/cm³)	Energy/area (mJ/cm²)
6.3 Volt @ 85°C													
TCJH686M006#0100E	H	68	6.3	105	40.8	6	100	1000	3	3	0.8	54	8.0
TCNT157M006#0200E	T	150	6.3	105	90	10	200	700	3	4	1.7	147	17.7
TCJH227M006#0170E	H	220	6.3	105	132	10	170	800	3	3	2.6	173	26
TCJD337M006#0040E	D	330	6.3	105	198	6	40	2400	2	3	3.8	42	12.2
TCNX477M006#0050E	X	470	6.3	85	282	10	50	1900	5	5	5.4	115	17.3
TCN4108M006#0055E	4	1000	6.3	85	600	20	55	1860	5	4	11.6	130	26
TCN4158M006#0055E	4	1500	6.3	85	900	20	55	1860	5	4	17.4	195	39
10 Volt @ 85°C													
TCJH476M010#0100E	H	47	10	105	47	6	100	1000	3	3	1.7	115	17.3
TCJC476M010#0100E	C	47	10	125	47	6	100	1300	1	3	1.7	34	8.8
TCJD686M010#0045E	D	68	10	105	68	6	45	2200	3	3	2.5	27	7.8
TCJD107M010#0045E	D	100	10	105	100	6	45	2200	3	3	3.6	40	11.5
TCJD157M010#0045E	D	150	10	105	150	6	45	2200	3	3	5.4	59	17.2
TCJD227M010#0040E	D	220	10	105	220	6	40	2400	3	3	7.9	87	25.2
TCJ5337M010#0100E	5	330	10	105	330	10	100	1300	2	3	11.9	100	37.8
16 Volt @ 85°C													
TCJH336M016#0150E	H	33	16	105	52.8	6	150	800	3	3	3.3	223	33.4
TCNT336M016#0200E	T	33	16	105	52.8	6	200	700	3	4	3.3	277	33.4
TCNT476M016#0150E	T	47	16	105	75.2	6	150	800	3	4	4.7	395	47.6
TCNT476M016#0200	T	47	16	105	75.2	6	200	700	3	4	4.7	395	47.6
TCJD686M016#0050E	D	68	16	105	108.8	6	50	2100	2	3	6.7	74	21.5
TCJD107M016#0050E	D	100	16	105	160	6	50	2100	2	3	9.9	109	31.6
TCNX157M016#0100E	X	150	16	105	240	6	100	1300	3	4	14.9	316	47.4
TCJD227M016#0050E	D	220	16	105	352	10	50	2100	2	3	21.8	240	69.5
TCN4227M016#0070E	4	220	16	105	352	20	70	1650	2	4	21.8	245	49
TCN4337M016#0070E	4	330	16	105	528	20	70	1650	3	4	32.7	367	73.5
TCJ5337M016#0100E	5	330	16	105	528	10	100	1300	2	3	32.7	274	104.2
TCJ5477M016#0100E	5	470	16	105	752	10	100	1300	3	3	46.6	391	148.5
20 Volt @ 85°C													
TCJD686M020#0055E	D	68	20	105	136	6	55	2000	3	3	8.4	92	26.7
TCJD107M020#0055E	D	100	20	105	200	6	55	2000	3	3	12.4	136	39.3
TCN4227M020#0100E	4	220	20	85	440	10	100	1380	5	4	27.2	305	61.1
25 Volt @ 85°C													
TCNT226M025#0200E	T	22	25	105	55	6	200	700	3	4	4.3	364	43.9
TCNT336M025#0250E	T	33	25	105	82.5	10	250	600	3	4	6.5	547	65.8
TCNX476M025#0100E	X	47	25	105	117.5	6	100	1300	2	5	9.2	195	29.3
TCJD686M025#0070E	D	68	25	105	170	6	70	1800	2	3	13.3	146	42.3
TCJD107M025#0070E	D	100	25	105	250	6	70	1800	2	3	19.6	215	62.3
TCN4107M025#0100E	4	100	25	105	250	6	100	1380	2	4	19.6	219	43.9
TCN4157M025#0070E	4	150	25	105	375	6	70	1650	2	4	29.3	329	65.9
TCN4227M025#0100E	4	220	25	105	550	10	100	1380	3	4	43.0	483	96.7
35 Volt @ 85°C													
TCNL475M035#0300E	L	4.7	35	105	16.5	6	300	600	2	5	1.8	186	18.6
TCNT475M035#0200E	T	4.7	35	105	16.5	10	200	700	3	4	1.8	154	18.6
TCNT106M035#0200E	T	10	35	105	35	10	200	700	3	4	3.9	328	39.5
TCJC156M035#0200E	C	15	35	105	52.5	6	200	900	3	3	5.8	116	30.3
TCJD226M035#0100E	D	22	35	105	77	6	100	1500	2	3	8.5	94	27.1
TCJD336M035#0070E	D	33	35	105	115.5	6	70	1800	2	3	12.8	141	40.7
TCNX476M035#0150E	X	47	35	105	165	10	150	1100	3	4	18.2	387	58.0
TCN4107M035#0100E	4	100	35	105	350	10	100	1380	2	3	38.8	435	87.1
50 Volt @ 85°C													
TCJC685M050#0200E	C	6.8	50	105	34	8	200	900	3	3	5.4	108	28.2
TCJD106M050#0120E	D	10	50	105	50	10	120	1400	3	3	8.0	87	25.3
TCJE156M050#0070E	E	15	50	105	75	6	70	1900	3	3	11.9	93	38

Energy is calculated by this formula (consider derating factor):

Energy = ½ C x $((Vr \times X)^2 - Vx^2)$

where C = Capacitance

Vr = Rated Voltage

X = Recommended derating factor

Vx= 3V (invariable)

Moisture Sensitivity Level (MSL) is defined according to J-STD-020.

All technical data relates to an ambient temperature of +25°C. Capacitance is measured at 120Hz, 0.5RMS with DC bias of 2.2 volts. DCL is measured at rated voltage after 5 minutes.

ESR allowed to move up to 1.25 times catalog limit post mounting.

For typical weight and composition see page 276.

NOTE: AVX reserves the right to supply higher voltage ratings in the same case size, to the same reliability standards.

RECOMMENDED DERATING FACTOR

Voltage and temperature derating as percentage of Vr

Product Category 1



Product Category 2



Product Category 3



Product Category 5



PRODUCT CATEGORY 1 (TEMPERATURE RANGE -55°C TO +125°C)

<table>
<tr><th>TEST</th><th>Condition</th><th colspan="7">Characteristics</th></tr>
<tr><td rowspan="5">Endurance</td><td rowspan="5">Apply rated voltage (Ur) at 85ºC and /or 2/3 rated voltage (Ur) at 125ºC for 2000 hours through a circuit impedance of ≤0.1Ω/V. Stabilize at room temperature for 1-2 hours before measuring.</td><td>Visual examination</td><td colspan="6">no visible damage</td></tr>
<tr><td>DCL</td><td colspan="6">1.25 x initial limit</td></tr>
<tr><td>ΔC/C</td><td colspan="6">within ±20% of initial value</td></tr>
<tr><td>DF</td><td colspan="6">1.5 x initial limit</td></tr>
<tr><td>ESR</td><td colspan="6">2 x initial limit</td></tr>
<tr><td rowspan="5">Storage Life</td><td rowspan="5">Store at 125ºC, no voltage applied, for 2000 hours. Stabilize at room temperature for 1-2 hours before measuring.</td><td>Visual examination</td><td colspan="6">no visible damage</td></tr>
<tr><td>DCL</td><td colspan="6">2 x initial limit</td></tr>
<tr><td>ΔC/C</td><td colspan="6">within ±20% of initial value</td></tr>
<tr><td>DF</td><td colspan="6">1.5 x initial limit</td></tr>
<tr><td>ESR</td><td colspan="6">2 x initial limit</td></tr>
<tr><td rowspan="5">Humidity</td><td rowspan="5">Store at 65ºC and 95% relative humidity for 500 hours, with no applied voltage. Stabilize at room temperature and humidity for 1-2 hours before measuring.</td><td>Visual examination</td><td colspan="6">no visible damage</td></tr>
<tr><td>DCL</td><td colspan="6">3 x initial limit</td></tr>
<tr><td>ΔC/C</td><td colspan="6">within +30/-20% of initial value</td></tr>
<tr><td>DF</td><td colspan="6">1.5 x initial limit</td></tr>
<tr><td>ESR</td><td colspan="6">2 x initial limit</td></tr>
<tr><td rowspan="5">Temperature Stability</td><td rowspan="5"><table><tr><th>Step</th><th>Temperature°C</th><th>Duration(min)</th></tr><tr><td>1</td><td>+20</td><td>15</td></tr><tr><td>2</td><td>-55</td><td>15</td></tr><tr><td>3</td><td>+20</td><td>15</td></tr><tr><td>4</td><td>+85</td><td>15</td></tr><tr><td>5</td><td>+125</td><td>15</td></tr><tr><td>6</td><td>+20</td><td>15</td></tr></table></td><td></td><td>+20ºC</td><td>-55ºC</td><td>+20ºC</td><td>+85ºC</td><td>+125ºC</td><td>+20ºC</td></tr>
<tr><td>DCL</td><td>IL*</td><td>n/a</td><td>IL*</td><td>10 x IL*</td><td>12.5 x IL*</td><td>IL*</td></tr>
<tr><td>ΔC/C</td><td>n/a</td><td>+0/-20%</td><td>±5%</td><td>+20/-0%</td><td>+30/-0%</td><td>±5%</td></tr>
<tr><td>DF</td><td>IL*</td><td>1.5 x IL*</td><td>IL*</td><td>1.5 x IL*</td><td>2 x IL*</td><td>IL*</td></tr>
<tr><td rowspan="4">Surge Voltage</td><td rowspan="4">Apply 1.3x 2.3x rated voltage (Ur) at 125ºC for 1000 cycles of duration 6 min (30 sec charge, 5 min 30 sec discharge) through a charge / discharge resistance of 1000Ω</td><td>Visual examination</td><td colspan="6">no visible damage</td></tr>
<tr><td>DCL</td><td colspan="6">initial limit</td></tr>
<tr><td>ΔC/C</td><td colspan="6">within +10/-20% of initial value for Vr ≤ 10V
within +20/-30% of initial value for Vr ≥ 16V</td></tr>
<tr><td>DF</td><td colspan="6">1.25 x initial limit</td></tr>
<tr><td rowspan="5">Mechanical Shock</td><td rowspan="5">MIL-STD-202, Method 213, Condition C</td><td>Visual examination</td><td colspan="6">no visible damage</td></tr>
<tr><td>DCL</td><td colspan="6">initial limit</td></tr>
<tr><td>ΔC/C</td><td colspan="6">within ±5% of initial value</td></tr>
<tr><td>DF</td><td colspan="6">initial limit</td></tr>
<tr><td>ESR</td><td colspan="6">initial limit</td></tr>
<tr><td rowspan="5">Vibration</td><td rowspan="5">MIL-STD-202, Method 204, Condition D</td><td>Visual examination</td><td colspan="6">no visible damage</td></tr>
<tr><td>DCL</td><td colspan="6">initial limit</td></tr>
<tr><td>ΔC/C</td><td colspan="6">within ±5% of initial value</td></tr>
<tr><td>DF</td><td colspan="6">initial limit</td></tr>
<tr><td>ESR</td><td colspan="6">initial limit</td></tr>
</table>

*Initial Limit Initial measurement max. 1hr after the removal from dry pack or after pretreatment at 85°C for 24 hours.

PRODUCT CATEGORY 2, 3 (TEMPERATURE RANGE -55°C TO +105°C)

<table>
<tr><th>TEST</th><th>Condition</th><th colspan="7">Characteristics</th></tr>
<tr><td rowspan="5">Endurance</td><td rowspan="5">Apply rated voltage (Ur) at 85ºC for 2000 hours through a circuit impedance of ≤0.1Ω/V (all CATEGORIES). And / or apply rated voltage (Ur) (CATEGORY 2) or 0.8x rated voltage (CATEGORY 3) at 105°C for 2000 hours through a circuit impedance of ≤0.1Ω/V. Always stabilize at room temperature for 1-2 hours before measuring.</td><td colspan="7">Visual examination</td><td>no visible damage</td></tr>
<tr><td colspan="7">DCL</td><td>1.25 x initial limit</td></tr>
<tr><td colspan="7">ΔC/C</td><td>within +10/-20% of initial value for Vr ≤ 16V
within ±20% of initial value for Vr ≥ 20V</td></tr>
<tr><td colspan="7">DF</td><td>1.5 x initial limit</td></tr>
<tr><td colspan="7">ESR</td><td>2 x initial limit</td></tr>
<tr><td rowspan="5">Storage Life</td><td rowspan="5">Store at 105ºC, no voltage applied, for 2000 hours. Stabilize at room temperature for 1-2 hours before measuring.</td><td colspan="7">Visual examination</td><td>no visible damage</td></tr>
<tr><td colspan="7">DCL</td><td>1.25 x initial limit</td></tr>
<tr><td colspan="7">ΔC/C</td><td>within +10/-20% of initial value for Vr ≤ 16V
within ±20% of initial value for Vr ≥ 20V</td></tr>
<tr><td colspan="7">DF</td><td>1.5 x initial limit</td></tr>
<tr><td colspan="7">ESR</td><td>2 x initial limit</td></tr>
<tr><td rowspan="5">Humidity</td><td rowspan="5">Store at 65ºC and 95% relative humidity for 500 hours, with no applied voltage. Stabilize at room temperature and humidity for 1-2 hours before measuring.</td><td colspan="7">Visual examination</td><td>no visible damage</td></tr>
<tr><td colspan="7">DCL</td><td>3 x initial limit</td></tr>
<tr><td colspan="7">ΔC/C</td><td>within +30/-20% of initial value</td></tr>
<tr><td colspan="7">DF</td><td>1.5 x initial limit</td></tr>
<tr><td colspan="7">ESR</td><td>2 x initial limit</td></tr>
<tr><td rowspan="8">Temperature Stability</td><td colspan="3"><table><tr><th>Step</th><th>Temperature°C</th><th>Duration(min)</th></tr><tr><td>1</td><td>+20</td><td>15</td></tr><tr><td>2</td><td>-55</td><td>15</td></tr><tr><td>3</td><td>+20</td><td>15</td></tr><tr><td>4</td><td>+85</td><td>15</td></tr><tr><td>5</td><td>+105</td><td>15</td></tr><tr><td>6</td><td>+20</td><td>15</td></tr></table></td><td></td><td>+20ºC</td><td>-55ºC</td><td>+20ºC</td><td>+85ºC</td><td>+105ºC</td><td>+20ºC</td></tr>
<tr><td colspan="2">DCL</td><td>IL*</td><td>n/a</td><td>IL*</td><td>10 x IL*</td><td>12.5 x IL*</td><td>IL*</td></tr>
<tr><td colspan="2">ΔC/C</td><td>n/a</td><td>+0/-20%</td><td>±5%</td><td>+20/-0%</td><td>+30/-0%</td><td>±5%</td></tr>
<tr><td colspan="2">DF</td><td>IL*</td><td>1.5 x IL*</td><td>IL*</td><td>1.5 x IL*</td><td>2 x IL*</td><td>IL*</td></tr>
<tr><td rowspan="4">Surge Voltage</td><td rowspan="4">Apply 1.3x rated voltage (Ur) at 105ºC for CATEGORY 2, or apply 1.3x 0.8x rated voltage (Ur) at 105ºC for CATEGORY 3 for 1000 cycles of duration 6 min (30 sec charge, 5 min 30 sec discharge) through a charge / discharge resistance of 1000Ω</td><td colspan="7">Visual examination</td><td>no visible damage</td></tr>
<tr><td colspan="7">DCL</td><td>initial limit</td></tr>
<tr><td colspan="7">ΔC/C</td><td>within +10/-20% of initial value for Vr ≤ 16V
within +20/-30% of initial value for Vr ≥ 20V</td></tr>
<tr><td colspan="7">DF</td><td>1.25 x initial limit</td></tr>
<tr><td rowspan="5">Mechanical Shock</td><td rowspan="5">MIL-STD-202, Method 213, Condition C</td><td colspan="7">Visual examination</td><td>no visible damage</td></tr>
<tr><td colspan="7">DCL</td><td>initial limit</td></tr>
<tr><td colspan="7">ΔC/C</td><td>within ±5% of initial value</td></tr>
<tr><td colspan="7">DF</td><td>initial limit</td></tr>
<tr><td colspan="7">ESR</td><td>initial limit</td></tr>
<tr><td rowspan="5">Vibration</td><td rowspan="5">MIL-STD-202, Method 204, Condition D</td><td colspan="7">Visual examination</td><td>no visible damage</td></tr>
<tr><td colspan="7">DCL</td><td>initial limit</td></tr>
<tr><td colspan="7">ΔC/C</td><td>within ±5% of initial value</td></tr>
<tr><td colspan="7">DF</td><td>initial limit</td></tr>
<tr><td colspan="7">ESR</td><td>initial limit</td></tr>
</table>

*Initial Limit Initial measurement max. 1hr after the removal from dry pack or after pretreatment at 85°C for 24 hours.

PRODUCT CATEGORY 5 (TEMPERATURE RANGE -55°C TO +85°C)

TEST	Condition	Characteristics	
Endurance	Apply rated voltage (Ur) at 85ºC for 2000 hours through a circuit impedance of ≤0.1Ω/V. Stabilize at room temperature for 1-2 hours before measuring.	Visual examination	no visible damage
		DCL	1.25 x initial limit
		ΔC/C	within +10/-20% of initial value for Vr ≤ 16V within ±20% of initial value for Vr ≥ 20V
		DF	1.5 x initial limit
		ESR	2 x initial limit
Storage Life	Store at 85ºC, no voltage applied, for 2000 hours. Stabilize at room temperature for 1-2 hours before measuring.	Visual examination	no visible damage
		DCL	1.25 x initial limit
		ΔC/C	within +10/-20% of initial value for Vr ≤ 16V within ±20% of initial value for Vr ≥ 20V
		DF	1.5 x initial limit
		ESR	2 x initial limit
Humidity	Store at 65ºC and 95% relative humidity for 500 hours, with no applied voltage. Stabilize at room temperature and humidity for 1-2 hours before measuring.	Visual examination	no visible damage
		DCL	5 x initial limit
		ΔC/C	within +40/-20% of initial value
		DF	1.5 x initial limit
		ESR	2 x initial limit
Temperature Stability	Step: 1 — Temperature°C: +20 — Duration(min): 15 Step: 2 — Temperature°C: -55 — Duration(min): 15 Step: 3 — Temperature°C: +20 — Duration(min): 15 Step: 4 — Temperature°C: +85 — Duration(min): 15 Step: 5 — Temperature°C: +20 — Duration(min): 15		+20ºC / -55ºC / +20ºC / +85ºC / +20ºC
		DCL	IL* / n/a / IL* / 10 x IL* / IL*
		ΔC/C	n/a / +0/-20% / ±5% / +20/-0% / ±5%
		DF	IL* / 1.5 x IL* / IL* / 1.5 x IL* / IL*
Surge Voltage	Apply 1.3x rated voltage (Ur) at 85ºC for 1000 cycles of duration 6 min (30 sec charge, 5 min 30 sec discharge) through a charge / discharge resistance of 1000Ω	Visual examination	no visible damage
		DCL	initial limit
		ΔC/C	within +10/-20% of initial value for Vr ≤ 16V within +20/-30% of initial value for Vr ≥ 20V
		DF	1.25 x initial limit
Mechanical Shock	MIL-STD-202, Method 213, Condition C	Visual examination	no visible damage
		DCL	initial limit
		ΔC/C	within ±5% of initial value
		DF	initial limit
		ESR	initial limit
Vibration	MIL-STD-202, Method 204, Condition D	Visual examination	no visible damage
		DCL	initial limit
		ΔC/C	within ±5% of initial value
		DF	initial limit
		ESR	initial limit

*Initial Limit — Initial measurement max. 1hr after the removal from dry pack or after pretreatment at 85°C for 24 hours.

SOLID ELECTROLYTIC CAPACITOR ROADMAP





FIVE CAPACITOR CONSTRUCTION STYLES



SERIES LINE UP : Conductive Polymer



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

AVX:

TCJH157M006R0200 TCJT476M006R0080 TCJT336M010R0070 TCJT476M006R0120 TCJD106M050R0120
TCJT686M004R0080 TCJC336M010R0100 TCJC476M010R0100 TCJT107M004R0150 TCJT336M010R0150
TCJT476M004R0080 TCJT226M006R0150 TCJT336M006R0150 TCJC686M006R0100 TCJT226M010R0150
TCJT106M016R0150 TCJC156M035R0200 TCJC226M025R0100 TCJC475M035R0200 TCJC685M035R0200
TCJD156M035R0070 TCJD156M035R0100 TCJD226M025R0060 TCJD226M025R0100 TCJD226M035R0070
TCJD226M035R0100 TCJD336M025R0060 TCJD336M025R0100 TCJD336M035R0070 TCJD336M035R0100
TCJD476M025R0060 TCJD476M025R0100 TCJE106M050R0070 TCJE156M050R0070 TCJE336M035R0055
TCJE476M025R0050 TCJE476M035R0055 TCJE686M025R0050 TCJC106M035R0200 TCJT106M016R0200
TCJC155M050R0300 TCJC225M050R0300 TCJC475M050R0200 TCJC685M050R0200 TCJD685M050R0120
TCJC225M063R0200 TCJC335M063R0200 TCJD475M063R0120 TCJD475M075R0150 TCJD685M063R0120
TCJD685M075R0120 TCJE106M063R0100 TCJE685M063R0100 TCJC475M063R0200 TCJC105M063R0300
TCJC155M063R0300 TCJE107M016R0040 TCJE107M020R0045 TCJE157M016R0040 TCJE686M020R0045
TCJC105M063S0300 TCJC155M063S0300 TCJC225M063S0200 TCJC335M063S0200 TCJC475M063S0200
TCJD475M063S0120 TCJD475M075S0150 TCJD685M063S0120 TCJD685M075S0120 TCJE106M063S0100
TCJE107M016S0040 TCJE107M020S0045 TCJE157M016S0040 TCJE685M063S0100 TCJE686M020S0045
TCJT476M006R0070 TCJT107M006R0200 TCJT686M006R0200 TCJD337M006R0050 TCJD227M006R0050
TCJD337M006R0040 TCJD337M004R0050 TCJD477M004R0050 TCJD107M020R0055 TCJD477M002R0050
TCJD686M020R0055 TCJD335M125R0250 TCJD157M010R0045 TCJD227M010R0050 TCJD227M010R0040
TCJD157M010R0055 TCJE107M025R0080 TCJD107M010R0055 TCJD477M004R0040 TCJD477M002R0040
TCJT107M006R0070 TCJD107M010R0045 TCJD227M006R0040 TCJD337M004R0040 TCJD157M010R0040