

# Terra: A Multi-Stage Language for High-Performance Computing

Presenter: Cunyuan

February 20, 2023

# Goals

- Performance matters!

# Goals

- Performance matters!
- Low-level languages(e.g. C) are good: we need to make best use of features of the target architecture(e.g. vector instructions).

# Goals

- Performance matters!
- Low-level languages(e.g. C) are good: we need to make best use of features of the target architecture(e.g. vector instructions).
- Programming is difficult!

# Goals

- Performance matters!
- Low-level languages(e.g. C) are good: we need to make best use of features of the target architecture(e.g. vector instructions).
- Programming is difficult!
- Solution: use high-level languages to generate low-level languages code(e.g. FFTW: OCaml  $\rightarrow$  C).

# New Problems

- In this case, we get three components.

# New Problems

- In this case, we get three components.
- Optimizer: generate plan to guide how to generate code.

# New Problems

- In this case, we get three components.
- Optimizer: generate plan to guide how to generate code.
- Compiler: generate target code based on the plan.



# New Problems

- In this case, we get three components.
- Optimizer: generate plan to guide how to generate code.
- Compiler: generate target code based on the plan.
- Runtime: support the generated code and provide feedback to the optimizer.

# New Problems

- In this case, we get three components.
- Optimizer: generate plan to guide how to generate code.
- Compiler: generate target code based on the plan.
- Runtime: support the generated code and provide feedback to the optimizer.
- Problem1: How can we get the runtime statistics in the compiler and generate high-performance code dynamically?

# New Problems

- In this case, we get three components.
- Optimizer: generate plan to guide how to generate code.
- Compiler: generate target code based on the plan.
- Runtime: support the generated code and provide feedback to the optimizer.
- Problem1: How can we get the runtime statistics in the compiler and generate high-performance code dynamically?
- Problem2: How can we re-use legacy libraries?

# Two-Language Design

- Lua: high-level, dynamically typed, automatic mm, first class functions.

# Two-Language Design

- Lua: high-level, dynamically typed, automatic mm, first class functions.
- Terra(new!): statically typed, manual mm.

# Two-Language Design

- Lua: high-level, dynamically typed, automatic mm, first class functions.
- Terra(new!): statically typed, manual mm.
- Use Lua to manipulate Terra code.

# Two-Language Design

- Lua: high-level, dynamically typed, automatic mm, first class functions.
- Terra(new!): statically typed, manual mm.
- Use Lua to manipulate Terra code.
- Shared lexical scoping, which is hygienic.

# Two-Language Design


- Lua: high-level, dynamically typed, automatic mm, first class functions.
- Terra(new!): statically typed, manual mm.
- Use Lua to manipulate Terra code.
- Shared lexical scoping, which is hygienic.
- Terra code runs independently, to avoid including high-level features.



# Two-Language Design

- Lua: high-level, dynamically typed, automatic mm, first class functions.
- Terra(new!): statically typed, manual mm.
- Use Lua to manipulate Terra code.
- Shared lexical scoping, which is hygienic.
- Terra code runs independently, to avoid including high-level features.
- Lua's stack-based C API makes it easy to interface with legacy code.

# Two-Language Design



# Some Code Examples

```
terra min(a: int , b: int ): int
    if a < b then return a
    else return b end
end
struct GreyScaleImage {
    data: &float
    N: int
}
```

# Features

- Terra entities are all first-class Lua values.

# Features

- Terra entities are all first-class Lua values.
- Terra functions will be executed in LLVM JIT.

# Features

- Terra entities are all first-class Lua values.
- Terra functions will be executed in LLVM JIT.
- You can dump Terra functions to an object file(i.e. something.o in Linux) if you like.

# Features

- Terra entities are all first-class Lua values.
- Terra functions will be executed in LLVM JIT.
- You can dump Terra functions to an object file(i.e. something.o in Linux) if you like.
- Quotation: using brackets([]) for escaping and backtick(expressions)/quote keyword(statements) for creating quotation.

# Quotation Example

```
local a = 5
terra sin5()
    return [ math.sin(a) ]
end
function addtwo(a,b)
    return 'a + b'
end
local printtwice = quote
    C.printf("hello\n")
    C.printf("hello\n")
end
```



# It Just Works!

```
-- C++                                | -- Lua/Terra
int add(int a, int b) {               | terra add(a : int, b : int) : int
    return a + b;                     |     return a + b
}                                     | end
                                     |
                                     | -- Conditional compilation is done
                                     | -- with control-flow that
                                     | -- determines what code is defined
#ifdef _WIN32                         | if iswindows() then
    void waitatend() {               |     terra waitatend()
        getchar();                   |         C.getchar()
    }                                 |     end
#else                                | else
    void waitatend() {}              |     terra waitatend() end
#endif                               | end
                                     |
                                     | -- Templates become Lua functions
                                     | -- that take a terra type T and
                                     | -- use it to generate new types
                                     | -- and code
template<class T>                    | function Array(T)
struct Array {                        |     struct Array {
    int N;                            |         N : int
    T* data;                          |         data : &T
    }                                  |     }
    T get(int i) {                   |     terra Array:get(i : int)
        return data[i];               |         return self.data[i]
    }                                 |     end
};                                    |     return Array
typedef                               | end
Array<float> FloatArray;              | FloatArray = Array(float)
```

# It Just Works!

- Now we can generate code dynamically.

# It Just Works!

- Now we can generate code dynamically.
- e.g. block the loop nests to make the memory access more friendly to the cache.

# The Formal Calculus: Terra Core

- For simplicity, Lua := imperative language + first-class functions,  
Terra := purely functional language

# The Formal Calculus: Terra Core

- For simplicity, Lua := imperative language + first-class functions, Terra := purely functional language
- Lua expression:  $e$ , evaluation of Lua:  $\xrightarrow{L}$

# The Formal Calculus: Terra Core

- For simplicity, Lua := imperative language + first-class functions, Terra := purely functional language
- Lua expression:  $e$ , evaluation of Lua:  $\xrightarrow{L}$
- Terra expression:  $\hat{e}$ , specialization of Terra:  $\xrightarrow{S}$

# The Formal Calculus: Terra Core

- For simplicity, Lua := imperative language + first-class functions, Terra := purely functional language
- Lua expression:  $e$ , evaluation of Lua:  $\xrightarrow{L}$
- Terra expression:  $\dot{e}$ , specialization of Terra:  $\xrightarrow{S}$
- Specialized Terra expression:  $\underline{\dot{e}}$ , execution of specialized Terra expression:  $\xrightarrow{T}$

## Lua Syntax:

$$\begin{aligned} e &::= b \mid \dot{T} \mid x \mid \text{let } x = e \text{ in } e \mid x := e \mid e(e) \mid \text{fun}(x)\{e\} \mid tdecl \mid \\ &\quad \text{tere}(x : e) : e\{\dot{e}\} \mid \backslash \dot{e} \\ v &::= b \mid l \mid \dot{T} \mid \langle \Gamma, x, e \rangle \mid \underline{\dot{e}} \\ \dot{T} &::= \dot{B} \mid \dot{T} \rightarrow \dot{T} \end{aligned}$$



## Terra Syntax:

$$\dot{e} ::= b \mid x \mid \dot{e}(\dot{e}) \mid t \text{let } x : e = \dot{e} \text{ in } \dot{e} \mid [e]$$
$$\underline{\dot{e}} ::= b \mid \underline{\dot{x}} \mid \underline{\dot{e}}(\underline{\dot{e}}) \mid t \text{let } \underline{\dot{x}} : \dot{T} = \underline{\dot{e}} \text{ in } \underline{\dot{e}} \mid I$$

$$v\Sigma \xrightarrow{L} v\Sigma \quad (\text{LVAL})$$

$$\frac{\Sigma = \Gamma, S, F}{x\Sigma \xrightarrow{L} S(\Gamma(x))\Sigma} \quad (\text{LVAR})$$

$$\frac{e_1\Sigma_1 \xrightarrow{L} v_1\Sigma_2 \quad \Sigma_2 = \Gamma, S, F \quad e_2\Sigma_2[x \leftarrow v_1] \xrightarrow{L} v_2\Sigma_3}{\text{let } x = e_1 \text{ in } e_2 \Sigma \xrightarrow{L} v_2(\Sigma_3 \leftarrow \Gamma)} \quad (\text{LLET})$$

$$\frac{e\Sigma \xrightarrow{L} v\Gamma, S, F \quad \Gamma(x) = a}{x := e \Sigma \xrightarrow{L} v\Gamma, S[a \leftarrow v], F} \quad (\text{LASN})$$

$$\frac{\Sigma = \Gamma, S, F}{\text{fun}(x)\{e\} \Sigma \xrightarrow{L} \langle \Gamma, x, e \rangle \Sigma} \quad (\text{LFUN})$$

$$\frac{e_1 \Sigma_1 \xrightarrow{L} \langle \Gamma_1, x, e_3 \rangle \quad e_2 \Sigma_2 \xrightarrow{L} v_1 \Gamma_2, S, F \quad a \text{ fresh } e_3 \Gamma_1[x \leftarrow a], S[a \leftarrow v_1], F \xrightarrow{L} v_2 \Sigma_3}{e_1(e_2) \Sigma_1 \xrightarrow{L} v_2 (\Sigma_3 \leftarrow \Gamma_2)} \quad (\text{LAPP})$$

$$\frac{l \text{ fresh } \Sigma = \Gamma, S, F}{tdec \Sigma \xrightarrow{L} l \Gamma, S, F[l \leftarrow \bullet]} \quad (\text{LTDECL})$$

$$\begin{array}{l}
 e_1 \Sigma_1 \xrightarrow{L} l \Sigma_2 \quad e_2 \Sigma_2 \xrightarrow{L} \dot{T}_1 \Sigma_3 \quad e_3 \Sigma_3 \xrightarrow{L} \dot{T}_2 \Sigma_4 \\
 \Sigma_4 = \Gamma_1, S_1, F_1 \quad \dot{x} \text{ fresh} \\
 \text{(LTDEFN)}
 \end{array}$$

$$\frac{\dot{e} \Sigma_4 [x \leftarrow \dot{x}] \xrightarrow{S} \dot{e} \Gamma_2, S_2, F_2 \quad F_2(l) = \bullet}{\text{ter } e_1(x : e_2) : e_3\{\dot{e}\} \Sigma_1 \xrightarrow{L} l \Gamma_1, S_2, F_2 [l \leftarrow \langle \dot{x}, \dot{T}_1, \dot{T}_2, \dot{e} \rangle]}$$

$$\frac{\dot{e} \Sigma_1 \xrightarrow{S} \dot{e} \Sigma_2}{\dot{e} \Sigma_1 \xrightarrow{L} \dot{e} \Sigma_2} \quad \text{(LTQUOTE)}$$

$$\begin{array}{c}
 e_1 \Sigma_1 \xrightarrow{L} l \Sigma_2 \quad e_2 \Sigma_2 \xrightarrow{L} b_1 \Sigma_3 \\
 \Sigma_3 = \Gamma, S, F \quad F(l) = \langle \dot{x}, \dot{T}_1, \dot{T}_2, \dot{e} \rangle \quad b_1 \in \dot{T}_1 \\
 \frac{[\dot{x} : \dot{T}_1], [l : \dot{T}_1 \rightarrow \dot{T}_2], F_2 \vdash \dot{e} : \dot{T}_2 \quad \dot{e}[\dot{x} \leftarrow b], F \xrightarrow{T} b_2}{e_1(e_2) \Sigma_1 \xrightarrow{L} b_2 \Sigma_3} \quad (\text{LTAPP})
 \end{array}$$

$$b\Sigma \xrightarrow{S} b\Sigma \quad (\text{SBAS})$$

$$\frac{\dot{e}_1 \Sigma_1 \xrightarrow{S} \underline{\dot{e}_1} \Sigma_2 \quad \dot{e}_2 \Sigma_2 \xrightarrow{S} \underline{\dot{e}_2} \Sigma_3}{\dot{e}_1(\dot{e}_2) \Sigma_1 \xrightarrow{S} \underline{\dot{e}_1}(\underline{\dot{e}_2}) \Sigma_3} \quad (\text{SAPP})$$

$$\frac{e\Sigma_1 \xrightarrow{L} \dot{T}\Sigma_2 \quad \dot{e}_1 \Sigma_2 \xrightarrow{S} \underline{\dot{e}_1} \Sigma_3 \quad \underline{\dot{x}} \text{ fresh} \quad \Sigma_3 = \Gamma, S, F \quad \dot{e}_2 \Sigma_3[x \leftarrow \underline{\dot{e}_2}] \xrightarrow{S} \underline{\dot{e}_2} \Sigma_4}{tlet x : e = \dot{e}_1 \text{ in } \dot{e}_2 \Sigma_1 \xrightarrow{S} tlet \underline{\dot{x}} : \dot{T} = \underline{\dot{e}_1} \text{ in } \underline{\dot{e}_2} (\Sigma_4 \leftarrow \Gamma)} \quad (\text{SLET})$$

$$\frac{e\Sigma_1 \xrightarrow{L} \dot{e}\Sigma_2}{[e]\Sigma_1 \xrightarrow{S} \dot{e}\Sigma_2} \quad (\text{SESC})$$

$$\frac{[x]\Sigma_1 \xrightarrow{S} \dot{e}\Sigma_2}{x\Sigma_1 \xrightarrow{S} \dot{e}\Sigma_2} \quad (\text{SVAR})$$

$$b\dot{\Gamma}, F \xrightarrow{T} b \quad (\text{TBAS})$$

$$l\dot{\Gamma}, F \xrightarrow{T} l \quad (\text{TFUN})$$

$$\dot{x}\dot{\Gamma}, F \xrightarrow{T} \dot{\Gamma}(\dot{x}) \quad (\text{TVAR})$$

$$\frac{\underline{e_1}\dot{\Gamma}, F \xrightarrow{T} v_1 \quad \underline{e_2}\dot{\Gamma}[\dot{x} \leftarrow v_1], F \xrightarrow{T} v_2}{tlet \dot{x} : \dot{T} = \underline{e_1} \text{ in } \underline{e_2} \dot{\Gamma}, F \xrightarrow{T} v_2} \quad (\text{TLET})$$

$$\frac{\underline{e_1}\dot{\Gamma}, F \xrightarrow{T} l \quad \underline{e_2}\dot{\Gamma}, F \xrightarrow{T} v_1 \quad F(l) = \langle \dot{x}, \dot{T}_1, \dot{T}_2, \underline{e_3} \rangle \quad \underline{e_3}\dot{\Gamma}[\dot{x} \leftarrow v_1], F \xrightarrow{T} v_2}{\underline{e_1}(\underline{e_2})\dot{\Gamma}, F \xrightarrow{T} v_2} \quad (\text{TAPP})$$



- The typing rules are very simple. Skip.

- The typing rules are very simple. Skip.
- Let's see the proof.

- The typing rules are very simple. Skip.
- Let's see the proof.
- No proof! :)

# Some Important Designs

- Use shared lexical environments to reduce the need for escape expressions.

# Some Important Designs

- Use shared lexical environments to reduce the need for escape expressions.
- Perform specialization eagerly.

# Some Important Designs

- Use shared lexical environments to reduce the need for escape expressions.
- Perform specialization eagerly.
- Perform typechecking and linking lazily.

# Some Important Designs

- Use shared lexical environments to reduce the need for escape expressions.
- Perform specialization eagerly.
- Perform typechecking and linking lazily.
- Type Reflection API.

# Why Specialize Eagerly?

```
let  $x_1 = 0$   
let  $y = \text{tertdecl}(x_2 : \text{int}) : \text{int} \{x_1\}$  in  
 $x_1 := 1; y(0)$ 
```



# Why Specialize Eagerly?

```
let  $x_1 = 0$   
let  $y = \text{tertdecl}(x_2 : \text{int}) : \text{int} \{x_1\}$  in  
 $x_1 := 1; y(0)$ 
```

- $y(0) = 0$  if we specialize eagerly.

# Why Specialize Eagerly?

```
let  $x_1 = 0$   
let  $y = \text{tertdecl}(x_2 : \text{int}) : \text{int} \{x_1\}$  in  
 $x_1 := 1; y(0)$ 
```

- $y(0) = 0$  if we specialize eagerly.
- If not, the Terra runtime must depends on the Lua runtime to get correct value of  $x_1$ .

# Why Specialize Eagerly?

```
let  $x_1 = 0$   
let  $y = \text{tertdecl}(x_2 : \text{int}) : \text{int} \{x_1\}$  in  
 $x_1 := 1; y(0)$ 
```

- $y(0) = 0$  if we specialize eagerly.
- If not, the Terra runtime must depend on the Lua runtime to get correct value of  $x_1$ .
- Or we need to re-compile  $y$  when  $x_1$  changes.

# Why Specialize Eagerly?

```
let  $x_1 = 0$   
let  $y = \text{tertdecl}(x_2 : \text{int}) : \text{int} \{x_1\}$  in  
 $x_1 := 1; y(0)$ 
```

- $y(0) = 0$  if we specialize eagerly.
- If not, the Terra runtime must depend on the Lua runtime to get correct value of  $x_1$ .
- Or we need to re-compile  $y$  when  $x_1$  changes.
- Requires declaration before using a symbol, which makes recursive function impossible.

# Why Specialize Eagerly?

```
let  $x_1 = 0$   
let  $y = \text{tertdecl}(x_2 : \text{int}) : \text{int} \{x_1\}$  in  
 $x_1 := 1; y(0)$ 
```

- $y(0) = 0$  if we specialize eagerly.
- If not, the Terra runtime must depend on the Lua runtime to get correct value of  $x_1$ .
- Or we need to re-compile  $y$  when  $x_1$  changes.
- Requires declaration before using a symbol, which makes recursive function impossible.
- Separate the declaration and definition.

# Why Typecheck Lazily?

- Possible if we use type annotations.

# Why Typecheck Lazily?

- Possible if we use type annotations.
- Since a function may have no definition, this may not help.

# Why Typecheck Lazily?

- Possible if we use type annotations.
- Since a function may have no definition, this may not help.
- So no need for type annotations.



# Why Typecheck Lazily?

- Possible if we use type annotations.
- Since a function may have no definition, this may not help.
- So no need for type annotations.
- Easier to override the default behavior of a type.

# Type Reflection

- Terra types are first-class in Lua.

# Type Reflection

- Terra types are first-class in Lua.
- Provide methods in Lua(e.g. `t:ispointer` or `t:isstruct`).

# Type Reflection

- Terra types are first-class in Lua.
- Provide methods in Lua(e.g. `t:ispointer` or `t:isstruct`).
- Use entries table to describe structures' in-memory layout.

```
struct Complex {  
  Complex.entries:insert { field = "real",  
    type = float }  
  Complex.entries:insert { field = "imag",  
    type = float }
```

# Type Reflection

- Terra types are first-class in Lua.
- Provide methods in Lua(e.g. `t:ispointer` or `t:isstruct`).
- Use entries table to describe structures' in-memory layout.

```
struct Complex {  
  Complex.entries:insert { field = "real",  
    type = float }  
  Complex.entries:insert { field = "imag",  
    type = float }
```

- Also the metamethods table: override certain compile-time behaviors(e.g. implicit conversion).

# Evaluation

- Similar performance to ATLAS, which is written in C and assembly.

# Evaluation

- Similar performance to ATLAS, which is written in C and assembly.
- Shorter code, easier to read/write/maintain.

# Summary

- Two-Languages design: Lua + Terra.



# Summary

- Two-Languages design: Lua + Terra.
- Shared lexical scoping.

# Summary

- Two-Languages design: Lua + Terra.
- Shared lexical scoping.
- Seperate Evaluationn: Lua(LuaJIT), Terra(LLVM JIT).

# Summary

- Two-Languages design: Lua + Terra.
- Shared lexical scoping.
- Seperate Evaluationn: Lua(LuaJIT), Terra(LLVM JIT).
- Type Reflection.

# Advantages

- No need to write C, but the performance is still good.

# Advantages

- No need to write C, but the performance is still good.
- Generating code dynamically allows us to use runtime information from LuaJIT.

# Advantages

- No need to write C, but the performance is still good.
- Generating code dynamically allows us to use runtime information from LuaJIT.
- Easy to re-use C/C++ libraries in Lua.

# Advantages

- No need to write C, but the performance is still good.
- Generating code dynamically allows us to use runtime information from LuaJIT.
- Easy to re-use C/C++ libraries in Lua.

# Shortages

- Lua is not statically typed.



# Reference

- Zachary DeVito, James Hegarty, Alex Aiken, Pat Hanrahan, and Jan Vitek. 2013. Terra: A multi-stage language for highperformance computing. In Proceedings of the 34th ACM SIGPLAN Conference on Programming Language Design and Implementation (PLDI'13). ACM, New York, 105–116.  
DOI:<https://doi.org/10.1145/2491956.2462166>
- Terra: A low-level counterpart to Lua. <https://terralang.org/>