

34-Pattern Matching

The “dark” side of expressions

Expressions

- Expressions
 - One of the central concepts in almost all languages is the *expression*.
 - An expression is essentially a function which takes some number of variables/constants/expressions and yields a result, e.g. $f(x,y,z)$ or $x+z*2$. Remember that this is just a human-readable form of $x+(z*(2))$.
 - In procedural languages, expressions form the right-hand-sides of statements such as assignments, return statements, constant declarations, the branches of an if/else/for/while/do construct, etc.
 - In Scala, the yield (return value) of *every part of the language is an expression*. The only exceptions are:
 - declarations of traits/classes/objects, methods and variables;
 - other non-expression constructs: import, package, “type” statements.

Patterns

- *Patterns* are the antithesis (i.e. opposite) of expressions and are found only in functional programming languages.
- A pattern allows you to take a variable and *produce* several variables (exactly the opposite of what an expression does).
- Let's look at an example:

```
def decode(x: (Int,String)): Unit =  
  x match {  
    case (k,v) => println(s"$k: $v")  
  }
```

- In this example, we are pattern-matching on a *Tuple* of *Int* and *String*. We only need one case whose pattern looks exactly like an expression forming a tuple from *k* and *v*. But it is a pattern instead and so *k* and *v* are extracted from the given tuple *x*, and become in-scope variables which can be used in the expression on the right-hand side.
- Thus, a pattern which looks like an expression is actually an *extractor*.

Patterns (1)

- Let's look at another example:

```
def print(xs: List[Int]): Unit =  
  xs match {  
    case h :: t => println(h); print(t)  
    case _ =>  
  }
```

- In this example, the construct $h :: t$ is a pattern. It looks *exactly* like an expression BUT instead of h and t being existing in-scope variables which will be applied to the $::$ operator to yield a value, instead the value is matched against the pattern and, if there is a match, variables h and t are, magically if you like, declared and in scope.
- In this situation, it is the variable xs which is matched against the patterns—in the order defined—and, if a match is found, the expression on the RHS of the “ $=>$ ” (“rocket symbol”) is invoked. Here, h is passed to *println* and t is passed, recursively, to *print*.

Patterns (2)

- Here again is our example:

```
def print(xs: List[Int]): Unit =  
  xs match {  
    case h :: t => println(h); print(t)  
    case _ =>  
  }
```

- There is also a catch-all pattern “_”, although any identifier name would do, such as “a”, “x”, etc. The unique thing about the “_” is that the pattern matches as it would to an identifier, but no variable is synthesized.
- I need to explain what $h :: t$ actually represents (whether as an expression or a pattern).
 - In the context of an expression, “::” is actually the case class “::” (which we pronounce “cons”) or, more precisely, the auto-magically generated *apply* method of the companion object “::”

Patterns (3)

- Here again is our example:

```
def print(xs: List[Int]): Unit =  
  xs match {  
    case h :: t => println(h); print(t)  
    case _ =>  
  }
```

- When we write $h :: t$ as an expression the compiler actually expands this into $::.apply(t, h)$.
- But when we write $h :: t$ as a pattern, a completely different mechanism is used. The compiler invokes the following method on “ $::$ ”:
 - $unapply[X](xs: List[X]): Option[(X, List[X])]$ which results in an (optional) tuple of two parameters: an X (the head) and a $List[X]$ (the tail). Any object can have an *unapply* method, but the magic of case classes is that they auto-generate the appropriate *unapply* method. That’s to say that case classes are *designed* for use in pattern-matching!
- Can you see that $h :: t$ as an expression and $h :: t$ as a pattern are simply two sides to the same coin? One expands to $::.apply(h, t)$ and the other to $::.unapply(h, t)$.

Patterns (4)

- Here again is our example:

```
def print(xs: List[Int]): Unit =  
  xs match {  
    case h :: t => println(h); print(t)  
    case _ =>  
  }
```

- A **case class** is just like an ordinary class but it has some very special additional properties. Our particular case class is defined in the API thus:

```
final case class ::[B](head: B, tl: List[B]) extends List[B] with Product with Serializable
```

- The additional properties that the compiler provides for a case class are:
 - the parameters of the case class are, by default, available as methods of the class (e.g. *xs.head*); the case class instances also behave as *Tuples* (as provided for by the *Product* trait);
 - *toString*, *equals* and *hashCode* methods are all automagic;
 - the companion object provides an *apply* method (which effectively obviates the need to use the “new” keyword) and an *unapply* method which, given an instance of the case class, will yield an optional tuple of the parameters. **This** is how the variables *h* and *t* are automatically generated from the *h :: t* pattern.

Patterns (5)

- Back to patterns. What other sorts of patterns are there?

- constant patterns, for example using *Nil* (the empty list):

```
xs match {  
  case Nil =>  
  case h :: t => println(h); print(t)  
}
```

- typed patterns, for example (the parentheses are not always required) where we are only interested in *Int* values:

```
xs match {  
  case Nil =>  
  case (h: Int) :: t => println(h); print(t)  
  case _ =>  
}
```

- arbitrarily-nested patterns, for example:

```
xs match {  
  case Nil =>  
  case h :: k :: t => println(h+k); print(t)  
  case _ =>  
}
```

- guarded patterns, for example:

```
xs match {  
  case Nil =>  
  case h :: t if h > 0 => println(h); print(t)  
  case _ => println("head was not positive")  
}
```


Wrap-up

- We will come across patterns again when we talk about for comprehensions. But for now, you can mostly think about them as being part of a *match* clause.
- Note that you can see the details of my examples in running code in the REPO. Just look for *PatternExample*.