

Worksheet: Material balances in liquid-liquid extraction


Name(s) _____

This experiment applies material balances to a liquid-liquid extraction process in which water as a solvent contacts an acetic acid/chloroform mixture in a steady-state counter flow experiment. Because acetic acid is much more soluble in water, it is extracted from the chloroform organic phase into the aqueous phase.

Student learning objectives

1. Be able to apply mass balances to a three-component system.
2. Be able to use phase equilibrium data to partially generate the phase envelope on a ternary phase diagram.
3. Be able to explain what happens during liquid-liquid extraction.

Equipment



The system consists of three stages where the aqueous phase contacts the organic phase in counter-current flow. The phases leaving each stage are in phase equilibrium.

S = solvent

F = feed

E = Extract

R = Raffinate

The water solvent extracts acetic acid solute from the organic feed (acetic acid, chloroform, and a small concentration of water). The raffinate phase is enriched in chloroform because acetic acid is removed from it.

Questions to answer before starting the experiment

How many independent mass balances can you write for each stage of this liquid-liquid extraction? Explain.

The two phases contact each other in a counter-current flow. What might be the advantage of counter-current flow over co-current flow?

Would you expect the feed stream (acetic acid, chloroform, water) to increase or decrease its flow rate as it flows down the extraction system? Why?

Would you expect the water solvent stream system to increase or decrease its flow rate as it flows up through the extraction? Why?

Before starting

The solvent only contains water. The mass fractions of the three components in the feed are:

Component	Mass fraction
Acetic acid	0.52
Chloroform	0.43
Water	0.05

Procedure:

1. Turn on the solvent pump and open the solvent valve to start solvent flow into the extraction system. After a time delay the feed pump will start and the feed valve will open.

The solvent valve is open in this position



2. Note that the intensity of the color in the flow streams is proportional to the concentration of acetic acid in that stream.

3. Allow time for the system to reach steady state and liquid to accumulate in the extract and raffinate tanks, and then determine the flow rates of the two feed streams and the two exit streams by recording the change in the volumes of each of the four tanks while recording the time elapsed with your phone. Record values in the Table below. You may not be able to measure all four flow rates in one experiment. To increase the accuracy of your volume measurements, zoom with the scroll wheel and drag your mouse to move the image.

4. Determine fluid densities in the four tanks by moving your mouse over the tank with fluid in it.

5. Calculate volumetric and mass flow rates and enter them in the Table.

Tank	Elapsed Time (s)	Volume Change (mL)	Density (g/mL)	Volumetric flow rate (mL/s)	Mass flow rate (g/s)
Feed					
Solvent					
Extract					
Raffinate					

6. Repeat these measurements

Tank	Elapsed Time (s)	Volume Change (mL)	Density (g/mL)	Volumetric flow rate (mL/s)	Mass flow rate (g/s)
Feed					
Solvent					
Extract					
Raffinate					

7. Calculate average mass flow rates

Tank	Average mass flow rate (g/s)
Feed	
Solvent	
Extract	
Raffinate	

Measure the compositions of each of the streams by moving your mouse over the stream.

		Mass fractions		
Stream		Acetic acid	Chloroform	Water
E ₁				
E ₂				
E ₃				
R ₁				
R ₂				
R ₃				

Data Analysis:

Do an overall mass balance on the system. That is, determine the total mass of the feed tank and the solvent tank at the beginning and determine the total mass in the four tanks after most of the feed tank contents have been fed to the system.

Total mass at beginning: _____

Total mass when stopped feed: _____

Percent difference: _____

Do an overall mass balance for each species

Total mass of acetic acid at beginning: _____

Total mass of acetic when stopped feed: _____

Percent difference: _____

Total mass of chloroform at beginning: _____

Total mass of chloroform when stopped feed: _____

Percent difference: _____

Total mass of water at beginning: _____


Total mass of water when stopped feed: _____

Percent difference: _____


Carry out component mass balance for each stage to determine the flow rates of R_1 , R_2 , E_2 , and E_3

Stream	Mass flow rate (g/s)
R ₁	
R ₂	
E ₂	
E ₃	


Plot the flow rates of the streams in each direction and explain the trends.




Plot the compositions of each component for the feed flow stream and explain the behavior.



Plot the compositions of each component for the solvent flow stream and explain the behavior.



The streams leaving each stage (e.g., E_2 and R_2) are in equilibrium. This means tie lines connect the two composition points that are in equilibrium on a ternary phase diagram. The two points are on the phase envelope. From the exit compositions from the three stages, locate the six points on the ternary phase diagram below and draw as much of the phase envelope as you can.



Questions to answer

1. Where might these measurement have errors?
2. What safety precautions would you take to conduct this experiment in the laboratory?