

```
1: import even_samples
2: import cifar_costf
3: import numpy as np
4: import keras
5:
6: a = {
7:     "best_params": [
8:         913.957430854217,      # minibatch
9:         0.0015701252586464568, # alpha
10:        0.6575874719325618,    # beta_1
11:        0.932720394784433,     # beta_2
12:        81.32088463431727      # num_epochs
13:    ],
14:     "best_cost": 1.8064099550247192
15: }
16:
17:
18: b = {
19:     "best_params": [
20:         534.4469442210992,      # minibatch
21:         0.0006231460669478447, # alpha
22:         0.7991814790199026,    # beta_1
23:         0.9007039736299371,    # beta_2
24:         44.05592177501114      # num_epochs
25:    ],
26:     "best_cost": 1.7486121654510498
27: }
28:
29: b_mod = {
30:     "best_params": [
31:         742.2428227795274,      # minibatch
32:         0.0009079703308546692, # alpha
33:         0.8199336231638713,    # beta_1
34:         0.6038924210437369,    # beta_2
35:         64.06011278706069      # num_epochs
36:    ],
37:     "best_cost": 1.7933474779129028
38: }
39:
40: versions = [("a", a), ("b", b), ("b_mod", b_mod)]
41:
42: (x_train, y_train), (x_test, y_test) = even_samples.even_sample_categories(50000)
43: with open("final-check.txt", "w") as f:
44:     for name, version in versions:
45:         params = np.array(version["best_params"])
46:         cost = cifar_costf.costf(params, (x_train[:1000], y_train[:1000]), (x_train[1000:], y_train[1000:]))
47:         version["test_cost"] = cost
48:         version["name"] = name
49:         print(version, file=f)
```