



PAN9 CYBERSECURITY ESSENTIALS

Lab 10: Using Dynamic Block Lists

Document Version: 2020-06-08

Copyright © 2020 Network Development Group, Inc.
www.netdevgroup.com

NETLAB Academy Edition, NETLAB Professional Edition, and NETLAB+ are registered trademarks of Network Development Group, Inc.

Palo Alto Networks and the Palo Alto Networks logo are trademarks or registered trademarks of Palo Alto Networks, Inc.

Contents

Introduction	3
Objective	3
Lab Topology	4
Lab Settings	5
10 Lab: Using Dynamic Block Lists	6
10.0 Load Lab Configuration	6
10.1 Create a List of Blocked Sites and Upload to DMZ Server	11
10.2 Create an External Dynamic List Object	14
10.3 Create a Security Policy	18
10.4 Commit and Test	21

Introduction


In this lab, you will configure a security policy to use a dynamic block list.

Objective

In this lab, you will perform the following tasks:

-) Create a List of Blocked Sites and Upload to DMZ Server
-) Create an External Dynamic List Object
-) Commit and Test

Lab Topology



Lab Settings

The information in the table below will be needed in order to complete the lab. The task sections below provide details on the use of this information.


Virtual Machine	IP Address	Account (if needed)	Password (if needed)
Client	192.168.1.20	lab-user	Train1ng\$
DMZ	192.168.50.10	root	Pal0Alt0
Firewall	192.168.1.254	admin	Train1ng\$

10 Lab: Using Dynamic Block Lists

10.0 Load Lab Configuration

In this section, you will load the Firewall configuration file.

1. Click on the **Client** tab to access the Client PC.




2. Log in to the Client PC as username **lab-user**, password **Train1ng\$**.
3. Double-click the **Chromium Web Browser** icon located on the desktop.



4. In the *Chromium address* field, type **https://192.168.1.254** and press **Enter**.




5. You will see a “Your connection is not private” message. Click on the **ADVANCED** link.






If you experience the “Unable to connect” or “502 Bad Gateway” message while attempting to connect to the specified IP above, please wait an additional 1-3 minutes for the Firewall to fully initialize. Refresh the page to continue.


6. Click on **Proceed to 192.168.1.254 (unsafe)**.




7. Log in to the Firewall web interface as username **admin**, password **Train1ng\$**.



8. In the web interface, navigate to **Device > Setup > Operations** and click on **Load named configuration snapshot** underneath the *Configuration Management* section.




9. In the *Load Named Configuration* window, select **pan9-ce-lab-10.xml** from the *Name* dropdown box and click **OK**.




The dialog box titled "Load Named Configuration" has a "Name" dropdown menu with "pan9-ce-lab-10.xml" selected. Below it is a "Decryption Key" field with four asterisks. There are two checkboxes: "Load Shared Objects" and "Load Shared Policies", both of which are unchecked. To the right, there is a checkbox labeled "Regenerate Rule UUIDs for selected named configuration", which is also unchecked. At the bottom right, there are "OK" and "Cancel" buttons.

10. In the *Loading Configuration* window, a message will show *Configuration is being loaded*. Please check the Task Manager for its status. You should reload the page when the task is completed. Click **Close** to continue.




The "Loading Configuration" message box contains the text: "Configuration is being loaded. Please check the Task Manager for its status. You should reload the page when the task is completed." At the bottom center, there is a "Close" button.

11. Click the **Tasks** icon located at the bottom-right of the web interface.



12. In the *Task Manager – All Tasks* window, verify the *Load* type has successfully completed. Click **Close**.




The "Task Manager - All Tasks" window displays a table with 5 columns: Type, Status, Start Time, Messages, and Action. The first row, "Load", is highlighted with a red box and shows a status of "Completed" and a start time of "03/06/20 12:55:38". Below it are several rows for "System Logs", "Config Logs", "Data Logs", and "Report", all with a status of "Completed". At the bottom, there is a "Show" dropdown menu set to "All Tasks", a "Clear Commit Queue" button, and a "Close" button.

Type	Status	Start Time	Messages	Action
Load	Completed	03/06/20 12:55:38		
System Logs	Completed	03/06/20 12:50:18		
Config Logs	Completed	03/06/20 12:50:18		
Data Logs	Completed	03/06/20 12:50:18		
Report	Completed	03/06/20 12:50:18		
Config Logs	Completed	03/06/20 12:45:19		
System Logs	Completed	03/06/20 12:45:19		
Report	Completed	03/06/20 12:45:19		
Auto Commit	Completed	03/05/20 21:50:01		

13. Click the **Commit** link located at the top-right of the web interface.



14. In the *Commit* window, click **Commit** to proceed with committing the changes.



15. When the commit operation successfully completes, click **Close** to continue.



The commit process takes changes made to the Firewall and copies them to the running configuration, which will activate all configuration changes since the last commit.


10.1 Create a List of Blocked Sites and Upload to DMZ Server

In this section, you will create a text file with a list of blocked sites.


1. Minimize **Chromium** in the upper-right.




2. Double-click the **Text Editor** icon located on the desktop.




3. In the *Text Editor* window, type **yahoo.com** and **google.com**, each on a separate line.



4. In the *Text Editor* window, click on **File > Save As....**



- In the *Save As* window, click on **Desktop** on the left. Then, type `block-list.txt` in the *Name* field. Next, click the **Save** button.



You will upload this file to the DMZ server. This file will be used by the Firewall to block the sites you listed.


- Click the **X** in the upper-right to close the *Text Editor*.




- Double-click the **FileZilla** icon located on the desktop.



- In the *FileZilla* window, type `sftp://192.168.50.10` for the *Host*, type `root` for the *Username*, type `pa10A1t0` for the *Password*. Lastly, type `22` for the *Port*. Then, click the **Quickconnect** button.



9. In the *Remember passwords?* window, select **Do not save passwords** and click **OK**.



Remember passwords?

Would you like FileZilla to remember passwords?

When allowing FileZilla to remember passwords, you can reconnect without having to re-enter a password after restarting FileZilla.

☐ Save passwords

☒ **Do not save passwords**

☐ Save passwords protected by a master password

Master password:


Repeat password:

A lost master password cannot be recovered! Please thoroughly memorize your password.

10. In the *FileZilla* window, from the dropdown menu, select **/<root>**, **home**, **lab-user**, and finally **Desktop**. Verify **/home/lab-user/Desktop/** is correct in the *Local site* field.




Local site:



Local site:

- ▼ /
- ▼ home
- ▼ lab-user
- ▶ Desktop


11. In the *Remote site* window, navigate to **/var/www/html**. Lastly, verify **/var/www/html** is in the *Name* field.



Remote site:

- run
- spool
- tmp
- ▼ www
 - cgi-bin
 - html
 - yp

12. Right-click on the **block-list.txt** file in the *Filename* tree and lastly, click **Upload**.



13. Click on the **Successful transfers** tab and verify the transfers were successfully downloaded.

Server/Local file	Director	Remote file	Size	Priority	Time
sftp://lab-user@192.1...					
/home/lab-user/Des...	-->	/home/lab-user/block-list...	21 B	Normal	03/18/2020 05:20:2...
Queued files Failed transfers Successful transfers (3)					

14. Minimize **FileZilla** in the upper-right.




10.2 Create an External Dynamic List Object

In this section, you will create an External Dynamic List. An External Dynamic List is a text file, such as the **block-list.txt** file you created, that is hosted on an external web server so that the Firewall can import objects such as IP addresses, URLs, and domains, to enforce policy.


1. Click on the **Chromium** icon from the taskbar to maximize the Firewall management interface.



2. Navigate to **Objects > External Dynamic Lists > Add**.



3. In the *External Dynamic Lists* window, type **block-list** for the *Name* field. Then, select **URL List** in the *Type* dropdown. Next, type **http://192.168.50.10/block-list.txt** in the *Source* field. Then, select **Five Minute** on the *Repeat* dropdown. Finally, click the **OK** button.





The IP address, **192.168.50.10**, refers to the DMZ server you uploaded the file to earlier. If the list is modified, the Firewall dynamically imports the list at the configured interval, in this case **Five Minutes**, and enforces policy without the need to make a configuration change or a commit on the Firewall. This is beneficial as the list could be changing by an administrator manually or, in some cases, an automated script.

If you click **Test Source URL** in this step it will fail. You need to finish the External Dynamic List by clicking ok and proceeding to the next step.

4. Click on the **block-list** object.

Name	Location	Description	Source	Certificate Profile	Frequency
Dynamic IP Lists					
<input type="checkbox"/> Palo Alto Networks - High risk IP addresses	High risk IP	Predefined	High risk IP addresses, shared IP addresses that have recently been featured in threat activity, sometimes distributed by high-trust organizations, however Palo Alto Networks does not have direct evidence of maliciousness	Palo Alto Networks - High risk IP addresses	
<input type="checkbox"/> Palo Alto Networks - Known malicious IP addresses		Predefined	Malicious IP addresses that are currently used almost exclusively by malicious actors to deliver malicious content, command-and-control, or for launching various attacks	Palo Alto Networks - Known malicious IP addresses	
Dynamic URL Lists					
<input checked="" type="checkbox"/> block-list			http://192.168.50.10/block-list.txt	None	Five Minute

5. In the *External Dynamic Lists* window, click on the **Test Source URL** button to test the URL source.

External Dynamic Lists

Name: block-list

Create List

List Entries And Exceptions

Type: URL List

Description:

Source: http://192.168.50.10/block-list.txt

Server Authentication

Certificate Profile: None


Repeat: Five Minute

Test Source URL

OK


Cancel

6. In the *Test Source URL* window, click the **Close** button. Verify the **Source URL is accessible**.



This is an important step to verify the Firewall can reach the URL. If the web server is unreachable, the Firewall will use the last successfully retrieved list for enforcing policy until the connection is restored with the web server.


7. In the *External Dynamic Lists* window, click the **OK** button.




10.3 Create a Security Policy

In this section, you will create a new Security Policy that utilizes the External Dynamic List you created, to filter traffic.


1. Navigate to **Policies > Security > Add**.




2. In the *Security Policy Rule* window, type **Block-List** in the *Name* field.




3. In the *Security Policy Rule* window, click the **Source** tab. Then, click the **Add** button in the *Source Zone* section. Next, select **inside** in the *Source Zone* column.




4. In the *Security Policy Rule* window, click the **Destination** tab. Then, click the **Add** button in the *Destination Zone* section. Next, select **outside** in the *Destination Zone* column.




5. In the *Security Policy Rule* window, click the **Service/URL Category** tab. Then, click the **Add** button in the *URL Category* section. Next, select **block-list** under the *External Dynamic Lists*.



6. In the *Security Policy Rule* window, click the **Actions** tab. Then, select **Deny** in the *Action* dropdown. Next, click the **OK** button.



- Click on **3** to select the *Block-List* rule. Then, click the **Move** button at the bottom. Next, select **Move Top**.




The order of the Security Policies is very important as traffic is matched in order from top to bottom. If **Block-List** were not moved to the top, traffic would have matched the **Allow-Inside-Out** policy first, allowing traffic listed in the **Block-List** to pass.


10.4 Commit and Test

In this section, you will commit your changes to the Firewall and test traffic matching the **Block-List** Security Policy.

- Click the **Commit** link located at the top-right of the web interface.



- In the *Commit* window, click **Commit** to proceed with committing the changes.




- When the commit operation successfully completes, click **Close** to continue.




- Open *Firefox* from the taskbar.



- In the address bar, type `http://google.com` and press **Enter**.




6. In the address bar, type `http://yahoo.com` and press **Enter**.



Due to the Dynamic Block Lists, you cannot get to **google.com** or **yahoo.com**.

7. In the address bar, type `https://www.facebook.com` and press **Enter**.



Here, the traffic did not match the Security Policy **Block-List**. Instead, it matched the next policy, **Allow-Inside-Out**.

8. The lab is now complete; you may end the reservation.