

KEEBOX

Authentication Architecture Specification

Registration, login, PIN security, OTP verification, recovery, JWT sessions, and local authentication

Specification version 1.0 | 03 September 2026

Core rule: account entry is protected by backend authentication, while routine app unlocking is local and remains fully usable without internet access.

This document consolidates the agreed Keebox authentication design. It is intended to act as the implementation contract for the Flutter client and Django Ninja backend.

1. Executive Summary

Keebox uses four distinct authentication mechanisms. Each mechanism has a separate responsibility and must not be conflated with the others.

Mechanism	Credential / Input	Verification Location	Primary Purpose
Account authentication	Email + password	Backend	Prove ownership of the Keebox account.
OTP authentication	OTP challenge ID + OTP code	Backend	Verify email access during registration and recovery flows.
Server PIN verification	PIN code	Backend	Complete login and manage the account-wide PIN.
Local PIN authentication	PIN code	Flutter device only	Unlock an already provisioned Keebox installation without internet.

The normal login process contains no OTP stage. It consists only of email/password authentication followed by server PIN verification. OTP is used for registration and recovery operations.

Password, PIN, and KBKey are independent security entities. Changing or resetting a password or PIN must never rotate or invalidate the user's KBKey.

2. Normative Authentication Decisions

- Registration starts with first name, last name, email, and password. The PIN is created only after registration OTP verification.
- Registration OTP verification uses a shared OTPChallenge implementation also used by password recovery and PIN recovery.
- Successful registration is completed only after /create-pin succeeds.
- Normal login is email + password followed by PIN verification. Login does not use OTP.
- A Login Challenge ID tracks the multi-stage login attempt between password verification and PIN verification.
- JWT access and refresh tokens are issued only after the complete registration or login flow succeeds.
- The final successful registration/login response includes first name, last name, email, KBKey, access token, and refresh token.
- The raw PIN is never stored in the backend database or device secure storage.
- The backend stores a slow password-hash representation of the PIN, additionally protected with a server-side PIN pepper.
- Flutter stores a local PIN verifier and related parameters in secure storage, not the raw PIN.
- Routine app unlocking uses the local verifier only and does not contact the backend.
- Forgot-password and forgot-PIN are separate recovery flows and both use the shared OTP subsystem.

3. Terminology

Term	Definition
Registration Challenge	Tracks one incomplete account-registration process from initial submission through OTP verification and PIN creation.
Login Challenge	Tracks one login process after password verification and before PIN verification completes the session.

Term	Definition
OTP Challenge	One-time email-code challenge used by registration and recovery flows.
Recovery Challenge	Tracks a password-reset or PIN-reset process independently from the OTP challenge used to authorize it.
KBKey	The user's stable Keebox Key. Returned only after full registration/login and used by the client to encrypt/decrypt KBoxes.
KMKey	The Keebox Master Key held by the server and used to protect stored KBKeys.
Local PIN verifier	A one-way Argon2id-derived representation of the PIN used to unlock the app locally.

4. Authentication Purpose Taxonomy

Keebox should define a small, stable set of high-level authentication purposes. These values describe why a challenge exists; they are not endpoint names and they are not individual stages such as PIN creation or OTP verification.

Constant	Stored Value	Meaning	Used By
REGISTRATION	registration	New-account registration and registration email verification.	RegistrationChallenge, OTPChallenge
LOGIN	login	Normal account login: email/password followed by PIN.	LoginChallenge
PASSWORD_RESET	password_reset	Recovery of a forgotten account password.	RecoveryChallenge, OTPChallenge
PIN_RESET	pin_reset	Recovery of a forgotten account/lock-screen PIN.	RecoveryChallenge, OTPChallenge

```
from django.db import models

class AuthenticationPurpose(models.TextChoices):
    REGISTRATION = "registration", "Registration"
    LOGIN = "login", "Login"
    PASSWORD_RESET = "password_reset", "Password reset"
    PIN_RESET = "pin_reset", "PIN reset"
```

4.1 Purpose restrictions by challenge type

A single system-wide TextChoices enum can be reused, but individual models must validate the subset that makes sense for them.

Model	Allowed Purpose Values
RegistrationChallenge	REGISTRATION only; the field can even be omitted because the model itself implies the purpose.
LoginChallenge	LOGIN only; the field can be omitted for the same reason.
RecoveryChallenge	PASSWORD_RESET or PIN_RESET.
OTPChallenge	REGISTRATION, PASSWORD_RESET, or PIN_RESET. LOGIN is explicitly invalid because normal login has no OTP stage.

PIN_CREATE, PIN_VERIFY, PIN_UPDATE, LOCAL_UNLOCK, and OTP_VERIFY should not be added as AuthenticationPurpose values. They are operations or stages inside a higher-level flow, not reasons for creating an authentication challenge.

5. State Taxonomy

Purpose identifies why a challenge exists. Status identifies how far that challenge has progressed. Keeping these concepts separate prevents ambiguous workflow logic.

Challenge	Recommended Status Choices
RegistrationChallenge	OTP_PENDING, OTP_VERIFIED, COMPLETED, EXPIRED, CANCELLED

Challenge	Recommended Status Choices
LoginChallenge	PASSWORD_VERIFIED, COMPLETED, EXPIRED, LOCKED
RecoveryChallenge	OTP_PENDING, OTP_VERIFIED, COMPLETED, EXPIRED, CANCELLED
OTPChallenge	PENDING, VERIFIED, EXPIRED, LOCKED, CONSUMED

```

class RegistrationStatus(models.TextChoices):
    OTP_PENDING = "otp_pending", "OTP pending"
    OTP_VERIFIED = "otp_verified", "OTP verified"
    COMPLETED = "completed", "Completed"
    EXPIRED = "expired", "Expired"
    CANCELLED = "cancelled", "Cancelled"

class LoginStatus(models.TextChoices):
    PASSWORD_VERIFIED = "password_verified", "Password verified"
    COMPLETED = "completed", "Completed"
    EXPIRED = "expired", "Expired"
    LOCKED = "locked", "Locked"

class RecoveryStatus(models.TextChoices):
    OTP_PENDING = "otp_pending", "OTP pending"
    OTP_VERIFIED = "otp_verified", "OTP verified"
    COMPLETED = "completed", "Completed"
    EXPIRED = "expired", "Expired"
    CANCELLED = "cancelled", "Cancelled"

```


6. Registration Architecture

6.1 Input

Field	Requirement
first_name	Required.
last_name	Required.
email	Required; normalized and unique.
password	Required; validated by the server password policy.

The PIN is intentionally not part of /register. It is created only after the email OTP has been verified.

6.2 Sequence



6.3 /register response

```
{
  "registration_challenge_id": "<opaque UUID>",
  "otp_challenge_id": "<opaque UUID>",
  "email": "user@example.com",
  "otp_expires_at": "..."
}
```

The response does not contain JWT tokens or KBKey because the account is not fully registered yet.

6.4 Shared /verify-otp behavior during registration

The client submits only the OTP challenge ID and code. The OTP record already knows its purpose and owning registration context. A successful verification marks the OTP consumed and transitions the related RegistrationChallenge to OTP_VERIFIED.

```
POST /verify-otp
{
  "otp_challenge_id": "...",
  "otp_code": "..."
}
```

6.5 /create-pin and registration completion

/create-pin must require the Registration Challenge ID. It must not accept an email address as sufficient proof that registration OTP verification happened.

- Confirm the registration challenge exists and has not expired.
- Require status OTP_VERIFIED.
- Validate the PIN against the centralized PIN policy.
- Hash the PIN using the server PIN hashing strategy.
- Generate the user's one-time stable KBKey.
- Encrypt/protect the KBKey using KMKey before database storage.
- Mark registration complete.
- Issue access and refresh JWTs.
- Return the final authenticated response.

```
{
  "first_name": "Nelson",
  "last_name": "...",
  "email": "nelson@example.com",
  "kbkey": "KBK-.....",
  "access_token": "...",
  "refresh_token": "..."
}
```

7. Login Architecture

Normal Keebox login does not use OTP. It consists of email/password verification followed by PIN verification.

7.1 Login initiation

```
POST /login
{
  "email": "nelson@example.com",
  "password": "..."
```

If the credentials are valid, the backend creates a LoginChallenge. The challenge represents the fact that the account password has been verified but the PIN requirement is still outstanding.

```
{
  "login_challenge_id": "<opaque UUID>",
  "expires_at": "..."
```

7.2 Why the Login Challenge ID exists

- It binds PIN verification to a specific password-authenticated login attempt.
- It prevents /verify-pin from accepting an email + PIN as a standalone login mechanism.
- It gives the backend an expiration window for completing the second stage.
- It provides a location for failed PIN attempt counters and temporary login lock state.
- It avoids issuing normal JWT credentials before the entire login process is complete.

7.3 PIN completion

```
POST /verify-pin
{
  "login_challenge_id": "...",
  "pin_code": "..."
```

The backend verifies the challenge state and submitted PIN. On success it marks the login challenge complete and returns the same final authenticated payload used after successful registration.

```
Email + password
  |
  v
LoginChallenge(PASSWORD_VERIFIED)
  |
  v
PIN verification
  |
  v
LoginChallenge(COMPLETED)
  |
  v
first_name + last_name + email + KBKey + access_token + refresh_token
```

8. PIN Management Architecture

The server endpoints /create-pin, /verify-pin, and /update-pin are PIN management operations. They do not replace local PIN authentication and must never become a network dependency for routine app unlocking.

Endpoint	Primary Context	Authorization Context
/create-pin	Initial registration only.	RegistrationChallenge in OTP_VERIFIED state.
/verify-pin	Complete normal login.	LoginChallenge in PASSWORD_VERIFIED state.
/update-pin	User intentionally changes a known PIN.	Authenticated JWT + current PIN.

8.1 PIN update

```

POST /update-pin
Authorization: Bearer <access token>

{
  "current_pin": "...",
  "new_pin": "..."
}

```

A successful PIN change updates the server verifier and the current device local verifier. KBKey is unchanged and no KBox re-encryption is required.

PIN changes should require network access. Changing only the local verifier while offline would desynchronize the local PIN from the server PIN used during the next login.

9. Server-Side PIN Protection

The server never stores the raw PIN. Because a PIN has a much smaller search space than a normal password, the stored verifier must use a deliberately expensive password-hashing algorithm and a server-side secret pepper.

```

PIN
+
KEEBOX_PIN_PEPPER
|
v
peppered PIN material
|
v
Argon2id + random salt
|
v
stored pin_hash

```

KEEBOX_PIN_PEPPER is a separate server secret. It must not be the KMKey, Django SECRET_KEY, JWT signing secret, or any other unrelated key.

9.1 Reference backend helper

```

import hashlib
import hmac
from django.conf import settings
from django.contrib.auth.hashers import make_password, check_password

def _pepper_pin(pin: str) -> str:
    return hmac.new(
        key=settings.KEEBOX_PIN_PEPPER.encode("utf-8"),
        msg=pin.encode("utf-8"),
        digestmod=hashlib.sha256,
    ).hexdigest()

def hash_pin(pin: str) -> str:
    return make_password(_pepper_pin(pin), hasher="argon2")

def verify_pin(pin: str, encoded_hash: str) -> bool:
    return check_password(_pepper_pin(pin), encoded_hash)

```

Django should be configured with Argon2PasswordHasher support. Account passwords should continue to use Django's normal set_password/check_password API rather than custom hashing logic.

9.2 PIN rate limits and logout

- Limit failed /verify-pin attempts per LoginChallenge.
- Rate-limit requests by account and network source where practical.
- After the configured threshold, temporarily lock or terminate the login challenge.
- Never expose whether a failure came from a malformed challenge, wrong PIN, or account state in a way that assists attackers.
- Local PIN verification should also add increasing delay or local logout after repeated failures.

10. Local PIN Authentication

After a successful registration or login, Flutter provisions local authentication. From that point onward, opening Keebox does not require the server simply to verify the PIN.

```

Normal app opening
|
v

```

```

Show local lock screen
  |
  v
User enters PIN
  |
  v
Derive candidate local verifier
  |
  v
Compare locally
  |
  +-- correct --> unlock Keebox
  |
  +-- wrong ----> deny + throttle

```

No HTTP request is required.

10.1 Local secure-storage contents

Item	Storage Recommendation	Notes
Local PIN verifier	flutter_secure_storage	Store only the derived verifier/hash, never the raw PIN.
PIN salt	flutter_secure_storage	Random per-device salt used for local Argon2id derivation.
PIN parameters	flutter_secure_storage or app constants	Memory, iterations, parallelism, version.
KBKey	flutter_secure_storage	Protect locally after successful registration/login.
Refresh token	flutter_secure_storage	Long-lived session secret.
Access token	Memory preferred; secure storage if persistence is required	Short-lived JWT.

10.2 Local verifier reference implementation

```

import 'dart:convert';
import 'dart:math';
import 'package:cryptography/cryptography.dart';
import 'package:flutter_secure_storage/flutter_secure_storage.dart';

final _storage = FlutterSecureStorage();
final _argon2 = Argon2id(
  memory: 19 * 1024,
  parallelism: 1,
  iterations: 2,
  hashLength: 32,
);

Future<List<int>> deriveLocalPinVerifier(
  String pin,
  List<int> salt,
) async {
  final key = await _argon2.deriveKeyFromPassword(
    password: pin,
    nonce: salt,
  );
  return key.extractBytes();
}

```

The parameter values above are implementation examples rather than immutable protocol constants. Benchmark them on the Android devices Keebox intends to support and version the local verifier parameters so they can be upgraded later.

11. Shared OTP Subsystem

Keebox has one OTP implementation. It is reused by registration, forgot-password, and forgot-PIN. Normal login does not use it.

Purpose	OTP Used?	Parent Context
REGISTRATION	Yes	RegistrationChallenge
LOGIN	No	LoginChallenge
PASSWORD_RESET	Yes	RecoveryChallenge
PIN_RESET	Yes	RecoveryChallenge

11.1 OTPChallenge logical fields

Field	Purpose
id	Opaque OTP challenge identifier.
purpose	AuthenticationPurpose: REGISTRATION, PASSWORD_RESET, or PIN_RESET.
user_id / email	Identity the challenge applies to.
context_challenge_id	RegistrationChallenge or RecoveryChallenge identifier associated with the OTP.
code_hash	One-way hash of the OTP; raw OTP is not persisted.
expires_at	Absolute expiry time.
attempt_count	Failed verification attempts.
resend_count	Number of resend operations.
last_sent_at	Used to enforce resend cooldown.
status	PENDING, VERIFIED/CONSUMED, EXPIRED, or LOCKED.
consumed_at	Time the challenge became unusable after successful verification.

11.2 /verify-otp

```
POST /verify-otp
{
  "otp_challenge_id": "...",
  "otp_code": "..."
}
```

- Load the OTP challenge.
- Reject expired, locked, or consumed challenges.
- Compare the submitted code with the stored one-way verifier.
- Increment attempt_count on failure and lock after the configured maximum.
- On success, consume the OTP so it cannot be reused.
- Advance the associated RegistrationChallenge or RecoveryChallenge to OTP_VERIFIED.

11.3 /resend-otp

The client submits the existing OTP Challenge ID. If the challenge is eligible for resend, the server generates a new OTP, replaces the old OTP verifier, resets the code expiry, increments resend_count, sends the new email, and keeps the same challenge ID. The previously sent OTP immediately becomes invalid.

```
POST /resend-otp
{
  "otp_challenge_id": "...
}

Response:
{
  "otp_challenge_id": "...",
  "otp_expires_at": "...",
  "resend_available_at": "...
}
```

12. Forgotten Account Password

Password recovery proves control of the registered email address and then allows the user to choose a new account password. KBKey and PIN are not modified.

```
POST /forgot-password
email
|
v
Create RecoveryChallenge(PASSWORD_RESET)
|
v
Create OTPChallenge(PASSWORD_RESET)
|
v
Send OTP
|
v
Return recovery_challenge_id + otp_challenge_id
|
v
POST /verify-otp
|
v
RecoveryChallenge = OTP_VERIFIED
|
v
POST /reset-password
recovery_challenge_id + new_password
|
v
Replace password hash
|
v
RecoveryChallenge = COMPLETED
|
v
Return to normal login
```

12.1 /forgot-password

```
POST /forgot-password
{
  "email": "nelson@example.com"
}
```

For anti-enumeration, the public response should remain generic when practical. Internally, an OTP is only sent when the account is eligible for recovery.

12.2 /reset-password

```
POST /reset-password
{
  "recovery_challenge_id": "...",
  "new_password": "..."
}
```

The recovery challenge must be PASSWORD_RESET, OTP_VERIFIED, unexpired, and unused. The new password is stored using Django `set_password()`. The endpoint returns success but does not issue a normal logged-in JWT session. The user proceeds through `/login` and `/verify-pin`.

Password reset does not rotate KBKey. Previously encrypted KCredentialBoxes and KNoteBoxes remain decryptable with the same KBKey.

13. Forgotten Lock-Screen PIN

A forgotten PIN cannot be recovered because the raw PIN is never stored. Keebox replaces it only after strong account verification.

The agreed recovery proof is account password plus email OTP.

```

POST /forgot-pin
email + password
|
v
Verify account password
|
v
Create RecoveryChallenge(PIN_RESET)
|
v
Create OTPChallenge(PIN_RESET)
|
v
Send OTP
|
v
POST /verify-otp
|
v
RecoveryChallenge = OTP_VERIFIED
|
v
POST /reset-pin
recovery_challenge_id + new_pin
|
v
Hash/store new PIN
|
v
Increment pin_version
|
v
Update local PIN verifier on current device

```

13.1 /forgot-pin

```

POST /forgot-pin
{
  "email": "nelson@example.com",
  "password": "..."
}

```

13.2 /reset-pin

```

POST /reset-pin
{
  "recovery_challenge_id": "...",
  "new_pin": "..."
}

```

If recovery was started from the local lock screen on an already provisioned installation, Flutter can create the new local PIN verifier immediately after the server accepts the new PIN. On a fresh installation or logged-out device, the user completes normal login after the reset.

PIN reset does not rotate KBKey and does not require KBox re-encryption.

14. If Both Password and PIN Are Forgotten

1. Complete forgot-password using email OTP and choose a new password.
2. Start forgot-PIN using the newly established password.
3. Verify the PIN-reset OTP and choose a new PIN.
4. Complete normal login with email + new password, then verify the new PIN.

The user's KBKey remains unchanged throughout the entire sequence, so backed-up KBoxes remain recoverable.

15. JWT Session Architecture

Keebox uses django-ninja-jwt for normal authenticated API sessions. Access and refresh tokens are issued only after the full authentication flow is complete.

Point in Flow	Issue Access/Refresh JWTs?
After /register	No
After registration /verify-otp	No
After registration /create-pin	Yes
After /login email/password validation	No
After login /verify-pin	Yes
After /reset-password	No; return to normal login
After /reset-pin	No new normal session unless the endpoint is already called in an authenticated PIN-change context

15.1 Final authentication response

```
{
  "user": {
    "first_name": "Nelson",
    "last_name": "...",
    "email": "nelson@example.com"
  },
  "kbkey": "KBK-.....",
  "access_token": "...",
  "refresh_token": "..."
}
```

The token refresh endpoint should refresh authentication tokens only. It should not re-send KBKey on every refresh. If the client no longer has its locally protected KBKey, a fresh login is the clean re-provisioning path.

16. Proposed Logical Data Models

These are logical models. Their exact physical representation can be adapted to the project's MongoDB integration, but the state and relationships should remain equivalent.

16.1 User authentication fields

Field	Notes
id	Stable user identifier.
first_name / last_name	Profile identity returned after successful authentication.
email	Normalized unique login identifier.
password	Django-managed password hash.
pin_hash	Argon2-based server PIN verifier; nullable until registration PIN creation.
pin_version	Monotonically increments whenever PIN is updated or reset.
encrypted_kbkey	KBKey encrypted/protected by KMKey.
email_verified	Registration email verification state.
registration_completed	True only after PIN creation and KBKey provisioning complete.
token_version	Recommended session-generation counter used to invalidate old JWT sessions after sensitive recovery.

16.2 Challenge models

```

class RegistrationChallenge:
    id: UUID
    user_id: UUID
    status: RegistrationStatus
    expires_at: datetime
    completed_at: datetime | None

class LoginChallenge:
    id: UUID
    user_id: UUID
    status: LoginStatus
    failed_pin_attempts: int
    expires_at: datetime
    completed_at: datetime | None

class RecoveryChallenge:
    id: UUID
    user_id: UUID
    purpose: AuthenticationPurpose # PASSWORD_RESET | PIN_RESET
    status: RecoveryStatus
    expires_at: datetime
    completed_at: datetime | None

class OTPChallenge:
    id: UUID
    user_id: UUID | None
    email: str
    purpose: AuthenticationPurpose # excludes LOGIN
    context_challenge_id: UUID
    code_hash: str
    status: OTPStatus
    attempt_count: int
    resend_count: int
    last_sent_at: datetime
    expires_at: datetime
    consumed_at: datetime | None

```

17. Endpoint Contract Summary

Method	Endpoint	Request	Successful Result
POST	/register	first_name, last_name, email, password	registration_challenge_id + otp_challenge_id
POST	/verify-otp	otp_challenge_id, otp_code	Consumes OTP and advances parent challenge
POST	/resend-otp	otp_challenge_id	New OTP sent; same OTP challenge ID
POST	/create-pin	registration_challenge_id, pin_code	Completes registration; user + KBKey + JWTs
POST	/login	email, password	login_challenge_id
POST	/verify-pin	login_challenge_id, pin_code	Completes login; user + KBKey + JWTs
POST	/update-pin	current_pin, new_pin + JWT	Updates server PIN + pin_version
POST	/forgot-password	email	recovery_challenge_id + otp_challenge_id
POST	/reset-password	recovery_challenge_id, new_password	Password replaced; login required
POST	/forgot-pin	email, password	recovery_challenge_id + otp_challenge_id
POST	/reset-pin	recovery_challenge_id, new_pin	PIN replaced + pin_version incremented
POST	/token/refresh	refresh token	New JWT token(s); no KBKey

18. PIN Versioning and Multi-Device Behavior

An account-wide PIN can be cached as a local verifier on more than one device. This creates an unavoidable offline-revocation limitation: a device that is fully offline cannot instantly learn that the PIN changed elsewhere.

A lightweight `pin_version` field makes this behavior manageable.

```
Server User.pin_version = 4

Device A local metadata:
  pin_version = 4  -> verifier current

Device B local metadata:
  pin_version = 3  -> stale once device checks server
```

- Increment `pin_version` after `/update-pin` and `/reset-pin`.
- Store the currently provisioned `pin_version` beside the local verifier.
- When the app is online and already performing authenticated network activity, compare the server `pin_version` with the local version.
- If the versions differ, require re-provisioning of local PIN authentication before treating the old verifier as current.
- A completely offline device may still accept its previously provisioned local PIN until it reconnects. Instant remote revocation is impossible without sacrificing offline unlock.

19. Challenge Security Rules

Rule	Requirement
Opaque IDs	Use UUIDs or equally unguessable identifiers. Challenge IDs are references, not user identity.
Expiry	Every <code>RegistrationChallenge</code> , <code>LoginChallenge</code> , <code>RecoveryChallenge</code> , and <code>OTPChallenge</code> expires.
Single use	OTP and recovery completion states cannot be replayed.
State validation	Every endpoint verifies the exact prerequisite status before transition.
Attempt limits	OTP and PIN verification track failures and lock/terminate excessive attempts.
Resend cooldown	OTP resend is rate-limited and old codes are invalidated.
Concurrency	State transitions should be atomic so two requests cannot complete one challenge twice.
Ownership	The user/context associated with a challenge is taken from server state, never trusted from an arbitrary email in the completion request.

20. Recommended Challenge Lifetimes

Exact durations remain configurable deployment policy. The implementation should centralize them in settings rather than scatter literal values through endpoints.

```
AUTH_REGISTRATION_CHALLENGE_TTL = ...
AUTH_LOGIN_CHALLENGE_TTL = ...
AUTH_RECOVERY_CHALLENGE_TTL = ...
AUTH_OTP_TTL = ...
AUTH_OTP_RESEND_COOLDOWN = ...
AUTH_OTP_MAX_ATTEMPTS = ...
```

```
AUTH_PIN_MAX_ATTEMPTS = ...
```

Challenge expiration should be evaluated by the server clock. The mobile client may display countdowns for UX, but it does not decide whether a challenge is valid.


21. Security Boundaries and Secret Separation

Secret / Value	Where It Exists	Must Not Be Reused As
Account password	User input; Django password hash in database	PIN, KBKey, KMKey
PIN	Transient user input; hashed server verifier + local verifier	Password, KBKey
KBKey	Encrypted on server; securely provisioned to client	Password hash or PIN verifier
KMKey	Server secret store only	PIN pepper or JWT signing secret
KEEBOX_PIN_PEPPER	Server secret store only	KMKey or Django SECRET_KEY
JWT signing secret/key	Server secret store	KMKey or PIN pepper
OTP code	Email + transient input; only hash/verifier persisted	Persistent authentication secret

No security secret should be logged. This includes raw passwords, PINs, OTP codes, KBKeys, KMKey, PIN pepper, access tokens, and refresh tokens.

22. KBKey Provisioning Integration

Authentication is the controlled point at which a device receives the user's KBKey. The backend database stores an encrypted KBKey; KMKey is used server-side to recover the raw KBKey only after full registration or login succeeds.



Recovery endpoints do not inherently need to return KBKey. Password recovery returns the user to normal login. PIN recovery can update the current device local verifier when appropriate, but a fresh/logged-out installation still obtains KBKey through normal login.

23. Logout and Local Authentication State

Logout must terminate the authenticated local security context. At minimum the client should clear access/refresh tokens, the locally provisioned KBKey, and the local PIN verifier. The treatment of the encrypted local KBox database is a separate data-retention policy and should be consistent with the backup/restore specification.

After logout, returning to the account requires the full normal login process: email + password, Login Challenge ID, and server PIN verification.

24. Django Ninja Reference Flow Skeleton

The following code is intentionally a service-layer skeleton. Production implementation should add transactions, rate limits, error mapping, challenge cleanup, audit events, and MongoDB-specific persistence details.

```

@router.post("/login")
def login(request, payload: LoginIn):
    user = authenticate_user(payload.email, payload.password)
    challenge = login_challenges.create(user=user)
    return {
        "login_challenge_id": str(challenge.id),
        "expires_at": challenge.expires_at,
    }

@router.post("/verify-pin")
def verify_login_pin(request, payload: VerifyPinIn):
    challenge = login_challenges.require_password_verified(
        payload.login_challenge_id
    )
    user = challenge.user

    pin_service.assert_valid(user, payload.pin_code, challenge)
    login_challenges.complete(challenge)

    kbkey = kbkey_service.decrypt_for_user(user)
    tokens = jwt_service.issue_pair(user)


    return build_auth_response(user, kbkey, tokens)
  
```

```
@router.post("/verify-otp")
def verify_otp(request, payload: VerifyOtpIn):
    otp = otp_service.get_active(payload.otp_challenge_id)
    otp_service.verify_and_consume(otp, payload.otp_code)

    if otp.purpose == AuthenticationPurpose.REGISTRATION:
        registration_service.mark_otp_verified(otp.context_challenge_id)
    elif otp.purpose in {
        AuthenticationPurpose.PASSWORD_RESET,
        AuthenticationPurpose.PIN_RESET,
    }:
        recovery_service.mark_otp_verified(otp.context_challenge_id)
    else:
        raise InvalidOtpPurpose()

    return {"success": True, "purpose": otp.purpose}
```

25. Flutter Authentication State Machine



25.1 Device provisioning after final auth

1. Persist the KBKey securely.
2. Create a fresh local random salt for PIN verification.
3. Derive and store the local PIN verifier using the PIN already validated by the server.
4. Persist the server pin_version with the local verifier.
5. Persist the refresh token securely and transition the app to the authenticated home state.

26. Error and Response Semantics

Condition	Recommended Client-Facing Category
Wrong email/password	INVALID_CREDENTIALS
Expired LoginChallenge	CHALLENGE_EXPIRED
Wrong server PIN	INVALID_PIN
PIN attempts exhausted	PIN_CHALLENGE_LOCKED
Wrong OTP	INVALID_OTP
Expired OTP	OTP_EXPIRED
OTP resend cooldown active	OTP_RESEND_COOLDOWN
Wrong challenge state	INVALID_CHALLENGE_STATE
Recovery already completed	CHALLENGE_CONSUMED
Network unavailable during local unlock	No error: local unlock does not use network

Error payloads should use stable machine-readable codes and safe user-facing messages. Internal exception details must not leak to clients.

27. Required Test Matrix

Registration

- Successful register → OTP → create PIN → JWT + KBKey.
- Wrong/expired OTP.
- create-pin before OTP verification is rejected.
- create-pin replay after completion is rejected.

- duplicate email registration behavior.

Login

- Correct password creates LoginChallenge but no JWT.
- Wrong password does not create usable challenge.
- Correct PIN completes challenge and returns JWT + KBKey.
- Expired LoginChallenge is rejected.
- PIN brute-force threshold locks/terminates the challenge.
- No OTP is generated or required during normal login.

Local unlock

- Valid local PIN unlocks while device has no internet.
- Wrong PIN is rejected locally.
- Raw PIN is absent from secure storage.
- Local verifier survives app restart but not explicit logout clearing.


Recovery

- Forgot password → OTP → reset → normal login.
- Forgot PIN requires valid account password before OTP issuance.
- Forgot PIN → OTP → reset updates server verifier and local verifier.
- Forgot both works sequentially.
- Neither password reset nor PIN reset changes KBKey.

OTP

- REGISTRATION/PASSWORD_RESET/PIN_RESET purposes work.
- LOGIN purpose is rejected for OTPChallenge.
- Resend invalidates the old code.
- Consumed OTP cannot be replayed.
- Attempt and resend limits are enforced.

28. Final Authentication Architecture



28.1 Registration

```

/register
-> RegistrationChallenge + OTPChallenge(REGISTRATION)
-> /verify-otp
-> /create-pin
-> generate/protect KBKey
-> access token + refresh token + user + KBKey

```

28.2 Login

```

/login (email + password)
-> LoginChallenge
-> /verify-pin
-> access token + refresh token + user + KBKey

```

NO OTP in normal login.

28.3 Password recovery

```

/forgot-password
-> RecoveryChallenge(PASSWORD_RESET)
-> OTPChallenge(PASSWORD_RESET)
-> /verify-otp
-> /reset-password
-> normal login

```

28.4 PIN recovery

```

/forgot-pin (email + password)
-> RecoveryChallenge(PIN_RESET)
-> OTPChallenge(PIN_RESET)
-> /verify-otp
-> /reset-pin
-> update local verifier or proceed to normal login

```

28.5 Routine use

```

App opens
-> local lock screen
-> local PIN verifier
-> home screen

```

Internet is not required.

The architecture deliberately makes account entry and account recovery server-controlled, while keeping everyday access to already provisioned encrypted KBoxes fast, local, and offline-capable.

29. Recommended Libraries and Platform Components

Area	Recommendation	Role
Backend authentication	Django authentication system	Password hashing, user identity, password validation.
API	Django Ninja	Authentication and recovery endpoints.
JWT	django-ninja-jwt	Access and refresh token sessions.
Password/PIN hashing	Django Argon2PasswordHasher + argon2-cffi	Slow one-way server verification.
OTP delivery	Brevo transactional email integration	Deliver registration and recovery codes.
Flutter secure persistence	flutter_secure_storage	Store local PIN verifier, KBKey, and refresh token.
Flutter local PIN KDF	cryptography package / Argon2id	Derive the local one-way PIN verifier.

30. Implementation Checklist

- Define AuthenticationPurpose TextChoices with exactly REGISTRATION, LOGIN, PASSWORD_RESET, and PIN_RESET.
- Implement RegistrationChallenge, LoginChallenge, RecoveryChallenge, and shared OTPChallenge state machines.
- Ensure OTPChallenge rejects LOGIN as an OTP purpose.
- Implement /register, /verify-otp, /resend-otp, /create-pin, /login, /verify-pin, and /update-pin.
- Implement /forgot-password, /reset-password, /forgot-pin, and /reset-pin.
- Issue JWTs only after /create-pin or successful login /verify-pin.
- Return KBKey only at completed registration/login provisioning points.
- Configure secure password and PIN hashing; keep KEEBOX_PIN_PEPPER separate from all other server secrets.
- Implement local Argon2id PIN verifier and secure storage in Flutter.
- Make routine local unlock completely network-independent.
- Implement pin_version synchronization for multi-device PIN changes.
- Add rate limits, challenge expiry, replay protection, OTP resend cooldown, and audit logging without secret values.
- Test offline unlock, recovery, challenge replay, brute-force limits, and KBKey invariance across password/PIN changes.