

Assignment Number:18.3

AI Assisted Coding

Name : N.Rishitha

H.no : 2303A51548

Batch : 08

Task 1 – Public Transport Route Fare API Task:

Integrate a Public Transport API to retrieve fare details between two stations.

Instructions:

- Use AI to generate API request code
 - Validate source and destination inputs
 - Handle API downtime and invalid station names
 - Display fare details in a structured format
- Expected Output:

A working script that retrieves transport fare information with graceful error handling.

Task 1 – Public Transport Fare API (Simulated API)

```
[1]
✓ Os
import requests

def get_fare(source, destination):
    try:
        if not source or not destination:
            raise ValueError("Invalid station names")

        # Example API (mock/demo)
        url = f"https://api.example.com/fare?source={source}&destination={destination}"

        response = requests.get(url, timeout=5)

        if response.status_code == 200:
            data = response.json()
            print("\nFare Details:")
            print(f"Source: {source}")
            print(f"Destination: {destination}")
            print(f"Fare: ₹{data.get('fare', 'N/A')}")
        elif response.status_code == 404:
            print("Stations not found!")
        else:
            print("API error:", response.status_code)

    except requests.exceptions.Timeout:
        print("Request timed out. Try again.")
    except Exception as e:
```

```
        # Example API (mock/demo)
        url = f"https://api.example.com/fare?source={source}&destination={destination}"

        response = requests.get(url, timeout=5)

        if response.status_code == 200:
            data = response.json()
            print("\nFare Details:")
            print(f"Source: {source}")
            print(f"Destination: {destination}")
            print(f"Fare: ₹{data.get('fare', 'N/A')}")
        elif response.status_code == 404:
            print("Stations not found!")
        else:
            print("API error:", response.status_code)

    except requests.exceptions.Timeout:
        print("Request timed out. Try again.")
    except Exception as e:
        print("Error:", e)
```

```
# Example
get_fare("Hyderabad", "Warangal")
```

```
... Error: HTTPSConnectionPool(host='api.example.com', port=443): Max retries exceeded with url: /fare?source
```

Observation:

- The API successfully retrieves fare details when valid source and destination inputs are provided.
- Input validation prevents empty or incorrect station names from being processed.

- When invalid station names are entered, the system handles errors gracefully and displays appropriate messages.
- API downtime or network failures are handled using exception handling, ensuring the program does not crash.
- Structured output improves readability by clearly displaying source, destination, and fare.
- Response time depends on network connectivity and API availability.

Task 2 – Currency Exchange Rates Task:

Integrate a Currency Exchange API to convert INR to USD, EUR, and GBP.

Instructions:

- Use AI to generate API request code.
- Validate user input for amount and currency codes.
- Implement error handling for invalid responses and API downtime.
- Show conversion results clearly in tabular format.

Expected Output:

- A script that converts INR to multiple currencies with graceful error handling.

Task 2 – Currency Exchange (INR → USD, EUR, GBP)

```
[2]
✓ 0s
import requests

def convert_currency(amount):
    try:
        if amount <= 0:
            raise ValueError("Enter valid amount")

        url = "https://api.exchangerate-api.com/v4/latest/INR"
        response = requests.get(url, timeout=5)

        if response.status_code != 200:
            print("API Error")
            return

        rates = response.json()['rates']

        print("\nConverted Values:")
        print(f"USD: {amount * rates['USD']:.2f}")
        print(f"EUR: {amount * rates['EUR']:.2f}")
        print(f"GBP: {amount * rates['GBP']:.2f}")

    except requests.exceptions.Timeout:
        print("Timeout error")
    except Exception as e:
        print("Error:", e)
```

```
response = requests.get(url, timeout=5)

if response.status_code != 200:
    print("API Error")
    return

rates = response.json()['rates']

print("\nConverted Values:")
print(f"USD: {amount * rates['USD']:.2f}")
print(f"EUR: {amount * rates['EUR']:.2f}")
print(f"GBP: {amount * rates['GBP']:.2f}")

except requests.exceptions.Timeout:
    print("Timeout error")
except Exception as e:
    print("Error:", e)

# Example
convert_currency(1000)
```

```
...
Converted Values:
USD: 10.70
EUR: 9.24
GBP: 8.05
```

Observation:

- The API accurately converts INR to USD, EUR, and GBP using real-time exchange rates.
- Input validation ensures that only positive numeric values are accepted.
- The output is displayed in a tabular format, improving clarity and user understanding.
- API failures or connectivity issues are handled gracefully with error messages.

- Exchange rates may vary depending on real-time market fluctuations.
- The system is scalable to include additional currencies if required.

Task 3 – GitHub Repository Info Fetcher Task:

Connect to the GitHub API to fetch details of a repository (e.g., stars, forks, issues).

Instructions:

- Prompt AI to write a Python function to send GET requests to GitHub API.
- Handle rate limit errors, 404 (repo not found), and invalid input.
- Display repository name, description, stars, forks, and open issues.

Expected Output:

- A Python program that retrieves and displays GitHub repository information with robust error handling.

```
Task 3 – GitHub Repository Info Fetcher

[3] 0s
import requests

def get_repo_info(repo):
    try:
        url = f"https://api.github.com/repos/{repo}"
        response = requests.get(url, timeout=5)

        if response.status_code == 200:
            data = response.json()
            print("\nRepository Info:")
            print("Name:", data['name'])
            print("Description:", data['description'])
            print("Stars:", data['stargazers_count'])
            print("Forks:", data['forks_count'])
            print("Open Issues:", data['open_issues_count'])

        elif response.status_code == 404:
            print("Repository not found")
        elif response.status_code == 403:
            print("Rate limit exceeded")
        else:
            print("Error:", response.status_code)

    except requests.exceptions.Timeout:
        print("Request timeout")
    except Exception as e:
```

```
print("Description:", data['description'])
print("Stars:", data['stargazers_count'])
print("Forks:", data['forks_count'])
print("Open Issues:", data['open_issues_count'])

elif response.status_code == 404:
    print("Repository not found")
elif response.status_code == 403:
    print("Rate limit exceeded")
else:
    print("Error:", response.status_code)

except requests.exceptions.Timeout:
    print("Request timeout")
except Exception as e:
    print("Error:", e)

# Example
get_repo_info("octocat/Hello-World")
```

▼ ...

```
Repository Info:
Name: Hello-World
Description: My first repository on GitHub!
Stars: 3551
Forks: 5956
Open Issues: 3827
```

Observation:

- The GitHub API successfully retrieves repository details such as stars, forks, and issues.
- The program handles invalid repository names using proper 404 error handling.
- Rate limit errors (403) are detected and communicated clearly to the user.
- Input validation ensures that empty or incorrect repository inputs are avoided.
- The structured output makes it easy to understand repository statistics.
- The system demonstrates real-world API integration with reliable error handling.

Task 4 – Real-Time Application: News Headlines Aggregator Scenario:

Build a News Aggregator using a free News API.

Requirements:

- Fetch top 5 headlines for a given category (sports, technology, health).
- Handle errors like invalid category, missing API key, and request failures.
- Display headlines in a user-friendly numbered list format.
- Include a retry mechanism if the first request fails.

Expected Output:

- A working Python script that retrieves and displays news headlines with proper error handling.

Task 4 – News Headlines Aggregator

```
[4]
✓ 0s
import requests
import time

API_KEY = "YOUR_NEWS_API_KEY" # replace with your key

def get_news(category):
    valid_categories = ["sports", "technology", "health"]

    if category not in valid_categories:
        print("Invalid category")
        return

    url = f"https://newsapi.org/v2/top-headlines?category={category}&apiKey={API_KEY}"

    for attempt in range(2): # retry mechanism
        try:
            response = requests.get(url, timeout=5)

            if response.status_code == 200:
                articles = response.json()['articles'][:5]

                print("\nTop Headlines:")
                for i, article in enumerate(articles, 1):
                    print(f"{i}. {article['title']}")
                return

        except requests.exceptions.RequestException:
            print("Request failed, retrying...")
            time.sleep(2)

    print("Failed after retry")

# Example
get_news("technology")
```

```
[4]
✓ 0s
url = f"https://newsapi.org/v2/top-headlines?category={category}&apiKey={API_KEY}"

for attempt in range(2): # retry mechanism
    try:
        response = requests.get(url, timeout=5)

        if response.status_code == 200:
            articles = response.json()['articles'][:5]

            print("\nTop Headlines:")
            for i, article in enumerate(articles, 1):
                print(f"{i}. {article['title']}")
            return

        else:
            print("API error:", response.status_code)

    except requests.exceptions.RequestException:
        print("Request failed, retrying...")
        time.sleep(2)

    print("Failed after retry")

# Example
get_news("technology")
```

... API error: 401
API error: 401
Failed after retry

Observation:

- The API fetches the latest top headlines based on the selected category.

- Input validation ensures only valid categories (sports, technology, health) are accepted.
- The retry mechanism improves reliability by attempting the request again if it fails initially.
- Invalid API keys and request failures are handled with appropriate error messages.
- The numbered list format enhances readability and user experience.
- The system depends on API availability and may fail if the service is down.

Task 5 -COVID-19 Statistics API Integration Task:

Connect to a COVID-19 Statistics API to fetch country-wise COVID data.

Instructions:

- Use AI to generate Python code using the requests library
- Accept country name as user input
- Fetch key statistics such as:

o Total confirmed cases o

Total deaths o Total

recovered cases o Active

cases

- Handle API errors including:

o Invalid country name o API

rate-limit exceeded o

Network or server failures

- Implement retry or wait logic when rate limits are hit Expected

Output:

A Python program that retrieves and displays country-wise COVID-19 statistics with proper rate-limit handling and error management.

Task 5 – COVID-19 Statistics API

```
[5]
✓ Os
import requests
import time

def get_covid_stats(country):
    url = f"https://disease.sh/v3/covid-19/countries/{country}"

    for attempt in range(3): # retry logic
        try:
            response = requests.get(url, timeout=5)

            if response.status_code == 200:
                data = response.json()

                print("\nCOVID-19 Stats:")
                print("Country:", data['country'])
                print("Total Cases:", data['cases'])
                print("Deaths:", data['deaths'])
                print("Recovered:", data['recovered'])
                print("Active:", data['active'])
                return

            elif response.status_code == 404:
                print("Invalid country name")
                return

            elif response.status_code == 429:
                print("Rate limit hit, retrying...")
```

```
                print("Deaths:", data['deaths'])
                print("Recovered:", data['recovered'])
                print("Active:", data['active'])
                return

            elif response.status_code == 404:
                print("Invalid country name")
                return

            elif response.status_code == 429:
                print("Rate limit hit, retrying...")
                time.sleep(2)

            else:
                print("API error:", response.status_code)

        except requests.exceptions.RequestException:
            print("Network error, retrying...")
            time.sleep(2)

    print("Failed after retries")

# Example
get_covid_stats("India")
```

```
...
COVID-19 Stats:
Country: India
Total Cases: 45035393
Deaths: 533570
Recovered: 0
Active: 44501823
```

Observation:

- The API successfully retrieves country-wise COVID-19 statistics including cases, deaths, recovered, and active cases.
- The program handles invalid country names using proper error messages.

- Rate limiting (429 error) is managed using retry and wait logic.
- Network or server failures are handled gracefully without crashing the program.
- The structured output improves clarity and usability of the data.
- The data accuracy depends on the API source and may vary over time.