Task-12 CODE

Question:

- 1. When you create any page in the project, you should trigger the event listener. After that, you should trigger the workflow, and it should add the Expirydate property to that page's jcr:content, with the value being the current date and time.
- 2. Continution: And when you create any page in another project, it should add the Expirydate property to that page's jcr:content, with the value being the previous date and time.

Answer:

import org.slf4j.Logger;

import org.slf4j.LoggerFactory;

EVENT LISTENER FOR CREATING PAGE WORKFLOW STARTED

```
package com.adobe.aem.guides.demo.core.listeners;
import java.util.HashMap;
import java.util.Map;
import javax.jcr.Session;
import javax.jcr.observation.Event;
import javax.jcr.observation.EventIterator;
import javax.jcr.observation.EventListener;
import org.apache.sling.api.resource.LoginException;
import org.apache.sling.api.resource.Resource;
import org.apache.sling.api.resource.ResourceResolver;
import org.apache.sling.api.resource.ResourceResolverFactory;
import org.apache.sling.jcr.api.SlingRepository;
import org.osgi.service.component.annotations.Activate;
import org.osgi.service.component.annotations.Component;
import org.osgi.service.component.annotations.Deactivate;
import org.osgi.service.component.annotations.Reference;
```

```
import com.day.cq.workflow.WorkflowException;
import com.day.cq.workflow.WorkflowService;
import com.day.cg.workflow.WorkflowSession;
import com.day.cq.workflow.exec.WorkflowData;
import com.day.cq.workflow.model.WorkflowModel;
@Component(immediate = true)
public class PageCreatedTask implements EventListener {
  private static final Logger log =
LoggerFactory.getLogger(PageCreatedTask.class);
  @Reference
  private WorkflowService;
  @Reference
  private ResourceResolverFactory resolverFactory;
  @Reference
  private SlingRepository repository;
  private Session observationSession;
  @Activate
  protected void activate() {
    try {
      observationSession = repository.loginService("hemanth", null);
observationSession.getWorkspace().getObservationManager().addEventListener(
        this,
        Event. NODE ADDED,
        "/content", // or any specific path you want to observe
        true.
        null,
        null,
        false
      );
```

```
log.info("PageCreationEventListener activated");
    } catch (Exception e) {
      log.error("Error activating PageCreationEventListener", e);
  }
  @Deactivate
  protected void deactivate() {
    if (observationSession != null) {
      try {
observationSession.getWorkspace().getObservationManager().removeEventListen
er(this);
        observationSession.logout();
      } catch (Exception e) {
        log.error("Error deactivating PageCreationEventListener", e);
      }
    }
  }
  @Override
  public void onEvent(EventIterator events) {
    while (events.hasNext()) {
      Event event = events.nextEvent();
      try {
        String path = event.getPath();
        handleResourceAddedEvent(path);
      } catch (Exception e) {
        log.error("Error handling event", e);
      }
    }
  }
  private void handleResourceAddedEvent(String path) {
    ResourceResolver resourceResolver = null;
    try {
      Map<String, Object> param = new HashMap<>();
```

```
param.put(ResourceResolverFactory. SUBSERVICE, "hemanth");
      resourceResolver = resolverFactory.getServiceResourceResolver(param);
      Resource resource = resourceResolver.getResource(path);
      if (resource != null && resource.isResourceType("cg:Page")) {
        log.info("Page created at path: {}", path);
        startWorkflow(path);
      }
    } catch (LoginException e) {
      log.error("Error obtaining resource resolver", e);
    } finally {
      if (resourceResolver != null) {
        resourceResolver.close();
      }
    }
  }
  private void startWorkflow(String payloadPath) {
    Map<String, Object> param = new HashMap<>();
    param.put(ResourceResolverFactory. SUBSERVICE, "hemanth");
    try (ResourceResolver resolver =
resolverFactory.getServiceResourceResolver(param)) {
      Session session = resolver.adaptTo(Session.class);
      WorkflowSession workflowSession =
workflowService.getWorkflowSession(session);
      String workflowModelPath = "/var/workflow/models/HemanthModel";
      WorkflowModel workflowModel =
workflowSession.getModel(workflowModelPath);
      WorkflowData workflowData =
workflowSession.newWorkflowData("JCR PATH", payloadPath);
      workflowSession.startWorkflow(workflowModel, workflowData);
      log.info("Workflow started for payload: {}", payloadPath);
    } catch (LoginException e) {
      log.error("LoginException while starting workflow", e);
```

```
} catch (WorkflowException e) {
      log.error("WorkflowException while starting workflow", e);
    } catch (Exception e) {
      log.error("Exception while starting workflow", e);
 }
ADD PROPERTY THROUGH WORKFLOW
package workflow;
import java.util.Calendar;
import java.util.HashMap;
import java.util.Map;
import javax.jcr.Node;
import javax.jcr.Session;
import org.apache.sling.api.resource.ResourceResolver;
import org.apache.sling.api.resource.ResourceResolverFactory;
import org.osgi.service.component.annotations.Component;
import org.osgi.service.component.annotations.Reference;
import org.slf4j.Logger;
import org.slf4j.LoggerFactory;
import com.adobe.granite.workflow.WorkflowSession;
import com.adobe.granite.workflow.exec.WorkItem;
import com.adobe.granite.workflow.exec.WorkflowProcess;
import com.adobe.granite.workflow.metadata.MetaDataMap;
@Component(service = WorkflowProcess.class, property = {"process.label=Page"
Created"})
public class PagecreatedWorkflow implements WorkflowProcess {
  private static final Logger log =
LoggerFactory.getLogger(PagecreatedWorkflow.class);
  @Reference
```

```
private ResourceResolverFactory resolverFactory;
  @Override
  public void execute(WorkItem workItem, WorkflowSession workflowSession,
MetaDataMap metaDataMap) {
    String payloadPath = workItem.getWorkflowData().getPayload().toString();
    ResourceResolver resourceResolver = null;
    try {
      // Using service user to obtain resource resolver
      Map<String, Object> param = new HashMap<>();
      param.put(ResourceResolverFactory. SUBSERVICE, "hemanth");
      resourceResolver = resolverFactory.getServiceResourceResolver(param);
      Session session = resourceResolver.adaptTo(Session.class);
      Node pageNode = session.getNode(payloadPath);
      if (pageNode != null && pageNode.hasNode("jcr:content")) {
        Node contentNode = pageNode.getNode("jcr:content");
        String templatePath =
contentNode.getProperty("cq:template").getString();
        Calendar currentDate = Calendar.getInstance();
        if (!"/conf/Demo/settings/wcm/templates/page-
content".equals(templatePath)) {
          currentDate.add(Calendar.DATE, -1);
        }
        contentNode.setProperty("expirydate", currentDate);
        session.save();
        log.info("Property 'expired' added to jcr:content of page at {}",
payloadPath);
      } else {
        log.warn("jcr:content node not found for page at {}", payloadPath);
    } catch (Exception e) {
```

```
log.error("Error adding property to jcr:content of page at {}", payloadPath,
e);
    throw new RuntimeException(e);
} finally {
    if (resourceResolver != null) {
        resourceResolver.close();
    }
    }
}
```











