

# Task-14 CODE

## QUESTION

Perform CRUD Operation -:

1) Create Operation -:

- i) On submission of your form, write onClick() function
- ii) Inside function make ajax call and provide data of each field and url.
- iii) With ajax url register servlet with path and make call to your servlet.
- iv) Override doGet() method and save form data to path into your Crx/de.

2) Read Operation -:

- i) Fetch all data from path provided using query in form data table component sling model.

Form Data Table Component -:

Name	Email	Subject	Message	Edit	Delete
Lakshmi	laksmi@vation.com	subject	message	Edit	Delete
Rohit	rohit@vation.com	subject	message	Edit	Delete
Saniya	saniya@vation.com	abc	xyz	Edit	Delete
nitin	nitin.tripathi@vation.com	subject	hh	Edit	Delete
virat	virat@vation.com	subject	message	Edit	Delete

3) If user click on the edit button it should take to the contact us component and the user can edit their field

4) If the user click on delete it should select particular row and it should delete that respective node in crx/de.

Answer :

### FRONT-END CODE FOR CRUD OPERATION

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <title>AJAX to AEM Servlet</title>
  <script src="https://code.jquery.com/jquery-3.6.0.min.js"></script>
  <style>
    table {
      width: 100%;
      border-collapse: collapse;
    }
    th, td {
      border: 1px solid orange;
      padding: 8px;
      text-align: left;
    }
    th {
      background-color: black;
      color: white;
    }
    td {
      background-color: black;
      color: white;
    }
    .edit, .delete {
      color: orange;
```

```
        cursor: pointer;
    }
</style>
</head>
<body>
    <form id="myForm">
        <input type="hidden" id="rowIndex" value="">
        <input type="text" name="param1" id="param1" placeholder="Name"><br></br>
        <input type="text" name="param2" id="param2" placeholder="Email"><br></br>
        <input type="text" name="param3" id="param3"
placeholder="Subject"><br></br>
        <input type="text" name="param4" id="param4"
placeholder="Message"><br></br>
        <div class="your-component" data-path="{resource.path @
context='unsafe'}"></div>
        <button type="button" onclick="sendData()">Submit</button>
    </form>
    <div id="formDataTable"></div>
    <script>
        function sendData() {
            const rowIndex = $("#rowIndex").val();
            const param1 = $("#param1").val();
            const param2 = $("#param2").val();
            const param3 = $("#param3").val();
            const param4 = $("#param4").val();
            const componentPath = $(".your-component").attr("data-path");

            console.log("Component Path:", componentPath);
        }
    </script>
</body>
</html>
```

```
$ajax({  
  url: '/bin/myServlet',  
  type: 'POST',  
  data: {  
    rowIndex: rowIndex,  
    param1: param1,  
    param2: param2,  
    param3: param3,  
    param4: param4,  
    componentPath: componentPath  
  },  
  success: function(response) {  
    console.log('Response from POST:', response);  
    alert('Response: ' + response.message);  
    fetchTableData();  
    clearForm();  
  },  
  error: function(xhr, status, error) {  
    console.error('Error: ' + error);  
  }  
});  
}
```

```
function fetchTableData() {  
  const componentPath = $(".your-component").attr("data-path");  
  
  console.log("Fetching data from path:", componentPath);
```

```
$.ajax({
  url: '/bin/myServlet',
  type: 'GET',
  data: { path: componentPath },
  success: function(response) {
    console.log('Response from GET:', response);
    if (response.data) {
      createTable(response.data);
    } else {
      console.error('No data received');
    }
  },
  error: function(xhr, status, error) {
    console.error('Error: ' + error);
  }
});
```

```
function createTable(data) {
  const tableContainer = document.getElementById('formDataTable');
  tableContainer.innerHTML = "";

  const table = document.createElement('table');
  const headerRow = document.createElement('tr');

  const headers = ['Name', 'Email', 'Subject', 'Message', 'Edit', 'Delete'];
  headers.forEach(headerText => {
    const th = document.createElement('th');
```

```
    th.textContent = headerText;
    headerRow.appendChild(th);
  });

  table.appendChild(headerRow);

  data.forEach((item, index) => {
    const dataRow = document.createElement('tr');

    const nameCell = document.createElement('td');
    nameCell.textContent = item.name;
    dataRow.appendChild(nameCell);

    const emailCell = document.createElement('td');
    emailCell.textContent = item.email;
    dataRow.appendChild(emailCell);

    const subjectCell = document.createElement('td');
    subjectCell.textContent = item.subject;
    dataRow.appendChild(subjectCell);

    const messageCell = document.createElement('td');
    messageCell.textContent = item.message;
    dataRow.appendChild(messageCell);

    const editCell = document.createElement('td');
    editCell.textContent = 'Edit';
    editCell.className = 'edit';
```

```
editCell.dataset.index = index;
editCell.onclick = function() {
    editRow(item, index);
};
dataRow.appendChild(editCell);

const deleteCell = document.createElement('td');
deleteCell.textContent = 'Delete';
deleteCell.className = 'delete';
deleteCell.dataset.index = index;
deleteCell.onclick = function() {
    deleteRow(index);
};
dataRow.appendChild(deleteCell);

table.appendChild(dataRow);
});

tableContainer.appendChild(table);
}

function editRow(item, index) {
    $("#rowIndex").val(index);
    $("#param1").val(item.name);
    $("#param2").val(item.email);
    $("#param3").val(item.subject);
    $("#param4").val(item.message);
}
```

```
function deleteRow(index) {  
const componentPath = $(".your-component").attr("data-path");  
  
$.ajax({  
    url: '/bin/myServlet',  
    type: 'POST',  
    data: {  
        rowIndex: index,  
        delete: 'true',  
        componentPath: componentPath  
    },  
    success: function(response) {  
        console.log('Response from DELETE:', response);  
        alert('Row deleted successfully');  
        fetchTableData();  
    },  
    error: function(xhr, status, error) {  
        console.error('Error: ' + error);  
    }  
});  
}
```

```
function clearForm() {  
    $("#rowIndex").val("");  
    $("#param1").val("");  
    $("#param2").val("");  
}
```



```
        $('#param3').val('');  
        $('#param4').val('');  
    }  
  
    document.addEventListener('DOMContentLoaded', function() {  
        fetchTableData();  
    });  
</script>  
</body>  
</html>
```

## SERVLET CODE

```
package com.adobe.aem.guides.demo.core.servlets;

import org.apache.sling.api.SlingHttpServletRequest;
import org.apache.sling.api.SlingHttpServletResponse;
import org.apache.sling.api.servlets.SlingAllMethodsServlet;
import org.osgi.service.component.annotations.Component;
import org.osgi.framework.Constants;
import com.google.gson.JsonArray;
import com.google.gson.JsonObject;
import javax.jcr.Node;
import javax.jcr.NodeIterator;
import javax.jcr.RepositoryException;
import javax.jcr.Session;
import org.apache.sling.jcr.api.SlingRepository;
import org.apache.sling.api.resource.ResourceResolver;
import org.apache.sling.api.resource.ResourceResolverFactory;
import org.apache.sling.api.resource.LoginException;
import org.apache.sling.api.resource.Resource;

import javax.servlet.Servlet;
import java.io.IOException;
import java.util.HashMap;
import java.util.Iterator;
import java.util.Map;

@Component(
    service = { Servlet.class },
    property = {
        Constants.SERVICE_DESCRIPTION + "=Example Servlet",
        "sling.servlet.paths=/bin/myServlet",
        "sling.servlet.methods={ GET, POST, DELETE}"
    }
)
public class MyServlet extends SlingAllMethodsServlet {

    @org.osgi.service.component.annotations.Reference
    private SlingRepository repository;

    @org.osgi.service.component.annotations.Reference
    private ResourceResolverFactory resolverFactory;

    @Override
    protected void doGet(SlingHttpServletRequest request, SlingHttpServletResponse response)
throws IOException {
        String componentPath = request.getParameter("path");
```

```

ResourceResolver resourceResolver = null;

try {
    // Get the resource resolver
    Map<String, Object> param = new HashMap<>();
    param.put(ResourceResolverFactory.SUBSERVICE, "hemanth");
    resourceResolver = resolverFactory.getServiceResourceResolver(param);

    // Get the resource at the specified path
    Resource resource = resourceResolver.getResource(componentPath + "/data");

    JSONArray dataArray = new JSONArray();

    if (resource != null) {
        Iterator<Resource> children = resource.listChildren();
        while (children.hasNext()) {
            Resource child = children.next();
            Node childNode = child.adaptTo(Node.class);
            if (childNode != null) {
                JsonObject dataObject = new JsonObject();
                dataObject.addProperty("name", childNode.getProperty("name").getString());
                dataObject.addProperty("email", childNode.getProperty("email").getString());
                dataObject.addProperty("subject", childNode.getProperty("subject").getString());
                dataObject.addProperty("message",
childNode.getProperty("message").getString());
                dataArray.add(dataObject);
            }
        }
    }

    JsonObject jsonResponse = new JsonObject();
    jsonResponse.add("data", dataArray);

    response.setContentType("application/json");
    response.setCharacterEncoding("UTF-8");
    response.getWriter().write(jsonResponse.toString());

} catch (LoginException | RepositoryException e) {
    logError(response, e);
} finally {
    if (resourceResolver != null) {
        resourceResolver.close();
    }
}
}

```

@Override

```
protected void doPost(SlingHttpServletRequest request, SlingHttpServletResponse response)
throws IOException {
    String rowIndex = request.getParameter("rowIndex");
    String delete = request.getParameter("delete");
    String componentPath = request.getParameter("componentPath");

    ResourceResolver resourceResolver = null;
    Session session = null;

    try {
        Map<String, Object> param = new HashMap<>();
        param.put(ResourceResolverFactory.SUBSERVICE, "hemanth");
        resourceResolver = resolverFactory.getServiceResourceResolver(param);
        session = resourceResolver.adaptTo(Session.class);

        Resource componentResource = resourceResolver.getResource(componentPath);
        Node componentNode = componentResource.adaptTo(Node.class);

        if (!componentNode.hasNode("data")) {
            componentNode.addNode("data", "nt:unstructured");
        }
        Node dataNode = componentNode.getNode("data");

        if (delete != null && delete.equals("true")) {
            // Handle delete
            if (dataNode.hasNode("item" + rowIndex)) {
                Node itemNode = dataNode.getNode("item" + rowIndex);
                itemNode.remove();
                session.save();
                reorderNodes(dataNode, session);
                session.save();

                sendJsonResponse(response, "success", "Data deleted and nodes reordered
successfully.");
            } else {
                sendJsonResponse(response, "error", "Node not found.");
            }
        } else {
            // Handle create/update
            String param1 = request.getParameter("param1");
            String param2 = request.getParameter("param2");
            String param3 = request.getParameter("param3");
            String param4 = request.getParameter("param4");

            Node itemNode;
```

```

        if (rowIndex == null || rowIndex.isEmpty()) {
            int itemIndex = 0;
            while (dataNode.hasNode("item" + itemIndex)) {
                itemIndex++;
            }
            itemNode = dataNode.addNode("item" + itemIndex, "nt:unstructured");
        } else {
            itemNode = dataNode.getNode("item" + rowIndex);
        }

        itemNode.setProperty("name", param1);
        itemNode.setProperty("email", param2);
        itemNode.setProperty("subject", param3);
        itemNode.setProperty("message", param4);
        session.save();

        sendJsonResponse(response, "success", "Data stored successfully.");
    }
} catch (LoginException | RepositoryException e) {
    logError(response, e);
} finally {
    if (session != null) {
        session.logout();
    }
    if (resourceResolver != null) {
        resourceResolver.close();
    }
}
}

private void reorderNodes(Node dataNode, Session session) throws RepositoryException {
    int itemIndex = 0;
    for (NodeIterator nodeIterator = dataNode.getNodes(); nodeIterator.hasNext(); ) {
        Node node = nodeIterator.nextNode();
        String newName = "item" + itemIndex;
        if (!node.getName().equals(newName)) {
            session.move(node.getPath(), dataNode.getPath() + "/" + newName);
        }
        itemIndex++;
    }
}

private void sendJsonResponse(SlingHttpServletResponse response, String status, String
message) throws IOException {
    JsonObject jsonResponse = new JsonObject();
    jsonResponse.addProperty("status", status);

```

```

        jsonResponse.addProperty("message", message);
        response.setContentType("application/json");
        response.setCharacterEncoding("UTF-8");
        response.getWriter().write(jsonResponse.toString());
    }

    private void logError(SlingHttpServletResponse response, Exception e) throws IOException
    {
        e.printStackTrace();
        JsonObject jsonResponse = new JsonObject();
        jsonResponse.addProperty("status", "error");
        jsonResponse.addProperty("message", e.getMessage());
        response.setContentType("application/json");
        response.setCharacterEncoding("UTF-8");
        response.getWriter().write(jsonResponse.toString());
    }
}

```

## FORM AND TABLE CREATION

Workflow: This page is subject to the workflow *sivamodel*. [Complete](#) [Step back](#) [View details](#)

hemanth sai

vishnu@gmail.com

aem6.5

this is the

Submit

Name	Email	Subject	Message	Edit	Delete
hemanth sai	vishnu@gmail.com	java script5	this is the	<a href="#">Edit</a>	<a href="#">Delete</a>
nagaraju	nagar@gmail.com	aem6.5	hi this is nagaraj	<a href="#">Edit</a>	<a href="#">Delete</a>
paddesh	paddesh@gmail	java	this is about java	<a href="#">Edit</a>	<a href="#">Delete</a>
shiva sai	shiva@gmail.com	aem	this is about java	<a href="#">Edit</a>	<a href="#">Delete</a>

## NODE CREATION AND STORED FORM DATA

The screenshot displays the CRXDE Lite web console. The left sidebar shows a tree view of the content structure, with the path `/content/Demo/us/en/jcr:content/root/hemanthcomponent1/data/item0` selected. The main area is divided into two panes. The top pane shows a code editor with a JavaScript function for deleting a row. The bottom pane shows a table of properties for the selected item.

```
175 componentPath: componentPath
176 },
177 success: function(response) {
178   console.log('Response from DELETE:', response);
179   alert('Row deleted successfully');
180   fetchTableData();
181 },
182 error: function(xhr, status, error) {
183   console.error('Error: ' + error);
184 }
```

Line 202, Column 8

Name	Type	Value	Protected	Mandatory	Multiple	Auto Created
1 subject	String	java script5	false	false	false	false
2 name	String	hemanth sai	false	false	false	false
3 message	String	this is the	false	false	false	false
4 jcr:primaryType	Name	nt:unstructured	true	true	false	true
5 email	String	vishnu@gmail.com	false	false	false	false

At the bottom, there is a form with fields for Name, Type (String), and Value, along with a Multi Add button.