

Dual booting Assignment

1. Created a boot directory in root & listed the logical volumes. And created a mount point

```
ubuntuserver [Running] - Oracle VirtualBox
File Machine View Input Devices Help
tharu@tharuserver1:~$ sudo mkdir -p /mnt/os2
tharu@tharuserver1:~$ sudo lvscan
  ACTIVE                '/dev/ubuntuvg-1/ubuntuv-1v' [<11.50 GiB] inherit
  ACTIVE                '/dev/ubuntuvg-1/ubuntuv-1v' [<11.50 GiB] inherit
tharu@tharuserver1:~$ sudo mount /dev/ubuntuvg-1/ubuntuv-1v /mnt/os2
mount: /mnt/os2: /dev/mapper/ubuntuvg-1-ubuntuv-1v already mounted on /mnt/os2.
tharu@tharuserver1:~$ _
```

2. Then I enabled the os-prober in GRUB

```
ubuntuserver [Running] - Oracle VirtualBox
File Machine View Input Devices Help
GNU nano 6.2 /etc/default/grub *
# /boot/grub/grub.cfg.
# For full documentation of the options in this file, see:
#   info -f grub -n 'Simple configuration'

GRUB_DEFAULT=0
GRUB_TIMEOUT_STYLE=hidden
GRUB_TIMEOUT=0
GRUB_DISTRIBUTOR=`lsb_release -i -s 2> /dev/null || echo Debian`
GRUB_CMDLINE_LINUX_DEFAULT=""
GRUB_CMDLINE_LINUX=""
GRUB_DISABLE_OS_PROBER=false

# Uncomment to enable BadRAM filtering, modify to suit your needs
# This works with Linux (no patch required) and with any kernel that obtains
# the memory map information from GRUB (GNU Mach, kernel of FreeBSD ...)
#GRUB_BADRAM="0x01234567,0xfefefefe,0x89abcdef,0xefefefef"

# Uncomment to disable graphical terminal (grub-pc only)
#GRUB_TERMINAL=console

# The resolution used on graphical terminal
# note that you can use only modes which your graphic card supports via VBE
# you can see them in real GRUB with the command `vbeinfo`
#GRUB_GFXMODE=640x480

# Uncomment if you don't want GRUB to pass "root=UUID=xxx" parameter to Linux
#GRUB_DISABLE_LINUX_UUID=true

# Uncomment to disable generation of recovery mode menu entries
#GRUB_DISABLE_RECOVERY="true"

# Uncomment to get a beep at grub start
#GRUB_INIT_TUNE="480 440 1"

^G Help      ^O Write Out ^W Where Is  ^K Cut       ^T Execute  ^C Location M-U Undo
^X Exit      ^R Read File ^N Replace   ^U Paste     ^J Justify  ^_ Go To Line M-E Redo
Right Ctrl
```

3. Then ran the os-prober

```
tharu@tharuserver1:~$ sudo os-prober
/dev/mapper/ubuntu--vg--1-ubuntu--lv:Ubuntu 22.04.5 LTS (22.04):Ubuntu:linux
tharu@tharuserver1:~$ sudo update-grub
Sourcing file `/etc/default/grub'
Sourcing file `/etc/default/grub.d/init-select.cfg'
Generating grub configuration file ...
Found linux image: /boot/vmlinuz-5.15.0-140-generic
Found initrd image: /boot/initrd.img-5.15.0-140-generic
Warning: os-prober will be executed to detect other bootable partitions.
Its output will be used to detect bootable binaries on them and create new boot entries.
Found Ubuntu 22.04.5 LTS (22.04) on /dev/mapper/ubuntu--vg--1-ubuntu--lv
done
tharu@tharuserver1:~$ _
```

4. Then rebooted vm and the GRUB showed the two OS's

