

מבוא לתכנות מדעי פיתון
תרגיל בית 8
שותפים: נימר נסייר 322626896
פאטמה נעמה 212100580

שאלה 1:

Link: https://py3.codeskulptor.org/#user306_PrU0tOM9n4_1.py


```
#Question 1
# all the possibilites...
N=6**3
#our double list such as first is bigger than the second and the
# second bigger than the third
x=[[i,j,w] for i in range(1,7) for j in range(1,7) for w in range(1,7) if i>j>w]
#we need the list length divided by all the possibilites
print("the probability is:")
print(len(x)/N)
```

```
Question1.py', wdir='/U.
the probability is:
0.09259259259259259|
```

שאלה 2:

Link: https://py3.codeskulptor.org/#user306_PrU0tOM9n4_2.py

```
#Question 2
import random
import matplotlib.pyplot as plt
def random_walk(n):
    #define left and right
    left=0
    right=0
    #our list starts with 0
    x=[0]
    y=[0]
    for i in range(n):
        # get random probability
        step=random.random()
        #as the questions asks probabilities
        if step<=0.49:
            left+=1
            right+=1
        elif step>=0.49 and step <=0.98:
            left+=1
            right+=-1
        else:
            left+=0
            right+=0
        #add the steps
        x.append(left)
        y.append(right)
    return [x,y]
#1000 steps as requested
#graph for show
simulatewalk = random_walk(1000)
plt.plot(simulatewalk[0],simulatewalk[1])
plt.show()
```



שאלה 3:

Link: https://py3.codeskulptor.org/#user306_PrU0tOM9n4_3.py

Part 1:

```
@author: nemernser
"""



#Question 3
#this answer is based on question 2
import matplotlib.pyplot as plt
# Using ourrange function introduced in class
def ourrange(start,stop,step=1):
    rez_range=[]
    if stop<start:
        return rez_range
    rez_range.append(start)
    while True:
        if rez_range[-1]+step<stop:
            rez_range.append(rez_range[-1]+step)
        else:
            break
    return rez_range
import random
import time
def random_walk(n):
    counter_p=0
    for j in range(10000):

        #define left and right
        left=0
        right=0
        #our list starts with 0
        x=[0]
        y=[0]
        for i in range(n):
            # get random probability
            step=random.random()
            #as the questions asks probabilities
            if step<=0.49:
                left+=1
                right+=-1
            elif step>=0.49 and step <=0.98:
                left+=1
                right+=1
            else:
                left=0
                right=0
            #add the steps
            x.append(left)
            y.append(right)
            # check if mikom is 10
            # if yes then we add 1 to our counter
            if right==10:
                passed=1
                counter_p+=passed
                #stop the for!
                break
            else:
                passed=0
        #get probability out of 10k simulations
        num=counter_p/10000
    return num
```

Part 2:

```
#1000 steps as requested
#graph for show
count=0
y=[]
y_ax=ourrange(0.1,1,0.1)
#list for our time
times=[]
x=ourrange(100,1001,100)
for i in x:
    #start counting time
    time_start=time.time()
    #finish the function
    count = random_walk(i)
    #end the time
    end_time=time.time()
    #add the time on each x... 100,200...1000
    times.append(end_time-time_start)
    y.append(count)
#drawing the graph...
plt.plot(x,y)
plt.xticks(x)
plt.yticks(y_ax)
plt.title("Probability")
plt.grid()
plt.show()
#second plot
plt.plot(x,times,color="red")
plt.xticks(x)
plt.grid()
plt.title("Elapsed time (in seconds)")
plt.show()
```

Part 3:



Link: https://py3.codeskulptor.org/#user306_PrU0tOM9n4_4.py

```
#Question 4
## pretend that there are 2 minimum in the list
def Normalize2d(two_d):
    #two numbers to help us navigate the list
    i=0
    j=0
    #duplicate list
    d=list(two_d)
    for row in two_d:
        #get minimum,maximum
        a=min(row)
        b=max(row)
        #we need to set the j back to 0 so we print first element in the second row
        j=0
        for col in row:
            #basic function as the question
            z=(col-a)/(b-a)
            #change the element in the duplicate array
            d[i][j]=z
            #go onto the second element
            j+=1
        #second row
        i+=1
    return d
## our x list for practice...
x=[[1,2,3],
   [5,8,10],
   [345,467,213]]
#*****
#input
rows=int(input("Enter number of rows: "))
cols=int(input("Enter number of columns: "))
#test list
matrix=[]
#get each number in the first row
#and then the second an so on...
print("Please enter the row numbers: ")
for i in range(rows):
    a=[]
    for j in range(cols):
        a.append(int(input()))
    matrix.append(a)
#just for showing our input list
print("our 2d array is:")
for i in range(rows):
    if i>=1:
        print("\n")
    for j in range(cols):
        print(matrix[i][j], end=" ")
print("\nafter doing normalize2d:")
print(Normalize2d(matrix))
```

```
4.py", wd1r="/Users/nemernse
```

```
Enter number of rows: 3
```

```
Enter number of columns: 3
```

```
Please enter the row numbers
```

```
1
```

```
2
```

```
3
```

```
5
```

```
8
```

```
10
```

```
345
```

```
467
```

```
213
```

```
213
```

```
our 2d array is:
```

```
1 2 3
```

```
5 8 10
```

```
345 467 213
```

```
after doing normalize2d:
```

```
[[0.0, 0.5, 1.0], [0.0, 0.6, 1.0]
```

```
[0.5196850393700787, 1.0, 0.0]]
```

Link: https://py3.codeskulptor.org/#user306_PrU0tOM9n4_5.py

```
@author: nemernser
"""

#question 6
# 4 for for a,b,c,d from 1 to 50
#set() method is used to convert any of the iterable
#to sequence of iterable elements with distinct elements, commonly called Set.

counter=0
lists=set()
list_check=[]
for a in range(1,51):
    for b in range(1,51):
        for c in range(1,51):
            for d in range(1,51):
                #each number to the power of 3
                a3 = a**a
                b3 = b**b
                c3 = c**c
                d3 = d**d
                ## checking the right numbers for the formula
                if(a3+b3==c3+d3):
                    if a!=b and b!=c and c!=d and a!=c and b!=d:
                        list_check+=[[a,b,c,d]]

#Tuples are immutable, ordered lists of data, unlike lists.
#Lists are mutable, which means you
#can change the contents of a list. Individual values in a tuple are called items.
#Tuples can store any data type.
        #so basically we are checking if there are duplicate elements
        #but we have to sort the a,b,c,d so we can check if they are duplicate
lists=list(set(tuple(sorted(i))for i in list_check))
#print each element in lists
#which is every 4 numbers a,b,c,d
for j in lists:
    print (j)
print("\n")
print("The number of unique quartets is",len(lists))

wdir='/Users/nemernser')
(6, 27, 45, 48)
(2, 18, 20, 24)
(1, 9, 10, 12)
(10, 19, 24, 27)
(17, 26, 36, 39)
(12, 31, 33, 40)
(4, 18, 30, 32)
(3, 27, 30, 36)
(4, 36, 40, 48)
(9, 16, 33, 34)
(2, 9, 15, 16)
(2, 15, 33, 34)

The number of unique quartets is 12
```