
Ajax


Ajax (also AJAX; pronounced <u>/'eɪdʒæks/</u> ; an acronym for <u>Asynchronous JavaScript</u> and <u>XML</u> )[1] is a group of interrelated <u>web development</u> methods used on the <u>client-sectors</u> to create asynchronous <u>web applications</u> . With Ajax, web applications can send data to, and retrieve data from, a <u>server</u> asynchronously (in the background) without interferent with the display and behavior of the existing page. Data is usually retrieved using the <u>XMLHttpRequest</u> <u>object</u> . Despite the name, the use of XML is not needed ( <u>JSON</u> is considered), and the requests do not need to be <u>asynchronous.[2]</u>	ring
Ajax is not one technology, but a group of technologies. HTML and CSS can be used in combination to mark up and style information. The DOM is accessed with JavaScript dynamically display, and to allow the user to interact with the information presented. JavaScript and the XMLHttpRequest object provide a method for exchanging data asynchronously between browser and server to avoid full page reloads.	ot to

 $\underset{\text{The Free Encyclopedia}}{\text{WikiPEDIA}}$ 




### classic web application model

Jesse James Garrett / adaptivepath.com





Ajax web application model

## auto complete



### results





## CRUD

HTTP	CRUD	SQL
put	create	insert
get	read	select
post	update	update
delete	delete	delete

## XMLHttpRequest Object

```
var xhr;
if(window.XMLHttpRequest) {
   xhr = new XMLHttpRequest();
} else if (window.ActiveXObject) {
   xhr = new ActiveXObject("Microsoft.XMLHTTP");
xhr.onreadystatechange = function () {
   if(xhr.readyState == 4) {
      if(xhr.status == 200) {
          alert(xhr.responseText);
   }
}
xhr.open(
   "GET",
   "number?max=" + encodeURI(10),
   true
);
xhr.send(null);
```

## jQuery

```
$(document).ready(function() {
    $("#jquery-button").click(function() {
       var max = $('#jquery-max').val();

    $.get('number', {max:max}, function(data) {
       $('#jquery-number').html(data);
      });

    });
});
```

# JSON

```
{
    "title": "Recent Uploads tagged mountrainier",
    "link": "http://www.flickr.com/photos/tags/mountrainier/",
    "description": "",
    "modified": "2013-03-05T06:15:36Z",
    "generator": "http://www.flickr.com/",
    "items": □
        "title": "Three volcanoes.",
        "link": "http://www.flickr.com/photos/urbanadventureleaguepdx/8529486681/",
        "media": {"m":"http://farm9.staticflickr.com/8367/8529486681_362bc972f8_m.jpg"},
        "date_taken": "2013-03-04T15:26:19-08:00",
        "published": "2013-03-05T06:15:36Z",
    "author": "nobody@flickr.com (urbanadventureleaguepdx)",
        "author_id": "63964930@N05",
        "tags": "mountrainier mountsthelens mountadams"
    },
        "title": "Flew home to a sunny day.",
        "link": "http://www.flickr.com/photos/architecturegeek/8530441688/",
        "media": {"m":"http://farm9.staticflickr.com/8383/8530441688_07f87db69f_m.jpg"},
        "date_taken": "2013-03-04T15:03:38-08:00",
        "published": "2013-03-05T03:39:39Z",
        "author": "nobody@flickr.com (architecturegeek)",
        "author_id": "42788598@N00".
        "tags": "seattle sky air aerial mountrainier mtrainier airplanewindow virginamerica"
     }]
```

# jQuery (JSON)

```
$.getJSON('ajax/test.json', function(data) {
   var items = [];

  $.each(data, function(key, val) {
     items.push('' + val + '');
   });

  $('', {
     'class': 'my-new-list',
     html: items.join('')
   }).appendTo('body');
});
```

cross site scripting

# JSONP

# cross site scripting JSONP

```
<!DOCTYPE html>
<html>
<head>
  <title>JSONP Example</title>
  <script src="http://ajax.googleapis.com/ajax/libs/jquery/1.9.1/jquery.min.js"></script>
</head>
<body>
  <div id="images">
  </div>
  <script>
  $.getJSON("http://api.flickr.com/services/feeds/photos_public.gne?jsoncallback=?",
    tags: "mount rainier",
    tagmode: "any",
    format: "json"
  },
  function(data) {
    $.each(data.items, function(i,item){
      $("<img/>").attr("src", item.media.m).appendTo("#images");
      if ( i == 3 ) return false;
    });
  });</script>
</body>
```

</html>

# cross site scripting JSONP

```
{
   "title": "Recent Uploads tagged mountrainier",
   "link": "http://www.flickr.com/photos/tags/mountrainier/",
   "description": "",
   "modified": "2013-03-05T06:15:36Z",
   "generator": "http://www.flickr.com/",
   "items": [
       "title": "Three volcanoes.",
       "link": "http://www.flickr.com/photos/urbanadventureleaguepdx/8529486681/",
       "media": {"m":"http://farm9.staticflickr.com/8367/8529486681_362bc972f8_m.jpg"},
       "date_taken": "2013-03-04T15:26:19-08:00",
       "published": "2013-03-05T06:15:36Z",
   "author": "nobody@flickr.com (urbanadventureleaguepdx)",
       "author_id": "63964930@N05",
       "tags": "mountrainier mountsthelens mountadams"
   },
{
       "title": "Flew home to a sunny day.",
       "link": "http://www.flickr.com/photos/architecturegeek/8530441688/",
       "media": {"m":"http://farm9.staticflickr.com/8383/8530441688_07f87db69f_m.jpg"},
       "date_taken": "2013-03-04T15:03:38-08:00",
       "published": "2013-03-05T03:39:39Z",
       "author": "nobody@flickr.com (architecturegeek)",
       "author_id": "42788598@N00",
       "tags": "seattle sky air aerial mountrainier mtrainier airplanewindow virginamerica"
     }]
```

# cross site scripting JSONP

```
jQuery191038457776024006307_1362672677064({
     "title": "Recent Uploads tagged mountrainier",
     "link": "http://www.flickr.com/photos/tags/mountrainier/",
     "description": "",
     "modified": "2013-03-05T06:15:36Z",
     "generator": "<a href="http://www.flickr.com/",">http://www.flickr.com/",</a>
     "items": □
     {
         "title": "Three volcanoes.",
         "link": "http://www.flickr.com/photos/urbanadventureleaguepdx/8529486681/",
         "media": {"m":"http://farm9.staticflickr.com/8367/8529486681_362bc972f8_m.jpg"},
         "date_taken": "2013-03-04T15:26:19-08:00",
         "published": "2013-03-05T06:15:36Z",
         "author": "nobody@flickr.com (urbanadventureleaguepdx)",
         "author_id": "63964930@N05",
         "tags": "mountrainier mountsthelens mountadams"
    },
{
         "title": "Flew home to a sunny day.",
         "link": "http://www.flickr.com/photos/architecturegeek/8530441688/",
         "media": {"m":"http://farm9.staticflickr.com/8383/8530441688_07f87db69f_m.jpg"},
         "date_taken": "2013-03-04T15:03:38-08:00",
         "published": "2013-03-05T03:39:39Z",
         "author": "nobody@flickr.com (architecturegeek)",
         "author_id": "42788598@N00",
         "tags": "seattle sky air aerial mountrainier mtrainier airplanewindow virginamerica"
     }
```



#### **CONTENTS INCLUDE:**

- Getting to Know HTTP
- Tips for Using XHR
- Ajax and Architecture
- Ajax Toolkits
- · Ajax User Interfaces
- Hot Tips and more..

### Getting Started with Ajax

By Dave Crane

#### **GETTING STARTED**

The standard way to do Ajax is to use the XMLHttpRequest object, known as XHR by its friends. Use XHR directly, or via one of the helpful Ajax libraries such as Prototype or jQuery. How do we use XHR "by hand"? To start with, we need to get a reference to it:

```
if (window.XMLHttpRequest) {
   xhr = new XMLHttpRequest();
} else if (window.ActiveXObject) {
   xhr = new ActiveXObject("Microsoft.XMLHTTP");
}
```

We can then open a connection to a URL:

```
chr.open(
    "GET",
    "my-dynamic-content.jsp?id="
    +encodeURI(myId),
    true
);
```

Specify a callback function to receive the response:

```
xhr.onreadystatechange = function(){
   processReqChange(req);
}
```

and then send the request:


xhr.send(null);

The server may be busy, or the network may be slow. We don't want to sit around doing nothing until the response arrives, and because we've assigned the callback function, we don't have to. That's the five-minute guide for the impatient. For those who like to know the details, we've listed the fuller details of the XHR object below.

Method Name	Parameters and Descriptions	
open(method, url, async)	open a connection to a URL method = HTTP verb (GET, POST, etc.) url = url to open, may include querystring async = whether to make asynchronous request	
onreadystatechange	assign a function object as callback (similar to onclick, onload, etc. in browser event model)	
setRequestHeader (namevalue)	add a header to the HTTP request	
send(body)	send the request body = string to be used as request body	
abort()	stop the XHR from listening for the response	
readyState	stage in lifecycle of response (only populated after send() is called)	
httpStatus	The HTTP return code (integer, only populated after response reaches the loaded state)	
responseText	body of response as a JavaScript string (only set after response reaches the interactive readyState)	
responseXML	body of the response as a XML document object (only set after response reaches the interactive readyState)	
getResponseHeader (name)	read a response header by name	
getAllResponseHeaders()	Get an array of all response header names	

#### **GETTING TO KNOW HTTP**

To make use of the XHR to its fullest, we recommend you become familiar with the workings of the HTTP protocol. Using Ajax, you have much more control over HTTP than with classic web app development.



 $\label{eq:http} \mbox{HTTP is a stateless request-response protocol}.$ 

- Both request and response contain headers and an optional body, which is free text.
- Only a POST request contains a body.
- A request defines a verb or method.
- The Mime type of request and response can be set by the header Content-type





#### **Get More Refcardz**

(They're free!)

- Authoritative content
- Designed for developers
- Written by top experts
- Latest tools & technologies
- Hot tips & examples
- Bonus content onlineNew issue every 1-2 weeks

Subscribe Now for FREE!
Refcardz.com

DZone, Inc. | www.dzone.com

