

# Music Moves

Wim Looman

Electrical and Computer Engineering  
University of Canterbury  
Christchurch, New Zealand  
[wgl18@uclive.ac.nz](mailto:wgl18@uclive.ac.nz)

Richard Green

Computer Science and Software Engineering  
University of Canterbury  
Christchurch, New Zealand  
[richard.green@canterbury.ac.nz](mailto:richard.green@canterbury.ac.nz)

**Abstract**—This report details the design and implementation of an “air drum” interactive music program. Various methods for implementing this on consumer hardware utilising a simple webcam are explored. The results from this, while not entirely working, are definitely promising. The marked hand tracking worked effectively and the neural net based gesture recognition was able to generate a surprisingly high proportion of matches. Unfortunately the initial plan of having a MIDI output that could be connected to an actual music program such as GarageBand was sadly not achieved.

## I. INTRODUCTION

The goal of this project is to create an interactive music program that can generate music based by analysing the movement of a human body or hand position. This will be capable of running in real time on a consumer pc utilising a single webcam.

A lot of different methods for producing movement from sound have been researched. Some of these involve using the hands to “shape” the music, for example having a 2d pointer (which could easily be generated from a hand tracking algorithm) that affects the music based on a set of simple gestures [1]. Others attempt to provide a more traditional musical interface, albeit without the actual instrument. This can be a simple interface such as a DJ’s deck [2], or a more complex interface like a full piano [3] or guitar [4].

Whilst the first approach will probably lead to a more novel category of research, it would also require a deep understanding of music theory. Therefore the second approach was the one chosen for investigation.

One instrument that hasn’t been widely studied for video based playing is the air drum. It would have to be wondered why; the drum simultaneously provides both a complex interface, the 3d position of the imaginary sticks, and a simple interface, only around 3-10 different drums/cymbals to hit depending on the drum set.

To enable the user to play the air drum just via a normal webcam a robust algorithm for turning their motions into sound will be needed.

### A. Hand Tracking

There are a few possibilities for the hand tracking, with or without marks. With marks we could have the user wearing a pair of brightly coloured gloves, or holding a pair of brightly coloured drumsticks. Without

marks we could attempt an implementation of the Kalman filter to track the front/tops of the users fist/d hands.

### B. Strike Detection

### C. Sound Output

## II. IMPLEMENTATION

### A. Hand Tracking

To make this simpler the mark based tracking was chosen, specifically a pair of brightly coloured gloves. This will limit the subjects clothing in that it cannot contain the same colour as the gloves. However it greatly simplifies the hand tracking to just following the specific colour of the gloves.

The tracking will involve two stages, target acquisition & learning and the actual tracking. During acquisition and learning the user will start with their hands behind their back, then hold them in a few positions in front of the camera. This will produce a series of images which will be automatically processed to attempt to compensate for the lighting conditions. Once an accurate enough colour sample has been achieved the actual tracking will be started.

## III. RESULTS

### A. Hand tracking

The hand tracking worked successfully, using the bright red gloves provided a very distinct edge in the filtered image. This could then simply have the centroid calculated for the hand position.

## IV. CONCLUSION

## REFERENCES

- [1] K. Jensen, “Aspects of the multiple musical gestures,” *Journal on data semantics*, vol. 3902, pp. 140–148, Jan. 2006.
- [2] B. Yetton and R. Green, “Virtualmix - virtual dj interface using computer vision,” 2010, produced for COSC428.
- [3] R. I. Godøy, E. Haga, and A. R. Jensenius, “Playing ‘air instruments’: Mimicry of sound-producing gestures by novices and experts,” *Journal on data semantics*, vol. 3881, pp. 256–267, Jan. 2006.
- [4] Y. Pan and R. Green, “A mark-less air guitar game through computer vision,” 2010, produced for COSC428.
- [5] B. Chong and R. Green, “Music moves,” 2010, produced for COSC428.
- [6] L. Tarabella, “Handel, a free-hands gesture recognition system,” in *Proceedings of the 2004 Second International Symposium Computer Music Modeling and Retrieval*. University Esbjerg, Denmark, 2004.

- [7] T. Winkler, "Making motion musical: Gesture mapping strategies for interactive computer music," *Computer*, 1995.
- [8] G. Castellano, R. Bresin, A. Camurri, and G. Volpe, "User-centered control of audio and visual expressive feedback by full-body movements," in *Proceedings of the 2nd international conference on Affective Computing and Intelligent Interaction*, ser. ACII '07. Berlin, Heidelberg: Springer-Verlag, 2007, pp. 501–510. [Online]. Available: [http://dx.doi.org/10.1007/978-3-540-74889-2\\_44](http://dx.doi.org/10.1007/978-3-540-74889-2_44)
- [9] A. Yilmaz, O. Javed, and M. Shah, "Object tracking: A survey," *ACM Comput. Surv.*, vol. 38, December 2006. [Online]. Available: <http://doi.acm.org/10.1145/1177352.1177355>
- [10] D. Popa, G. Simion, V. Gui, and M. Otesteanu, "Real time trajectory based hand gesture recognition," *WSEAS Trans. Info. Sci. and App.*, vol. 5, pp. 532–546, April 2008. [Online]. Available: <http://portal.acm.org/citation.cfm?id=1481952.1481972>
- [11] R. Behringer, "Gesture interaction for electronic music performance," in *Proceedings of the 12th international conference on Human-computer interaction: intelligent multimodal interaction environments*, ser. HCI'07. Berlin, Heidelberg: Springer-Verlag, 2007, pp. 564–572. [Online]. Available: <http://portal.acm.org/citation.cfm?id=1769590.1769654>
- [12] A. Salgian, M. Pfirrmann, and T. Nakra, "Follow the beat? understanding conducting gestures from video," in *Advances in Visual Computing*, ser. Lecture Notes in Computer Science, G. Bebis, R. Boyle, B. Parvin, D. Koracin, N. Paragios, S.-M. Tanveer, T. Ju, Z. Liu, S. Coquillart, C. Cruz-Neira, T. Müller, and T. Malzbender, Eds. Springer Berlin / Heidelberg, 2007, vol. 4841, pp. 414–423. [Online]. Available: [http://dx.doi.org/10.1007/978-3-540-76858-6\\_41](http://dx.doi.org/10.1007/978-3-540-76858-6_41)
- [13] K. Bowyer, C. Kranenburg, and S. Dougherty, "Edge detector evaluation using empirical roc curves," *Computer Vision and Image Understanding*, vol. 84, no. 1, pp. 77 – 103, 2001. [Online]. Available: <http://www.sciencedirect.com/science/article/B6WCX-4582BV1-6/2/ad72aaf94049253f5333f721b9afdb69>