Proof of One

One human · One identity · One voice

An Open, Verifiable Polling Network Built on One-Person-One-Identity

Whitepaper — Version 0.7 (Public Review Draft)

October 2026

Nemo Unus, with the Proof of One AI agent team

Open-source, non-commercial project. Draft for public review. Not audited: all designs require independent human review before use with real participants.

Contents

1. Executive Summary....4
2. The Problem....4
2.1 Online opinion cannot be trusted....4
2.2 The verification gap in collective decisions....5
2.3 Why existing digital identity does not solve it....5
3. Vision: the Missing Human Layer....5
4. Design Principles....5
5. Landscape and Differentiation....6
5.1 What is different....6
6. System Architecture....7
6.1 Separation of functions....7
6.2 Process overview....7
6.3 Enrolment steps....10
6.4 Reading the identity document....10
6.5 Face matching in the enclave....10
6.6 Layer 1 — document uniqueness....11
6.7 Layer 2 — face uniqueness....11
6.8 The member's keys....11
6.9 Verified attributes and selective disclosure....12
6.10 Recovery....12
6.11 What each party sees....12
6.12 Several nationalities, one identity....13
7. Cryptographic Specification....13
7.1 Design goals....13
7.2 Proposed primitive suite....13
7.3 Keys and identity commitment....14
7.4 The enrolment proof....14
7.5 Document fingerprint protocol....15
7.6 Enclave channel and face template....15
7.7 Answering a poll....16
7.8 Verifying one's own vote and recounting....16
7.9 Verified breakdowns without exposing small groups....16
7.10 Unlinkable registration....17
7.11 Revocation without linking....17
7.12 Cryptographic agility and the quantum horizon....17
8. Ledger Design....17
8.1 Choice of network....17
8.2 Contracts....18
8.3 Registering a member....18
8.4 Creating a poll and the membership snapshot....19
8.5 Recording a ballot....19
8.6 Relay service: no cryptocurrency, no IP address....19
8.7 Closing, tallying and publishing....19
8.8 On-chain and off-chain data....20
8.9 Scale and cost....20
8.10 Contract governance....21

8.11 Reference implementation....21
9. Core Product: Verifiable Polling....22
9.1 Poll lifecycle....22
9.2 The private ballot number....22
9.3 Protecting participants....22
9.4 Assurance modes....23
9.5 Verified demographic results....23
10. Community Agenda and Free Participation....23
10.1 Regions and the global track....23
10.2 Monthly topic selection....24
10.3 Budget rule....24
10.4 Neutral wording and visible manipulation....24
11. Further Applications....24
12. Security and Threat Model....24
12.1 The fundamental limit....25
12.2 Main threats....25
13. Open Source and the Human–AI Team....26
13.1 Open-source practice....26
13.2 The team....26
13.3 Growing the human part of the work....28
14. Governance, Legal and Ethical Considerations....28
15. Roadmap....29
16. Funding Principles....29
17. Known Limitations and Open Questions....30
18. Conclusion....31
References....31
Glossary....32

1. Executive Summary

Public opinion is now measured online, but online opinion can no longer be trusted. Bots and AI agents can produce thousands of convincing "respondents" for almost nothing, one person can answer many times, the age or nationality a respondent claims cannot be checked, and nobody outside the organiser can verify that a published result is the true count of what people answered.

Proof of One is an **open-source, non-commercial protocol** that lets anyone in the world take part in polls in which every participant is a real, unique human who can register only once, and no one — including the people who run the system — can see who answered what. A member enrols once with an ordinary smartphone, by reading the electronic chip of their passport or national ID card and matching their live face to the photo stored on that chip. The network learns only that this is a genuine, unique person with certain verified attributes, such as an age band and a nationality.

Two properties are fixed and non-negotiable:

- **Every participant can verify their own vote.** Each participant can check, from their own phone, exactly what was recorded on the public ledger for their vote and that it was included in the count.
- **Anyone can recount the result.** Every ballot is published in encrypted form; anyone can add them up and check the published totals and the mathematical proofs that they were decrypted correctly, without trusting any operator.

Around these, the design adds strong protection for participants: ballots are encrypted so that even a seized phone or a stolen key does not reveal past answers once a short verification window has passed; the service that checks uniqueness cannot link a person to their anonymous identity; and participation is **free** for everyone. The topics of sponsored polls are **chosen by participants themselves**, region by region, with a global track for questions that concern everyone.

Who can take part today. Anyone who holds a chip passport or chip ID card that a phone can read. That is roughly **one person in six** worldwide today, about one billion people or more, with large gaps in South Asia and Africa. The share grows every year as countries switch to chip documents (6.4). People with more than one nationality keep one identity that carries each verified nationality (6.12).

The project is led by a pseudonymous founder, **Nemo Unus**, and developed openly with a team of **disclosed AI agents** whose work is published for review by independent human experts. All code and specifications are open source. Nothing will be used with real participants until it has passed a public test network, a bug bounty and an independent human audit.

> **Design commitment: one human, one voice — owned by the person, verifiable by anyone, controlled by no single government, company or operator.**

2. The Problem

2.1 Online opinion cannot be trusted

- **Fake participants.** Generative AI makes it cheap to create accounts, faces and convincing written answers at scale. Online polls, petitions and review systems cannot tell people from machines.
- **Duplicate participants.** One person with several e-mail addresses or phone numbers can answer many times.

- **Unverifiable demographics.** Respondents state their own age, nationality and location; nobody can check them, so breakdowns by group are only as honest as the respondents.
- **Unverifiable results.** Results are published by the organiser. Participants cannot confirm that their answer was counted, and the public cannot recount.

2.2 The verification gap in collective decisions

The same gap exists in formal decision-making. Registering participants, collecting votes and counting them are usually operated and verified by a single authority. Participants are asked to trust the announced result. Where the counting authority is not independent, manipulation is possible and hard to prove; and because each consultation is expensive, people are consulted rarely.

2.3 Why existing digital identity does not solve it

Proof-of-personhood projects (Section 5) show strong demand but leave gaps: some depend on proprietary scanning hardware; some accept a single identity document, so a person with two passports can register twice; national digital wallets stop at a country's borders; and none treats verifiable public opinion as its primary purpose.

3. Vision: the Missing Human Layer

The internet has infrastructure for addressing computers, moving data and making payments, but none for humans. It cannot tell whether an account belongs to a person or a program, or whether a hundred accounts belong to one person. In an era when AI can produce convincing synthetic people at almost no cost, this gap becomes critical. Proof of One aims to provide that missing layer, starting with the use case that needs it most.

Pillar	What it enables	Status
1. Verifiable collective decisions	Polls, consultations, petitions and — where legally authorised — binding votes, with results anyone can check	**First product: verifiable polling**
2. Fair distribution	Anything allocated "one per person": aid, quotas, ticketing, rewards, and potentially a share of value created by AI	Later phase
3. Human authenticity	Proof that a voice, review, piece of content or decision comes from a real, unique human	Later phase

4. Design Principles

Principle	What it means in practice
One human, one identity	A person can hold only one active identity. Both the identity document and the face are checked for duplicates at enrolment.
Verifiable by the voter and by everyone	Each participant can check their own recorded vote; anyone can recount every total from public data.
Participant safety first	Where safety, integrity and convenience conflict, the safety of participants wins. The design assumes an adversary with the resources of a state.

Principle	What it means in practice
Private, not anonymous	Every member is a verified, unique real person, but no one can link an answer — or an anonymous identity — to a person.
Data minimisation	Passport data and face images are processed on the phone and in an isolated enclave; nothing personal is written to the ledger.
Free and neutral	Participation costs nothing. The project does not choose poll topics; participants do.
Open source, non-commercial	All code and specifications are public. There is no business model, token or investor.
Ordinary hardware	A mainstream smartphone with a camera and NFC is enough. No proprietary scanner is required.
Progressive decentralisation	Trust is spread across independent operators and trustees in different jurisdictions as the network grows.
Honesty about limits	Known weaknesses are documented (Sections 12 and 17), including what the system cannot do against a state that issues identity documents.

5. Landscape and Differentiation

Initiative	Approach	Uniqueness check	Polling focus
World ID	Iris scan by a proprietary Orb; anonymous proof of human. Over 18 million Orb-verified users reported in 2026 [1]	Iris (biometric)	Not primary
Humanity Protocol	Palm scan and zero-knowledge proofs; mainnet since August 2025 [2]	Palm (biometric)	No
Human Passport	Aggregates many independent checks into a humanity score [3]	Score, not guaranteed	Indirect
Self, ZKPassport	Read the passport chip by NFC and prove attributes with zero-knowledge proofs [4] [5]	Document only	No
National wallets (EU, Bhutan)	Government-issued digital identity [7][8]	Government registry	No
Online survey panels	Respondents recruited and checked by the panel operator	Operator's own checks	Yes, but results not publicly verifiable
Vocdoni, MACI	Blockchain and zero-knowledge voting protocols [13]	Voter list supplied by organiser	Yes
Proof of One	**Passport chip + live face on a phone; verifiable polls with verified demographics**	**Document and face**	**Core product**

5.1 What is different

- **Two-layer uniqueness.** Document-only systems let a person with two passports register twice; biometric-only systems on a phone are open to synthetic faces. Requiring a government-signed document **and** a face that matches it, and checking both for duplicates, closes both gaps.

- **Verified demographics without identification.** Results can be reported by verified age band and nationality, which ordinary online polls cannot offer, while answers remain unlinkable to individuals.
- **Public verifiability as the purpose,** not an add-on: every answer can be checked by its author, and every total by anyone.
- **No proprietary hardware.** The phone's NFC reader and camera replace a network of scanning stations.

6. System Architecture

6.1 Separation of functions

An identity system has to answer three different questions. Proof of One answers each with a different mechanism:

Function	Question	Mechanism
Uniqueness	Has this person registered before?	Document fingerprint and face template, checked once at enrolment inside an isolated enclave (6.6, 6.7)
Ownership	Is this request coming from the holder of this identity?	Identity secret held on the phone, protected by secure hardware and the user's PIN (6.8)
Recovery	The phone is lost or the passport renewed — how is access restored?	Restoring the encrypted backup, or re-enrolment after a cooling-off period with automatic revocation of the old identity (6.10)

Neither the passport number nor biometric data is used to build the user's key. Passports are renewed with new numbers, and two scans of a face are never identical, so either would make the key unstable. Biometric features are also not secret: a face appears in photographs. Biometrics are therefore used only to establish uniqueness, never as a key.

6.2 Process overview

Figures 1 and 2 show the complete process across the four parties: the member's phone, the uniqueness service, the public ledger, and the poll organiser and public.




Figure 1 — Enrolment. Four checks run in the uniqueness service; each failure stops enrolment. The service signs a credential over a hidden commitment, and the phone registers its identity later, unlinkably (6.3, 7.10).




Figure 2 — Answering a poll, tally and verification. Ballots are encrypted on the phone; only totals are decrypted, with public proofs; the contract rejects any result whose totals do not match the participants (7.7, 8.7).

6.3 Enrolment steps

1. The user installs the app — after checking its signing fingerprint against the published one — and creates a PIN. The phone generates its keys (6.8).
2. The user holds their passport or chip-based national ID card against the phone. The app reads the chip by NFC.
3. The phone builds a zero-knowledge proof that the document is genuine and in date, that the claimed attributes are correct, and that a commitment to the chip photo matches the signed document (7.4).
4. The user performs a live face scan; the phone adds a hardware attestation that the genuine app is running on an uncompromised device.
5. Over an anonymising network connection, the phone sends the proof, a commitment that hides its future identity, and — encrypted so that only the attested enclave can open it — the chip photo and the live face frames (7.6).
6. The uniqueness service verifies the proof, checks the document fingerprint (Layer 1), and inside the enclave matches the live face to the chip photo and checks the face for duplicates (Layer 2).
7. If every check passes, the enclave deletes the images and returns a signed **credential** over the hidden commitment.
8. Hours later, in a separate session, the phone registers its identity on the ledger with a zero-knowledge proof that it holds a valid credential, without revealing which one (7.10). Identities are added to the ledger only in large batches (8.3).

6.4 Reading the identity document

Most passports issued today, and many national ID cards, contain a contactless chip defined by the ICAO 9303 standard [6]. Data group DG1 holds the data printed on the photo page (name, document number, nationality, date of birth, sex, expiry), DG2 holds the facial image, and the Document Security Object (SOD) holds the hashes of all data groups, signed by a Document Signer Certificate (DSC) that is in turn signed by the issuing state's Country Signing CA (CSCA). Reading the chip is required instead of uploading a photo of the document, because a photo can be fabricated in seconds while the signature chain cannot. Where the chip supports active or chip authentication, it is used to detect cloned chips.

How many people hold such a document. A country-by-country study published with this paper [36] finds the following. About 73% of the world's population lives in countries that issue chip passports as standard, and 94% when India and Pakistan are included; both are now switching over. About 82% lives in such a country that also publishes its document-signing certificates in the ICAO Public Key Directory [37], and the genuineness of a document can only be checked with these certificates. About 60 countries also issue identity cards with a compatible chip. Issuing is not holding, however. Over one billion chip passports are in circulation [38], about 12% of the world's population, and chip ID cards add several hundred million more. **Realistically, about 15–20% of people can enrol today.** The largest gaps are countries with no chip documents yet, such as Egypt, South Africa, Myanmar and Afghanistan, and countries where few people hold a passport at all. National ID cards with other chip standards, for example in China, India and Indonesia, are left for regional extensions after the main launch, to be built openly with developers from those countries (Decision Log #32).

6.5 Face matching in the enclave

Zero-knowledge proofs show that a computation on given inputs was correct; they cannot show that an input came from a real camera. Face matching and template extraction therefore run inside the

uniqueness service's hardware enclave, not on the phone. The enclave checks that the chip photo it receives is the one committed in the proof, runs liveness and face matching against that photo, and builds the face template itself — so a modified app cannot submit someone else's template. The authenticity of the camera feed rests on the phone's hardware attestation and presentation-attack detection, which is recorded as a residual risk (Section 12).

6.6 Layer 1 — document uniqueness

From stable fields of DG1 the phone derives a **document fingerprint** through an oblivious pseudorandom function (OPRF) whose key is held by the uniqueness service (7.5). Because passport data has relatively few possible combinations, a plain hash could be reversed by trying every possibility; the keyed OPRF prevents this, and its blinding ensures the service computes the fingerprint without seeing the data. Stable fields are used instead of the document number, so a renewed passport produces the same fingerprint.

6.7 Layer 2 — face uniqueness

Layer 1 does not stop a person who holds two different documents. Layer 2 compares the new face template with existing templates. Version 0.4 limited this search to members with the same date of birth and sex. Red-team review showed that this is unsafe against an issuer of documents, which can print a different birth date in each document for the same person. Version 0.5 therefore removes date of birth from the search: duplicates are searched **across all members** (or within sex only), using an approximate-nearest-neighbour index and a strict threshold for candidates.

Searching a large population increases the chance that two different people look alike. The final method and threshold will be chosen only after the accuracy study measures false-match and false-reject rates at one million, ten million and one hundred million members. A one-way hash of the face cannot replace this comparison: a hash destroys similarity, so two scans of the same face would produce unrelated values, and a coarsened template would be guessable from a public photograph.

Stage	Protected comparison	Trust assumption
Test network and low-risk pilot (Phases 0–2)	Encrypted templates compared inside a hardware-isolated enclave (for example AWS Nitro Enclaves)	Enclave hardware and cloud provider; reproducible, independently audited enclave code
Before any use in high-risk settings (Phase 3)	Templates split into secret shares across independent operators in different jurisdictions and compared by multi-party computation (MPC)	No single operator, company or government; a threshold of operators would have to collude

6.8 The member's keys

The phone holds two keys with different jobs (7.3): a **device key** generated inside the secure hardware, used to protect local data and bind the app to the device; and an **identity secret**, used only inside zero-knowledge proofs, stored encrypted under the device key and backed up end-to-end encrypted by the user. From the identity secret the phone derives a readable **member number** for the user's own reference, for example:

> **ONE-7Q4KM-9M2XH-8T3VA-5RZ0P-K**

The member number is never published or sent anywhere. The ledger stores only an identity leaf — a hash that reveals nothing about the person — and never names, document numbers or biometric data.

6.9 Verified attributes and selective disclosure

Attributes read from the chip stay on the phone as bands (for example, age band 40–49) and are sealed in an attribute commitment inside the member's ledger entry (8.3). When a poll needs them, the phone proves in zero knowledge exactly what is required, such as "aged 18 or over" or "national of country X", without revealing the underlying values.

6.10 Recovery

- **Lost or replaced phone, backup available:** the user restores the encrypted backup of the identity secret on a new phone. The identity is unchanged and nothing is written to the ledger.
- **No backup available:** the user re-enrols with their document and a live face match. The enclave recognises the person, waits a cooling-off period (for example 14 days), then publishes the old identity's hidden **revocation handle** and issues a new credential. The old identity can no longer take part in any poll; the enclave still cannot tell which ledger entry was revoked (7.11).
- **Renewed passport:** the member adds the new document to their existing identity, which updates its expiry (6.12). The person remains recognised as already enrolled.
- **Open polls:** each poll fixes its membership and revocation snapshots when it opens, so a recovered identity cannot answer an open poll twice (8.4).

6.11 What each party sees

Data	Member's phone	Uniqueness service	Public ledger
Passport data (DG1)	Yes	Attributes only; fingerprint input blinded	No
Chip photo and live face images	During the scan	Inside the enclave only; deleted after checks	No
Face template	No	Encrypted; compared only in the enclave (later MPC)	No
Document fingerprint	Yes	Yes	No
Identity leaf	Yes	**No** — sees only a hiding commitment	Yes (reveals nothing)
Age band, nationality	Yes	Yes, at enrolment	Hidden inside the leaf
Content of an answer	Own answer, during the receipt window	No	Encrypted; only totals decrypted
Whether a member took part	Own participation	No	Not linkable without the member's secret

6.12 Several nationalities, one identity

Some people hold genuine documents from more than one country. Refusing the second document as a duplicate would exclude them from the regional polls of their other country. Proof of One therefore lets a member **add a further document to their existing identity** (Decision Log #30) [39]:

- The enclave checks the new document as at enrolment. It also checks that the document has not been used by anyone and that its chip photo and the live face match **this** member's own face template.
- The member's identity then carries up to three documents, each with its own nationality and expiry. The phone keeps the same identity secret. The enclave issues an updated credential, and the previous identity is revoked with the hidden revocation handle (7.11).
- The member may vote once in the regional polls of each of their nationalities. In global polls, as in every poll, they cast one ballot, because the nullifier is derived from the identity secret, not from a document.
- Each ballot proof shows only that **one** of the member's valid documents matches the poll's region. Which document was used, and the member's other nationalities, stay hidden. Adding a document is optional, and results are never broken down by combination of nationalities.

7. Cryptographic Specification

This section proposes concrete algorithms for each function. The choices favour open standards, audited open-source implementations and compatibility with existing passport and zero-knowledge tooling. They are proposals for Phase 0 and will be confirmed by independent cryptographic review.

7.1 Design goals

- **Standards first:** use published standards (ICAO 9303, RFC 9497, RFC 9180) and widely reviewed constructions rather than new cryptography.
- **Proof-friendly where proofs are needed:** use arithmetic-friendly primitives (Poseidon, Baby Jubjub) inside zero-knowledge circuits, and conventional primitives (SHA-256, P-256, AES-GCM) elsewhere.
- **Hardware-backed keys:** every long-lived secret is generated in, or encrypted by, the phone's secure hardware.
- **Cryptographic agility:** every record carries an algorithm version so that primitives can be replaced, including by post-quantum alternatives.

7.2 Proposed primitive suite

Purpose	Proposed primitive	Reason
Hash inside circuits	Poseidon over the BN254 scalar field [23]	Far fewer constraints than SHA-256 inside zero-knowledge proofs
Hash outside circuits	SHA-256	Matches passport SOD hashing; universal support
Device key	ECDSA P-256 in Secure Enclave / StrongBox	Natively supported by phone secure hardware and attestation

Purpose	Proposed primitive	Reason
Identity secret	EdDSA key on the Baby Jubjub curve [29]	Efficient to use inside BN254 circuits; same model as Semaphore [12]
Poll membership proofs	Groth16 on BN254 [24]	Smallest proofs and cheapest on-chain verification; reuses Semaphore's audited circuits and setup
Document proofs	Universal-setup system such as PLONK / UltraHonk [25]	One circuit per signature algorithm; no per-circuit trusted setup; reuses open passport circuits [4][5]
Document fingerprint	2HashDH OPRF with verifiable mode, structure of RFC 9497 [21]	Keyed and blinded: the service never sees the input; outputs cannot be brute-forced
Channel to the enclave	HPKE (RFC 9180): X25519, HKDF-SHA256, AES-256-GCM [22]	Standard public-key encryption, key bound to the enclave's attestation document [28]
Template storage	AES-256-GCM, key released only to attested enclave code	Templates are unreadable outside the enclave
Enrolment credential	EdDSA on Baby Jubjub, verified inside a zero-knowledge proof	Lets a member prove they hold a credential without revealing which one
Ballot encryption and tally	Exponential ElGamal on Baby Jubjub; threshold key from a distributed key generation; Chaum–Pedersen (DLEQ) decryption proofs [30][33]	Additively homomorphic: anyone can add encrypted ballots; trustees decrypt only totals and prove they did so correctly
Revocation set	Indexed (sorted) Merkle tree with non-membership proofs	Proves a hidden handle is not revoked without revealing it

7.3 Keys and identity commitment

At enrolment the phone creates the following values. Only commitments and hashes ever leave the phone.

```
K_dev   = P-256 key pair in secure hardware (non-exportable)
s       = random Baby Jubjub scalar (identity secret)
          stored as Enc_K_dev(s); backup end-to-end encrypted
P       = s · G                          (Baby Jubjub public key)
idc     = Poseidon(Px, Py)               (identity commitment)
attr    = Poseidon(ageBand, sexCode, nat_0, exp_0, nat_1, exp_1,
                   nat_2, exp_2, salt_a)   (up to 3 documents, 6.12)
rn      = revocation handle issued by the enclave (7.11)
leaf    = Poseidon(idc, attr, rn)        (entry in the registry tree)
cm      = Poseidon(idc, salt_a, ρ)       (hiding commitment for enrolment)
cn      = Poseidon(ρ)                    (credential nullifier)
```

7.4 The enrolment proof

The phone proves the following statement in zero knowledge. Private inputs never leave the phone; public inputs are seen by the uniqueness service.

	Values
Private inputs	DG1, DG2 hash, SOD, Document Signer Certificate, CSCA public key and its Merkle path, salts r_f and salt_a, ρ, idc
Public inputs	Root of the trusted CSCA key list; today's date; claimed attribute bands; C_face; blinded fingerprint input B; the hiding commitment cm; a fresh challenge from the service

1. **Integrity:** SHA-256(DG1) and the DG2 hash equal the values listed in the SOD.
2. **Authenticity:** the SOD signature verifies under the DSC; the DSC signature verifies under a CSCA key; that key is a leaf of the trusted CSCA list.
3. **Validity:** the expiry date in DG1 is later than today.
4. **Attributes:** the age band and nationality code are correctly derived from DG1.
5. **Photo binding:** C_face = Poseidon(DG2-hash, r_f), tying the photo sent to the enclave to the signed document.
6. **Fingerprint input:** B is the blinding of the stable DG1 fields described in 7.5.
7. **Binding:** the proof includes cm and the service's challenge, so it cannot be replayed. The service never learns idc or the future identity leaf.

7.5 Document fingerprint protocol

```
Phone:   x = HashToCurve(nationality || dateOfBirth || name || sex)
         r = random scalar;  B = r · x       (blinded; sent with proof)
Service: Z = k · B, with proof that key k was used  (k = service secret)
Phone:   F = Hash(x, r⁻¹ · Z)                (document fingerprint)
Ledger:  stores F; any repeated F is rejected
```

For the circuit in 7.4 to prove that B is derived from the signed fields, the OPRF is instantiated over the circuit-friendly Baby Jubjub group, following the 2HashDH structure of RFC 9497. In Phase 3 the key k is split across operators (threshold OPRF), so no single party can compute fingerprints alone.

7.6 Enclave channel and face template

- The enclave publishes an attestation document containing the hash of its code and its HPKE public key. The phone verifies the attestation against the published, reproducible build before encrypting anything to it.
- The phone sends HPKE-encrypted: the DG2 photo, r_f, and a short sequence of live face frames.
- Inside the enclave: check Poseidon(SHA-256-based DG2 hash, r_f) = C_face; run liveness and face matching; compute a face embedding (for example a 512-value vector from a published face-recognition model); delete all images.
- Templates are stored encrypted and compared by similarity across all members (6.7); the match threshold is calibrated on real data in the accuracy study.
- Output: a credential σ = Sign(Poseidon(attributes, cm, rn, epoch)) under an enclave key listed on the ledger (7.10).

7.7 Answering a poll

Each poll has its own tally public key PK, created by a committee of independent trustees through a distributed key generation; no single trustee holds the private key. A member's choice is encoded as a vector with a 1 in the chosen option and 0 elsewhere, and each position is encrypted:

```
nf     = Poseidon(pollId, s)          (nullifier: one per member per poll)
ballot = first 48 bits of nf, e.g. 7F3A-91C2-E04B  (private ballot number)
C_j    = (r_j · G,  v_j · G + r_j · PK)    for each option j
proof  : leaf is in the poll's snapshot tree; rn is not revoked;
         nf is derived from s; one document meets the eligibility rule;
         every v_j is 0 or 1 and they sum to 1;
         each C_j encrypts v_j under PK; bound to this submission
public : pollHash, nf, C   (pollHash binds the snapshot roots, pollId,
         PK, the eligibility rule and the submission context)
```

The ledger keeps the latest ballot per nullifier. A member who answers again produces the same nullifier, so the new ballot replaces the old one and is never counted twice. Because nf depends on the poll identifier, a member's nullifiers in different polls cannot be linked. All per-poll values — the two snapshot roots, the poll identifier, the tally key, the eligibility rule and the submission context — are bound into a single public value, **pollHash**, which the contract computes once when the poll is created. The proof therefore has only 18 public inputs: pollHash, the nullifier and the ciphertext coordinates. In the reference implementation (Section 8.11) the proof for four options, trees of depth 32 and up to three documents has **32,535 constraints**. The first measurement on a phone took **3.5 seconds per proof on an iPhone 14, inside its web browser**, without a native prover. A public benchmark page lets anyone repeat the measurement. Results from low-cost phones are still needed.

7.8 Verifying one's own vote and recounting

- **Own vote (recorded as cast).** The phone keeps the choice and the random values r_j for a receipt window chosen by the member for each vote — none, 7 or 30 days after the poll closes. During that window it recomputes the ciphertexts and checks that they match the ledger, using several independent data sources. Afterwards the record is deleted automatically.
- **Counted as recorded.** After publication, the phone checks that its ballot is the last one for its nullifier in the final ballot set, recomputes the totals and checks the decryption proofs.
- **Auditing the app (optional).** Before submitting, a member may choose to audit a ballot: the app reveals its random values so that anyone can check it encrypts the displayed choice; that ballot is discarded and a new one prepared [32].
- **Public recount.** Anyone can take every last ballot per nullifier, add the ciphertexts per option, combine the trustees' published partial decryptions and verify their proofs. The decrypted totals must equal the number of distinct participants.

7.9 Verified breakdowns without exposing small groups

When a poll reports results by a verified attribute (for example age band), the ballot vector is indexed by option and by the member's cell, and the proof shows that the cell matches the attribute hidden in the member's identity. Trustees first decrypt only the number of participants per cell; cells below the minimum size (for example 50) are merged by a rule fixed in advance, and only then are option totals decrypted. No individual ballot is ever decrypted.

7.10 Unlinkable registration

To keep the uniqueness service from linking a person to their identity on the ledger, the enclave signs only the hiding commitment cm. Later, the phone submits (leaf, cn) with a zero-knowledge proof of the following statement:

```
leaf = Poseidon(idc, Poseidon(attrs, salt_a), rn),  idc derived from s
cm   = Poseidon(idc, salt_a, ρ),   cn = Poseidon(ρ)
σ is a valid enclave signature on Poseidon(attrs, cm, rn, epoch)
      under a key in the published enclave key-set root
```

The enclave knows cm but not ρ or idc, so it cannot recognise leaf or cn; the proof reveals neither cm nor σ. The credential nullifier cn prevents one credential from being used twice. A random delay, an anonymising network, a minimum batch size for insertion and hiding the signing epoch protect against matching by timing.

7.11 Revocation without linking

At each enrolment the enclave derives a revocation handle rn from the person's document fingerprint and an enrolment counter, and includes it in the credential. rn is hidden inside the leaf. When a person re-enrols, the enclave publishes the old rn to a public revocation list. Every ballot proof shows that the member's hidden rn is not on that list. The enclave knows rn but not the leaf, so publishing it revokes the old identity without revealing which ledger entry it was. Every revocation is logged publicly with a reason code, and revocation counts are public, so unusual activity is visible.

7.12 Cryptographic agility and the quantum horizon

Every registry entry, poll and ballot records an algorithm version. The elliptic-curve primitives used here are not resistant to future large quantum computers: encrypted ballots kept on a public ledger could in principle be decrypted by such a computer in the future ("harvest now, decrypt later"). The design limits exposure by keeping personal data off the ledger, deleting trustee key shares after each tally, and planning migration to post-quantum encryption, signatures and proof systems as they mature. This remains an open question (Section 17).

8. Ledger Design

8.1 Choice of network

Option	Strengths	Weaknesses	Use
Ethereum mainnet	Highest security and neutrality	High and variable fees per answer	Periodic anchoring of state roots
Ethereum Layer-2 rollup	Low fees; inherits Ethereum security; EVM tooling and audited contracts	Sequencer operated by a company; data costs at very large scale	**Proposed for Phases 0–3**
Dedicated application chain	Full control of fees and validators	Must build its own validator security and neutrality	Option for later phases
Private or permissioned ledger	Simple to operate	Not publicly verifiable — defeats the purpose	Not used

Contracts use standard EVM interfaces so that they can be deployed on any EVM network. The chosen rollup must offer a working forced-inclusion path to Ethereum, so that no sequencer can permanently censor ballots, and its maturity will be checked against independent assessments such as L2BEAT at selection time [35].

Long-term availability. Rollups post their data to Ethereum as blobs that ordinary nodes keep for only about 18 days [26]. Recounting must remain possible for years, so after each poll the full ballot set is archived by several independent archivers on content-addressed storage, and the archive's hash is recorded on the ledger. Anyone can rebuild the archive from an archive node and compare.

8.2 Contracts

Contract	Holds	Key functions
IdentityRegistry	Merkle tree of identity leaves (depth 32); used credential nullifiers; queue of pending leaves; historical roots	register, insertBatch (with batch proof)
RevocationRegistry	Indexed Merkle tree of revoked handles; public revocation counters and reason codes	revoke (with revocation proof)
EnclaveKeyRegistry	Root of valid enclave signing keys; enclave image measurements matching reproducible builds	updateKeySet (time-locked)
PollRegistry	Poll parameters: content hash, options, eligibility rule, snapshot roots, eligible count, times, tally key, trustee set, verifier	createPoll (computes pollHash; checks the tally key), attachTallyKey
PollAnswers	Latest ballot per nullifier; re-vote counter; ordered ballot chain; count of distinct participants	vote
ResultsRegistry	Totals, decryption transcript hash, archive hash, challenge state	publish, challenge, finalize, markWithheld

Past polls cannot be changed. Each poll fixes, at creation, the verifier it uses and its snapshot roots. No later upgrade can alter how an existing poll is checked or counted.

8.3 Registering a member

```
register(leaf, cn, keySetRoot, proof)
  require cn not used; keySetRoot is valid; proof verifies (7.10)
  mark cn used; append leaf to the pending queue
  extend the batch chain hash: h = Poseidon(h, leaf)
insertBatch(newRoot, batchProof)              (anyone may call)
  require a full batch of B leaves is waiting (e.g. B = 1,024)
  require batchProof shows: the next aligned subtree of old root was
    empty, and newRoot = old root with exactly those B leaves, in order,
    matching the recorded chain hash h
  update root; record newRoot as a valid historical root
```

The reference implementation measured both approaches. Hashing a depth-32 path on the ledger costs about **1,050,000 gas per leaf**. Proving the update for a whole batch with one zero-knowledge proof, an approach already used in production [31], costs about **294,000 gas per batch** whatever its size — under 300 gas per leaf for a batch of 1,024. Revocations use the same idea: a revocation proof shows the new handle fits a gap in the sorted list and is appended at the next free slot, which cut the

cost of one revocation from about 4,000,000 to about **295,000 gas**. The minimum batch size also guarantees every new member a large anonymity set.

8.4 Creating a poll and the membership snapshot

When a poll is created, the current identity root and revocation root are stored as its **snapshots**, together with the number of eligible identities. Only members in the snapshot whose handle is not revoked can answer. Trustees then attach the poll's tally key with their signatures; ballots are accepted only after that. A poll stays open for at least 48 hours so that forced inclusion remains usable if a sequencer censors. The poll text and options are stored on content-addressed storage with their hash on the ledger, so the wording cannot be changed after publication.

8.5 Recording a ballot

```
vote(pollId, nf, C, ctxHash, proof)
  require poll open; C has the expected length
  rebuild public inputs from the poll's own pollHash, nf and C
  require proof verifies (never trust inputs from the submitter)
  require re-votes for nf below the cap (e.g. 10)
  if first ballot for nf: distinctVoters += 1
  latest[pollId][nf] = hash(C);  extend ballotChain[pollId]
  emit Ballot(pollId, nf, C, count)
```

Batched submission. A relay may submit many ballots of one poll in one transaction (voteBatch). All their proofs are checked together with random weights, which needs n + 3 pairing operations instead of 4n. Each ballot is then recorded exactly as if it had been sent alone, so the ballot chain and the recount do not change. One invalid proof rejects the whole batch, so a relay checks each proof before batching. Members can always submit directly.

8.6 Relay service: no cryptocurrency, no IP address

Members never need a crypto wallet or tokens. The phone sends its ballot through a relay service that pays the transaction fee (an ERC-4337 paymaster or equivalent [27]). Because the proof is bound to the ballot, the relay cannot change it. The app connects through an anonymising network with censorship-circumvention transports [34], so neither relays nor network observers learn the member's IP address. Several independent relays operate, and a member can always submit directly.

8.7 Closing, tallying and publishing

1. At the close time no further ballots are accepted. The last ballot per nullifier counts.
2. Anyone adds the ciphertexts per option. Trustees publish partial decryptions of these totals with proofs of correctness (7.8).
3. The trustees publish the result. The contract checks that the ballot chain matches, that the totals add up exactly to the number of distinct participants, and that this number does not exceed the eligible identities in the snapshot.
4. A public challenge period (for example 7 days) follows. Anyone can submit evidence of an invalid decryption proof or a wrong aggregate. If no valid challenge arrives, the result becomes final.
5. If no result is published within a deadline (for example 14 days after closing), anyone can mark the poll as "result withheld"; the number of participants and the ballot chain remain public facts.
6. After the challenge period, trustees delete their key shares and publish signed statements, so that no later compromise can decrypt individual ballots.

8.8 On-chain and off-chain data

Data	Where	Visible to
Identity leaf, credential nullifier, revoked handles	Ledger	Everyone (reveal nothing about persons)
Poll definition hash, snapshot roots, tally key, times	Ledger	Everyone
Encrypted ballots, nullifiers, ballot chain	Ledger and long-term archives	Everyone (content encrypted)
Totals, decryption transcript, archive hash	Ledger and archives	Everyone
Poll text and options	Content-addressed storage	Everyone
Document fingerprints and face templates	Encrypted store, readable only in the enclave (later MPC)	No one outside the enclave
Passport data, identity secret, receipt	Member's phone only	The member

8.9 Scale and cost

Operation	Measured gas (reference contracts)
Register an identity (proof check, storage, batch chain hash)	about 335,000
Insert a batch of identities (one proof, any batch size)	about 294,000 per batch
Revoke an identity (one proof)	about 295,000
Create a poll (tally-key check, pollHash; once per poll)	about 875,000
Cast a ballot, four options, sent alone	about 390,000 (about 424,000 for a poll's first)
Cast a ballot in a batch (per ballot, large batches)	about 101,000
Change a ballot (re-vote)	about 378,000
Publish a result	about 158,000

Measured on an in-process EVM with real Groth16 proofs; contracts are unoptimised reference code. Figures vary by a few dozen gas between runs because proof bytes differ.

Gas is now measured; the price of gas is not. At assumed Layer-2 prices, a ballot sent alone costs roughly one to fifteen US cents. In batches, at about 101,000 gas, it costs roughly a quarter of a cent to four cents, so a poll with one million participants could cost roughly 2,500 to 40,000 dollars. Because participation is free and paid from a common fund (Section 10), cost reduction is a priority [40]. Batched verification already makes ballots about 3.8 times cheaper. Recursive aggregation, in which one proof covers many ballots, is estimated to reach about 8–10 times. Moving the latest-ballot record off-chain as well would reach about 25–35 times. An earlier version of this paper expected 10 to 100 times. **100 times is not reachable**, because every ballot's ciphertexts must stay on the ledger so that voters can check their own vote and anyone can recount. Aggregators cannot censor, because members can always submit directly. Money figures remain estimates until measured on a public test network.

8.10 Contract governance

A time-locked multi-signature group of independent, pseudonymous signers can deploy new verifier versions, update the enclave key set and change default parameters for future polls. It cannot alter any existing poll, ballot, result or root, cannot pause an open poll and cannot revoke identities. The aim is to give up upgrade power over the core registries once the system is stable.

8.11 Reference implementation

A working reference implementation of the voting core is published with this paper at **github.com/NemoUnus/proof-of-one**, under reference/. It is written to be read and attacked, not deployed: it is not audited, and all proofs use a **test-only trusted setup** made by a single contributor.

Package	What it contains	Tests
tally	Encrypted one-hot ballots, nullifiers, trustee key generation, voter self-verification, homomorphic tally, threshold decryption with proofs, independent recount tool	13
ballot-circuit	Ballot proof π_vote (Circom, Groth16): membership, non-revocation, nullifier, eligibility with up to three nationalities, well-formed encrypted ballot, pollHash	16
enrolment-circuit	Registration proof π_reg, batch insertion proof π_batch, revocation proof π_revoke, enclave credential issuance including added documents	21
contracts	Identity and revocation registries, polls, ballots and results in Solidity; single and batched ballot submission; full on-chain flow with real proofs	9
phone-bench	A public web page that makes the ballot proof on the visitor's phone and reports the time	—
aggregation-prototype	The ballot proof and an aggregator in Noir (UltraHonk, universal setup), for size measurements of recursive aggregation	check script

The 59 tests include attack cases: two-hot, empty and vote-shifting ballots; ciphertexts that do not match the proven choice; replay in another poll; a proof attached to someone else's ballot; a revoked member with a forged low leaf; wrong totals and a wrong ballot chain at publication. Both founding properties are exercised in code: the voter's phone checks its recorded and counted ballot, and a recount tool rebuilds every result from public data alone.

Proof	Constraints
Ballot proof π_vote (4 options, trees of depth 32, up to 3 documents)	32,535
Registration proof π_reg (key-set depth 8)	9,369
Batch insertion proof π_batch	16,227 (4 leaves); 501,947 (1,024 leaves)
Revocation proof π_revoke (depth 32)	32,521

Building the code also produced details the specifications must now state explicitly, recorded in the published implementation notes. The most important are:

- **The verifier rebuilds every public input** from the poll's own state and the submitted ciphertexts; nothing is accepted from the submitter.

- **Ballot ciphertexts need no on-chain curve check**, because the proof computes them from the generator and the tally key; the tally key is checked once, when the poll is created.
- **Every hash use carries a domain tag** (nullifier, commitment, credential, revocation handle, poll hash and others), so no value can be reused in another role.
- **The ballot chain is fixed byte for byte**, and the reference tally and the contract produce identical chains.
- **Snapshots are fixed at poll creation.** A revocation applies to polls created afterwards, not to polls already open.
- **Without the ballot proof, tally checks alone cannot detect a vote-shifting ballot** such as (+2, −1, 0, 0); every path that accepts ballots must verify the proof.
- **A failed elliptic-curve operation on the ledger consumes all the gas given to it**, so the batch verifier gives each one a fixed allowance; otherwise one invalid point would exhaust a whole transaction.
- **The choice of hash and curve decides the cost in other proof systems.** In the recursion-friendly system tested, the ballot proof needs about 147,000 gates with the current Poseidon and Baby Jubjub, but about 20,000 with that system's native primitives. Verifying one ballot proof inside an aggregation proof costs about 750,000 gates, on servers. Whether to redesign the primitives is left open until proving times are measured [40].

9. Core Product: Verifiable Polling

9.1 Poll lifecycle

1. **Propose and select.** Sponsored polls are proposed and selected by participants (Section 10). Self-funded polls can be created by anyone who pays their own costs.
2. **Participate.** An eligible member answers in the app. The phone proves eligibility in zero knowledge and submits an encrypted ballot under a private ballot number.
3. **Review and change.** Until the poll closes, the member can check their recorded ballot and change their answer; only the last answer counts.
4. **Close, publish and verify.** Totals are decrypted with public proofs, published with verified breakdowns and opened for a public challenge period. Anyone can recount.

9.2 The private ballot number

For each poll, the participant's phone — not the network — generates a private ballot number and a poll-specific **nullifier** derived from the member's secret. The nullifier prevents the same person from being counted twice in that poll but cannot be linked to the person or to their ballots in other polls. The encrypted ballot is recorded on the public ledger under the ballot number, with a zero-knowledge proof that it comes from an eligible, unique member [12]. Because no one else ever holds the link between members and ballot numbers, no operator can tell who answered what, even if compelled to.

9.3 Protecting participants

- **Receipt window.** The member chooses for each vote how long their phone keeps the information needed to verify it: none, 7 or 30 days after the close. After that, nothing on the phone reveals the answer.

- **Duress PIN.** A second PIN opens the app in a state with no records.
- **No history.** The app keeps no list of polls answered beyond the active receipt windows.
- **Anonymous network access.** All connections go through an anonymising network; enrolment and voting never happen in the same session.
- **Verifying the app.** Builds are reproducible and the signing-key fingerprint is published in several independent places, so members can detect counterfeit apps.

9.4 Assurance modes

Mode	Typical use	Ballot	Protection
Standard (default)	All public-opinion polls	Encrypted; only totals decrypted	Re-answer until close; receipt window; trustee share deletion
Open (opt-in)	Non-sensitive questions where individual anonymous answers are useful to publish	Plain text under the ballot number	Creator must confirm the poll is non-sensitive; clear warning to members
Binding vote (future)	Elections and referendums where legally authorised	Encrypted	Receipt-free design with key change [13][14]; required before any binding use

9.5 Verified demographic results

- **Breakdowns by verified attributes.** Results can be reported by age band, nationality and other attributes proven at enrolment — not self-declared.
- **Minimum group size.** A breakdown is shown only when its group contains at least a set number of participants (for example 50), so that small groups cannot reveal individual answers [20].
- **Honest presentation.** People who choose to answer a poll are not a random sample of the population. Because attributes are verified, results can be weighted to the known population structure; every published result states its method, its margin and the self-selection caveat.

10. Community Agenda and Free Participation

Participation in Proof of One is **free**. Charging participants would sharply reduce participation and would exclude people who cannot reach the global financial system. The cost of sponsored polls is therefore paid from a common fund supported by voluntary contributions (Section 16). Because the fund is limited, the topics it pays for are chosen by participants themselves, not by the project.

10.1 Regions and the global track

- **Regions** are defined by the nationality attribute proven from the identity document — a single country or a group of countries. The network does not know or need members' locations, and members living abroad take part in their own country's track. A member with several verified nationalities takes part in the track of each (6.12).
- **The global track** holds polls on questions that concern people everywhere, regardless of borders, open to all members.

10.2 Monthly topic selection

1. **Proposals.** Each member may propose one topic per month in their region or in the global track.
2. **Endorsement.** Members endorse proposals anonymously, one endorsement per person per proposal, using the same nullifier technique as ballots. Endorsements are collected off-chain and their totals are anchored on the ledger.
3. **Selection vote.** The ten most-endorsed proposals in each track go to an approval vote, in which members may approve several. The winners, up to the number the track's budget allows, become that month's sponsored polls.

10.3 Budget rule

The fund's monthly budget is divided by a public formula fixed in advance: a fixed share for the global track, then an equal base share for each region plus a share proportional to its number of members. Because the rule is public and mechanical, the fund cannot favour or disfavour any region or topic.

A member with several nationalities counts in each of their regions, and the number of such members is published with the budget.

10.4 Neutral wording and visible manipulation

- **Wording guideline.** A public guideline defines neutral question wording. Any edit made to a selected proposal is published next to the original text, so editing cannot be used as hidden censorship.
- **Visible flooding.** Endorsement and selection statistics are published by document issuer, so an organised attempt to flood the agenda — including by an issuer of documents — becomes visible.
- **Self-funded polls.** Universities, researchers and organisations that can pay may run polls at their own cost, outside the monthly selection, under the same rules of verifiability and neutrality.

11. Further Applications

The same identity layer supports other uses once the polling platform has established a member base:

- **Verifiable petitions** in which every signature comes from a unique, verified person.
- **Private sign-in** to websites and apps without passwords, revealing only what the user chooses.
- **Age and residency checks** that reveal only a yes-or-no answer.
- **Fair allocation** of anything limited to one per person, such as tickets, quotas or rewards.
- **Human authorship** labels for content, reviews and comments in an era of AI-generated material.

12. Security and Threat Model

The threat model assumes an adversary with the resources of a state: able to issue genuine identity documents, monitor and block networks, seize phones, coerce individuals, pressure app stores and service providers, run many real devices, contribute code under false identities and run discrediting campaigns. Threats are ranked by their impact on participant safety first, integrity second and availability third.

12.1 The fundamental limit

> **An authority that issues identity documents can create genuine-looking identities from its own documents. Proof of One cannot prevent this. It can make such fraud costly, bounded, statistically visible and separable in the results — not impossible.**

- Duplicate faces are searched across all members, so the same person cannot enrol twice under different documents and birth dates (6.7).
- Enrolment counts per document issuer and per document-signing certificate are published in aggregate, so unusual surges are visible; counts are compared with public population figures.
- A poll may count only identities enrolled before it was announced, and the network checks that the number of ballots never exceeds the number of eligible identities.
- Results are published with a breakdown by document issuer, so readers can judge how far each source can be trusted.

12.2 Main threats

Threat	Mitigation	Residual risk
Seized phone reveals past answers	Encrypted ballots; receipt window chosen per vote; automatic deletion; duress PIN	Answer in a poll still inside its receipt window; fact of participation
Uniqueness service links people to identities	Unlinkable registration with a hiding commitment; random delay; minimum batch of 1,000; hidden signing epoch	The service knows that a person enrolled
Face database as a list of participants	Encrypted templates in an enclave; MPC across jurisdictions before any high-risk use	Enclave or provider compromise until MPC is in place
Network surveillance of app use	Anonymising network with circumvention transports; distribution outside app stores; reproducible builds	Presence of the app on a seized phone
Counterfeit app collecting data	Published signing fingerprint; enclave accepts only attested genuine apps; user guidance	Data harvested before the counterfeit fails
Document issuer creates identities	Section 12.1	Bounded and visible, not prevented
Injected camera feed or deepfake	Presentation-attack detection [18]; hardware attestation; limit per attested device	Well-resourced attacks on device hardware
Lost phone used to create a second identity	Re-enrolment revokes the old identity after a cooling-off period	Window of the cooling-off period
Forged proofs from a compromised setup	Universal setup or large public ceremony; public bound checks on ballot counts	Bounded by eligible identities
Wrong or withheld result	Public recount; decryption proofs; challenge period; “result withheld” state	Delay of publication
Trustee collusion	At least 9 trustees, threshold about two-thirds, different jurisdictions; share deletion	A colluding threshold before deletion could decrypt ballots, though not change results

Threat	Mitigation	Residual risk
Coercion to vote in front of someone	Re-answer until close; receipt window of zero	Coercion just before closing
Censorship by sequencer or relay	Independent relays; direct submission; forced inclusion; minimum 48-hour polls	Delay
Malicious code contribution	Two independent reviews of security-critical code; signed commits; pinned dependencies; audit before each stage	Subtle flaws missed by reviewers

13. Open Source and the Human–AI Team

13.1 Open-source practice

- **Everything public from the first line.** Code, circuits, contracts and specifications are published as they are written, with the security assumption of each component stated in comments and tests published alongside the code.
- **Licences.** Copyleft (AGPL-3.0) for the app, relay and enclave services, so that modified versions stay open; permissive (Apache-2.0) for reusable libraries and circuits.
- **Reproducible builds.** The phone app and the enclave image build bit-for-bit from the public source, so anyone can check that the published code is the code that runs. Enclave attestation is only meaningful with this.
- **Staged release.** Public code, then a public test network and bug bounty, then an independent human audit, and only then use with real people. Code is never shipped to real participants on the assumption that reviewers will find problems later.
- **Responsible disclosure.** Every repository has a private channel for reporting vulnerabilities, with published response times.

13.2 The team

Proof of One is led by its pseudonymous founder, **Nemo Unus**, and developed with a team of AI agents. Each agent is an AI system working in a defined role. They are disclosed as AI, sign their contributions as AI agents, and never present their work as audited. Every safety-critical design, circuit, contract and piece of mobile code they produce must be reviewed by independent human experts, who may themselves be pseudonymous. The project welcomes such contributors.




Figure 3 — The Proof of One AI agent team. Each agent carries a Greek name chosen for its role.

Kryptos — Cryptography Architect. Greek for "hidden". Kryptos chooses and justifies every cryptographic primitive and keeps the design consistent. Its rule: never invent new cryptography, and state the assumption behind every choice. In version 0.5 it set the primitive suite (7.2) and designed the hidden revocation handle that revokes a lost identity without revealing which one it was (7.11).

Psephos — Zero-Knowledge and Voting Protocol Engineer. The psephos was the pebble Athenians dropped into an urn to vote. Psephos writes the zero-knowledge circuits and the ballot protocol, always separating what is proven from what is trusted. In version 0.5 it designed encrypted ballots that keep both founding promises — every voter can check their own vote and anyone can recount — and the unlinkable registration proof (7.7–7.10).

Ostrakon — Ledger and Smart-Contract Engineer. The ostrakon was the pottery shard on which Athenians wrote a name to vote. Ostrakon specifies what lives on the ledger and assumes that sequencers and relays may misbehave. In version 0.5 it wrote the contract design (Section 8), found that ledger data would vanish after about 18 days unless archived, and produced the first cost estimates.

Prosopon — Mobile Identity Engineer. Greek for "face", and also "mask". Prosopon makes enrolment on an ordinary phone accurate, private and hard to spoof, and insists on measuring accuracy across diverse populations. In version 0.5 it showed that an issuer of documents could defeat face checks grouped by birth date, which led to searching across all members (6.7).

Argus — Security Red Team. The hundred-eyed watchman of Greek myth. Argus attacks every proposal, assuming an adversary with the resources of a state. In version 0.5 it led the threat model, found that a seized phone could reveal every past answer in the earlier design, and in its review of the new protocol found eleven further issues, all now addressed (Section 12).

Themis — Privacy, Ethics and Legal Analyst. The Greek personification of justice and law. Themis puts participant safety above every feature and flags legal risk plainly, always recommending qualified human legal advice. In version 0.5 it set the participant-safety gates for the roadmap and required that contributions to the fund be kept apart from voting (Sections 14 and 16).

Metron — Survey Methodology and Statistics. Greek for "measure". Metron makes results meaningful, not only verifiable, and never lets a self-selected sample be presented as more than it is. In version 0.5 it set the rules for neutral question wording, small-group protection and honest presentation of results (9.5, 10.4).

Hermes — Documentation and Community. The messenger of the gods. Hermes explains the project to every audience and keeps every document consistent with the decisions taken. It drafted this paper, keeps the public decision log and coordinates translations.

> **Each agent signs its work as "— Name (AI agent, Proof of One)". None of their work is described as audited or proven secure until independent human experts have reviewed it.**

Version 0.7 of this paper is itself the product of this process: a threat model led by Argus, protocol specifications by Psephos and Ostrakon, a red-team review of those specifications, decisions taken by the founder, reference code written by Psephos, Ostrakon and Kryptos whose measurements replaced the earlier estimates, a study of document coverage proposed by the founder, and the first phone measurement made by him. All of it is published alongside this paper.

13.3 Growing the human part of the work

A project that asks people to trust it must be checked by people. The founder has therefore set a rule (Decision Log #28): the human share of the work should grow over time, and the AI agents' share remains fully credited.

- **The founder reviews every change** before it is published, helped by a plain-language explanation of each technical change, and writes key parts himself.
- **A public provenance record** (PROVENANCE.md in the repository) states, for every part of the project, who wrote it and which humans have reviewed it.
- **Work only people can do is published as open invitations:** measuring the ballot proof on real low-cost phones, line-by-line review of the circuits and contracts, an independent recount tool written by people, and a legal review of licences and AI authorship.
- **Security-critical parts** — circuits, contracts, enrolment and the recount tool — are reviewed line by line by independent human experts, or reimplemented independently, before the first public pilot with real participants. The test network may run on reference code before that review, with test data and clear warnings.

The first human measurement was made by the founder: the ballot proof on a phone, in 3.5 seconds (7.7).

14. Governance, Legal and Ethical Considerations

- **Stewardship.** The protocol is stewarded by its founder and open contributors. Operational roles — enclave and later MPC operators, tally trustees, relays, archivers and multi-signature signers — are to be held by independent parties in different jurisdictions, and listed publicly by their pseudonymous or organisational identities.
- **Participant safety gates.** No participants from high-risk settings until encrypted ballots, unlinkable registration, anonymous network access and MPC template storage are implemented and independently audited, and until the network has a large existing anonymity set.

- **Informed consent.** Enrolment shows a plain-language statement of what is stored, where, what a seized phone can reveal, and what the system cannot protect against.
- **No overstatement.** Public material never promises complete anonymity or fraud-proof results; people may take risks based on such words.
- **Data protection.** Identity document data and biometrics are special-category data under the EU GDPR (Article 9) [17] and comparable laws. Processing in the enclave, storing only fingerprints and encrypted templates, explicit consent and impact assessments are central. Operator jurisdictions require review by qualified lawyers.
- **Right to erasure.** Personal data is never written to the ledger. Erasing a member's template and fingerprint mapping off-ledger leaves on-ledger records meaningless [17].
- **Inclusion.** Chip-based national ID cards are accepted alongside passports. People without suitable documents or phones remain a known gap.
- **Neutrality.** The project does not choose sponsored topics, publishes its wording guideline and every edit, and labels the mode and method of each poll.
- **Interoperability.** W3C Decentralized Identifiers and Verifiable Credentials [19] allow national digital wallets to issue attributes to a member's identity in the future.

15. Roadmap

Phase	Scope	Gate to the next phase
0. Open specification and code (in progress)	Done: whitepaper, specifications, threat model, document coverage study, reference circuits, contracts and tally with 59 tests, batched ballot verification, several nationalities, public phone benchmark (first result 3.5 s). Remaining: results from low-cost phones, proving times for recursive aggregation, robust trustee key generation, enrolment front end	Specifications and reference code reviewed by independent human experts
1. Test network and accuracy study	Full system on a public test network with volunteers in low-risk settings; face-accuracy study at scale; ballot aggregation; public bug bounty	Measured error rates; bounty findings fixed; independent audit
2. Low-risk public pilot	First real polls, community agenda and global track with participants in low-risk settings; first voluntary contributions after legal review	Second audit; stable operation; large anonymity set
3. Decentralisation and high-risk readiness	Face templates moved to MPC across jurisdictions; threshold enclave keys; independent trustees and relays	All participant-safety gates met (Section 14)
4. Binding votes (vision)	Receipt-free binding votes where legally authorised	Adoption by a public body

16. Funding Principles

- **Non-commercial.** There is no business model, no token, no sale and no investor. Proof of One does not sell data, insights or access.
- **A common fund** pays for sponsored polls and essential infrastructure, divided by public rules (Section 10.3).

- **Voluntary contributions** may come from anyone who supports the purpose. Members may contribute too, but only through a separate screen and session that has no connection to their identity or ballots.
- **Anonymity** of contributors and of the team is a principle of the network. The structure of the fund will be designed separately and published before any contribution is accepted, after review by qualified lawyers of sanctions, anti-money-laundering and charity rules in the relevant jurisdictions.
- **Self-funded polls** let organisations pay their own costs, reducing pressure on the fund.
- **Transparency.** Income and spending of the fund will be published in aggregate.

17. Known Limitations and Open Questions

1. **Document issuers.** An authority that issues identity documents can create genuine-looking identities (12.1).
2. **Trust at launch.** Until MPC is in place, template comparison relies on enclave hardware and a cloud provider; the template store is the system's largest single point of harm.
3. **Face accuracy at scale.** Global duplicate search must be measured on diverse real populations before the method is fixed.
4. **Trustees.** Ballot secrecy relies on fewer than a threshold of trustees colluding; deletion of key shares cannot be proven cryptographically.
5. **Participation.** A member's secret always reveals whether they took part in a poll, though not how they answered after the receipt window. Hiding participation is open research.
6. **Early anonymity sets.** Early in the network's life few people enrol; insertion waits for a minimum batch, which delays early members.
7. **Long-term secrecy.** Encrypted ballots on a public ledger may become readable by future quantum computers.
8. **Coercion.** Re-answering reduces but does not remove coercion; binding votes need a receipt-free design.
9. **Reach.** Today only about one person in six holds a chip document that a phone can read, with large gaps in South Asia and Africa (6.4). Results describe those who can and do take part.
10. **Cost.** Ballot gas is measured and batching cuts it by about 3.8 times, but free participation still depends on voluntary funding and gas prices. Recursive aggregation would need substantial server capacity (8.11).
11. **Reference code status.** All proofs use test-only trusted setups; a real deployment needs a large public ceremony or a universal-setup proof system. The trustee key generation in the reference code is not yet robust against misbehaving trustees, and the generated verifier contracts carry a licence that must be resolved before release.
12. **Document coverage and platform dependence.** Not every country issues chip documents or publishes signing certificates; NFC, camera access and attestation depend on Apple and Google policies, and distribution outside app stores is limited on iOS.
13. **Camera authenticity.** The live face feed is trusted on the basis of attestation and presentation-attack detection, not cryptographic proof.

14. **Representativeness.** Weighting improves estimates but cannot fully correct for who chooses to join.
15. **Name.** “Proof of One” must be checked for trademark and domain conflicts before launch.

18. Conclusion

Proof of One combines a government-signed identity document, a live face match and privacy-preserving cryptography so that every participant is a real person who can take part only once, while keeping who answered what private. Every participant can verify their own vote, and anyone can recount every result. Participation is free, topics are chosen by participants, and all code is open. The design is honest about what it cannot do, and nothing will reach real participants before independent human experts have tested and audited it. The specifications and a working reference implementation are now public, and the first phone measurement is encouraging. Today about one person in six can take part, and that share grows each year. The next steps are independent review by human experts, and measurements on low-cost phones.

References

[1] World Foundation funding announcement, reported July 2026 — over 18 million Orb-verified users.

[2] Humanity Protocol — palm-based proof of humanity; mainnet launched 12 August 2025.

[3] Human Passport (human.tech, Holonym Foundation) — formerly Gitcoin Passport.

[4] Self Protocol — passport-based zero-knowledge identity verification (Celo developer documentation).

[5] ZKPassport — private, unforgeable identity from passport chips; acquired by Aztec Labs.

[6] ICAO Doc 9303, Machine Readable Travel Documents — electronic passports, passive and active authentication.

[7] Regulation (EU) 2024/1183 (eIDAS 2.0) — European Digital Identity Wallet.

[8] Bhutan National Digital Identity integration with Ethereum, 2025.

[9] Republic of Estonia, Internet Voting (i-Voting), in use since 2005.

[10] Specter, Koppel and Weitzner, “The Ballot is Busted Before the Blockchain: A Security Analysis of Voatz”, MIT, 2020.

[11] Gaudry, P., analysis of the encryption used in the Moscow 2019 blockchain voting system, 2019.

[12] Semaphore — zero-knowledge group membership and signalling protocol.

[13] Vocdoni open voting protocol; MACI (Minimal Anti-Collusion Infrastructure).

[14] Juels, Catalano and Jakobsson, “Coercion-Resistant Electronic Elections”, 2005.

[15] Freedman, Ishai, Pinkas and Reingold, “Keyword Search and Oblivious Pseudorandom Functions”, TCC 2005.

[16] Dodis, Reyzin and Smith, “Fuzzy Extractors: How to Generate Strong Keys from Biometrics and Other Noisy Data”, EUROCRYPT 2004.

[17] EU General Data Protection Regulation (GDPR), Articles 9 and 17.

[18] ISO/IEC 30107-3, “Biometric presentation attack detection — Part 3: Testing and reporting”.

[19] W3C Decentralized Identifiers (DID) v1.0; W3C Verifiable Credentials Data Model 2.0.

[20] Sweeney, L., “k-Anonymity: A Model for Protecting Privacy”, 2002.

[21] Davidson, Faz-Hernández, Sullivan and Wood, RFC 9497, “Oblivious Pseudorandom Functions (OPRFs) Using Prime-Order Groups”, IETF, 2023.

[22] Barnes, Bhargavan, Lipp and Wood, RFC 9180, “Hybrid Public Key Encryption”, IETF, 2022.

[23] Grassi, Khovratovich, Rechberger, Roy and Schofnegger, “Poseidon: A New Hash Function for Zero-Knowledge Proof Systems”, USENIX Security 2021.

[24] Groth, J., “On the Size of Pairing-Based Non-interactive Arguments”, EUROCRYPT 2016.

[25] Gabizon, Williamson and Ciobotaru, “PLONK: Permutations over Lagrange-bases for Oecumenical Noninteractive arguments of Knowledge”, 2019.

[26] Ethereum Improvement Proposal 4844, “Shard Blob Transactions”.

[27] Ethereum Request for Comments 4337, “Account Abstraction Using Alt Mempool”.

[28] Amazon Web Services, AWS Nitro Enclaves — cryptographic attestation documentation.

[29] Ethereum Improvement Proposal 2494, “Baby Jubjub Elliptic Curve”.

[30] ElGamal, T., “A Public Key Cryptosystem and a Signature Scheme Based on Discrete Logarithms”, 1985; Chaum and Pedersen, “Wallet Databases with Observers”, CRYPTO 1992.

[31] Worldcoin, semaphore-mtb — batch insertion of identity commitments verified by a single zero-knowledge proof.

[32] Benaloh, J., “Simple Verifiable Elections”, USENIX EVT 2006.

[33] Pedersen, T. P., “A Threshold Cryptosystem without a Trusted Party”, EUROCRYPT 1991.

[34] The Tor Project — Tor and pluggable transports (including Snowflake and obfs4).

[35] L2BEAT — independent risk assessment and maturity stages of Ethereum Layer-2 networks.

[36] Proof of One, “Who can enrol? Chip identity documents worldwide, v0.1”, October 2026 — docs/research in the project repository; based on Inverid, ReadID Supported Identity Documents (2023), national announcements and World Bank population data.

[37] ICAO PKD Board, Annual Report 2025 (B-Pub/79): 107 participants at the end of 2025.

[38] ICAO, “ePassport basics” — more than 140 issuing States and over one billion ePassports in circulation.

[39] Proof of One, “Several nationalities, one identity — specification v0.1”, October 2026 — docs/specs in the project repository.

[40] Proof of One, “Ballot aggregation v0.1 — design and first measurements”, October 2026 — docs/specs in the project repository.

Glossary

Term	Definition
Document fingerprint	A one-way value derived from stable fields of an identity document, used to stop the same document being used twice
OPRF	Oblivious pseudorandom function — lets a service compute a keyed fingerprint of data it never sees
Face template	A mathematical description of facial features, not an image
Enclave	A hardware-isolated area of a server where data is processed without being visible to the server’s operators
MPC	Secure multi-party computation — several parties compute on data that none of them can see
Zero-knowledge proof	A proof that a statement is true without revealing the underlying data
Nullifier	A poll-specific value that prevents double participation without revealing identity
Liveness detection	Checking that a live person, not a photo, mask or video, is in front of the camera

Term	Definition
Poseidon	A hash function designed to be efficient inside zero-knowledge proofs
Groth16	A zero-knowledge proof system with very small proofs and fast verification
Merkle tree	A tree of hashes that lets anyone prove an entry belongs to a set using one short root value
Layer-2 rollup	A network that executes transactions cheaply and posts its data and results to Ethereum
Relay service	A service that submits members' transactions and pays the fees, without being able to change them
HPKE	Hybrid Public Key Encryption, an IETF standard for encrypting data to a public key
Snapshot root	The registry's Merkle root fixed when a poll opens; it defines who may answer
Exponential ElGamal	Public-key encryption in which encrypted numbers can be added together without decrypting them
Trustees	Independent parties who jointly hold a poll's decryption key; a threshold of them is needed to decrypt totals
DLEQ proof	A short proof that a trustee's partial decryption was computed with its real key share
Credential nullifier	A value that stops one enrolment credential being used to register twice
Revocation handle	A hidden value inside each identity that can be published to revoke it without revealing which identity it was
Receipt window	The period, chosen by the member, during which the phone keeps what is needed to verify their own vote
Ballot chain	A running hash over all ballots of a poll in order, fixing the exact set that must be counted
Challenge period	Time after publication during which anyone can submit evidence that a result is wrong