EDF Notification Model

Contents

1 Introduction 3
2 Common information 4
2.1 Header product Identification 4
2.2 Packaging 5
3 EDF_Hotel Inventory and Rates 6
3.1 Basic Data Element 6
3.2 Selling Data 8
4 EDF_Allotment Allotment 15
4.1 Hotel deactivation 18
5 Appendices 19
5.1 Appendix A Custom Types definition 19
5.2 Appendix B RatePlan Codes 20
6 Versions 21

1 Introduction

This document covers all the messages realted to the EDF based notifications. Needed for any “push” model integration based on the EDF format. (*All the basic definitions of the push model as well as the EDF definitions (XSD and WSDL) can be found in the Axisdata Integration Documentation)*

EDF (**E**inheitliches **D**aten **F**ormat) is a component based XML data format, specifically for the exchange of travel offer and product data between tour operators and distributors.
Is a product developed by Peakwork
The EDF format guarantees quantity, quality, accuracy and speed whilst presenting the detailed and precise inclusion of all travel offer attributes. In addition, EDF also includes specific calculations to mirror exactly the rules applied within the tour operator system. EDF ensures travel products are delivered to distribution channels with the highest possible degree of accuracy, detail and quality.

EDF is used to populate the Players and the data delivery consists of the product components together with compound rules, meaning offers and offer combinations can be calculated in real time.

EDF updates can be sent either as complete data delivery or as a delta delivery for updating existing products.

EDF have two basic notification types:

- EDF_HOTEL where Inventory and rates information is delivered.
- EDF_ALLOTMENT including only allotment information per day.

EDF include also the posibilty to describe properties of touristic goods and services true the DRV GlobalTypes.

GlobalTypes® describe uniform descriptions of touristic attributes which are uniquely coded. With GlobalTypes®, tour operators can especially highlight the service scope of their products whilst attributing products themselves. At the same time, the search for suitable offers is simplified for final consumers and travel agents. Thousands of attributes in 19 categories can currently be viewed as room type, accommodation attributes etc.).

The definition of the DRV GlobalTypes with corresponding SubTypes and AdditionalTypes.

http://www.globaltypecenter.de/index.php?language=en

Examples in the section 3.1

2 Common information

2.1 Header product Identification

The header of the both Notifications contains the same relevant information that makes reference to the product on sale.

HotelRoot xmlns="http://www.vilauma.de/edf/Hotel">
<BasicData Code="ATRDLM6NX6" FileKey="S16" **FileKeyCombination**="true" **ProgramType** ="OWN1" **Source**="XXX" **TourOperatorCode**="XXX"Usage="HotelOnly">

HotelAllotmentRoot Delta="false">
<BasicData Code="ATRDLM6NX6" FileKey="S16" **FileKeyCombination**="true"**ProgramType**="OWN1" **Source**="XXX" **Tour OperatorCode**="XXX"Usage="HotelOnly"/>

FileKeyCombination is relevant only for seasonal transitions. This is controlled via the hotel opening overtime rates can be established.
For this the same hotel will be sought with another Filekey. All other attributes, such as code, source, Tour Operator Code, Travel Type, Program Type must be the same

ProgrammType
The attribute is optional and will only be written, if a program type is required for booking the product. For German tour operators like TUI this approach is common practice.
The ProgramType attribute is only filled, if a product is to be passed in with one or more program types.
As varying sales terms such as prices, rooms, incentives, etc. may apply depending on the program type, these terms are written into separate hotel EDF files.

The Source attribute designates the hotel and product origin, if the tour operator procures services from external sources (incoming agency, hotel beds database, etc.). The use of the attribute is optional.
Since some tour operators procure their products from different sources, for example, for dynamic packaging, the source may be indicated here.
The attribute is relevant for dynamic packaging in order to update a sales system with information indicating the source when booking a hotel service.

The TourOperatorCode attribute is used to specify the tour operator code. Since the tour operator code is needed for a technical booking, this attribute is mandatory.
Hence, the tour operator code required for a booking is supplied here.

Note: Source and Touroperator attributes should be mapped at client side.

2.2 Packaging

The interface support two main package models, pre package and dynamic package

- Pre Package

With the prepackage model, 2 or more services are offered together, services are grouped in two ways:
A combination of two products (for example hotel and rent-a-car). Two different products are combined to a new room with an inventory Block code. But also different hotels can be combined to a round-trip package this way. Hotel code includes a 2 character extension, I.E. AR for Accomodation RentACar, AG for Accomodation, Golf, etc..

Car packages are notified as an additional Inventory Block Code (InvBlockCode) at room level. These car codes follow ACRISS estandart (http://www.acriss.org/car-codes.asp). Car codes can be found in the Appendix section Car codes per hotel can be retrieved from the services section of the OTA_HotelDescriptiveInfo message using SUMMARY template (see OTA communication Model, mapping section). Prices and availability for these room + car packages are available inside the notification messaging.

Example:

- Hotel supplied extras are often offered as a different room code containing a compulsory extra. This is most commonly used for offers that include for example spa treatments. Disadvantage is poor visibility of room descriptions in the German market and dependency on room descriptions in the search results in other markets
- The Invert attribute is only set, if a distribution channel is to be inverted. If no inversion is desired, the attribute need not be written.Default value is *False*.

3 EDF_Hotel Inventory and Rates

This XML contains all relevant sales prices information and inventory information and is structured in two blocks, Basic data and Selling data.

<HotelRoot xmlns="http://www.vilauma.de/edf/Hotel">
<BasicData Code="AMTSPT0023" FileKey="NON" FileKeyCombination="true" ProgramType="SUP1" Source="xxx" TourOperatorCode="xxx" Usage="HotelOnly">
…
<SellingData ChildrenAgeOrder="Descending" Currency="EUR" DefaultHotelPriceTable="HOTEL">
…

3.1 Basic Data Element

The Basic Data element contains all relevant basic data. These include hotel name, hotel chain, Giata Code, IFF code, hotel address, geoinformation on the hotel location, arrival airport, departure airport, transfer information hotel attributes and hotel reviews.

Example:

- Name

  <Name>Comet Deluxe Hotel</Name>

- References

  <References>
  <GiataCode/>
  <HotelKey>ATRDLM6NX6</HotelKey>
  </References>

- Adress

  <Address>
  <Street>Armutalan Mah. , Mehmet Akif Ersoy Cad. ,No:17</Street>
  <ZipCode>48700</ZipCode>
  <City>Marmaris</City>
  <Country>TR</Country>
  <Phone>+90-252-4123388</Phone>
  <Fax>+90-252-4122424</Fax>
  <Email>info@cometotel.com</Email>
  </Address>

- GeoInfos

```
<GeoInfos>
        <Location
                Code = "TR"
                Name = "TR"
                Type = "Country"/>
        <Location
                Code = "249MAR"
                Name = "Marmaris"
                Type = "Region"/>
        <Location
                Code = "1142MA"
                Name = "Marmaris"
                Type = "City"/>
        </GeoInfos>
```

- ArrivalAirports

```
        <ArrivalAirports>
                <Airport
                IataCode = "DLM" Order = "1"
                Package = "true"/>
        </ArrivalAirports>
```

- Attributes

```
        <Attributes>
        <Attribute Name = "Category" Value = "3"/>
        </Attributes>
```

- DRVGlovalTypes

```
 DRVGlobalTypes>
<DRVGlobalType Type = "DRV">
  <GTAttribute GT = "GT03-ESSP">
    <Description Language = "EN">Languages Spoken: Languages: English, Turkish</Description>
  </GTAttribute>
  <GTAttribute GT = "GT03-MACA">
    <Description Language = "EN">Payment Type: Payment Type: Euro/Master Card, Visa Card</Description>
  </GTAttribute>
  <GTAttribute GT = "GT03-TOFL">
    <Description Language = "EN">No. Floors (max): Quantity: 5</Description>
  </GTAttribute>
  <GTAttribute GT = "GT03-TORO">
    <Description Language = "EN">Total Units/Rooms: Quantity: 60</Description>
  </GTAttribute>
```

3.2 Selling Data

The SellingData element contains all relevant selling data. These include the season labels, hotel-related incentives as well as additional expenses, restrictions like stop sales or minimum stays, bookable rooms and their occupancies and prices. Elements as Extras, Restictions, Global Extras can be set both at the hotel level and at the room level.

CHILDRENAGEORDER

ChildrenAgeOrder - indicates the sort order of the child discounts per age.
Possible values:

- Ascending - Sort in ascending order. The discount will be applied to the youngest child, followed by the next older child, etc.
- Descending - Sort in descending order. The discount will be applied to the oldest child, followed by the next younger child, etc.

Example:

ChildrenAgeOrder = "Descending"

CURRENCY

The Currency element is used to assign the sales currency of a product.
For data delivery for the German market, the sales currency indicated here will usually be Euros. The currency is indicated by the 3-digit ISO currency code.
The sales currency is indicated by the 3-digit currency code stated in ISO 4217. Example: EUR for Euros

Example:

Currency = "EUR"

DEFAULTHOTELPRICETABLE="HOTEL"

The DefaultPriceTable attribute references a default price table or season table.
The use of the attribute is optional. The attribute is required, however, if the ChargeBlock element contains multiple price tables with different names. In this case, the name of the price table must be specified, where the standard prices can be found. To reference another price table (e. g. for an early bird discount), the Extra element is used. The Extra element will then contain a note that a different price table will apply under certain conditions.

3.2.1.1 Rounding

The Rounding element contains rounding rules.
The element indicates how prices will be rounded, if the price calculation uses decimal places.
The user can control, whether rounding is desired and if the price will be rounded up, off or to two positions behind the decimal point.
Additionally, the rounding precision can be specified by indicating the number of decimal places for the rounding. Example:

```
<Rounding DecimalPlace = "2" Mode = "Commercial"/>
```

3.2.1.2 SeasonDefinitions

The SeasonDefinitions element defines the season periods and selling seasons.
The definition of individual season labels is not mandatory. If season letters are not supported by the tour operator, the Season block will not be written. In this case, the ChargeBlock element can be configured with a DateRestriction to control pricings based on time ranges. Example:

```
<SeasonDefinitions End = "2016-10-31" Identifier = "S16" Start = "2016-04-01"/>
```

3.2.1.3 Extras

In the Extras element any further information is assigned that goes beyond the definition of a basic charge for a product.
These include incentives, offers, charges, galas, included additional services, child discounts, deviating seasons, etc.
The Extras element can be set both at the hotel level and at the room level.

Example 50% discount for FullPayers only, with offer code from the hotel and GlobalTypes included with Custom Type to express the discount applied in a front-end

```
<Extras>
  <Extra ApplianceCode="DPO" BookingCode="OPABR20" CombiGroupId="1" GlobalType="IC" OffersAllowed="true" SortIndex="1" Type="DPO2">
    <Restrictions>
      <Restriction>
        <DateRestrictions>
          <DateRestriction ApplyTo="Stay" BookingEnd="2020-12-16" BookingStart="2020-11-27" End="2021-10-31" Start="2020-12-20"/>
        </DateRestrictions>
      </Restriction>
    </Restrictions>
    <CompatibleExtras>
      <CompatibleWith GroupId="1"/>
      <CompatibleWith GroupId="99"/>
    </CompatibleExtras>
    <Descriptions>
      <Description>Special Date Offers</Description>
    </Descriptions>
    <Reductions>
      <Reduction Calculation="PN" Percent="50.00">
        <Appliances>
          <Appliance Code="ExtraDay" Type="Charge"/>
          <Appliance Code="B" Type="Person"/>
        </Appliances>
      </Reduction>
    </Reductions>
    <DRVGlobalTypes>
      <DRVGlobalType>
        <GTAttribute CT="DPO-5000P" GT="GT07-TD"/>
      </DRVGlobalType>
    </DRVGlobalTypes>
  </Extra>
```

3.2.1.4 Restrictions

The Restrictions element contains restrictions for the level at which it is located. This allows assignment of restrictions with regard to time frame (date), days of the week (weekday), durations of stay (stay), season labels (season), persons (guests), board (board) and flights (flights). Restrictions are understood as stop sales, minimum and maximum stays, fixed arrival days, etc. These restrictions can be set both at the hotel level and at the room level

Example:

```
<Restrictions>
        <Restriction>
                <DateRestrictions ReleaseTime = "P1D">
                <DateRestriction
                ApplyTo = "Arrival"
                End = "2016-10-31"
                Start = "2016-04-01"/>
                </DateRestrictions>
        </Restriction>
</Restrictions>
```

3.2.1.5 Rooms

The Rooms element contains all rooms along with their rateplan codes, occupancies, possible board types and prices for the travel type and/or program type.

DESCRIPTIONS

The room description.
The long description of the room to be shown in the sales systems is specified here.

Example:

```
<Descriptions>
<Description Language = "DE">Zimmer_Standard/Doppel</Description>
<Description Language = "EN">Room_Standard/Double</Description>
</Descriptions>
```

RATEPLANCODES

RatePlan Code and its description are displayed in Room section. They consist of five alphanumeric characters where each position provides an information regarding other factor affecting the rate. From these five elements, first two elements are shown just for the Distributor's product management purposes (TO/OTA), only the last three are visible and form part of the room description for the final client to explain why the same room is bookable with different prices.

The components, descriptions and Explications are listed in Appendix B.
A RatePlan code is constructed from below RatePlan code elements:
Rate Type(1)|Rate Group(1)|Rate Refund(1)|Rate Sub Type(2)
Example: BHSP2 - Bar/Retail - Hotel only - Semi-flexible – Promotional Rate 2

There is also a possibility of duplicating RatePlan which already exists in the contract. In this case the "." character, and a number starting with 1, and then subsecuently every iteration.
Example: BHSP2.1

Where in **Rate Type** column the elements mean:
0 - If the character is 0 would say that the value has been not defined – the rate stays unchanged like in the basic contract edition.

B - Bar - best available rates (changing due to rate updates)
S - Static – unchanged contract rate till the time of a promotion or an offer introduction
F - FIT - free individual traveller rates
R - Retail – advised end-price

Rate Group:
H - Hotel only - rates valid when booking contains only hotel
P - Packaging - rates valid when booking contains hotel + another product
O - Opaque - hotel rates must not be visible for end consumer
R - Rack - walk-in hotel rates for end consumer

Rate Refund:
N - Non refundable - immediately after booking; Nonrefundable rooms can be also still communicated within the RoomCode as a last character like it used to was (RMSD00000N)
S - Semi-flexible – cancellation without fees up to 12 hours after booking
F - Flexible – cancellation without fees up to 24 hours after booking

And in **Rate Sub Type**:
A - Advanced Purchase - booking has to be paid before confirming
P - Promotion rate

RatePlan Codes can be expressed by two following options:

- as a "RMSDIN0000;BHS02" adding to the RoomCode the RatePlanCode, this is not required any development and all RatePlans are simply expressed in different code attributes. However existing room mapping has to be amended for all hotels where we deliver rate plans. If Best Price logic is implemented on the mapped code, then only the cheapest option across all rate plans can be shown. Be aware that non refundable rate plans may exist in normal rooms without an “N” on the tenth position of the room code.
  Example:

  <Room Code="RMSDIN0000;BHS02">
  <Descriptions>
  <Description Language="EN">Standard Room - promotion rates/non-refundable</Description>
  </Descriptions>

- as a separate room code attribute " RMSDIN0000" and an attribute RoomKey " BHS02". This requires the implementation of the RoomKey attribute but has the benefit that mapping does not change.
  Example:

  <Room Code=" RMSDIN0000" RoomKey=" BHS02">
  <Descriptions>
  <Description Language="EN">Standard Room - promotion rates/non-refundable</Description>
  </Descriptions>

The option chosen by the client has to be setup in our system. In the INT environment distributor ID TST1 is setup as the one with RatePlan in separate code and distributor ID TST2 as concataneted room code and rateplan code.

OCCUPANCIES

Occupancies is a parent element that contains one or more Occupancy blocks.
This is indispensable in cases where one room can have several occupancies which may e. g. be based on time ranges. Using this, occupancies can be overridden based on time ranges
Within the Room/Occupancies element the following attributes are mandatory in order to precisely specify occupancy:
Min, Max, MinAdult, MaxAdult.
Without this information, a sales system is not able to calculate the possible room occupancies

Example:

```
<Occupancies>
    <Occupancy Max = "3" MaxAdult = "3" MaxChild = "1" Min = "2" MinAdult = "2"  MinChargedPersons = "2"
MinChild = "0">
        <Infants ApplyToOccupancy = "No" MaxCount = "1"/>
        <Children MaxAge = "12" MinAge = "2"/>
  </Occupancy>
</Occupancies>
```

Boards

The Boards element controls any valid board services offered with this room. Board contains the board defined for this room. To support higher-level matching operations, a GlobalType must be set for this board.
A global unique board code the internal board codes will be matched with.
The GlobalType allows for unified searches of board services across sales systems.

Example:

```
<Boards>
        <Board Code = "BB" GlobalType = "BB">
          <Descriptions>
            <Description Language = "DE">Fruehstueck</Description>
          </Descriptions>
          <DRVGlobalTypes>
            <DRVGlobalType Type = "DRV">
              <GTAttribute GT = "GT06-BR"/>
            </DRVGlobalType>
          </DRVGlobalTypes>
        </Board>
        <Board Code = "HB" GlobalType = "HB">
          <Descriptions>
            <Description Language = "DE">Halbpension</Description>
          </Descriptions>
          <DRVGlobalTypes>
            <DRVGlobalType Type = "DRV">
              <GTAttribute GT = "GT06-HB"/>
            </DRVGlobalType>
          </DRVGlobalTypes>
        </Board>
      </Boards>
```

RESTRICTIONS (already explained at Hotel level)
EXTRAS (already explained at Hotel level)

CHARGEBLOCKS

The ChargeBlocks element is used to pass in the sales prices of the respective rooms. A ChargeBlock contains all information pertaining to the price calculation.
Here, base or extra day prices for charged persons as well as age-related reductions can be found.
The Restrictions sub element can be used to restrict price data with regard to stays, time ranges, guests, etc. The sales prices are assigned depending on the season label and/or time range. This element is also used to specify board charges. A ChargeBlock is comprised of the following elements:

- Restrictions
- Sections (time ranges, season labels and prices applying to a ChargeBlock)
- BoardCharges (board charges)
- GuestCharges (guest-related extra charges and reductions such as child discounts, etc.

Example:

```
<ChargeBlock Type = "Basic">
  <Sections>
        <Section Board = "BB" End = "2016-03-31" Start = "2016-03-19">
             <BaseCharges CalculationMode = "O" HotelPriceTable = "HOTEL" SeasonStrategy = "Hotel"
        SeasonStrategyMode = "Stay">
                  <BaseCharge Amount = "71.95" Duration = "P1D" Type = "ExtraDay"/>
              </BaseCharges>
        </Section>
```

Example:

```
<BoardCharge Amount = "0.00" Board = "BB" End = "2016-04-22" Start = "2016-04-21"/>
<BoardCharge Amount = "0.00" Board = "HB" End = "2016-04-22" Start = "2016-04-21"/>
```

Example:

```
<GuestCharge AddToBaseCharge = "false" Amount = "21.59" ApplyToBoard = "false" Board = "BB" End = "2016-03-31"
MaxAge = "12" MaxCount = "1" MinAge = "2" MinCount = "1" PersonType = "C" Start = "2016-03-19" Type =
"ExtraDay"/>
<GuestCharge AddToBaseCharge = "false" Amount = "36.42" ApplyToBoard = "false" Board = "HB" End = "2016-03-31"
MaxCount = "1" MinCount = "1" PersonType = "A" Start = "2016-03-19" Type = "ExtraDay"/>
```

DRVGLOBALTYPES (already explained at Hotel level)

4 EDF_Allotment Allotment

The BasicData element contains all relevant basic data that are required to map the allotment file to a Hotel EDF file. This element is also used to control the allotment strategy (with regard to arrival or stay).

This includes the hotel code, product type (package or hotel only)

The Code attribute contains the hotel code or the product code that is used to book the hotel or product.Therefore, the hotel code or product code is a unique identifier for the hotel or the accommodation product. The hotel code that is specified here must match the hotel EDF file, since this is used to map the vacancy to a product.

The Strategy attribute is used to control the allotment strategy.Possible values are:
Arrival or Stay
The default value is Stay.
The distribution of allotments for each day of the validity.
If different allotments are available depending on occupancy, distribution channels, time ranges or durations, the Allotment element is to be repeated for each restriction.

The number of rooms is used to specify the available allotments.
The availability is specified using the following values:

0-9: The number of rooms available on the specific date
*: The number of rooms available on the specific date is greater than 9
R: The room is bookable on the specific date on request
S: The room is set to Stop Sale on the specific date

A free sale is indicated using the value *. Unavailable rooms are assigned the value 0

The PatternLength attribute controls the length of the pattern string.
The default value is 1 and need not be written. The PatternLength attribute must be set, if the tour operator wants to specify dedicated availabilities greater than 9, e. g. 18 available rooms.

The start of the time range that the allotment applies to. Format YYYY-MM-DD.
A number of allotments must be set in the Pattern attribute for each day of the time range that is specified here.

Example: Start=May 01 End=May 20, the Pattern attribute contains exactly 20 characters.
Whereby the first character stands for the date May 01, the second character for May 02, etc.
Pattern=RR00**********57

On May 01 and May 02, the status is on request. On May 03 and May 04, no allotment is available. In the period from May 05 until May 18, the allotment is greater than 9 rooms. On May 19, there are 5 rooms available. On May 20, there are 7 rooms available

The Delta attribute is a mandatory attribute. It controls whether a full stock delivery or a Delta delivery (update) is performed.

Delta=false
If the attribute is set to Delta="false", a full stock delivery of vacancy information is performed.

Delta=true:
If the attribute is set to Delta="true", a Delta allotment delivery, containing only the changed data, is performed.
A Delta delivery is used to submit changed data on vacancies or stop sales that are used to update the sales system.
A Delta delivery is typically used to explicitly update individual dates.
The following actions can be performed using a Delta delivery:
- Change a current allotment
- Set the status to "booked out"
- Set the status to "StopSale" or "On Request"

Recommendations and important note on data deliveries:
One full stock delivery of the hotel allotments is performed per day. During the day, individual dates for specific hotel, room and board combinations are updated using a Delta EDF file.

A Delta EDF Allotment file cannot be delivered by itself (i. e., without performing a full stock delivery). A Delta delivery overrides the vacancy information included in the full stock delivery.
Only the dates, rooms or boards contained in the Delta EDF file will be overridden or updated. Alle other dates related to this hotel, that are included in the full stock delivery, but not in the Delta EDF file, remain unchanged.

Example Full Notification

<HotelAllotmentRoot **Delta="false"**>
<BasicData Code="AMTSPT0023" FileKey="NON" FileKeyCombination="true" ProgramType="SUP1" Source="xxx" TourOperatorCode="xxx" Usage="HotelOnly"/>

Example Delta Notification

<HotelAllotmentRoot **Delta="true"**>
<BasicData Code="AMTSPT0023" FileKey="NON" FileKeyCombination="true" ProgramType="SUP1" Source="xxx" TourOperatorCode="xxx" Usage="HotelOnly"/>

4.1 Hotel deactivation

A hotel can be fully eactivated by sending an allotment update without a specific room/board for all the remaining days set as stop sale (SS). This is an example for a total deactivation of S16 season:


```
<HotelAllotmentRoot xmlns="http://www.vilauma.de/edf/Hotel/Allotment"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" SchemaVersion="1.012" Delta="true">
	<BasicData Usage="HotelOnly" FileKeyCombination="true" Code="AAUTO14C" TourOperatorCode="TEST"
ProgramType="OWN1" FileKey="S16" Source="TEST"/>
	<SellingData SeasonIdentifier="S16">
		<Allotments>
			<Allotment
Pattern="SSSS
```

5 Appendices

5.1 Appendix A Custom Types definition

Custom Types are used as part of the DRV GlobalType structure (see www.globaltypecenter.de) or as standa alone identifications without reference to DRV-GT's

4 How are CustomTypes coded?

As with GlobalTypes® there are specific encoding rules:

- Coding length must not exceed 11 characters in length.
- Special characters are not used (such as "!"; "Ä", "&", "%", "+", etc.).
- The coding always starts **either** with the three-digit tour operator code (eg "UKH") **or** with the CustomType prefix "CTxx" (which is identical to the GlobalType prefix "GTxx" with a "C" in place of the "G"), in both cases followed by a delimiter "-". You should never start with "GT <digit> <digit>", "ST <digit> <digit>" or "AT <digit> <digit>".
- The remaining seven characters can be defined by the tour operator in an alphanumeric form.

Note: The uniqueness of the CustomTypes can only be guaranteed if you start the coding with the three digit tour operator code.

The maximum length of a CT is 11 chars, conclusively we have 6 positions left to define. I.e: CTxx-abcdef

Category	CustomType	Description
SOA	CT03-SOASTC	SealOfApproval - Safe Tourism Certified. Spain
	CT03-SOASST	SealOfApproval - Certificate Of Safe Tourism. Turkey
	CT03-SOASTM	SealOfApproval - Safe Travels CPPSIT. Mexico
	CT03-SOACSP	SealOfApproval - Clean and Safe. Portugal
	CT03-SOACCM	SealOfApproval - Certified Compliant COVID-19. Malta
	CT03-SOAAUE	SealOfApproval - Assured DUBAI
	CT03-SOAAPC	SealOfApproval - Advanced Precaution Certified. NORTH CYPRUS
	CT03-SOARST	SealOfApproval - Ready and Safe. Tunisia
General NHSP	CT03-WHO	Compliance of the WHO recomendations and local laws
	CT03-SASCSE	Safe access with sanitary controls to suppliers and employees
	CT03-SRP	Staff Replacement Policy
	CT03-ICDPAA	Intense cleaning and disinfection protocols for all areas
	CT03-SCO	Self Catering Options available
	CT03-DIST2M	General distance of 2 meters
Restaurant	CT03-DK	Disposable Kitchenware
	CT03-TBLD2M	Table distance of 2 meters
	CT03-ICBO	Individual / Closed Bottles only
Pool	CT03-AACRA	Additional adapted Chill-out/ Relaxation areas
	CT03-SBDD2M	SunBed distance of 2 meters
Guest	CT03-SPGAG	Self-protecting gear Available for guests (Masks/ Gloves/ Hand sanitizer)
	CT03-ACTFG	Available Covid-19 tests for guests
	CT03-GIP	Guest Infection Policy
	CT03-TCMFG	Temperature control measures for guests
Housekeeping	CT05-CSR	Clean and sanitized room
	CT05-EDCP	Intensification of disinfection / Cleaning protocols
	CT05-24CICO	24h time between check-out and check-in
	CT05-IO	Individual amenities
	CT05-IWT	Individual wraped Towels

	CT05-CTSC	Clean Towels (service cycle)
	CT05-RDSC	Room disinfection (Service cycle)
Kids Club	CT03-AAKC	Adapted Activities at Kids Club
	CT03-RGGA	Reduced Groups and Guided activities
Spa & Wellness	CT03-ASWT	Adapted Spa / Wellness Treatments
	CT03-ASWRA	Adapted Spa and Wellness Relax Areas
Gym	CT03-SPGG	Self-protecting gear Available in the gym
	CT03-UCRLG	Usage of Changing Rooms/ Lockers in the gym

5.2 Appendix B RatePlan Codes

Our system provides different options to deal with multiple prices for the same room, expressed in RatePlans. With these options, we target to cater for need of simplicity, best-price logic (in general preferred by B2C partners) or provide all options (in general preferred by B2B partners).

RatePlanCode consists of five alphanumeric characters where each position provides an information regarding other factor affecting the rate. From these five elements, first two elements are shown just for the Distributor's product management purposes (TO/OTA), only the last three are visible and form part of the room description for the final client to explain why the same room is bookable with different prices.

A RatePlan code is constructed from below RatePlan code elements:
Rate Type(1)|Rate Group(1)|Rate Refund(1)|Rate Sub Type(2)
Example: BHSP2 – BAR Rates - Hotel only - Semi-flexible – Promotional Rate 2

There is also a possibility of duplicating RatePlan which already exists in the contract. In this case the "." character, and a number starting with 1, and then subsecuently every iteration.
Example: BHSP2.1

Where in **Rate Type** column the elements mean:
0 → If the character is 0 would say that the value has been not defined – the rate stays unchanged like in the basic contract edition.
B → Bar - best available rates (changing due to rate updates)
S → Static – unchanged contract rate till the time of a promotion or an offer introduction
F → FIT - free individual traveller rates
R → Retail – advised end-price

Rate Group:
H → Hotel only - rates valid when booking contains only hotel
P → Packaging - rates valid when booking contains hotel + another product
O → Opaque - hotel rates must not be visible for end consumer
R → Rack - walk-in hotel rates for end consumer

Rate Refund:
N→Non refundable - immediately after booking; Nonrefundable rooms can be also still communicated within the RoomCode as a last character like it used to was (RMSD00000N)
S→ Semi-flexible – cancellation without fees up to 12 hours after booking

F→ Flexible – cancellation without fees up to 24 hours after booking

And in **Rate Sub Type**:
A→ Advanced Purchase - booking has to be paid before confirming
P→ Promotion rate

Rate Type(1), Rate Group(1), Rate Refund(1), Rate Sub Type(2)

Rate Type		**Rate Group**		**Rate Refund**		**Rate Sub Type**	
Code	**Description**	**Code**	**Description**	**Code**	**Description**	**Code**	**Description**
0	Rates	0	undefined	0	Undefined	00	Undefined
R	Retail rates	H	Hotel only	N	Non refundable	A0	Advanced Purchase
S	Static rates	P	Packaging	S	Semi-flexible	A2	Advanced Purchase 2
F	FIT Rates	O	Opaque	F	Flexible	A3	Advanced Purchase 3
B	BAR rates	R	Rack			P0	Promotional Rate
						P2	Promotional Rate 2
						P3	Promotional Rate 3
						P4	Promotional Rate 4
						P5	Promotional Rate 5
						P6	Promotional Rate 6
						P7	Promotional Rate 7
						P8	Promotional Rate 8
						P9	Promotional Rate 9
						01	[1]
						02	[2]
						03	[3]
						04	[4]
						05	[5]
						06	[6]
						07	[7]
						08	[8]
						09	[9]

6 Versions

Date	Version	Name	Revision
17/08/2016	V.1.0	Sergi Sanchez	
30/04/2021	V.1.1	Anna Siczek	Added Custom Types appendix Added RatePlan Codes and Appendix B