Problem 2 - Tax Calculator

The National Revenue Agency hired you to create software, which will help them to calculate the vehicle taxes.

You will be given **a string representing vehicles that will be taxed**. Each vehicle is separated by **">>",** where the first element is a string representing the **car type**, the second element is an integer representing the **years the tax should be paid**, and the third element is an integer representing the **kilometers** traveled.

There are three valid types of vehicles:

- **`"family"` –** the initial tax for a family car is **50 euros**
- **`" heavyDuty"` –** the initial tax for a heavy-duty is **80 euros**
- **`"sports"` –** the initial tax for a sports car is **100 euros**

If the car is not valid print **`"Invalid car type."`** and continue to the next vehicle.

When calculating tax keep in mind the following rules:

- For a **`family`** car, the tax declines by **5 euros** for every year in use. Also, the tax increases by **12 euros** for every **3000 km.** traveled.
- For a **`heavyDuty`** car, the tax declines by **8 euros** for every year in use. Also, the tax increases by **14 euros** for every **9000 km.** traveled.
- For a **`sports`** car, the tax declines by **9 euros** for every year in use. Also, the tax increase by **18 euros** for every **2000 km.** Traveled.

Input

You receive a **string** representing the vehicles, separated with ">>": **`"vehicle`$_1$`>>vehicle`$_2$`>>vehicle`$_3$`…"`**.

Output

- Upon every successful taxed car print: **`"A {car type} car will pay {total tax to pay} euros in taxes."`** Format the **total tax to pay** to the **second** digit after the decimal point.

- On the last line, print how much the National Revenue Agency will collect: **`"The National Revenue Agency will collect {total tax collected} euros in taxes."`** Formatted to the **second digit** after the decimal point.

Examples

Input	Output

`family 3 7210>>van 4 2345>>heavyDuty 9 31000>>sports 4 7410`	`A family car will pay 59.00 euros in taxes.`
	`Invalid car type.`
	`A heavyDuty car will pay 50.00 euros in taxes.`
	`A sports car will pay 118.00 euros in taxes.`

	`The National Revenue Agency will collect 227.00 euros in taxes.`

Comment
We start looping through the array, the first car is a **`family`** car, which is **3 years** in use and has **traveled 7210 km**. 3000 is contained 2 times in 7210. The taxes are calculate as follows: `2 * 12 + (50 - 3 * 5)` = **`59.00 euros`** The **`family`** car must pay **59.00 euros** in taxes. The next car is a **van**, which is an **invalid car type**. Next, we have **heavyDuty** car, with is **9 years** in use and has **traveled** 31000 km. The tax which **heavyDuty** car should pay is **50.00 euros**. On the last iteration, we have a **`sports`** car that is **4 years** in use and has **traveled** 7410 km. The tax which the **`sports`** car should pay is **118.00 euros**. At the end the National Revenue Agency collected 59.00 + 50.00 + 118.00 = **227.00 euros** in taxes.

Input	Output

`family 5 3210>>pickUp 1 1345>>heavyDuty 7 21000>>sports 5 9410>>family 3 9012`	`A family car will pay 37.00 euros in taxes.`
	`Invalid car type.`
	`A heavyDuty car will pay 52.00 euros in taxes.`
	`A sports car will pay 127.00 euros in taxes.`
	`A family car will pay 71.00 euros in taxes.`
	`The National Revenue Agency will collect 287.00 euros in taxes.`

JS Examples

The input will be an array with a **string**.

Input	Output

`([ 'family 3 7210>>van 4 2345>>heavyDuty 9 31000>>sports 4 7410' ])`	`A family car will pay 59.00 euros in taxes.`
	`Invalid car type.`
	`A heavyDuty car will pay 50.00 euros in taxes.`
	`A sports car will pay 118.00 euros in taxes.`
	`The National Revenue Agency will collect 227.00 euros in taxes.`

Comments
We start looping through the array, the first car is a **`family`** car, which should pay taxes for **3 years** in use and has **traveled 7210 km**.

3000 is contained 2 times in 7210.

The taxes are calculate as follows: `2 * 12 + (50 - 3 * 5) = 59.00 euros`

The **`family`** car must pay **59.00 euros** in taxes.

The next car is a **van**, which is an **invalid car type**.

Next, we have **heavyDuty** car, with **9 years** in use, and has **traveled** 31000 km. The tax which **heavyDuty** car should pay is **50.00 euros**.

On the last iteration, we have a **`sports`** car that is **4 years** in use and has **traveled** 7410 km. The tax which the **`sports`** car should pay is **118.00 euros**.

At the end the National Revenue Agency collected 59.00 + 50.00 + 118.00 = **227.00 euros** in taxes.

Input	Output

`([ 'family 5 3210>>pickUp 1 1345>>heavyDuty 7 21000>>sports 5 9410>>family 3 9012' ])`	`A family car will pay 37.00 euros in taxes.`
	`Invalid car type.`
	`A heavyDuty car will pay 52.00 euros in taxes.`
	`A sports car will pay 127.00 euros in taxes.`
	`A family car will pay 71.00 euros in taxes.`
	`The National Revenue Agency will collect 287.00 euros in taxes.`