

Session 1.

1. Install Node.js and use `npx create-react-app` to set up a new React project called `InstaCloneStarter` on your computer.

2. Open `App.js` in your `InstaCloneStarter` project and change the default text to display 'Welcome to My React Zomato App' inside an `<h1>` tag.

3. Create a new functional component called `TrendingSong.js` that returns an `<h2>` element with the text 'Trending on Spotify: Calm Down'. Import and use this component inside `App.js` so it shows below your main heading.

4. Explain in your own words (3-4 lines) how React's Virtual DOM makes updating the UI faster compared to traditional DOM manipulation.

Answer : -

1. Create a React Project

Open Terminal (or Command Prompt) and run:

`npx create-react-app InstaCloneStarter`

Move into the project folder:

`cd InstaCloneStarter`

Start the development server:

`npm start`

This will create a new React application named `InstaCloneStarter` and open it in your browser..

2. Update **App.jsx**

```
import TrendingSong from "../TrendingSong";

function App() {
  return (
    <div>
      <h1>Welcome to My React Zomato App</h1>
      <TrendingSong />
    </div>
  );
}
```

```
export default App;
```

TrendingSong.jsx

```
function TrendingSong() {  
  return (  
    <h2>Trending on Spotify: Calm Down</h2>  
  );  
}  
  
export default TrendingSong;
```

4. React Virtual DOM (3–4 Lines)

React uses a Virtual DOM, which is a lightweight copy of the real DOM. When data changes, React first updates the Virtual DOM and compares it with the previous version. It then updates only the changed elements in the real DOM instead of reloading the entire page. This makes UI updates faster and improves application performance.