

Session 5.

1. Create a React component called LikeButton that displays a button and a count. When the button is clicked, increment the count and update the display.
2. Build a SearchBar component where the user can type a product name (like Flipkart search). As the user types in the input box, display the current value below in real-time using React state.
3. Create a simple LoginForm component with two input fields: username and password. When the form is submitted, display an alert with the entered username and password.

Hint: Use the onSubmit event on the form and prevent the default page reload.
4. Build a PlaylistAdder component for a Spotify-style app: allow the user to enter a song name and artist, and when the form is submitted, add the song to a displayed list below the form.
5. Refactor your LoginForm to clear the input fields after successful form submission.

Constraint: Do not reload the page or use window.location.

Answer:-

LikeButton.jsx

```
import { useState } from 'react';
import { FaHeart } from 'react-icons/fa';

const LikeButton = () => {
  const [state, setState] = useState(0);
  return (
    <div>
      <h1><FaHeart className='' />{state}</h1>
      <button onClick={() => setState(state + 1)}>clicked</button>
    </div>
  )
}

export default LikeButton
```

SearchBar.jsx

```
import { useState } from "react";

const arr = ["hello", "mello", "jay ho", "mahadev", "Prem"];
```

```

const SearchBar = () => {
  const [name, setName] = useState("");

  return (
    <div>
      <input type="text" placeholder="Enter Your fav name"
        value={name}
        onChange={(e) => { setName(e.target.value) }}
      />
      {
        arr.filter((item) =>
item.toLowerCase().includes(name.toLowerCase()))
          .map((item, index)=>(
            <h1 key={index}>{item}</h1>
          ))
      }
    </div>
  )
}

export default SearchBar

```

LoginForm.jsx

```

import { useState } from "react";

const LoginForm = () => {

  const [userName, setUserName] = useState("");
  const [password, setPassword] = useState("");

  const handleSubmit = (e) =>{
    e.preventDefault();
    if(userName.trim() && password.trim()){
      alert(`UserName:-${userName} Password:-${password}`);
    }
    else{
      alert("Blank submission.....")
    }
    setUserName("");
    setPassword("");
  }

  return (
    <form
      onSubmit={handleSubmit}
      className="flex flex-col gap-[1rem] text-center mt-[2.4rem]">
      <div>

```

```

        <label>UserName: </label>
        <input type="text" className="border" value={userName}
onChange={e=> setUsername(e.target.value)}/>
      </div>
      <div>
        <label>Password: </label>
        <input type="password" className="border" value={password}
onChange={e=> setPassword(e.target.value)}/>
      </div>
      <div>
        <button className="border px-[0.5rem]" type="submit">Submit</button>
      </div>
    </form>
  )
}

export default LoginForm

```

PlaylistAdder.jsx

```

import { useState } from 'react';

const PlaylistAdder = () => {
  const [song, setSong] = useState("");
  const [artist, setArtist] = useState("")
  const [songs, setSongs] = useState([]);

  const handleSubmit = (e) => {
    e.preventDefault();
    setSongs([...songs, {song, artist}]);
  }

  return (
    <>

      <form onSubmit={handleSubmit}>
        <div>
          <label htmlFor="">Song Name</label>
          <input type="text" placeholder='Enter Song..' value={song}
onChange={e => setSong(e.target.value)} className='border' />
        </div>
        <div>
          <label htmlFor="">Artist Name</label>
          <input type="text" placeholder='Enter ArtistName...'
value={artist} onChange={e => setArtist(e.target.value)} className='border'
/>
        </div>
        <div>
          <button type='submit'>Submit</button>

```

```

        </div>
      </form>
    <ul>
      {
        songs.map((item, index)=>(
          <li key={index}>{item.song} - {item.artist}</li>
        ))
      }
    </ul>
  </>
)
}

export default PlaylistAdder

```

App.jsx

```

import LoginForm from "../Exercise/LoginForm"

const App = () => {
  return (
    <>
      <LikeButton />
      <SearchBar />
      <LoginForm />
      <PlaylistAdder />
    </>
  )
}

export default App

```