

Session 6.

1. Create a React component called Playlist that takes an array of song objects (with title and artist) as a prop and uses map() to render each song in an unordered list.
2. Build a React component called OrderStatus that receives a prop isDelivered (boolean) and conditionally renders 'Order Delivered 🎉' if true, or 'Order on the way 🚚' if false, using a ternary operator.
3. In a React component called FollowerList, render a list of followers (array of usernames). If the array is empty, display 'No followers yet' instead of the list.

***Hint:** Use a conditional check before mapping the array.*
4. Create a React component called CartSummary that takes an array of cart items (each with name and price). Use map() to display each item, and show 'Cart is empty' if there are no items. Add a button that only appears if there are 3 or more items, labeled 'Checkout Now'.

Answer:-

Playlist.jsx

```
const Playlist = ({ arr }) => {
  return (
    <div>
      <ul>{
        arr.map((item, index) => (
          <li key={index}>{item.song} - {item.artist}</li>
        ))
      }
    </ul>
  </div>
)
}

export default Playlist
```

OrderStatus.jsx

```
const OrderStatus = ({isActive}) => {
```

```

    return (
      <div>
        {isActive ? <h1>Order Delivered 🚚</h1> : <h1>Order on the way
🚚</h1>}
      </div>
    )
  }
}

export default OrderStatus

```

FollowerList.jsx

```

const arr = ["name1", "name2", "name3", "name4", "name5"];

const FollowerList = () => {
  return (
    <div>
      <h2>Follower</h2>
      {
        arr.length > 0 ? (
          <ul>
            {
              arr.map((item, index) => (
                <li key={index}>{item}</li>
              ))
            }
          </ul>
        ) : (<p>No follower yet</p>)
      }
    </div>
  )
}

export default FollowerList

```

CartSummary.jsx

```

const arr = [
  {name : "name1", price:"price1"},
  {name : "name2", price:"price2"},
  {name : "name3", price:"price3"},
]

const CartSummary = () => {

```

```

return (
  <div>
    <h1>CartSummary Details....</h1>
    <ul>
      { arr.length > 0 ? (
        arr.map((item,index)=>(
          <li key={index}> {item.name} - {item.price}</li>
        ))): ( <h1>Cart is empty</h1> )
      }
    </ul>
    {arr.length >= 3 ? <button>Checkout Now</button> : "" }
  </div>
)
}

export default CartSummary

```

App.jsx

```

import { useState } from "react";
import CartSummary from "../Session6/CartSummary";
import FollowerList from "../Session6/FollowerList";
import OrderStatus from "../Session6/OrderStatus";
import Playlist from "../Session6/Playlist";

const arr = [
  { song: "title1", artist:"artist1"},
  { song: "title2", artist:"artist2"},
  { song: "title3", artist:"artist3"},
]

const App = () => {

  const [isActive, setIsActive] = useState(false);
  return (
    <div>
      <Playlist arr = {arr}/>
      <button onClick={()=> setIsActive(!isActive)}>Done</button>
      <OrderStatus isActive={isActive}/>
      <FollowerList />
      <CartSummary />
    </div>
  )
}

export default App

```