

Session 7.

1. Create a React component called TrendingSongs that uses the useEffect hook to log 'Component mounted' in the console when the component first renders.
2. Build a React component called IPLScoreFetcher that uses useEffect to fetch live match data from <https://jsonplaceholder.typicode.com/posts> when the component mounts, and display the title of the first post as the current 'match headline'.
3. Create a MovieSuggestions component that fetches a list of movies from <https://jsonplaceholder.typicode.com/users> inside useEffect on mount, and displays the names in a list. Show a loading message while the data is being fetched.

Hint: Use a loading state variable and update it once data is received.
4. Refactor an existing React component that fetches data in a button click handler to instead use useEffect so the data is fetched automatically when the component mounts, not on button click.

Constraint: Only move the fetch logic; do not change the UI or styling.

Answer:-

TrendingSongs.jsx

```
import { useEffect } from 'react'

const TrendingSongs = () => {
  useEffect(() => {
    console.log("Components Mounted succesfully...")
  }, [])
  return (
    <div>TrendingSongs</div>
  )
}

export default TrendingSongs
```

IPLScoreFetcher.jsx

```
import { useEffect, useState } from "react";
```

```

const IPLScoreFetcher = () => {

  const [iplDataPosts, setIplDataPosts] = useState([]);
  const [iplDataAlbum, setIplDataAlbum] = useState([]);
  const [iplDataPhotos, setIplDataPhotos] = useState([]);

  useEffect(() => {
    async function fetchData() {
      const results = await Promise.allSettled([
        fetch("https://jsonplaceholder.typicode.com/posts")
          .then((res) => res.json()),
        fetch("https://jsonplaceholder.typicode.com/albums")
          .then((res) => res.json()),
        fetch("https://fakestoreapi.com/products").then((
res) => res.json())
      ]);
      console.log(results);

      if (results[0].status == "fulfilled") {
setIplDataPosts(results[0].value) }
      if (results[1].status == "fulfilled") {
setIplDataAlbum(results[1].value) }
      if (results[2].status == "fulfilled") {
setIplDataPhotos(results[2].value) }
    }
    fetchData();
  }, [])

  return (
    <div className="grid lg:grid-cols-4 sm:grid-cols-2 gap-
[0.5rem] text-center px-[0.5rem] mt-[0.5rem] mb-[0.5rem]" >
      {iplDataPhotos.map((photos) => {
        return <div key={photos.id} className="border
flex flex-wrap flex-col justify-center items-center max-w-[400px]
min-h-[250px]">
          <img src={photos.image} alt={photos.title}
className="h-50"/>
          <h1>{photos.title}</h1>
        </div>
      })}
    </div>
  )
}

```

```

    }
  </div>
)
}

export default IPLScoreFetcher

```

MovieSuggestions.jsx

```

import { useState } from 'react';

const MovieSuggestions = () => {
  const [users, setUsers] = useState([]);
  const [isLoading, setLoading] = useState(true);

  // useEffect(() => {
  //   setLoading(true);
  //   const fetchData = async () => {
  //     const result = await
fetch("https://jsonplaceholder.typicode.com/users")
  //       .then((res) => res.json())
  //       .then((data) => setUsers(data))
  //       .catch((error) => alert(error.message))
  //       .finally(setLoading(false))
  //   }
  //   fetchData();
  // }, [])

  const handleData = () => {
    setLoading(true);
    fetch("https://jsonplaceholder.typicode.com/users")
      .then((res) => res.json())
      .then((data) => setUsers(data))
      .catch((error) => alert(error.message))
      .finally(setLoading(false))
  }

  return (
    <div>
      {isLoading ? <h1>Loadinggg</h1> : ""}

```

```

    {
      users.map((user) => {
        return <div key={user.id}>
          <h1>{user.name}</h1>
        </div>
      })
    }
    <button onClick={handleData}>Fetched Data</button>
  </div>
)
}
export default MovieSuggestions

```

App.jsx

```

import IPLScoreFetcher from './Session7/IPLScoreFetcher'
import MovieSuggestions from './Session7/MovieSuggestions'
import TrendingSongs from './Session7/TrendingSongs'

const App = () => {
  return (
    <div>
      <TrendingSongs />
      <IPLScoreFetcher />
      <MovieSuggestions />
    </div>
  )
}

export default App

```