

Session 8.

1. Create a React component called `SearchBar` with an input field and a button. Use `useRef` to focus the input field automatically when the component mounts.
2. Build a simple login form with two controlled input fields (username and password) using `useState`. After the user clicks the 'Login' button, use `useRef` to clear and focus the username field.
3. Make a React component called `AddToPlaylist` where users can enter a song name and click 'Add'. After adding, use `useRef` to focus the input again so users can quickly add another song.
Hint: Call `inputRef.current.focus()` after updating the playlist.
4. Refactor an existing React form (for example, a feedback form with name and message fields) to use controlled components for both inputs, and add a button that, when clicked, focuses the message input using `useRef`.

Answer:-

`SearchBar.jsx`

```
import { useRef, useState } from 'react';

const SearchBar = () => {
  const userRef = useRef();
  const [username, setUsername] = useState("");
  const [password, setPassword] = useState("");
  const [text, setText] = useState("");

  const handleSubmit = (e) => {
    alert(`Username: ${username}\nPassword: ${password}\n
Message:- ${text}`);
    setPassword("");
    setUsername("");
    setText("");
    userRef.current.focus();
  }

  return (
    <div className='flex flex-col max-w-[350px] '>
      <input type="text"
        placeholder='Search Product...'
        value={username}
        onChange={(e) => {setUsername(e.target.value)}}
      />
    </div>
  )
}
```

```

        />
        <input type="text"
            placeholder='Search paswrod...'
            value={password}
            onChange={(e)=>{setPassword(e.target.value)}}
        />
        <textarea placeholder='Enter Your Message..'
            value={text}
            onChange={(e)=>setText(e.target.value)}
            ref={userRef}
        ></textarea>
        <button onClick={handleSubmit}>Submit</button>
    </div>
)
}

export default SearchBar

```

AddToPlaylist.jsx

```

import { useRef, useState } from 'react';

const AddToPlaylist = () => {
    const inputRef = useRef();
    const [song, setSong] = useState("");
    const [playlist, setPlaylist] = useState([]);
    const handleSong = () => {
        setPlaylist([...playlist, song])
        setSong("");
        inputRef.current.focus();
    }
    return (
        <>
            <div className='flex gap-2'>
                <input type="text"
                    placeholder='Enter Song'
                    value={song}
                    onChange={(e) => setSong(e.target.value)}
                    ref={inputRef}
                    className='border'
                />

```

```

        <button onClick={handleSong} className='border
px-[0.5rem]' >Add</button>
      </div>
      <ul>
        {
          playlist.map((item, index)=>(
            <li key={index}>{item}</li>
          ))
        }
      </ul>
    </>
  )
}

export default AddToPlaylist

```

App.jsx

```

import AddToPlaylist from "../Session8/AddToPlaylist"
import SearchBar from "../Session8/SearchBar"

const App = () => {
  return (
    <div>
      <SearchBar />
      <AddToPlaylist />
    </div>
  )
}

export default App

```