

Session 11.

1. Install Axios in your React project and use it to fetch a list of trending movies from the TMDb API (<https://api.themoviedb.org/3/movie/popular>) and display the first 5 movie titles in a component.

Hint: You can sign up for a free API key at TMDb or use a mock API like <https://jsonplaceholder.typicode.com/posts> if you want to skip authentication.

2. Create a React component called AddPlaylist that lets a user enter a playlist name and description, then use Axios to POST this data to <https://jsonplaceholder.typicode.com/posts> and show a success message when the request completes.

3. Build a simple search bar that lets users search for restaurants by name using Axios to GET data from <https://mocki.io/v1/570c5e5c-8c8b-4c1e-8c8b-4c1e8c8b4c1e> (or any public mock API with a list of restaurants), filter the results as the user types, and display matching restaurant names.

4. Update your movie list component to handle loading and error states: show 'Loading...' while the Axios request is in progress and display an error message if the API call fails.

Hint: Use useState to track loading and error states.

5. Use ChatGPT or GitHub Copilot to generate an example of an Axios POST request in React, then adapt the code to submit a new comment (with fields: username and comment) to <https://jsonplaceholder.typicode.com/comments> and display the response below your form.

Answer:-

AddPlaylist.jsx

```
import axios from 'axios';
import { useState } from 'react';

const AddPlaylist = () => {
  const [username, setUsername] = useState("");
  const [message, setMessage] = useState("");
  const [error, setError] = useState("");
  const handleSubmit = async (e) => {
    e.preventDefault();
    try {
      const response = await
      axios.post("https://jsonplaceholder.typicode.com/posts", {
```

```

        username , message
      })
      console.log(response.data);
      setUsername("");
      setMessage("");
    }catch(error){
      console.log(error.message)
      setError(error.message);
    }
  }
}
return (
  <div>
    <form onSubmit={handleSubmit}>
      <label>UserName</label>
      <input type="text"
        placeholder='Enter UserName'
        value={username}
        onChange={(e)=> setUsername(e.target.value)}
      />
      <label>Message</label>
      <input type="text"
        placeholder='Enter Message'
        value={message}
        onChange={(e)=> setMessage(e.target.value)}
      />
      <button type='submit'>Submit</button>
    </form>
    { error && <p>{error}</p> }
  </div>
)
}
export default AddPlaylist

```

MoviesFetchData.jsx

```

import axios from 'axios';
import { useEffect, useState } from 'react';

const MoviesFetchData = () => {
  const [movies, setMovies] = useState([]);
  useEffect(() => {
    const fetchData = async () =>{
      const result = await
        axios.get("https://fakestoreapi.com/products")
      setMovies(result.data);
    }
    fetchData();
  });
}

```

```

    }, [])
    return (
      <div>
        {
          movies.map((movie) => (
            <h1 key={movie.id}>{movie.title}</h1>
          ))
        }
      </div>
    )
  }
}

export default MoviesFetchData

```

FilterData.jsx

```

import axios from 'axios';
import { useEffect, useState } from 'react';

const FilterData = () => {
  const [comments, setComments] = useState([]);
  const [search, setSearch] = useState("");
  const [isLoading, setIsLoading] = useState(true);

  useEffect(()=>{
    setIsLoading(true);
    try {
      const fetchData = async () =>{
        const result = await
        axios.get("https://jsonplaceholder.typicode.com/comments")
        console.log(result.data)
        setComments(result.data);
      }
      fetchData();
    } catch (Error) {
      throw new Error(error.message)
    }
    setIsLoading(false);
  },[])

  return (
    <div>
      <input type="text"
        placeholder='Enter Your name'
        value={search}
        onChange={(e)=>setSearch(e.target.value)}
      />
      { isLoading ? <p>Loading....</p> : ""}
    </div>
  )
}

```

```

        {
          comments
            .filter((comment)=>
comment.name.toLowerCase().includes(search.toLowerCase()))
            .map((comment)=> <h1 key={comment.id}> {comment.name}</h1>)
        }
      </div>
    )
  }
}

export default FilterData

```

App.jsx

```

import AddPlaylist from "../Session11/AddPlaylist"
import FilterData from "../Session11/FilterData"
import MoviesFetchData from "../Session11/MoviesFetchData"

const App = () => {
  return (
    <div>
      <AddPlaylist />
      <MoviesFetchData/>
      <FilterData />
    </div>
  )
}

export default App

```