

SOP: Creating a Receipt Header (GRN) in Speed WMS

Sensitivity: Internal

1. Purpose

To define the standard procedure for creating a receipt header (GRN) in Speed WMS in order to formally declare incoming goods before stock creation and processing.

2. Accessing the Receipt Creation Screen

The receipt creation function can be accessed by:

- **Selecting Create Receipt from the contextual menu, or**
- **Clicking the Add (+) button in the Receipts module**

Once opened, the receipt screen is divided into two sections:

- **Upper section: Receipt Header**
 - **Lower section: Receipt Lines (goods details)**
-

3. Receipt Header – System-Initialized Fields

The following fields are automatically populated when the receipt form opens and are not editable unless stated otherwise:

- **Activity Code**
 - **Represents the current Speed WMS environment**
 - **Read-only field**
- **Speed Receipt Number (REE_NORE)**
 - **System-generated internal counter**
 - **Unique and non-modifiable**
- **Receipt Date and Time**
 - **Defaults to the creation date and time**
 - **Can be modified if required**
- **Default Reception Dock**
 - **Pre-selected based on system configuration**

- **Displays all dock-type locations available in the environment**
-

4. Mandatory User-Defined Fields

The user must complete the following fields before saving the receipt:

- **Customer Account (REE_CCLI)**
 - **Required if the activity manages multiple customers**
 - **Supplier / Third-Party Code**
 - **Selected from the list of third parties configured in the environment**
 - **A new third-party record can be created directly from the selection screen**
 - **Receipt Reference**
 - **Alphanumeric field**
 - **Optional but strongly recommended**
 - **Facilitates searching and identification instead of using the Speed receipt number**
-

5. Receipt Lines (Goods Declaration)

- **Goods are entered in the lower table of the receipt screen**
 - **Each line represents an item declared on the receipt**
 - **Lines are stored in REL_DAT once the receipt is saved**
-

6. Outcome

After saving:

- **A receipt header record is created in REE_DAT**
 - **Associated receipt lines are created in REL_DAT**
 - **The receipt becomes available for validation, storage, and downstream processes (stock, movements, missions)**
-

7. Related Tables

- **REE_DAT – Receipt Header**
 - **REL_DAT – Receipt Lines**
 - **STK_DAT – Stock (generated after validation)**
 - **MVT_DAT – Movements**
-

8. Common RAG Questions This SOP Supports

- ***How do I create a GRN in Speed WMS?***
- ***Which fields are mandatory when creating a receipt?***
- ***What information is auto-generated in a receipt header?***
- ***Where are receipt headers and lines stored in the database?***