

Sensitivity: Internal

Speed WMS – Standardized SQL Scripts Reference

Scope: JetPark, Durban Northbound, and other contract warehouses

Tables Used:

Table Name Description

REE_DAT Receipt Header

REL_DAT Receipt Lines

STK_DAT Stock

MVT_DAT Movements

OPE_DAT Order Header

OPL_DAT Order Lines

MIE_DAT Mission Header

MIL_DAT Mission Lines

CHG_DAT Loading Header

CHL_DAT Loading Lines

1. Reversal of a Closed GRN

this step can only be done by the support teams as they have access to the database.

Check the GRN status:

```
SELECT REE_ETRE, REE_KEYU, REE_CCLI, *  
FROM REE_DAT  
WHERE ACT_CODE = ' Activity Code'  
AND REE_NORE = 'Receipt Number';
```

Notes:

- **ACT_CODE** = Activity Code
- **REE_NORE** = Receipt Number
- **REE_ETRE** = GRN Status
- **REE_KEYU** = Receipt ID

Sensitivity: Internal

- **REE_CCLI** = Customer Account Code
- **REE_TOP1** = Status for Pegasus: 1 = sent, 0 = not sent

Optional update to reverse a closed GRN:

UPDATE REE_DAT

SET REE_ETRE = '100',

REE_TOP1 = 0

WHERE ACT_CODE = ' Activity Code'

AND REE_NORE = 'Receipt Number ';

AND REE_KEYU = ' Receipt ID '

AND REE_CCLI = ' Customer Account Code ';

2. Checking Receipt Lines

Query all lines for a given receipt:

SELECT REE_KEYU, REL_KEYU, REL_NoSU, *

FROM REL_DAT

WHERE ACT_CODE = 'Activity Code'

AND REE_NoRE = ' Receipt Number';

Explanation:

This shows all individual lines under a specific GRN, with their unique identifiers.

3. Resending Files to Pegasus

Reset the REE_TOP1 flag for resending:

UPDATE REE_DAT

SET REE_TOP1 = 0

WHERE ACT_CODE = 'Activity Code'

AND REE_NORE = ' Receipt Number'

AND REE_KEYU = ' Receipt ID'

AND REE_CCLI = 'Customer Account Code';

Sensitivity: Internal

Tips for Safe Execution:

- 1. Always run SELECT first to check records before running UPDATE.**
- 2. Keep a backup or snapshot of relevant tables if updating production data.**
- 3. Use these scripts only if automated processes fail, to avoid breaking**

dependencies.