

Handling Loaded Support Tickets (Loading Management)

Sensitivity: Internal

System: Speed WMS

Module: Loading Management

Audience: Support / Technical Team

Purpose

This procedure is used when a **support ticket indicates that containers are already loaded**, but the **Loading Management Line table (CHL_DAT)** is not correctly updated.

Important:

These steps should be executed **only if the system does not update automatically**.

Step 1: Create Temporary Order Table (#order_table)

This step creates a temporary table to capture **order numbers linked to loaded containers** for further processing.

```
SELECT DISTINCT
    chg.chg_lib,
    chl.ope_nooe,
    chg.act_code
INTO #order_table
FROM chg_dat chg
JOIN chl_dat chl
    ON chg.chg_code = chl.chg_code
    AND chg.chg_date = chl.chg_date
WHERE chg.act_code = 'ZAR';
```

Outcome:

- Temporary table #order_table is created
 - Contains order numbers associated with loading records
-

Step 2: Identify Containers Missing in CHL_DAT

This step checks for **containers that exist in CHG_DAT** but are **missing from the Loading Management Line table (CHL_DAT)**.

```
SELECT
    'ZAR' AS act_code,
    ord.ope_nooe AS ope_nooe,
    chg.chg_date,
    chg.chg_code,
    '100' AS chl_pour,
    'SUPPORT' AS chl_crqi,
    GETDATE() AS current_time
FROM chg_dat chg
JOIN #order_table ord
    ON chg.act_code = ord.act_code
    AND chg.chg_lib = ord.CHG_LIB
LEFT JOIN chl_dat chl
    ON chg.chg_code = chl.chg_code
    AND chg.chg_date = chl.chg_date
    AND chg.act_code = 'ZAR'
WHERE chl.chg_code IS NULL
    AND chg.chg_stat BETWEEN '030' AND '040';
```

Interpretation

-  **No results:** No issue, data already aligned
-  **Results returned:** Containers exist but are **not recorded in CHL_DAT**

Step 3: Insert Missing Records into CHL_DAT

If Step 2 returns results, insert the missing container records into the Loading Management Line table.

```
INSERT INTO chl_dat
```

```

(act_code, ope_nooe, chg_date, chg_code, chl_pour, chl_crqi, chl_crda)
SELECT
  'ZAR',
  ord.ope_nooe,
  chg.chg_date,
  chg.chg_code,
  '100',
  'SUPPORT',
  GETDATE()
FROM chg_dat chg
JOIN #order_table ord
  ON chg.act_code = ord.act_code
  AND chg.chg_lib = ord.CHG_LIB
LEFT JOIN chl_dat chl
  ON chg.chg_code = chl.chg_code
  AND chg.chg_date = chl.chg_date
  AND chg.act_code = 'ZAR'
WHERE chl.chg_code IS NULL
  AND chg.chg_stat BETWEEN '030' AND '040';

```

Outcome:

- Missing loading records are inserted
- Containers now appear correctly in Loading Management

Step 4: Clean Up Temporary Table

After completing the update, remove the temporary table.

```
DROP TABLE #order_table;
```

Important Notes

1. Automated Updates (Preferred)

- This logic is already integrated with:
 - **Container Release Note**
 - **GDN ETAT**
- When **Operations preview any container** in the Loading Management module, the system **should update automatically**

2. Manual Intervention (Support Only)

- Use this procedure **only when automatic updates fail**
- Intended for **troubleshooting and correction**
- Requires **database access**

Expected Outcome

- All loaded containers are correctly reflected in CHL_DAT
- Loading Management data is consistent
- Support ticket can be resolved without impacting operations