

React Continued

Vincent Huang

That's right, I use React



R I can't

E Setup

A Node environment

C Help

T

Review: Component Tree



Review: Component Tree

When should you break a component down into smaller parts?

- Code getting too long/hard-to-read
 - i.e. Building a house: instead of making the whole house-plan at once, you have specific plans for the bathroom, the master bedroom, the kitchen, etc.
- It conceptually “contains” parts that encapsulate their own functionality
 - i.e. In a shopping mall: each store has its own set of staff, merchandise, etc, so it would make sense to encapsulate a “store” as its own part.
- Controlling information flow between app sections!

Think... refactoring code to make your life easier as the *architect* of a web app.

Quora

Home

Following

Answer

Spaces

Notifications

Search Quora

Profile

World

Add Question

Massachusetts Institute of Technology

Hunger

Psychology

Visiting and Travel

Science

Movies

Food

Cooking

Technology

History

Books

Music

Discover Spaces

About · Careers · Terms · Privacy · Acceptable Use · Businesses · Your Ad Choices

Claire Cheng

What is your question or link?


Answer · Recommended for you

Dodi Zaku · November 22

I have good taste about fact and data.

Have you ever met a celebrity who asked you, "Do you know who I am?" and you said no?

I dated Jennifer Lawrence in 2008. I met her at a yoga class in Santa Monica. I had no idea who she was when I met her. I just thought she was cute and I started talking to her. She said I shouldn't watch a lot of TV, and that she was on a [c](#) [\(more\)](#)



36.1K

72

113

Worldlifestyle

Sponsored

Improve Your Feed

☐ Follow 5 more Spaces

☒ Upvote 5 more good pieces of content

☐ Ask your first question

☐ Fill out your profile

☒ Answer a question

Spaces to follow

Writing & Blogging

Writing Articles | Publishing Stories [...]

Better Programming

Advice and tutorials for programming and...

Reactjs Javascript

We share best articles and content about...

Python & Machine Learning

Suggestions to learn Python for machine...

Code

Novice or Advanced, we have advice. Start...

College Admission Secrets

Great advice and the

Quora: what are the underlying components?

4

Quora

Home

Following

Answer

Spaces

Notifications

Search Quora

Add Question

Massachusetts Institute of Technology

Hunger

Psychology

Visiting and Travel

Science

Movies

Food

Cooking

Technology

History

Books

Music

Discover Spaces

About · Careers · Terms · Privacy · Acceptable Use · Businesses · Your Ad Choices

Feed

Claire Cheng

What is your question or link?


Answer · Recommended for you

Dodi Zaku · November 22

I have good taste about fact and data.

Have you ever met a celebrity who asked you, "Do you know who I am?" and you said no?

I dated Jennifer Lawrence in 2008. I met her at a yoga class in Santa Monica. I had no idea who she was when I met her. I just thought she was cute and I started talking to her. She said I shouldn't watch a lot of TV, and that she was on a [c](#) [\(more\)](#)



36.1K | 72 | 113

Worldlifestyle

Sponsored

Improve Your Feed

☐ Follow 5 more Spaces

☒ Upvote 5 more good pieces of content

☐ Ask your first question

☐ Fill out your profile

☒ Answer a question

Spaces to follow

Writing & Blogging

Writing Articles | Publishing Stories [...]

Better Programming

Advice and tutorials for programming and...

Reactjs Javascript

We share best articles and content about...

Python & Machine Learning

Suggestions to learn Python for machine...

Code

Novice or Advanced, we have advice. Start...

College Admission Secrets

Great advice and the

Quora: what are the underlying components?

5

Navbar

Quora Home Following Answer Spaces Notifications [Add Question](#)

Massachusetts Institute of Technology

Hunger

Psychology

Visiting and Travel

Science

Movies

Food

Cooking

Technology

History

Books

Music

Discover Spaces

About · Careers · Terms · Privacy · Acceptable Use · Businesses · Your Ad Choices

Feed

Claire Cheng

What is your question or link?

Answer · Recommended for you

Dodi Zaku · November 22

I have good taste about fact and data.

Have you ever met a celebrity who asked you, "Do you know who I am?" and you said no?

I dated Jennifer Lawrence in 2008. I met her at a yoga class in Santa Monica. I had no idea who she was when I met her. I just thought she was cute and I started talking to her. She said I shouldn't watch a lot of TV, and that she was on a [c](#) [\(more\)](#)

36.1K 72 113

Worldlifestyle
Sponsored

Improve Your Feed

☐ Follow 5 more Spaces

☒ Upvote 5 more good pieces of content

☐ Ask your first question

☐ Fill out your profile

☒ Answer a question

Spaces to follow

Writing & Blogging
Writing Articles | Publishing Stories [...]

Better Programming
Advice and tutorials for programming and...

Reactjs Javascript
We share best articles and content about...

Python & Machine Learning
Suggestions to learn Python for machine...

Code
Novice or Advanced, we have advice. Start...

College Admission Secrets
Great advice and the

Quora: what are the underlying components?

Navbar

Quora

Home

Following

Answer

Spaces

Notifications

Search Quora

Add Question

Massachusetts Institute of Technology

Hunger

Psychology

Visiting and Travel

Science

Movies

Food

Cooking

Technology

History

Books

Music

Discover Spaces

About · Careers · Terms · Privacy · Acceptable Use · Businesses · Your Ad Choices

Feed

Claire Cheng

What is your question or link?


Answer · Recommended for you

Dodi Zaku · November 22

I have good taste about fact and data.

Have you ever met a celebrity who asked you, "Do you know who I am?" and you said no?

I dated Jennifer Lawrence in 2008. I met her at a yoga class in Santa Monica. I had no idea who she was when I met her. I just thought she was cute and I started talking to her. She said I shouldn't watch a lot of TV, and that she was on a [c](#) [\(more\)](#)



36.1K

72

113

Worldlifestyle

Sponsored

Improve Your Feed

☐ Follow 5 more Spaces

☒ Upvote 5 more good pieces of content

☐ Ask your first question

☐ Fill out your profile

☒ Answer a question

Spaces to follow

Writing & Blogging

Writing Articles | Publishing Stories [...]

Better Programming

Advice and tutorials for programming and...

Reactjs Javascript

We share best articles and content about...

Python & Machine Learning

Suggestions to learn Python for machine...

Code

Novice or Advanced, we have advice. Start...

College Admission Secrets

Great advice and the


Left Sidebar

Right Sidebar

Quora: what are the underlying components?



7

Navbar



Quora: what are the underlying components?

Review: States & Props



Important!!!!!!!!!!!!!!

You can't directly edit a
component's state from another
component!

A Workaround: Callback Functions

passing setState function to child and then calling it from there

```
//ParentComponent
const changeCatHappiness = () => {
  setCatHappiness(catHappiness + 1);
}
```

```
return (
  <ChildComponent updateFunction={changeCatHappiness} />
);
```

```
//ChildComponent
props.updateFunction();
```

A workaround...

passing setState function to child and then calling it from there

```
//ParentComponent  
const changeCatHappiness = () => {  
  setCatHappiness(catHappiness + 1);  
}
```

```
return (  
  <ChildComponent updateFunction={changeCatHappiness} />  
);
```

keyword:
WORKAROUND


```
//ChildComponent  
props.updateFunction();
```

Make **states stay**, make **props pass**


Make **states stay**, make **props pass**
(downwards)

props practice


Which of these should be props?




Which of these should be props?




Which of these should be props?





Which of these should be props?



Which of these should be props?



Which of these should be props?



each **comment** & **like** should have a post ID associated with it so we know which post it belongs to!


now... more on state

In-depth: Utilizing state

Scenario: Initializing state

```
const MyHouse = (props) => {  
  const [persons, setPersons] = useState([]);  
  const [pets, setPets] = useState([]);  
  const [exists, setExists] = useState(false);
```

In-depth: how to modify state



Modifying state → setting state



```
exists = True;
```

In-depth: Utilizing state

Scenario: Setting new values

```
setExists(true);
```

In-depth: Utilizing state

Scenario: Modifying original state

```
buyDog = () => {  
  |   setPets(pets.concat("dog"));  
  }  
}
```

In-depth: Utilizing state

Scenario: Alternative way to update state with object destructuring (generally recommended)

```
buyDog = () => {  
  |   setPets([...pets, "dog"]);  
  }  
}
```

What is this function going to print?

```
testingStuff = () => {  
  /* assume persons starts as an empty array [] */  
  setPersons([...persons, "me"]);  
  console.log(persons);  
}
```

A. []

B. ["me"]

What is this function going to print?

```
testingStuff = () => {  
  /* assume persons starts as an empty array [] */  
  setPersons([...persons, "me"]);  
  console.log(persons);  
}
```

NO GUARANTEE!

A. []

B. ["me"]

Setting State is *ASYNC*.

What if we want to do something immediately after state is changed?


eg. add someone to persons and then print the persons array

We need a new React feature for this:
the `useEffect` hook!

But first...


Review: Lifecycle Timeline

Lifecycle Timeline




(continue to render after every state variable change)

Lifecycle Timeline



Lifecycle Timeline



useEffect() hook

- Runs after specific variables change
 - Can think of as response to state change
 - Commonly used to load data into state
 - Call an API/perform some computation/etc. at specific times
- syntax: `useEffect(function, optional dependency array)`
 - runs function every time a variable in dependency array changes

useEffect() example

```
testingStuff = () => {  
  /* assume persons starts as an empty array [] */  
  setPersons([...persons, "me"]);  
  console.log(persons);  
}
```

```
testingStuff = () => {  
  setPersons([...persons, "me"]);  
}  
  
useEffect(() => {  
  console.log(persons);  
}, [persons])
```

useEffect() hook - dependency array examples

- `useEffect(function, [var1, var2])` runs function every time `var1` or `var2` changes
- `useEffect(function, [])` runs function once, immediately after initialization
- `useEffect(function)` runs every time *any* state variable changes

get() and post()

Nitty gritty details: [utilities.js](#)

```
get("/api/foo", { bar: 0 }).then((res) => console.log(res));
```


Fetching data

```
useEffect(() => {  
  get("/api/packages").then((packageList) => {  
    setPackages(packageList);  
  })  
}, [])
```

Sending data

```
<Button onClick={handleToggleAdmin} />
```

```
const handleToggleAdmin = () => {  
  post("/api/user/admin", {admin: !admin}).then(() => {  
    setAdmin(!admin);  
  })  
}
```

Review: JSX

Just a way to write HTML onto the page, but from JavaScript!

```
const element = <h1> Follow me at http://twitter.com/vvhuang\_ </h1>;
```

Example: JSX for multiple pieces of content


```
let header = <h1>I love kevin qian</h1>;
let content = <p>uwu</p>;

return (
  <div>
    {header}
    {content}
  </div>
)
```

Example: JSX for multiple pieces of content

```
let header = <h1>I love kevin qian</h1>;  
let content = <p>uwu</p>;
```

```
return (  
  <div>  
    {header}  
    {content}  
  </div>  
)
```



valid JavaScript!

Example: display a loading indicator

Some state indicating if the page is still loading data or not

Show “Loading...” while page is loading data, otherwise the content

Conditional rendering

```
return loading ? (  
  <div>  
    <h1>Title</h1>  
    <p>Loading... Buy bitcoin while waiting for the page to load</p>  
  </div>  
) : (  
  <div>  
    <h1>Title</h1>  
    <p>Actual page content</p>  
  </div>  
);
```

condition ? resultIfTrue : resultIfFalse

More modular conditional rendering

```
let content = loading ? (  
  <p>Loading... Buy bitcoin while waiting for the page to load</p>  
) : (  
  <p>Actual page content</p>  
);  
  
return (  
  <div>  
    <h1>Title</h1>  
    {content}  
  </div>  
)
```


Concise conditional rendering

```
return (  
  <div>  
    <h1>Title</h1>  
    <p>  
      {loading  
        ? "Loading... Buy bitcoin while waiting for the page to load"  
        : "Actual page content"}  
    </p>  
  </div>  
)
```

Loop rendering

- Common pattern: render an array of data in React
- Need a simple way to *map* data to HTML


Review: map()

Creates a new array by applying the callback function to every element of the starting array.

```
let myArray = [1, 2, 3, 4, 5];  
let modifiedArray = myArray.map(x => x * 3);  
// modifiedArray === [3, 6, 9, 12, 15]
```

```
const celsiusToFahrenheit = tempC => {  
  const tempF = tempC * 1.8 + 32;  
  return tempF;  
}  
  
let celsius = [-40, -20, 0, 20, 40];  
let fahrenheit = celsius.map(celsiusToFahrenheit);  
// fahrenheit === [-40, -4, 32, 68, 104]
```

Using map() in React



Example: HTML

```
let data = [  
  { id: 0, text: "My favorite food is doritos" },  
  { id: 1, text: "I like nachos because they look like doritos" },  
];  
return data.map((item) => {  
  return <div key={item.id}>{item.text}</div>;  
});  
//<>  
//<div key={0}>My Favorite food is doritos</div>  
//<div key={1}>I like nachos because they look like doritos</div>  
//</>
```

Example: Components

```
let data = [  
  { id: 0, text: "My favorite food is doritos" },  
  { id: 1, text: "I like nachos because they look like doritos" },  
];  
return data.map((item) => {  
  return <ItemComponent key={item.id}>{item.text}</ItemComponent>;  
});  
//<>  
//<ItemComponent key={0}>My Favorite food is doritos</ItemComponent>  
//<ItemComponent key={1}>I like nachos because they look like doritos</ItemComponent>  
//</>
```

Example: Components (more concise)

Don't need to **return** if you skip the curly braces — otherwise you do!

```
let data = [
  { id: 0, text: "My favorite food is doritos" },
  { id: 1, text: "I like nachos because they look like doritos" },
];
return data.map((item) =>
  <ItemComponent key={item.id}>{item.text}</ItemComponent>
);
//<>
//<ItemComponent key={0}>My Favorite food is doritos</ItemComponent>
//<ItemComponent key={1}>I like nachos because they look like doritos</ItemComponent>
//</>
```

Questions?

Oh wait we still have extra time...
Let's talk more about JS and React!
(but feel free to zone out if you need a break)

Math

As with many languages, JS has a Math object with helpful methods:

- `Math.abs()`
- `Math.min()`, `Math.max()`
- `Math.PI`, `Math.sin()`
- etc.

Dates

JS has built-in Date objects that will save your life when making certain kinds of apps (eg. anything with a calendar):

```
let bday = new Date(1912, 10, 30) // Nov 30
let nextDay = new Date(bday);
let nextDay.setDate(nextDay.getDate() + 1); // nextDay is Dec 1
```

Sets

- Arrays and objects should be enough for storing most of your site data
- Sometimes you'll also want to use sets, which only store distinct values.

```
let s = new Set()  
let s.add(1)  
let s.add(2)  
let s.add(1) // s = {1, 2}
```

JSON

Convert objects into strings and vice versa!

```
let x = {1: 2, foo: {uwu: 'owo'}}  
let y = JSON.stringify(x) // y is '{"1":2,"foo":{"uwu":"owo"}}'  
let z = JSON.parse(y) // retrieves x
```

- Useful if you need to store info as a string (eg. in a database) and then retrieve it later
- Our utilities.js get/post request code does this

Other React info if you're bored

Hooks reference: <https://reactjs.org/docs/hooks-reference.html>

- React provides other hooks besides `useState` and `useEffect` to support features like global context and memoization. (We won't cover these because they're used much less often.)

OK now we're actually done