NeoSignal

AI Intelligence Daily · Multi-Source · Cross-Verified

12 October 2026

108 verified · 229 raw · 5 sources

108	2	106	0
TOTAL	VERIFIED	CONFIRMED	EMERGING

Pipeline

Scrape HackerNews (Show/Top/New), Reddit (r/artificial, r/MachineLearning, r/singularity, r/LocalLLaMA), TechCrunch AI, VentureBeat AI, MIT Tech Review, The Verge AI, Wired AI, ArXiv CS.AI

Filter 40+ AI keyword patterns — LLMs, alignment, safety, research, tooling

Dedup Title-similarity (45% threshold) merges cross-source variants

Score Authenticity = 0.5 base + 0.3 per extra source + diversity + HN score bonuses

Rank Sorted by authenticity. Below 0.25 threshold are dropped.

Authenticity Tiers

VERIFIED	**0.80 - 1.00**	3+ independent sources including media
CONFIRMED	**0.50 - 0.79**	2 sources or 1 high-quality media
EMERGING	**0.25 - 0.49**	Single-source; passes AI keyword filter

Source Breakdown

Source	Articles	Category
ArXiv CS.AI	99	Media
TechCrunch AI	4	Media
HackerNews	4	Community
The Verge AI	3	Media
MIT Tech Review	1	Media

VERIFIED INTELLIGENCE — 2 stories

VERI

Neural networks are more modular than single neurons suggest

ArXiv CS.AI +2 sources 100%

arXiv:2610.12842v1 Announce Type: new Abstract: Neural networks routinely develop representations in which individual neurons contribute to multiple distinct functions, leading to the widespread view that such networks lack modular organization. We challenge this conclusion by...

https://arxiv.org/abs/2610.12842

VERI

Satya Nadella says we should assume all AI models are ‘compromised’

The Verge AI +1 source 80%

In a lengthy post on X, Microsoft's CEO laid out his views on the dangers posed by highly advanced AI models and how to confront those risks. Nadella says we can no longer accept a world where AI is treated as a "set of nested black boxes" whose advice and actions we simply...

https://www.theverge.com/ai-artificial-intelligence/1009337/satya-nadella-says-we-shoul...

CONFIRMED SIGNALS — 106 stories

CONF

Show HN: Littleguys – Claude Code, Codex and OpenClaw agents in your menu bar

HackerNews 50% HN 15

A long running thorn in my side, solved by Claide.

https://littleguys.hervalicio.us

CONF

Show HN: Skills Hub, a desktop app for managing AI agent skills

HackerNews 50% HN 9

Updated API with faster responses and added MCP 2.0

https://github.com/qufei1993/skills-hub

CONF

Show HN: Preloop – GitHub Actions locally in microvms and SSH/pause failures

HackerNews 50% HN 8

No summary — see link for full article.

https://github.com/preloopdev/preloop

CONF

Show HN: LLMxRay an open-source observability tool for LLMs

HackerNews 50% HN 6

No summary — see link for full article.

https://github.com/LogneBudo/llmxray

CONF

Can the AI industry persuade data center opponents by getting rid of NDAs?

TechCrunch AI 50%

On Equity, we debate the impact of data center moratoriums and whether the AI industry has a communication problem.

https://techcrunch.com/2026/10/11/can-the-ai-industry-persuade-data-center-opponents-by...

CONF

These execs think voice AI hasn’t reached its ChatGPT moment yet

TechCrunch AI 50%

Voice AI's often misses important points for its context layer, and causes the whole pipeline to break

https://techcrunch.com/2026/10/11/these-execs-think-voice-ai-hasnt-reached-its-chatgpt-...

CONF

Silicon Valley is falling in line with Trump’s attempt to rename AI

The Verge AI 50%

When President Donald Trump announced his plans to rebrand artificial intelligence as "super intelligence," you'd be forgiven for being skeptical that it would catch on. While most of the broader population is sticking with AI, some of Silicon Valley's most powerful are falling...

https://www.theverge.com/ai-artificial-intelligence/1009406/silicon-valley-is-falling-i...

0 CONF

Learning to use local AI is exciting, overwhelming, and frustrating

The Verge AI 50%

I'm embarking on a journey I've so far been hesitant to go on: actually using AI on the regular. Giving my most personal data to cloud services has been a major hold up for me, but it's increasingly possible to run powerful models locally to see what they're capable of. Is this...

https://www.theverge.com/ai-artificial-intelligence/1008484/learning-local-ai-hermes-qw...

1 CONF

Faithfulness Without Anchors: A Position Paper on the Structural Misalignments of Explainable AI Faithfulness Metrics for Feature Importance

ArXiv CS.AI 50%

arXiv:2610.12493v1 Announce Type: new Abstract: Explainable Artificial Intelligence (XAI) tools have often been presented as methods to increase trust in machine learning models by making aspects of their algorithms more human-understandable. However, evidence accumulated over...

https://arxiv.org/abs/2610.12493

2 CONF

A Multi-Agent LLM System for Automated Tuning of Specialized Neural Network Models

ArXiv CS.AI 50%

arXiv:2610.13663v1 Announce Type: new Abstract: Many machine learning approaches are two-level: an expert selects a class of methods, within this class the choice of key components is critical and usually manual. This paper addresses the automatic tuning of these components and...

https://arxiv.org/abs/2610.13663

3 CONF

Representation Alignment from a Few Paired Data via Distilled Optimal Transport

ArXiv CS.AI 50%

arXiv:2610.12781v1 Announce Type: new Abstract: Aligning two independently pretrained unimodal encoders typically demands millions of paired examples. In this paper, we study the regime where only $N \sim 100$--500 pairs are available, while unpaired data on either side is...

https://arxiv.org/abs/2610.12781

4 CONF

VEPA: Verified Evolving Formal Policy for Lifelong LLM Agent Guardrails

ArXiv CS.AI 50%

arXiv:2610.12813v1 Announce Type: new Abstract: LLM agents increasingly operate over sensitive resources, such as private documents and mutable system states, which can create serious safety and security risks. Runtime guardrails should therefore make inspectable, reproducible,...

https://arxiv.org/abs/2610.12813

5 CONF

Mitigating Capability Degradation in LLM Self-Improvement via Representation Geometry Regularization

ArXiv CS.AI 50%

arXiv:2610.12855v1 Announce Type: new Abstract: On-Policy Self-distillation is a self-improvement paradigm that enables large language models (LLMs) to improve their capabilities by leveraging the same model as both teacher and student under different conditioning contexts....

https://arxiv.org/abs/2610.12855

6 CONF

MPMMine: Better Benchmarks for Constraint Acquisition

ArXiv CS.AI 50%

arXiv:2605.26279v2 Announce Type: replace Abstract: Constraint Acquisition (CA) and related research on the validation and enhancement of Mathematical Programming (MP) models using domain knowledge artifacts are currently limited by inadequate benchmarks. The existing benchmarks...

https://arxiv.org/abs/2605.26279

7 CONF

DeFiRank: Federated Pairwise Ranking for Governance in Decentralized Financial Networks

ArXiv CS.AI 50%

arXiv:2610.12916v1 Announce Type: new Abstract: Existing governance approaches in decentralized financial networks rely on manual review processes conducted by human committees, which introduces subjective bias, creates a scalability bottleneck under high network volume, and...

https://arxiv.org/abs/2610.12916

8 CONF

AI-Mediation in Retail Markets: Revenue Effects and Assortment Optimization

ArXiv CS.AI 50%

arXiv:2610.12917v1 Announce Type: new Abstract: AI shopping assistants increasingly influence which products consumers consider. We study retail assortment planning under AI mediation, where a retailer chooses a catalog, an AI intermediary forms a customer-facing shortlist, and...

https://arxiv.org/abs/2610.12917

9 CONF

Learning More by Training Less: Uncertainty-Guided Progressive Contraction for Efficient Reasoning Post-Training

ArXiv CS.AI 50%

arXiv:2610.12933v1 Announce Type: new Abstract: Large language models have achieved remarkable advances in complex reasoning. However, scaling reasoning post-training with ever-larger corpora can substantially increase training cost without proportional performance gains. In...

https://arxiv.org/abs/2610.12933

0 CONF

SmartSalesBench: A Resistance-Aware Multi-Turn Benchmark for Evaluating LLM Sales Agents

ArXiv CS.AI 50%

arXiv:2610.12975v1 Announce Type: new Abstract: We present SmartSalesBench, the first multi-turn conversational benchmark explicitly designed to evaluate large language model (LLM) sales agents against psychologically grounded, resistant buyer personas. Existing task-oriented...

https://arxiv.org/abs/2610.12975

1 CONF

ABLEIST: Intersectional Disability Bias in LLM-Generated Hiring Scenarios

ArXiv CS.AI 50%

arXiv:2510.10998v2 Announce Type: replace-cross Abstract: Large language models (LLMs) are increasingly under scrutiny for perpetuating identity-based discrimination in high-stakes domains such as hiring, particularly against people with disabilities (PwD). However, existing...

https://arxiv.org/abs/2510.10998

2 CONF

Benchmarking Embedding Geometries and Clustering Algorithms for Unsupervised Patent Claim Classification

ArXiv CS.AI 50%

arXiv:2610.12997v1 Announce Type: new Abstract: Prior-art retrieval systems are structurally organized around classification codes, making cross-code discovery difficult. This paper asks if an unsupervised representation trained on patent text can recover relevant connections...

https://arxiv.org/abs/2610.12997

3 CONF

Hindsight Structured Advice Distillation: Steering Executor Agents with Advisors Trained on Their Failures and Task Characteristics

ArXiv CS.AI 50%

arXiv:2610.13000v1 Announce Type: new Abstract: Language-model agents are used for specialized work such as financial research, healthcare and law. Such agents are often capable enough for a task but still miss its details. In finance, for example, these details include which...

https://arxiv.org/abs/2610.13000

4 CONF

Provenance-Aware Belief Updating in Human-AI Feedback Loops

ArXiv CS.AI 50%

arXiv:2610.13008v1 Announce Type: new Abstract: In repeated human-AI interaction, a single observation can be quoted, summarized, and returned to a model as multiple reports, making repetition look like independent corroboration. We study whether language models can use supplied...

https://arxiv.org/abs/2610.13008

5 CONF

Attention Sees, MLP Refuses: Tracing the Attention-to-MLP Safety Pathway in LLMs

ArXiv CS.AI 50%

arXiv:2610.13078v1 Announce Type: new Abstract: Safety-aligned large language models (LLMs) remain vulnerable to jailbreaks and can over-refuse benign requests. Understanding these failures requires distinguishing harmfulness recognition from the computation that writes refusal....

https://arxiv.org/abs/2610.13078

6 CONF

DRYLAB-Bench: Benchmarking the Biosecurity Risk of Agentic LLM Mutation Design

ArXiv CS.AI 50%

arXiv:2610.13116v1 Announce Type: new Abstract: As large language models (LLMs) acquire advanced biological design capabilities, they offer substantial research benefits but simultaneously introduce severe dual-use risks, such as engineering enhanced pathogens or drug-resistant...

https://arxiv.org/abs/2610.13116

7 CONF

Locate, Judge, Read: Role-Specialized Tool Agents over a Knowledge-Point Index for Open-Domain Multimodal Document QA

ArXiv CS.AI 50%

arXiv:2610.13128v1 Announce Type: new Abstract: Question answering over large heterogeneous document collections requires first finding the right passages and then reading them, yet current retrieval-augmented agents give one model both kinds of tools and let it schedule itself....

https://arxiv.org/abs/2610.13128

8 CONF

Looking Ahead and Back: Anticipatory Generative Modeling for Road-Network Trajectories

ArXiv CS.AI 50%

arXiv:2610.13131v1 Announce Type: new Abstract: Trajectory generation underpins urban applications such as traffic management and urban planning. Within road networks, vehicle movement along road segments is largely deterministic, whereas transitions at intersections are...

https://arxiv.org/abs/2610.13131

9 CONF

DP-MIND: Differentially private memory-guided Long context Inference

ArXiv CS.AI 50%

arXiv:2610.13132v1 Announce Type: new Abstract: LLM-as-a-Service has become a dominant paradigm for accessing large language models without requiring local deployment. However, the process raises severe privacy concerns when user queries may include sensitive or confidential...

https://arxiv.org/abs/2610.13132

0 CONF

Competence-Aware Orchestration for LLM-Based Multi-Agent Systems

ArXiv CS.AI 50%

arXiv:2610.13144v1 Announce Type: new Abstract: LLM-based multi-agent systems (MAS) have emerged as a promising paradigm for enhancing complex reasoning through role specialization and collaboration, yet a key challenge remains: how can collaboration be adapted to a backbone's...

https://arxiv.org/abs/2610.13144

1 CONF

VIGOR: Verifiable Industrial Geometry Optimization and Repair in Scene Programs

ArXiv CS.AI 50%

arXiv:2610.13145v1 Announce Type: new Abstract: Large language models (LLMs) increasingly generate structured layouts and executable scene programs from natural-language instructions. However, executability does not imply engineering feasibility: an industrial scene program may...

https://arxiv.org/abs/2610.13145

2 CONF

SWE-Critix: Post-Training Generalist Verifiers for Assessing Coding-Agent Trajectories

ArXiv CS.AI 50%

arXiv:2610.13356v1 Announce Type: new Abstract: Coding agents are increasingly deployed for end-to-end software engineering tasks, where a readily available oracle evaluator that defines the success criteria is often absent. This motivates verifications for coding agents that...

https://arxiv.org/abs/2610.13356

3 CONF

Forgetting is Not Always Bad: A Neuro-Inspired Memory Repair Mechanism for Poisoned LLM Agents

ArXiv CS.AI 50%

arXiv:2610.13267v1 Announce Type: new Abstract: Large language model (LLM) agents are highly vulnerable to memory-poisoning attacks. Existing defenses primarily rely on external modules for either static memory isolation or continuous online auditing, resulting in low memory...

https://arxiv.org/abs/2610.13267

4 CONF

Masked Diffusion Language Agents for Tool-Integrated Chemical Reasoning

ArXiv CS.AI 50%

arXiv:2610.13330v1 Announce Type: new Abstract: Designing tool-integrated reasoning agent systems for complex chemical tasks remains a fundamental challenge. Although recent chemical agents have demonstrated promising performance through the integration of external tools, they...

https://arxiv.org/abs/2610.13330

5 CONF

Preference-Conditioned Multi-Objective Reinforcement Learning for Tactical Decision Making in Heavy-Duty Vehicles

ArXiv CS.AI 50%

arXiv:2601.18783v3 Announce Type: replace-cross Abstract: A central difficulty in applying reinforcement learning to real-world applications such as autonomous driving is that conventional scalar reward formulations obtained by aggregating multiple often competing objectives may...

https://arxiv.org/abs/2601.18783

6 CONF

Reasoning-Token Spikes Under Prompted Untruthful Responses in Large Language Models

ArXiv CS.AI 50%

arXiv:2610.10405v2 Announce Type: replace Abstract: Monitoring the chain-of-thought of reasoning artificial intelligence (AI) models remains a key approach to detecting deception and other forms of misbehavior in such models. However, semantic chain-of-thought monitoring depends...

https://arxiv.org/abs/2610.10405

7 CONF

A Local Agentic AI Framework to Generate Edge Case Scenarios for Safety Assurance

ArXiv CS.AI 50%

arXiv:2610.13479v1 Announce Type: new Abstract: Generating edge case scenarios is crucial for training, testing and safety assuring autonomous systems. This identifies hazardous failures to increase system reliability and robustness, ensures the system can still function safely...

https://arxiv.org/abs/2610.13479

8 CONF

Beyond Domain-Routed Supervision: Cross-Teacher Guarding for Multi-Teacher On-Policy Distillation

ArXiv CS.AI 50%

arXiv:2610.13521v1 Announce Type: new Abstract: Multi-teacher on-policy distillation (MOPD) extends on-policy distillation (OPD) by routing domain-specific data to specialized teachers, integrating their capabilities through dense token-level supervision on student-generated...

https://arxiv.org/abs/2610.13521

9 CONF

MAGMA-Bench: Evaluating Long-Horizon Embodied Agents under Dynamic Tasks and Execution Failures

ArXiv CS.AI 50%

arXiv:2610.13534v1 Announce Type: new Abstract: Long-horizon embodied agents must maintain task-relevant information, coordinate heterogeneous robots, and adapt their decisions as execution unfolds. Existing benchmarks investigate dynamic task execution and embodied multi-agent...

https://arxiv.org/abs/2610.13534

0 CONF

MENTOR: Learning from Failure with On-Policy Pedagogical Intervention

ArXiv CS.AI 50%

arXiv:2610.13594v1 Announce Type: new Abstract: Reinforcement Learning from Verifiable Rewards (RLVR) is a key driver for Large Reasoning Models, but it is vulnerable to "zero-reward collapse", a training failure where a sudden increase in task difficulty causes the learning...

https://arxiv.org/abs/2610.13594

1 CONF

Learning Size Independent Constraint Models from Input Data and Positive and Negative Example Solutions

ArXiv CS.AI 50%

arXiv:2610.13640v1 Announce Type: new Abstract: In this paper we describe a Constraint Acquisition Tool that generates size independent constraint programs from input data and positive and negative example solutions of multiple problem instances. The system finds size specific...

https://arxiv.org/abs/2610.13640

2 CONF

UkrMeme: Multimodal Explainable Persuasion Detection in Ukrainian Memes

ArXiv CS.AI 50%

arXiv:2610.13783v1 Announce Type: new Abstract: Memes play a central role in modern online communication, especially in contexts of political conflict where visual and textual cues combine to convey persuasive messages. We study persuasive technique detection in Ukrainian memes...

https://arxiv.org/abs/2610.13783

3 CONF

Studying Comics at Scale with Artificial Intelligence: The PAGE Framework and Three Studies of American Comics and Japanese Manga

ArXiv CS.AI 50%

arXiv:2610.13840v1 Announce Type: new Abstract: Comics are one of the great visual records of the twentieth century: hundreds of thousands of pages in which a mass readership saw its leaders, its wars and its heroes. Most of this record has never been studied as a whole; comics...

https://arxiv.org/abs/2610.13840

4 CONF

RATED: Reliability-Aware AI Agent Tool Retrieval via Execution Dynamics

ArXiv CS.AI 50%

arXiv:2610.13889v1 Announce Type: new Abstract: As AI agents increasingly rely on external tools, accurate retrieval is essential for reliable behavior. Existing methods optimize semantic relevance but largely ignore tool availability during execution. To address this gap, we...

https://arxiv.org/abs/2610.13889

5 CONF

Energy-Efficient Spiking Neural Networks for Sensing-Aided Beam Prediction

ArXiv CS.AI 50%

arXiv:2610.12507v1 Announce Type: cross Abstract: Sensing-aided beam prediction can reduce the beam-training overhead of millimeter-wave (mmWave) systems by leveraging environmental information from complementary modalities such as vision and position. However, the resulting...

https://arxiv.org/abs/2610.12507

6 CONF

AutoIndexer: Flexible-Order Decoding by Training Causal Models on Chains of Edits

ArXiv CS.AI 50%

arXiv:2610.12545v1 Announce Type: cross Abstract: Autoregressive decoding is less suited to non-causally ordered data, e.g., cross-references or future dependencies, since their outputs cannot be revised post hoc, unlike iterative human reasoning. Diffusion LLMs partially...

https://arxiv.org/abs/2610.12545

7 CONF

Mesh-Native Tokenisation: Retrofitting Foundation Models to Unstructured Data

ArXiv CS.AI 50%

arXiv:2610.12618v1 Announce Type: cross Abstract: Physics foundation models are an increasingly popular approach for building versatile emulators for spatiotemporal systems. They require tokenisation layers that lift physical field data into a latent representation suitable for...

https://arxiv.org/abs/2610.12618

8 CONF

Machine Learning and Time-Series Foundation Models for Day-Ahead Electricity Forecasting in a University Building

ArXiv CS.AI 50%

arXiv:2610.12638v1 Announce Type: cross Abstract: Day-ahead electricity forecasts can help building operators schedule heating, ventilation, and other services around anticipated demand. Choosing a forecasting model also requires balancing accuracy with its forecast-time inputs,...

https://arxiv.org/abs/2610.12638

9 CONF

GeoFitBench-LLM: A Benchmark for Assessing Large Language Models' Capabilities in Geospatial Data Requirements Elicitation for Geo-Analytic Tasks

ArXiv CS.AI 50%

arXiv:2610.12669v1 Announce Type: cross Abstract: Large language models are becoming central to GeoAI systems, yet their evaluation rarely considers the elicitation of geospatial data requirements. This omission is critical as retrieval oriented geo-analytic tasks cannot be...

https://arxiv.org/abs/2610.12669

0 CONF

Unsupervised Multimodal Reward Modeling

ArXiv CS.AI 50%

arXiv:2610.12707v1 Announce Type: cross Abstract: Vision-language reward models are trained on annotated preference pairs, which are expensive to collect, can disagree, and are ranked by benchmark accuracy. We build one with no human preference label: a linear head on an...

https://arxiv.org/abs/2610.12707

1 CONF

Semantic Views: Certified Reuse of LLM Labels Across Semantic Queries

ArXiv CS.AI 50%

arXiv:2610.12768v1 Announce Type: cross Abstract: Semantic query engines evaluate natural-language filters with a large language model, and every evaluation is a costly oracle call. Optimizers that reduce these calls face a dilemma: cascades that trust a cheap proxy miss their...

https://arxiv.org/abs/2610.12768

2 CONF

Meta-Reflective Evolution Effectively Improves Production AI Systems

ArXiv CS.AI 50%

arXiv:2610.12794v1 Announce Type: cross Abstract: Large Language Model (LLM)-guided evolutionary optimization has successfully improved prompts, programs, and even entire AI systems. Most optimization methods select a candidate from the search frontier, then mutate it in one LLM...

https://arxiv.org/abs/2610.12794

3 CONF

UniConFlow: A Unified Constrained Flow-Matching Framework for Certified Motion Planning

ArXiv CS.AI 50%

arXiv:2506.02955v3 Announce Type: replace-cross Abstract: Generative models have become increasingly powerful tools for robot motion generation, enabling flexible and multimodal trajectory generation across various tasks. Yet, most existing approaches remain limited in handling...

https://arxiv.org/abs/2506.02955

4 CONF

When Generative Models Act as Simulators

ArXiv CS.AI 50%

arXiv:2610.12847v1 Announce Type: cross Abstract: A simulator summarizes an environment in a state that users can read and change. Generative models learn representations of the world without explicit specification, but offer no built-in way to edit that world's state. We...

https://arxiv.org/abs/2610.12847

5 CONF

Co-Modifying Application Code and Deployment Infrastructure: A Causal Study of AI Agent Pull Requests

ArXiv CS.AI 50%

arXiv:2610.12849v1 Announce Type: cross Abstract: Current software engineering agents are evaluated predominantly inside isolated sandboxes against synchronous local tests. However, deploying features in collaborative repositories requires modifying continuous integration...

https://arxiv.org/abs/2610.12849

6 CONF

Localized Generative Design of Ship Hulls with Diffusion Models and High-Fidelity Assessment

ArXiv CS.AI 50%

arXiv:2610.12870v1 Announce Type: cross Abstract: Practical ship design requires localized refinement and performance evaluation. This paper presents a reward-directed diffusion framework for localized hull optimization. Parametric masking during dataset generation restricts...

https://arxiv.org/abs/2610.12870

7 CONF

Surfing the Activation Wave: Analyzing the Information and Geometry of LLM Hidden States for Speculative Decoding

ArXiv CS.AI 50%

arXiv:2610.12939v1 Announce Type: cross Abstract: Decoder hidden states from different layers of large language models (LLMs) often encode complementary information. However, existing speculative decoding methods typically rely on a small set of target-model layers chosen using...

https://arxiv.org/abs/2610.12939

8 CONF

Matched-Context Group Policy Optimization for LLM Agent Training

ArXiv CS.AI 50%

arXiv:2610.13755v1 Announce Type: cross Abstract: Training long-horizon language model agents requires assigning credit to intermediate decisions from sparse terminal feedback. Within a finite group of sibling rollouts, useful action comparisons depend on their context, evidence...

https://arxiv.org/abs/2610.13755

9 CONF

MotionCoach: Constructing Multimodal Guidance for Video Professional Motion Editing

ArXiv CS.AI 50%

arXiv:2610.12963v1 Announce Type: cross Abstract: Video editing models achieve strong performance in modifying appearance, backgrounds, styles, and motions, empowered by large-scale training data. Beyond general scenarios, professional motions are significant in performance,...

https://arxiv.org/abs/2610.12963

0 CONF

The Evidence Anchoring Boundary: Where Visual Interventions Matter and When They Help in Multimodal LLMs

ArXiv CS.AI 50%

arXiv:2610.12981v1 Announce Type: cross Abstract: Visual interventions provide a training-free way to reduce hallucinations in multimodal large language models. However, an intervention may have little leverage at some layers and may damage a correct answer even when it changes...

https://arxiv.org/abs/2610.12981

1 CONF

What Should SFT Learn? Conditional Information Gain for Generalizable Post-Training

ArXiv CS.AI 50%

arXiv:2610.12995v1 Announce Type: cross Abstract: Supervised fine-tuning (SFT) remains a widely used approach for post-training large language models, because fixed demonstrations can directly introduce desired reasoning strategies and behavioral patterns. Yet forcing a model to...

https://arxiv.org/abs/2610.12995

2 CONF

Generalized Proximal Policy Optimization: Unifying LLM RL Algorithms from the Perspective of Divergence

ArXiv CS.AI 50%

arXiv:2610.13015v1 Announce Type: cross Abstract: Reinforcement learning has become the foundational paradigm for enhancing the reasoning capabilities of LLMs. Yet the dominant approach, Proximal Policy Optimization (PPO), relies on a geometrically degenerate clipping proxy that...

https://arxiv.org/abs/2610.13015

3 CONF

Evolving Creatives with Clicks: CTR-Driven Advertising image Editing via Attribute Disentanglement and Preference Alignment

ArXiv CS.AI 50%

arXiv:2610.13066v1 Announce Type: cross Abstract: The optimization objective for e-commerce advertising creatives has shifted from aesthetic quality to online business metrics like click-through rate (CTR). Recent methods generate appealing ad images from product images by...

https://arxiv.org/abs/2610.13066

4 CONF

How Reliable are AMR Parser Outputs? Uncertainty Estimation for AMR Parsing

ArXiv CS.AI 50%

arXiv:2610.13236v1 Announce Type: cross Abstract: Recent advances have significantly improved the performance of Abstract Meaning Representation (AMR) parsers, yet determining when their outputs can be trusted remains largely unexplored. This work presents the first study of...

https://arxiv.org/abs/2610.13236

5 CONF

Agent4Spec: An LLM-based Agentic System to Optimize API Specifications through Automated Validation and Market Analysis

ArXiv CS.AI 50%

arXiv:2610.13273v1 Announce Type: cross Abstract: API specifications serve as critical documentation for modern software development, directly impacting integration efficiency and client code generation. While recent advancements have leveraged Large Language Models (LLMs) to...

https://arxiv.org/abs/2610.13273

6 CONF

Agreement Without Alignment: Label-Free Rubric Clarification Increases LLM-Judge Consensus but Not Agreement with Humans

ArXiv CS.AI 50%

arXiv:2610.13303v1 Announce Type: cross Abstract: LLM judges are increasingly deployed as panels, and disagreement among panel members is often read as a symptom of an unclear rubric. We test a label-free procedure that turns this disagreement into rubric repairs. The procedure...

https://arxiv.org/abs/2610.13303

7 CONF

In-Context Learning for System Identification: Probabilistic Formulation, Long-Sequence Handling, and Benchmark Validation

ArXiv CS.AI 50%

arXiv:2610.13411v1 Announce Type: cross Abstract: Traditional system identification typically involves two steps: initially, training data is processed to estimate a model of the system of interest; then, the model is used to predict outputs for new input queries. In contrast,...

https://arxiv.org/abs/2610.13411

8 CONF

CNN-Transformer with Sigmoid Label for High-Resolution Sub-Degree DOA Estimation

ArXiv CS.AI 50%

arXiv:2610.13433v1 Announce Type: cross Abstract: This paper addresses the grid quantization error of deep-learning (DL)-based direction-of-arrival (DOA) estimation. Classification- based DOA methods discretize the continuous angular space into a grid, so that with a peak-based...

https://arxiv.org/abs/2610.13433

9 CONF

When MLLMs miss what humans read: diagnosing and learning to read squint text

ArXiv CS.AI 50%

arXiv:2610.13465v1 Announce Type: cross Abstract: Multimodal LLMs can fail to read text embedded in an image's coarse structure (text a human recovers by squinting) and report that no text is present. We name this class Squint Text and study it as a recognition deficiency,...

https://arxiv.org/abs/2610.13465

0 CONF

Graph World Models for Constrained Epidemic Policy Planning

ArXiv CS.AI 50%

arXiv:2609.35545v2 Announce Type: replace-cross Abstract: Epidemic policy planning often requires coordination between geographical regions, taking into account mobility-driven spillovers and how to make use of limited resources. Existing methods either lack action-conditioned...

https://arxiv.org/abs/2609.35545

1 CONF

Defence against the dark arts of distillation: Unsupervised discovery of subliminal learning

ArXiv CS.AI 50%

arXiv:2610.13536v1 Announce Type: cross Abstract: When a language model is distilled from a teacher that shares its base parameters, the student can inherit behavioural traits of the teacher---including misalignment---even from data that is semantically unrelated to the trait...

https://arxiv.org/abs/2610.13536

2 CONF

AudioTETRIS: Token Elimination via Transitional Importance Signals for Efficient Audio LLMs

ArXiv CS.AI 50%

arXiv:2610.13600v1 Announce Type: cross Abstract: Large Audio Language Models (LALMs) achieve strong performance on speech-text tasks, but standard audio encoders produce hundreds of tokens for even short audio clips. Because self-attention scales quadratically in sequence...

https://arxiv.org/abs/2610.13600

3 CONF

SelectArena: A Modern Benchmark for Feature Selection on Real-world Tabular Data

ArXiv CS.AI 50%

arXiv:2610.13644v1 Announce Type: cross Abstract: Selecting a subset of features (columns) from a tabular dataset is a ubiquitous challenge in real-world applications. Industry experts seek to minimize model training costs, climate scientists require an interpretable subset of...

https://arxiv.org/abs/2610.13644

4 CONF

Pretraining and Test-Time Training Budgets Matter for ARC: A Controlled Study of VARC and TRM

ArXiv CS.AI 50%

arXiv:2610.13660v1 Announce Type: cross Abstract: The Abstraction and Reasoning Corpus (ARC) is increasingly used to evaluate whether neural networks can infer task-specific transformations from few demonstrations. Recent ARC models differ in architecture, but also in broader...

https://arxiv.org/abs/2610.13660

5 CONF

Inject a Turn, Not a Token: Learning Where to Redirect LLM Reasoning for Self-Correction

ArXiv CS.AI 50%

arXiv:2610.13672v1 Announce Type: cross Abstract: Large language models struggle to reliably identify and correct errors in their own reasoning. Unlike prior training-based approaches that fine-tune an LLM to generate revisions or feedback, we learn where to intervene in failed...

https://arxiv.org/abs/2610.13672

6 CONF

Calibration in One Go: Jointly Learning Accurate and Calibrated Neural Networks

ArXiv CS.AI 50%

arXiv:2610.13693v1 Announce Type: cross Abstract: Neural networks (NNs), while highly flexible and versatile, are often poorly calibrated. Post-hoc calibration methods adjust the outputs of an already trained model using a separate calibration dataset and additional calibration...

https://arxiv.org/abs/2610.13693

7 CONF

Amortized Counterfactual Prediction with Graph Neural Networks

ArXiv CS.AI 50%

arXiv:2610.13724v1 Announce Type: cross Abstract: Counterfactual inference asks how an observed outcome might have differed under different circumstances, such as whether a patient would have recovered had they received a different treatment. Such questions arise whenever...

https://arxiv.org/abs/2610.13724

8 CONF

LAPT-Scale: Scaling Embodied Policies with Latent Action Pre-Training on Human Videos

ArXiv CS.AI 50%

arXiv:2610.13732v1 Announce Type: cross Abstract: Scaling generalist robotic policies is limited by the high cost of collecting embodied interaction data. Large-scale egocentric human videos offer a rich alternative, but they lack robot action labels, and existing action...

https://arxiv.org/abs/2610.13732

9 CONF

When Edge Independence Fails: Joint Graph Diffusion with Latent Sociability Priors

ArXiv CS.AI 50%

arXiv:2610.13765v1 Announce Type: cross Abstract: Discrete graph diffusion models corrupt graph structure through independent edge updates with a Markovian noise model. Combined with the exchangeability requirement on the output distribution, the terminal prior is necessarily an...

https://arxiv.org/abs/2610.13765

0 CONF

DualQuant: Dual-scale Calibration-free Weight-and-Activation Quantization for LLMs

ArXiv CS.AI 50%

arXiv:2610.13767v1 Announce Type: cross Abstract: Low-bit inference on accelerators with native 4-bit support requires quantizing both weights and activations to realize the full throughput gains these formats provide. While post-training weight quantization has been extensively...

https://arxiv.org/abs/2610.13767

1 CONF

DeltaLLM: Delta-Key Sparse Attention for Edge LLMs

ArXiv CS.AI 50%

arXiv:2507.19608v2 Announce Type: replace Abstract: On-device LLM inference is increasingly important for edge platforms but remains challenging due to high computational and memory demands and tight resource constraints. Modern applications often involve long prompts. Although...

https://arxiv.org/abs/2507.19608

2 CONF

Global Consistency Repair for Natural-Language Claim Sets

ArXiv CS.AI 50%

arXiv:2601.13600v2 Announce Type: replace Abstract: NLP systems increasingly aggregate claims from retrieved passages, documents, and generated reasoning steps. Yet current factuality methods mostly verify claims individually or compare pairs of claims, leaving open the question...

https://arxiv.org/abs/2601.13600

3 CONF

NeuronSpark: Selective Spiking State Space Models with Adaptive Computation for Language Modeling

ArXiv CS.AI 50%

arXiv:2603.16148v2 Announce Type: replace Abstract: Spiking neural networks promise brain-inspired neural dynamics, yet native large-scale spiking language-model pretraining remains largely unexplored relative to conversion, distillation, and backbone-adaptation approaches. We...

https://arxiv.org/abs/2603.16148

4 CONF

When Simulation Lies: A Sim-to-Real Benchmark and Domain-Randomized RL Recipe for Tool-Use Agents

ArXiv CS.AI 50%

arXiv:2605.11928v2 Announce Type: replace Abstract: Tool-use language agents are evaluated on benchmarks that assume clean inputs, unambiguous tool registries, and reliable APIs. Real deployments violate all these assumptions: user typos propagate into hallucinated tool names, a...

https://arxiv.org/abs/2605.11928

5 CONF

Measuring Harness-Induced Belief Divergence in Multi-Step LLM Agents

ArXiv CS.AI 50%

arXiv:2607.04528v2 Announce Type: replace Abstract: Software agents are becoming increasingly important in modern coding workflows, where they solve complex tasks through multi-step interaction with code repositories. A central component of these systems is the execution...

https://arxiv.org/abs/2607.04528

6 CONF

Enhancing Tabular Learners with Context-Aware Semantic Embeddings

ArXiv CS.AI 50%

arXiv:2608.03565v2 Announce Type: replace Abstract: While modern tabular learners excel at capturing statistical patterns, they frequently operate in a semantic vacuum, treating textual features as discrete symbols, ignoring the rich semantics inherent in feature names or cell...

https://arxiv.org/abs/2608.03565

7 CONF

H2Table: Hierarchical Hypergraph-Enhanced Large Language Models for Complex Table Reasoning

ArXiv CS.AI 50%

arXiv:2609.01216v2 Announce Type: replace Abstract: Tables are ubiquitous across diverse domains, yet reasoning over them remains a significant challenge for modern large language models (LLMs). Current approaches typically linearize tables into sequences, inherently overlooking...

https://arxiv.org/abs/2609.01216

8 CONF

Multi-Harness Reinforcement Learning for Coding Agents: Training Gains and Harness Dependence

ArXiv CS.AI 50%

arXiv:2609.04518v2 Announce Type: replace Abstract: Recent systems train coding agents with reinforcement learning (RL) on trajectories collected through multiple execution harnesses. However, gains under the training harnesses leave open whether the improvements transfer to...

https://arxiv.org/abs/2609.04518

9 CONF

PHRBench: A Behavioral Evaluation of Post-Hallucination Reasoning in LLMs

ArXiv CS.AI 50%

arXiv:2610.10455v2 Announce Type: replace-cross Abstract: Hallucinated information can propagate through multi-stage LLM systems and become part of the context for subsequent reasoning. Existing studies of post-hallucination reasoning (PHR) mainly characterize changes in final...

https://arxiv.org/abs/2610.10455

0 CONF

From Benchmark to Bench: Can Agents Survive Real-World Drug Discovery?

ArXiv CS.AI 50%

arXiv:2610.06411v2 Announce Type: replace Abstract: Agentic systems increasingly coordinate molecular-design tools, but it is unclear which layer of the stack limits outcomes on real projects. We developed MAGI, an open modular agent that authors objectives, launches and...

https://arxiv.org/abs/2610.06411

1 CONF

Conditional Vendi Score: Prompt-Aware Diversity Evaluation for Generative AI Models and LLMs

ArXiv CS.AI 50%

arXiv:2411.02817v3 Announce Type: replace-cross Abstract: Generative models guided by text prompts are widely evaluated for fidelity and prompt alignment, yet their ability to produce diverse outputs remains underexplored. Existing diversity metrics such as Vendi and RKE, which...

https://arxiv.org/abs/2411.02817

2 CONF

Understanding Transformer-based Vision Models through Inversion

ArXiv CS.AI 50%

arXiv:2412.06534v5 Announce Type: replace-cross Abstract: Understanding the internal mechanisms of deep neural networks remains a central challenge in machine learning. In computer vision, one promising yet only preliminarily explored approach is feature inversion via inverse...

https://arxiv.org/abs/2412.06534

3 CONF

LLMail-Inject: A Dataset from a Realistic Adaptive Prompt Injection Challenge

ArXiv CS.AI 50%

arXiv:2506.09956v2 Announce Type: replace-cross Abstract: Indirect prompt injection attacks exploit a fundamental weakness of LLMs: executing unauthorized tasks from untrusted sources. Despite the practical significance of this attack vector, existing benchmarks rely on small...

https://arxiv.org/abs/2506.09956

4 CONF

A Theory of the Mechanics of Information: Generalization Through Measurement of Uncertainty (Learning is Measuring)

ArXiv CS.AI 50%

arXiv:2510.22809v2 Announce Type: replace-cross Abstract: Traditional machine learning relies on explicit models and domain assumptions, often limiting flexibility and interpretability. We introduce a "model-free" framework of instance-based learning using surprisal (information...

https://arxiv.org/abs/2510.22809

5 CONF

HAFixAgent: History-Aware Agentic Program Repair

ArXiv CS.AI 50%

arXiv:2511.01047v4 Announce Type: replace-cross Abstract: Automated program repair (APR) has recently shifted toward large language models and agent-based systems, while prior work shows that repository history can help repair single-line bugs. We conduct a large-scale empirical...

https://arxiv.org/abs/2511.01047

6 CONF

On the Rate of Convergence of GD in Non-linear Neural Networks: An Adversarial Robustness Perspective

ArXiv CS.AI 50%

arXiv:2603.02095v2 Announce Type: replace-cross Abstract: We study the convergence dynamics of Gradient Descent (GD) in a minimal binary classification setting, consisting of a two-neuron ReLU network and two training instances. We prove that even under these strong simplifying...

https://arxiv.org/abs/2603.02095

7 CONF

Automatic-Differentiation-Enabled Finite Element Model Updating: Learning Constitutive Neural Networks from Structural Deformation Data

ArXiv CS.AI 50%

arXiv:2606.05199v2 Announce Type: replace-cross Abstract: The identification of constitutive neural network models from heterogeneous full-field deformation data provides a robust alternative to traditional calibration methods based on homogeneous stress-strain experiments,...

https://arxiv.org/abs/2606.05199

8 CONF

Let Large Language Models Judge Each Other: Multi-Agent Peer-Reviewed Reasoning for Medical Question Answering

ArXiv CS.AI 50%

arXiv:2606.15419v2 Announce Type: replace-cross Abstract: Objective: To enhance the accuracy, interpretability, and robustness of large language models (LLMs) in medical question answering (MedQA). Method: We designed a multi-agent peer-reviewed reasoning method in which...

https://arxiv.org/abs/2606.15419

9 CONF

The One-Word Census: Answer-Choice Conformity Across 105 Language Models

ArXiv CS.AI 50%

arXiv:2607.12796v4 Announce Type: replace-cross Abstract: When a language model must choose one answer from a large space of equally valid options, which answer does it choose, and how often is it the answer every other model chooses? Asked to "pick a word," 105 language models...

https://arxiv.org/abs/2607.12796

00 CONF

Medical foundation models converge less under label supervision

ArXiv CS.AI 50%

arXiv:2607.20274v3 Announce Type: replace-cross Abstract: Diagnostic classifiers and imaging biomarkers are fitted on the embeddings of medical foundation models. These models are replaced as new versions appear. This practice assumes that different models represent images...

https://arxiv.org/abs/2607.20274

01 CONF

Learning from All-Failed Groups via First-Visit Coverage in Long-Horizon Agentic Tasks

ArXiv CS.AI 50%

arXiv:2607.22724v2 Announce Type: replace-cross Abstract: Group-based policy optimization has been increasingly used to train large language model (LLM) agents from sparse outcome rewards by comparing trajectories or steps within a group. However, on difficult long-horizon...

https://arxiv.org/abs/2607.22724

02 CONF

First-Order In-Context Shapley: Scalable Data Auditing for LLM Alignment and Evaluation

ArXiv CS.AI 50%

arXiv:2607.22766v2 Announce Type: replace-cross Abstract: Post-training alignment of Large Language Models is increasingly bottlenecked by data quality: preference and instruction-tuning corpora accumulate label noise, safety inversions, and inter-annotator contradictions that...

https://arxiv.org/abs/2607.22766

03 CONF

RLVR^{2}: Reinforcement Learning with Verifiable Rubric-based Ranking

ArXiv CS.AI 50%

arXiv:2609.23457v2 Announce Type: replace-cross Abstract: Reinforcement Learning with Verifiable Rewards (RLVR) is expanding from tasks with well-defined correctness signals, such as mathematics and code, toward multifaceted quality requirements specified by multi-dimensional...

https://arxiv.org/abs/2609.23457

04 CONF

Useful to Whom? The Easy-versus-Coverage Boundary Moves with the Learner

ArXiv CS.AI 50%

arXiv:2610.00221v2 Announce Type: replace-cross Abstract: Is the same data equally useful to every learner? The question is whether the value of a training sample belongs to the sample or arises in its interaction with the learner. We test it with a selection experiment. Under a...

https://arxiv.org/abs/2610.00221

05 CONF

Exploring More, Reasoning Better: Stepwise Risk-Sensitive GRPO for Diffusion Language Models

ArXiv CS.AI 50%

arXiv:2610.00661v2 Announce Type: replace-cross Abstract: Diffusion large language models (dLLMs) generate text by denoising a sequence or successive blocks, allowing several tokens to be revealed in parallel. Reinforcement learning with verifiable rewards (RLVR) reuses terminal...

https://arxiv.org/abs/2610.00661

06 CONF

Selection-Based Structured Reasoning: Toward Efficient Multimodal Search Agents

ArXiv CS.AI 50%

arXiv:2610.01892v2 Announce Type: replace-cross Abstract: Multimodal agents commonly generate free-form reasoning before each action. For small models, limited model capacity can result in lengthy reasoning that provides little useful guidance for action generation while...

https://arxiv.org/abs/2610.01892

07 CONF

TRIAGE: Direction-Aware Mismatch Stabilization of Native NVFP4 Reinforcement Learning

ArXiv CS.AI 50%

arXiv:2610.07043v2 Announce Type: replace-cross Abstract: Low-precision execution can substantially accelerate reinforcement learning (RL) for large language models, but discrepancies between learner and sampler execution can destabilize policy optimization. In this paper, we...

https://arxiv.org/abs/2610.07043

08 CONF

Decoupling Logic from Persona: Structural Immunity of Edge LLM Agents to Context Pollution

ArXiv CS.AI 50%

arXiv:2610.09772v2 Announce Type: replace-cross Abstract: Edge language-model agents must hold a persona and reason correctly at once, in one context window that fills with history and persona instructions. We study what happens to the logical part of such an agent when that...

https://arxiv.org/abs/2610.09772