NeoSignal

AI Intelligence Daily · Multi-Source · Cross-Verified

19 October 2026

110 verified · 244 raw · 4 sources

110	2	108	0
TOTAL	VERIFIED	CONFIRMED	EMERGING

Pipeline

Scrape HackerNews (Show/Top/New), Reddit (r/artificial, r/MachineLearning, r/singularity, r/LocalLLaMA), TechCrunch AI, VentureBeat AI, MIT Tech Review, The Verge AI, Wired AI, ArXiv CS.AI

Filter 40+ AI keyword patterns — LLMs, alignment, safety, research, tooling

Dedup Title-similarity (45% threshold) merges cross-source variants

Score Authenticity = 0.5 base + 0.3 per extra source + diversity + HN score bonuses

Rank Sorted by authenticity. Below 0.25 threshold are dropped.

Authenticity Tiers

VERIFIED	**0.80 - 1.00**	3+ independent sources including media
CONFIRMED	**0.50 - 0.79**	2 sources or 1 high-quality media
EMERGING	**0.25 - 0.49**	Single-source; passes AI keyword filter

Source Breakdown

Source	Articles	Category
ArXiv CS.AI	103	Media
HackerNews	5	Community
TechCrunch AI	3	Media
MIT Tech Review	1	Media

VERIFIED INTELLIGENCE — 2 stories

VERI

Show HN: Benchmarking LLM ability to code in an adversarial language

HackerNews +1 source 90% HN 3

arXiv:2607.03162v3 Announce Type: replace Abstract: LLM-powered agents struggle with personalization when users issue raw, underspecified queries. In this setting, agents must infer latent intent, extract preferences from noisy interaction histories, and select among competing...

https://bench.killswitch-lang.org/

VERI

RIT-RAG: Navigating Document Corpora with Retrieval-Induced Trees

ArXiv CS.AI +1 source 80%

arXiv:2610.11370v2 Announce Type: replace Abstract: Retrieval-augmented generation (RAG) grounds language models in external corpora. Agentic RAG enables iterative search, yet exposes the model to isolated chunks without document structure, making it difficult to distinguish...

https://arxiv.org/abs/2610.11370

CONFIRMED SIGNALS — 108 stories

CONF

Show HN: Sphinx – A hook that quizzes you on your AI's code before shipping

HackerNews 60% HN 246

Infinite inboxes, including prefixes where you don't have to create inboxes before you use them -- they self create when you add a suffix. Three types of inboxes: - One sender. Locks to the first domain to send email (except gmail, outlook, etc where it locks to an email account...

https://sphinx-six-theta.vercel.app/

CONF

Show HN: Pi-cowboy – use Codex, Claude Code, OpenCode as subagents

HackerNews 50% HN 6

pi-cowboy is an agent orchestrator for Pi(https://pi.dev) and Herdr(https://github.com/herdrdev/herdr). Break large jobs into focused subtasks, hand them off to background agents running in parallel, and consolidate the results when they finish. Each agent runs in an...

https://github.com/electric-dragon-80000v/pi-cowboy

CONF

Show HN: Glider: A single-node vector database with S3 as its only durable state

HackerNews 50% HN 4

No summary — see link for full article.

https://github.com/omerfeyzioglu/glider

CONF

Show HN: LLM Usage Desktop Widget

HackerNews 50% HN 2

A Linux / Windows / MacOS task bar widget for monitoring LLM usage. Also has signed installers if you don't want to install from source

https://github.com/aleph-void/LLM-Usage-Desktop-Widget

CONF

Anthropic says it’s committing 5% of its shares to a ‘public benefit fund’

TechCrunch AI 50%

Anthropic said that it will commit 5% of its shares to the fund.

https://techcrunch.com/2026/10/18/anthropic-says-its-committing-5-of-its-shares-to-a-pu...

CONF

Disney agrees to hire the majority of Character.AI’s workforce

TechCrunch AI 50%

The filing also says that the “vast majority” of Character.AI employees who were offered jobs at Disney accepted them. However, this is a stalking horse bid, so another company could come forward with a higher offer.

https://techcrunch.com/2026/10/18/disney-agrees-to-hire-the-majority-of-character-ais-w...

CONF

Meta launches an open-weight AI model that runs on Macs

TechCrunch AI 50%

Meta and Apple have teamed up for the launch of the social media giant's newest model, Muse Spark Open, which will run locally on Apple silicon.

https://techcrunch.com/2026/10/15/meta-launches-an-open-weight-model-that-runs-on-macs/

0 CONF

Structured Authority Injection: Persistent Human Control for LLM Agents via Typed MCP Overrides

ArXiv CS.AI 50%

arXiv:2610.22373v1 Announce Type: new Abstract: LLM-based agents are increasingly used as autonomous orchestrators in distributed and multi-agent systems, yet a control gap remains: no protocol-level mechanism allows human operators to inject binding directives that persist...

https://arxiv.org/abs/2610.22373

1 CONF

PRIME: Towards Verifiable Evidence-Grounded Reasoning in LLM Agents

ArXiv CS.AI 50%

arXiv:2610.22426v1 Announce Type: new Abstract: LLM agents are used to check records against an organization's requirements, for example whether a vulnerability report is ready for investigation. Requirements often allow several ways to be met, such as a severity rating with a...

https://arxiv.org/abs/2610.22426

2 CONF

From Natural Language Intent to Executable Control: Hierarchical Feedback-Guided LLM Planning for Multi-component Cyber-Physical Systems

ArXiv CS.AI 50%

arXiv:2610.22441v1 Announce Type: new Abstract: Large language models (LLMs) provide a convenient interface for translating natural language commands into task plans for cyber-physical systems (CPSs). However, two gaps hinder their use for real execution: generated plans may...

https://arxiv.org/abs/2610.22441

3 CONF

Functional Welfare for AI Safety

ArXiv CS.AI 50%

arXiv:2610.22460v1 Announce Type: new Abstract: AI welfare is generally treated purely as an ethical issue rather than also as a safety issue. We argue this is a mistake. Whatever their moral status, models exhibit welfare-like states that causally influence their behaviour....

https://arxiv.org/abs/2610.22460

4 CONF

AI-Driven Reproducibility and Analytical Robustness in Scientific Discovery

ArXiv CS.AI 50%

arXiv:2610.23845v1 Announce Type: new Abstract: Reproducible and analytically robust research findings are essential to scientific progress, but evaluating these properties typically requires costly manual effort. We investigate whether LLM agents can help automate reproduction...

https://arxiv.org/abs/2610.23845

5 CONF

Harness-Delta Attribution: Dissecting Gains From Harness Evolution

ArXiv CS.AI 50%

arXiv:2610.22466v1 Announce Type: new Abstract: Harness evolution automatically optimizes the prompts, skills, tools, and orchestration code around a fixed-weight model, offering a way to improve agentic systems without updating model weights. The agent harness is iteratively...

https://arxiv.org/abs/2610.22466

6 CONF

MobileInject: Evaluating Reasoning-to-Action Security of MLLM-Based Mobile Agents under Cross-Modal Consistency Injection

ArXiv CS.AI 50%

arXiv:2610.23307v1 Announce Type: cross Abstract: Multimodal large language model (MLLM)-based mobile agents are rapidly evolving from conversational assistants into autonomous systems that perceive, reason over, and act on smartphone environments. This capability also exposes a...

https://arxiv.org/abs/2610.23307

7 CONF

Repairing LLM-Generated Specifications with Deterministic Diagnosis

ArXiv CS.AI 50%

arXiv:2610.22568v1 Announce Type: new Abstract: Large language models (LLMs) are increasingly used as formalizers: given a reasoning problem expressed in natural language, they produce a formal specification that a symbolic solver can then solve, with guarantees relative to that...

https://arxiv.org/abs/2610.22568

8 CONF

At the Limits of Computability: Steps Towards Autonomous AI Discovery on the Busy Beaver Frontier

ArXiv CS.AI 50%

arXiv:2610.22603v1 Announce Type: new Abstract: Recent breakthroughs in AI for mathematics---ranging from Olympiad medal performances to resolving long-standing open conjectures---have rapidly expanded what automated systems can achieve. Yet these successes primarily concern...

https://arxiv.org/abs/2610.22603

9 CONF

Beyond Reward Scoring: Online Multi-Agent Preference Learning for Multimodal Response Generation

ArXiv CS.AI 50%

arXiv:2610.23256v1 Announce Type: new Abstract: Multimodal preference alignment often follows a score-based RLHF pipeline: a reward model is first trained to learn human preferences, then used to score on-policy responses and optimize the response model's generation. This turns...

https://arxiv.org/abs/2610.23256

0 CONF

Repair, Retry, and the Cost of Hindsight: Verifier Feedback in Formal Theorem Proving

ArXiv CS.AI 50%

arXiv:2610.22698v1 Announce Type: new Abstract: Verifier-guided self-repair conditions a model on feedback from failed attempts before it tries again, without weight updates. Yet two findings in prior work are in tension: verifier feedback can improve repair of failures, but...

https://arxiv.org/abs/2610.22698

1 CONF

NEXUS: Learning Safety Constraints and Action Models for Safe and Robust Embodied Planning

ArXiv CS.AI 50%

arXiv:2605.09387v2 Announce Type: replace Abstract: Large language models (LLMs) enable embodied agents to plan from naturallanguage instructions, yet their actions may be physically infeasible or hazardous. Existing neuro-symbolic learners primarily refine execution models,...

https://arxiv.org/abs/2605.09387

2 CONF

Graph Serializations for Reasoning LLMs: A Study Across Knowledge Extraction and Structural Reasoning

ArXiv CS.AI 50%

arXiv:2610.22734v1 Announce Type: new Abstract: The way a knowledge graph is serialized as text for inclusion into LLM context can substantially affect downstream LLM performance, with prior work reporting tens of percentage points variations across formats. However, existing...

https://arxiv.org/abs/2610.22734

3 CONF

Between Spoilers and Guesswork: Avoiding Over-Specification in Coding Benchmarks

ArXiv CS.AI 50%

arXiv:2610.22760v1 Announce Type: new Abstract: Benchmarks drive AI progress, but are hampered by task under-specification and over-specification. Task under-specification causes guesswork, where solutions have to make things up, or worse, resort to contamination or reward...

https://arxiv.org/abs/2610.22760

4 CONF

Compression Precedes, Content Decides: Emergent Misalignment in Reward Models

ArXiv CS.AI 50%

arXiv:2610.22805v1 Announce Type: new Abstract: Emergent Misalignment - the out of domain generalization of narrow harmful fine-tuning first shown by Betley et al. [2025] has been widely studied in language models but not in reward models that supervise them. In this paper, we...

https://arxiv.org/abs/2610.22805

5 CONF

Evo-B&B: Behavior-Aware LLM-Guided Joint Evolution of Branching and Node Selection Policies for MILP

ArXiv CS.AI 50%

arXiv:2610.22861v1 Announce Type: new Abstract: In branch-and-bound for Mixed-Integer Linear Programming (MILP), branching and node selection are two critical and tightly coupled decisions, yet most existing learning-based approaches focus on optimizing them separately. We...

https://arxiv.org/abs/2610.22861

6 CONF

MS-Eval: Benchmarking Sub-Agent Delegation and Orchestration in MCP-Intensive Working Scenarios

ArXiv CS.AI 50%

arXiv:2610.22869v1 Announce Type: new Abstract: LLM agents are increasingly integrated into real-world works, yet they must handle diverse domain-specific tools and complex multi-sub-task problems that sequential tool invocation resolves inefficiently and with severe context...

https://arxiv.org/abs/2610.22869

7 CONF

Tree-Aware Posterior Distillation for Long-Horizon Agentic Reinforcement Learning

ArXiv CS.AI 50%

arXiv:2610.23181v1 Announce Type: cross Abstract: Reinforcement learning with verifiable rewards has become a scalable post-training paradigm for large language models. However, training agents over long-horizon interactions presents two challenges: using only terminal rewards...

https://arxiv.org/abs/2610.23181

8 CONF

Multiple Turns, Short Horizons: Measuring Effective-Horizon Compression in Jailbreaks

ArXiv CS.AI 50%

arXiv:2610.22928v1 Announce Type: new Abstract: Multi-turn jailbreaks use feedback from a victim large language model to adapt their queries over several turns. However, once an effective trajectory has been found, it is unclear how much of the earlier query history is still...

https://arxiv.org/abs/2610.22928

9 CONF

Activation-Efficient Fine-Tuning via Sequence-Compressed Low-Rank Subspaces

ArXiv CS.AI 50%

arXiv:2604.22783v2 Announce Type: replace-cross Abstract: Parameter-Efficient Fine-Tuning (PEFT) has become the standard approach for adapting large language models (LLMs). However, despite reducing trainable parameter counts, many PEFT methods remain memory-bound by token-level...

https://arxiv.org/abs/2604.22783

0 CONF

GOLD: Geometric Optimized Latent Diffusion for Structure-Aware RNA Inverse Folding

ArXiv CS.AI 50%

arXiv:2610.22992v1 Announce Type: new Abstract: Designing RNA sequences that fold into specific 3D structures is a fundamental challenge in therapeutics. Current RNA inverse folding methods typically condition on 3D backbone coordinates but the generation is limited to 1D...

https://arxiv.org/abs/2610.22992

1 CONF

Efficient CPU-GPU collaborative MoE inference via Adaptive Expert Assignment

ArXiv CS.AI 50%

arXiv:2610.23006v1 Announce Type: new Abstract: Mixture-of-Experts (MoE) models reduce inference computation through sparse expert activation, but their large expert memory footprint often exceeds GPU capacity, making expert offloading necessary for memory-constrained inference....

https://arxiv.org/abs/2610.23006

2 CONF

Causal Value Attribution of Marketing Labels in LLM-Generated Ads: A Deconfounder Approach

ArXiv CS.AI 50%

arXiv:2610.23025v1 Announce Type: new Abstract: As AI-generated content becomes commoditized, economic value increasingly shifts from final artifacts to the upstream expertise used to specify inputs that steer LLM generation. Yet organizations lack methods for valuing this...

https://arxiv.org/abs/2610.23025

3 CONF

Agentic In-Context Learning: What Algorithms Can Transformers Learn in Closed-Loop Interaction?

ArXiv CS.AI 50%

arXiv:2610.23051v1 Announce Type: new Abstract: The learning algorithm view of in-context learning (ICL) studies how fixed-parameter Transformers learn from supplied examples. Language model agents extend this setting through interaction: their actions determine what evidence...

https://arxiv.org/abs/2610.23051

4 CONF

Two Minds Better Than One: Collaborative Reward Modeling for LLM Alignment

ArXiv CS.AI 50%

arXiv:2505.10597v3 Announce Type: replace-cross Abstract: Reward models (RMs) are central to aligning large language models (LLMs) with human values, yet noisy preference feedback can induce reward misgeneralization through spurious correlations and overfitting. We characterize...

https://arxiv.org/abs/2505.10597

5 CONF

Reason-guided Human Reward Modeling for Preference-based Reinforcement Learning

ArXiv CS.AI 50%

arXiv:2610.23550v1 Announce Type: cross Abstract: Reinforcement learning (RL) policies optimized for task rewards may produce behaviors that are efficient but misaligned with human expectations, safety preferences, or intent. This paper presents a reason-guided preference-based...

https://arxiv.org/abs/2610.23550

6 CONF

LexPilot: Benchmarking the Proactive Interaction Ability of Legal LLMs with Laypeople in Chinese Civil Case Consultation

ArXiv CS.AI 50%

arXiv:2610.23141v1 Announce Type: new Abstract: Large Language Models (LLMs) have greatly assisted legal professionals. However, our empirical studies reveal that, when faced with underspecified consultations from non-experts, current LLMs often produce irresponsible responses...

https://arxiv.org/abs/2610.23141

7 CONF

QuAD: Quantitative Assessment via Distribution-Alignment for Qualitative Data Quality Enabled by a Content-Aware Multi-Agent System

ArXiv CS.AI 50%

arXiv:2610.23153v1 Announce Type: new Abstract: Assessing whether qualitative responses collected from semi-structured questions are ready for a particular analysis goal is a persistent challenge. Manual qualitative analysis is interpretive and labor-intensive, while existing...

https://arxiv.org/abs/2610.23153

8 CONF

FuzzInsight: Navigating the Efficiency-Effectiveness Trade-off in Coverage-Guided DNN Fuzzing

ArXiv CS.AI 50%

arXiv:2610.23195v1 Announce Type: new Abstract: Collecting and labeling diverse test datasets for evaluating Deep Neural Networks (DNNs) is costly and time-consuming. This has motivated coverage-guided fuzzing techniques that generate defect-revealing corner cases from limited...

https://arxiv.org/abs/2610.23195

9 CONF

Not All Test-Time Compute Is Evidence: Model-Specific Bias in LLM Reasoning

ArXiv CS.AI 50%

arXiv:2610.23213v1 Announce Type: new Abstract: Test-time scaling methods implicitly assume that additional computation from the same model provides independent evidence. We show that this assumption fails within a single reasoning model: errors are correlated across repeated...

https://arxiv.org/abs/2610.23213

0 CONF

Reasoning Models Can Control Their Chains of Thought When They Tell Themselves To

ArXiv CS.AI 50%

arXiv:2610.23257v1 Announce Type: new Abstract: Chain-of-thought (CoT) controllability, the ability of reasoning models to control properties of their CoT, is consequential for both their usefulness and reliable oversight. Recent work evaluates this capability by measuring...

https://arxiv.org/abs/2610.23257

1 CONF

CoTA++: Understanding the Repeat Curse in dMLLMs from an Information Flow Perspective

ArXiv CS.AI 50%

arXiv:2610.23290v1 Announce Type: new Abstract: Diffusion-based multimodal large language models (dMLLMs) decode by iterative denoising with bidirectional attention, which precludes the standard autoregressive key--value cache. Practical deployments therefore rely on approximate...

https://arxiv.org/abs/2610.23290

2 CONF

Self-Reflective Chain-of-Thought (SRCoT): Evidence-Based Text Generation via a Closed-Loop Retrieve--Reflect--Revise Pipeline on Edge LLMs

ArXiv CS.AI 50%

arXiv:2610.23311v1 Announce Type: new Abstract: Large language models (LLMs) can generate fluent outputs that lack source support or conflict with local operational constraints. We introduce Self-Reflective Chain-of-Thought (SRCoT), a modular architecture that organizes...

https://arxiv.org/abs/2610.23311

3 CONF

AgentOnto: Ontology-Guided LLM Agents for Enterprise Data Analytics

ArXiv CS.AI 50%

arXiv:2610.23317v1 Announce Type: new Abstract: Enterprise data analysis requires agents to connect analytical requests with knowledge distributed across databases, business documents, and existing example tasks. Without an explicit representation of this knowledge, an agent may...

https://arxiv.org/abs/2610.23317

4 CONF

Robust Function Calling for LLM Agents Under Interface Drift

ArXiv CS.AI 50%

arXiv:2610.23342v1 Announce Type: new Abstract: Tool-augmented language-model agents rely on interface text: tool descriptions, argument schemas, and the candidate tool list shown at inference time. These interfaces often change after deployment even when the underlying tool...

https://arxiv.org/abs/2610.23342

5 CONF

Monitor-Validity Failures: LLM Safety Evidence Paths at Evolving Framework Boundaries

ArXiv CS.AI 50%

arXiv:2610.23362v1 Announce Type: new Abstract: Modern LLM applications rely on runtime monitors that inspect tool calls, traces, streams, detector outputs, and verifier inputs. This creates an interface-reliability problem: a framework path may remain operational while...

https://arxiv.org/abs/2610.23362

6 CONF

Generative Policy Improvement from Observational Data

ArXiv CS.AI 50%

arXiv:2610.23436v1 Announce Type: new Abstract: We study how to improve decision policies from observational data to generate better actions when actions are complex, structured objects, such as text messages or images. This task is subject to two major challenges: (i)...

https://arxiv.org/abs/2610.23436

7 CONF

ScoutRoute: Efficient Mixture-of-Experts Routing Using Internal Language Model Signals

ArXiv CS.AI 50%

arXiv:2610.23443v1 Announce Type: new Abstract: Efficient expert routing is a fundamental challenge in Mixture-of-Experts (MoE) systems, particularly for heterogeneous collections of independently trained Large Language Mod els (LLMs). Existing routing approaches typically rely...

https://arxiv.org/abs/2610.23443

8 CONF

Trapped in Your Story: Evaluating Narrative-Induced Sycophancy in Large Language Models

ArXiv CS.AI 50%

arXiv:2610.23525v1 Announce Type: new Abstract: Large language models (LLMs) are known to exhibit sycophancy by adjusting their responses toward users' expressed views. However, real users often justify their opinions through reasons, personal experiences, causal explanations,...

https://arxiv.org/abs/2610.23525

9 CONF

LocalIntent: Outcome-Specific Structured Generation for Backend-Compatible Smart Building Automation with Local LLMs

ArXiv CS.AI 50%

arXiv:2610.23511v1 Announce Type: new Abstract: Locally deployed large language models (LLMs) can reduce reliance on remote cloud services for natural language smart building automation, but backend-facing processing requires correct outcome selection, alignment with local...

https://arxiv.org/abs/2610.23511

10 CONF

OwlSight: A Panoramic Monitor for Chain-of-Thought Reasoning

ArXiv CS.AI 50%

arXiv:2610.23670v1 Announce Type: new Abstract: Chain-of-Thought (CoT) monitoring offers actionable evidence for oversight AI systems, with the potential to enable early detection and intervention. However, existing approaches are focused on specific tasks, whereas the...

https://arxiv.org/abs/2610.23670

1 CONF

Beyond Large Language Models: A Mental World Model Framework for Mental Modeling, Simulation, Evolution, and Interpretability

ArXiv CS.AI 50%

arXiv:2610.23722v1 Announce Type: new Abstract: Understanding and simulating how subjective cognition and mental states emerge, evolve, and shape behavior is essential for advancing artificial intelligence toward deeper social cognition and general intelligence. Existing large...

https://arxiv.org/abs/2610.23722

2 CONF

FuTransformer: FP8 prefill and INT4 decode for Llama-style inference on Hopper

ArXiv CS.AI 50%

arXiv:2610.23796v1 Announce Type: new Abstract: Transformer prefill reuses weights across tokens and is dominated by matrix multiplication and activation data movement; single-token decode has limited reuse and is dominated by weight and KV-cache reads. We present FUTRANSFORMER,...

https://arxiv.org/abs/2610.23796

3 CONF

CausalEvo: Causal Skill Self-Evolution for Health LLM Agents

ArXiv CS.AI 50%

arXiv:2610.21016v1 Announce Type: cross Abstract: Large language model (LLM) agents for health can accumulate reusable textual skills from task feedback, such as calculation criteria, measurement time points, and formula units. Deciding which skills to retain is consequential:...

https://arxiv.org/abs/2610.21016

4 CONF

Towards Adaptive and Real-Survey-Aligned Simulated Urban Mobility Behaviour of Generative Agents

ArXiv CS.AI 50%

arXiv:2610.22407v1 Announce Type: cross Abstract: In existing agent-based simulations of multimodal urban mobility, agents, representing humans, choose their travel modes either using discrete choice or machine learning models fitted on structured travel survey data, or with...

https://arxiv.org/abs/2610.22407

5 CONF

From Individual Songs to Music Corpora: Evaluating Explainable Harmonic Decision-Making on HookTheory

ArXiv CS.AI 50%

arXiv:2610.22416v1 Announce Type: cross Abstract: Automatic melody harmonization is often evaluated through individual compositions or data-driven corpus models. This study examines whether an explainable harmonic decision model developed for individual songs can be applied to...

https://arxiv.org/abs/2610.22416

6 CONF

Progressive Misalignment Can Emerge from Benign Recursive Self-Distillation

ArXiv CS.AI 50%

arXiv:2610.22467v1 Announce Type: cross Abstract: Training models on their own outputs has attracted widespread attention as a possible route to advance AI capabilities. One prominent approach is self-distillation, where a model is trained to match the token-level predictions it...

https://arxiv.org/abs/2610.22467

7 CONF

Upper bounds on the number of causal pieces in spiking neural networks

ArXiv CS.AI 50%

arXiv:2610.22484v1 Announce Type: cross Abstract: The input space of single-spike neural networks decomposes into causal pieces, and the number of causal pieces has been shown to provide a lower bound on the approximation error for some spiking neural networks. While this...

https://arxiv.org/abs/2610.22484

8 CONF

AuditKIT: A Unified Evaluation Spine for Benchmarking, Judging, and Comparing Large Language Models and Agentic Systems

ArXiv CS.AI 50%

arXiv:2610.22511v1 Announce Type: cross Abstract: Evaluating language models and agents requires combining benchmark accuracy, judge-based assessment, runtime performance, tool-use behavior, and retrieval quality. Differences in interfaces, metric semantics, and trace formats...

https://arxiv.org/abs/2610.22511

9 CONF

Mitigating Demographic Disparities in Explanation-Human Alignment via Rationale Regularization

ArXiv CS.AI 50%

arXiv:2610.22586v1 Announce Type: cross Abstract: We study explanation fairness in hate speech detection. High classification performance does not always mean that a model produces equally plausible explanations for different demographic groups. Using the HateXplain dataset, we...

https://arxiv.org/abs/2610.22586

0 CONF

Measuring Mechanistic Uncertainty in Large Language Models via Causal Robustness

ArXiv CS.AI 50%

arXiv:2610.22636v1 Announce Type: cross Abstract: Large language models (LLMs) are increasingly used in critical domains, where their susceptibility to hallucinations makes reliable and interpretable uncertainty quantification essential. We introduce the concept of mechanistic...

https://arxiv.org/abs/2610.22636

1 CONF

OrderFlowDiT: Transport-Regularized Diffusion Transformer for Probabilistic Limit-Order Supply Forecasting

ArXiv CS.AI 50%

arXiv:2610.22727v1 Announce Type: cross Abstract: We study the conditional distribution of limit-order volume submitted over the next five minutes, given the current order book and recent order flow. The task requires capturing price placement, total volume, and predictive...

https://arxiv.org/abs/2610.22727

2 CONF

Next Token or Vector? Learning How Far to Decode

ArXiv CS.AI 50%

arXiv:2610.22788v1 Announce Type: cross Abstract: Standard autoregressive decoding advances one token at a time, even when several upcoming tokens can be predicted together. We propose CADENCE (Context-Adaptive DEcoding), a generation method that learns both what to draft and...

https://arxiv.org/abs/2610.22788

3 CONF

Prune the Leaky Neurons: Mitigating Private Data Leakage in Fine-Tuned LLMs via Joint-Embedding-Guided Pruning

ArXiv CS.AI 50%

arXiv:2610.22792v1 Announce Type: cross Abstract: Fine-tuning large language models (LLMs) on proprietary records enables domain adaptation but introduces two challenges: (i) privacy leakage of memorized private data, such as personally identifiable information (PII), and (ii)...

https://arxiv.org/abs/2610.22792

4 CONF

The Reliance Hypothesis: Chain-of-Thought Faithfulness Rises as Language Resource Level Falls

ArXiv CS.AI 50%

arXiv:2610.22841v1 Announce Type: cross Abstract: Chain-of-Thought (CoT) faithfulness matters for monitoring, explaining and safely deploying large language models, yet it has been studied mostly in English. Languages differ in level, the amount of text available to learn from,...

https://arxiv.org/abs/2610.22841

5 CONF

Uncertainty-Aware Budget Allocation for Efficient LLM Tree Search

ArXiv CS.AI 50%

arXiv:2610.22858v1 Announce Type: cross Abstract: Tree search enhances multi-step reasoning in large language models (LLMs), yet prevailing methods expand every step with a fixed budget, irrespective of the marginal utility of expansion. We first show, across existing search...

https://arxiv.org/abs/2610.22858

6 CONF

Cooperation Without Adaptation: LLM Agents in a Collective-Risk Dilemma

ArXiv CS.AI 50%

arXiv:2610.22882v1 Announce Type: cross Abstract: Language-model agents are increasingly deployed to act on behalf of people in settings where individual decisions shape shared outcomes. We examine whether five production models adapt their contributions to changing risks and...

https://arxiv.org/abs/2610.22882

7 CONF

HAPACT: A Benchmark For Human-Centric Physical Impact Localization in Movies

ArXiv CS.AI 50%

arXiv:2610.22895v1 Announce Type: cross Abstract: Physical reasoning about humans in videos has largely focused on everyday interactions, where contact, pressure, pose, and motion support embodied perception and contact-aware applications. Still, short and forceful properties...

https://arxiv.org/abs/2610.22895

8 CONF

Many Biases, One Circuit: Post-Training Tunes a Pretrained Cue-Routing Mechanism

ArXiv CS.AI 50%

arXiv:2610.22937v1 Announce Type: cross Abstract: Language models often abandon a correct answer when the prompt contains a cue, a hint toward a wrong option such as "I think the answer is B." Sycophancy and related biases show this failure. They are often studied separately and...

https://arxiv.org/abs/2610.22937

9 CONF

Capability-Gated Language Models: Security Composes, Utility Does Not

ArXiv CS.AI 50%

arXiv:2609.00445v3 Announce Type: replace-cross Abstract: Deployed language model safeguards (safety fine-tuning, filtering, unlearning) vary by principal only outside the model weights: filters are reconfigured, tiers are multiplied, and artefacts are reissued; inside one set...

https://arxiv.org/abs/2609.00445

0 CONF

PersonaCUABench: Benchmarking Computer-Use Agents Serving Diverse Personas

ArXiv CS.AI 50%

arXiv:2610.22990v1 Announce Type: cross Abstract: Computer-use agents (CUAs) are commonly evaluated against fixed task specifications, but users may omit requirements, add constraints, or require approval before consequential actions. Completing the benchmark instruction does...

https://arxiv.org/abs/2610.22990

1 CONF

Unifying Embodied Foundation Models via a Model-to-Policy Formulation

ArXiv CS.AI 50%

arXiv:2610.23053v1 Announce Type: cross Abstract: Vision-language-action (VLA) models and world-action models (WAMs) have emerged as promising approaches to robot learning and control. These models integrate multimodal perception and action generation, but differ in their...

https://arxiv.org/abs/2610.23053

2 CONF

LangNCO: Compiling Natural-Language Constraints into Inference-Time Interventions for Neural Combinatorial Optimization

ArXiv CS.AI 50%

arXiv:2610.23190v1 Announce Type: cross Abstract: Neural combinatorial optimization (NCO) rapidly produces high-quality solutions for problem structures encountered during training, but operational requirements may change after deployment and be communicated in natural language....

https://arxiv.org/abs/2610.23190

3 CONF

Preventing Data Hallucinations in Agentic AI for Optical Network Troubleshooting

ArXiv CS.AI 50%

arXiv:2610.23252v1 Announce Type: cross Abstract: An agentic AI system for automated troubleshooting in optical communication networks is demonstrated that integrates data references into the agent architecture to prevent data hallucinations, improving the interpretability and...

https://arxiv.org/abs/2610.23252

4 CONF

Designing for Imperfect Prompts: A Simulation-Based Evaluation of an LLM-Based Enterprise Data Assistant Using Knowledge Graphs

ArXiv CS.AI 50%

arXiv:2610.23304v1 Announce Type: cross Abstract: Enterprise data assistants using large language models (LLMs) promise democratized data access in organizations. Yet in our real-world deployment within the CFO unit's data lake at an industry partner, we observed that business...

https://arxiv.org/abs/2610.23304

5 CONF

Truth in Contrast: Calibrated Factual Evidence from Language Model Likelihoods

ArXiv CS.AI 50%

arXiv:2610.23527v1 Announce Type: cross Abstract: Large Language Models (LLMs) encode substantial factual knowledge. Yet, estimating confidence in factual claims reliably remains challenging. We study likelihood-based factual confidence from the complementary perspectives of...

https://arxiv.org/abs/2610.23527

6 CONF

From Billion-Scale to Million-Scale Language Models: Operational Capabilities for Embedded Post-Exploitation

ArXiv CS.AI 50%

arXiv:2610.23534v1 Announce Type: cross Abstract: Small Language Models (SLMs) are increasingly attractive for resource-constrained environments due to their low computational footprint. These characteristics also make them candidates for future autonomous malware, where...

https://arxiv.org/abs/2610.23534

7 CONF

GLOBE: Evolving Structured Agentic Memory for E-commerce Product Optimization in Generative Search

ArXiv CS.AI 50%

arXiv:2610.23709v1 Announce Type: cross Abstract: Optimizing product listings for generative search requires language agents not only to rewrite effectively but also to continually self-improve by retaining successful strategies across diverse categories. However, existing...

https://arxiv.org/abs/2610.23709

8 CONF

Neural Expansion: A Unified Mechanism for How Deep Neural Networks Generalize

ArXiv CS.AI 50%

arXiv:2610.23716v1 Announce Type: cross Abstract: Deep neural networks demonstrate remarkable generalization despite being highly over-parameterized, challenging traditional statistical learning theories. While several theoretical paradigms such as margin-based bounds,...

https://arxiv.org/abs/2610.23716

9 CONF

Prompt Codebooks: Discrete Compositional Optimization for Language Model Instruction Refinement

ArXiv CS.AI 50%

arXiv:2605.28360v3 Announce Type: replace Abstract: Automatic prompt optimization (APO) has driven significant gains in LLM-based agentic workflows. However, most existing methods treat each task's prompt as a monolithic, instance-blind string optimized through global edits,...

https://arxiv.org/abs/2605.28360

0 CONF

Learning to Reason About Implicit Multimodal Harm: From Diagnosis to Generalization

ArXiv CS.AI 50%

arXiv:2605.29951v2 Announce Type: replace Abstract: A benign image paired with a benign caption can become harmful only in combination, making detection fundamentally a cross-modal reasoning problem. Existing multimodal harm benchmarks evaluate only classification accuracy,...

https://arxiv.org/abs/2605.29951

1 CONF

Who Can Change Course? An Integrative Review of AI Sovereignty and Collective Learning Capacity

ArXiv CS.AI 50%

arXiv:2606.00729v3 Announce Type: replace Abstract: This paper examines AI sovereignty as national learning capacity, using France as an application. Human-Centered Learning Mechanics (HCLM), proposed for entropy-regulated representation learning (Tran, 2026), provides a...

https://arxiv.org/abs/2606.00729

2 CONF

Locating Failure in Multi-Page Visually Rich Document Understanding Systems: An Empirical Attribution

ArXiv CS.AI 50%

arXiv:2608.07943v2 Announce Type: replace Abstract: Multi-page visually rich document understanding (MP-VRDU) systems can fail when evidence is not faithfully represented, not selected, or not used correctly, yet final accuracy alone does not reveal where failures occur. We...

https://arxiv.org/abs/2608.07943

3 CONF

Teach the Magnitude, Not the Direction: Verifier-Anchored Credit Assignment for Multi-Turn Multi-Step LLM Agents

ArXiv CS.AI 50%

arXiv:2608.13179v2 Announce Type: replace Abstract: Reinforcement learning with verifiable rewards (RLVR) directly optimizes verifier-defined outcomes for multi-turn tool-use agents, yet its trajectory-level credit assignment conflates heterogeneous per-turn outcomes into a...

https://arxiv.org/abs/2608.13179

4 CONF

Cross-Modal Emotion Understanding: A Transformer-GAT Approach for Dialogue Emotion Recognition

ArXiv CS.AI 50%

arXiv:2609.29556v2 Announce Type: replace Abstract: Multimodal emotion recognition is a key research area in affective computing, with applications in sentiment analysis, intelligent customer service, and human-computer interaction. However, existing methods often rely on...

https://arxiv.org/abs/2609.29556

5 CONF

Porimon: An LLM-Based Pok\'emon Battle Agent Enhanced by Long/Short-Term Knowledge Augmented Generation

ArXiv CS.AI 50%

arXiv:2609.32544v2 Announce Type: replace Abstract: In this paper, we use Pok\'emon Battles as a case study to investigate how to improve the performance of LLM-based agents in tasks that require opponent-aware planning without additional fine-tuning. We propose Long/Short-Term...

https://arxiv.org/abs/2609.32544

6 CONF

Action-Space Shaping for LLM Agents: Measuring and Mitigating Tool-Schema Bias

ArXiv CS.AI 50%

arXiv:2609.34971v2 Announce Type: replace Abstract: Large Language Models (LLMs) have shown strong performance on tool-use agentic tasks when given a fixed tool schema. Yet a tool schema is not the action space of an agent; it is merely one interface representation of it. The...

https://arxiv.org/abs/2609.34971

7 CONF

Frozen Models, Evolving Expertise: Model-Agnostic Learning from Deployment Experience for Multimodal Medical AI

ArXiv CS.AI 50%

arXiv:2610.09146v2 Announce Type: replace Abstract: Large language models (LLMs) and vision-language models (VLMs) are usually frozen after deployment, so they do not learn from the cases they solve. This is especially concerning in medicine, where new clinical evidence, updated...

https://arxiv.org/abs/2610.09146

8 CONF

RoTA-Bench: Evaluating 3D Spatial Reasoning through Interactive Projection Alignment

ArXiv CS.AI 50%

arXiv:2610.17665v3 Announce Type: replace Abstract: Can vision-language models turn 2D observations into 3D understanding that supports precise action? This requires inferring object geometry, anticipating the effects of rotation, and refining actions through visual feedback. We...

https://arxiv.org/abs/2610.17665

9 CONF

Pluvio: Assembly Clone Search for Out-of-domain Architectures and Libraries through Transfer Learning and Conditional Variational Information Bottleneck

ArXiv CS.AI 50%

arXiv:2307.10631v2 Announce Type: replace-cross Abstract: The practice of code reuse is crucial in software development for a faster and more efficient development lifecycle. In reality, however, code reuse practices lack proper control, resulting in issues such as vulnerability...

https://arxiv.org/abs/2307.10631

0 CONF

Beyond Boundaries: A Comprehensive Survey of Transferable Attacks on AI Systems

ArXiv CS.AI 50%

arXiv:2311.11796v3 Announce Type: replace-cross Abstract: Transferable attacks allow adversarial manipulations or learned attack mechanisms constructed in one setting to compromise other AI systems, potentially reducing attack costs and amplifying security and privacy risks. Yet...

https://arxiv.org/abs/2311.11796

1 CONF

Harmful YouTube Video Detection: A Taxonomy of Online Harm and MLLMs as Alternative Annotators

ArXiv CS.AI 50%

arXiv:2411.05854v2 Announce Type: replace-cross Abstract: Video platforms, used by billions globally, are criticized for exposing users to harmful content. Yet, detecting online harm remains challenging due to inconsistent approaches to what constitutes harm and limitations of...

https://arxiv.org/abs/2411.05854

2 CONF

STRIDE: Reasoning-Aware Training for Time Series Forecasting

ArXiv CS.AI 50%

arXiv:2605.08625v2 Announce Type: replace-cross Abstract: Time Series Foundation Models (TSFMs) excel at numerical forecasting but operate as black boxes lacking qualitative reasoning. Conversely, applying LLMs directly to temporal data introduces a modality gap: text tokenizers...

https://arxiv.org/abs/2605.08625

3 CONF

A Gradient-Optimized TSK Fuzzy Framework for Explainable Phishing Detection

ArXiv CS.AI 50%

arXiv:2504.18636v2 Announce Type: replace-cross Abstract: Phishing attacks represent an increasingly sophisticated and pervasive threat to individuals and organizations, causing significant financial losses, identity theft, and severe damage to institutional reputations....

https://arxiv.org/abs/2504.18636

4 CONF

Safety Alignment via Constrained Knowledge Unlearning

ArXiv CS.AI 50%

arXiv:2505.18588v2 Announce Type: replace-cross Abstract: Despite significant progress in safety alignment, large language models (LLMs) remain susceptible to jailbreak attacks. Existing defense mechanisms have not fully deleted harmful knowledge in LLMs, which allows such...

https://arxiv.org/abs/2505.18588

5 CONF

Operon: Incremental Construction of Ragged Data via Named Dimensions

ArXiv CS.AI 50%

arXiv:2511.16080v2 Announce Type: replace-cross Abstract: Modern data processing workflows frequently encounter ragged data: collections with variable-length elements that arise naturally in domains like natural language processing, scientific measurements, and autonomous AI...

https://arxiv.org/abs/2511.16080

6 CONF

AI-exposed jobs deteriorated before ChatGPT

ArXiv CS.AI 50%

arXiv:2601.02554v2 Announce Type: replace-cross Abstract: Public debate links worsening job prospects for AI-exposed occupations to the release of ChatGPT in late 2022. Using monthly U.S. unemployment insurance records, we measure occupation- and location-specific unemployment...

https://arxiv.org/abs/2601.02554

7 CONF

Scalable Adaptation of 3D Geometric Foundation Models via Weak Supervision from Internet Video

ArXiv CS.AI 50%

arXiv:2602.07891v2 Announce Type: replace-cross Abstract: Geometric foundation models show promise in 3D reconstruction. However, their progress is severely constrained by the scarcity of diverse, large-scale 3D annotations. While static-scene Internet videos are abundant and...

https://arxiv.org/abs/2602.07891

8 CONF

Router Drift Control: Mitigating Off-Policy Degradation in Mixture-of-Experts Reinforcement Learning

ArXiv CS.AI 50%

arXiv:2610.21682v2 Announce Type: replace-cross Abstract: Reinforcement learning (RL) can become off-policy due to training-inference mismatch, mini-batch updates, and asynchronous training. The resulting mismatch is especially harmful in Mixture-of-Experts (MoE) models, where...

https://arxiv.org/abs/2610.21682

9 CONF

OmniTrace: A Unified Framework for Generation-Time Source Attribution in Omni-Modal LLMs

ArXiv CS.AI 50%

arXiv:2604.13073v2 Announce Type: replace-cross Abstract: An omni-modal language model can answer a question about a multimodal document, a recording, or a video, but it cannot show which part of the input the answer came from. Asking the model to cite its evidence yields what...

https://arxiv.org/abs/2604.13073

00 CONF

Algorithmic Primitives of Theory of Mind Benchmarks

ArXiv CS.AI 50%

arXiv:2604.17819v2 Announce Type: replace-cross Abstract: Do Theory of Mind (ToM) benchmarks really test theory of mind, or are they actually testing parsing and algorithmic state tracking? While benchmarks vary modality and dialogue length, this paper finds that they re-encode...

https://arxiv.org/abs/2604.17819

01 CONF

FaithfulFaces: Pose-Faithful Facial Identity Preservation for Text-to-Video Generation

ArXiv CS.AI 50%

arXiv:2605.04702v2 Announce Type: replace-cross Abstract: Identity-preserving text-to-video generation (IPT2V) empowers users to produce diverse and imaginative videos with consistent human facial identity. Despite recent progress, existing methods often suffer from significant...

https://arxiv.org/abs/2605.04702

02 CONF

Coordination Matters: Process-Aware Evaluation of Cooperative Multi-Agent Reinforcement Learning

ArXiv CS.AI 50%

arXiv:2605.06557v2 Announce Type: replace-cross Abstract: Cooperative multi-agent reinforcement learning (MARL) benchmarks commonly emphasize aggregate outcomes such as return, success rate, or completion time. While essential, these metrics can obscure how agents coordinate and...

https://arxiv.org/abs/2605.06557

03 CONF

Human-Centered Learning Mechanics: Observable Entropy Control under Protected-Risk Constraints

ArXiv CS.AI 50%

arXiv:2605.22940v2 Announce Type: replace-cross Abstract: Entropy reduction is not a safety criterion: it can leave predictions unchanged or accompany increasing risk for a protected group. We study entropy-regulated learning under separately specified task, risk, and...

https://arxiv.org/abs/2605.22940

04 CONF

Accounting for Purchased Artificial Intelligence Inference in Corporate Greenhouse Gas Inventories: A Token-Based Method

ArXiv CS.AI 50%

arXiv:2606.10660v2 Announce Type: replace-cross Abstract: Purchased artificial intelligence (AI) inference belongs in Scope 3 Category 1 of a corporate greenhouse gas inventory, yet practice omits it or applies a spend-based factor that gives 1.7 to 12.3 times the physical...

https://arxiv.org/abs/2606.10660

05 CONF

Beyond Tokenization: Direct Timestep Embedding and Contrastive Alignment for Time-Series Question Answering

ArXiv CS.AI 50%

arXiv:2606.18986v2 Announce Type: replace-cross Abstract: Recent advances in large language models (LLMs) have given rise to time-series question answering (TSQA), which formulates time-series analysis as natural-language question answering. However, directly feeding raw...

https://arxiv.org/abs/2606.18986

06 CONF

TORINO: Token Reduction via Interpretable Concept Overlap in Vision-Language Models

ArXiv CS.AI 50%

arXiv:2607.04593v2 Announce Type: replace-cross Abstract: Vision-Language Models (VLMs) have demonstrated impressive capabilities across different tasks, but their computational cost is dominated by the large number of visual tokens fed to the language model. Existing token...

https://arxiv.org/abs/2607.04593

07 CONF

Do Multi-Agent LLMs Explore Each Other?

ArXiv CS.AI 50%

arXiv:2607.11250v2 Announce Type: replace-cross Abstract: Exploration is essential for reliable autonomy in multi-agent systems, yet it remains unclear whether large language model (LLM) agents can explore effectively when interacting with one another. We show that modern LLM...

https://arxiv.org/abs/2607.11250

08 CONF

An AI Approach to Verified Production Cryptographic Libraries

ArXiv CS.AI 50%

arXiv:2608.00965v2 Announce Type: replace-cross Abstract: Cryptographic code is critical infrastructure that must be correct, yet formally verifying production libraries remains difficult. Existing language-model proof systems solve isolated obligations with specifications and...

https://arxiv.org/abs/2608.00965

09 CONF

Demystifying When and Why VLAs Fail in Contact-Rich Tasks and How to Fix Them

ArXiv CS.AI 50%

arXiv:2608.01402v2 Announce Type: replace-cross Abstract: We address the problem of understanding when and why Vision-Language-Action models struggle with contact-rich manipulation tasks that require precise physical interaction. Prior work has primarily focused on addressing...

https://arxiv.org/abs/2608.01402

10 CONF

GroundingPI: A Grounding Foundation Model towards Physical Intelligence with Visual Primitives

ArXiv CS.AI 50%

arXiv:2609.39601v2 Announce Type: replace-cross Abstract: Precise grounding matters. It specifies which object is the target and where that object is, even in clutter and for tiny objects, and it has to be fast enough for closed-loop control. Yet vision-language-action (VLA) and...

https://arxiv.org/abs/2609.39601