NeoSignal

AI Intelligence Daily · Multi-Source · Cross-Verified

21 October 2026

174 verified · 318 raw · 5 sources

174	1	173	0
TOTAL	VERIFIED	CONFIRMED	EMERGING

Pipeline

Scrape HackerNews (Show/Top/New), Reddit (r/artificial, r/MachineLearning, r/singularity, r/LocalLLaMA), TechCrunch AI, VentureBeat AI, MIT Tech Review, The Verge AI, Wired AI, ArXiv CS.AI

Filter 40+ AI keyword patterns — LLMs, alignment, safety, research, tooling

Dedup Title-similarity (45% threshold) merges cross-source variants

Score Authenticity = 0.5 base + 0.3 per extra source + diversity + HN score bonuses

Rank Sorted by authenticity. Below 0.25 threshold are dropped.

Authenticity Tiers

VERIFIED	**0.80 - 1.00**	3+ independent sources including media
CONFIRMED	**0.50 - 0.79**	2 sources or 1 high-quality media
EMERGING	**0.25 - 0.49**	Single-source; passes AI keyword filter

Source Breakdown

Source	Articles	Category
ArXiv CS.AI	149	Media
TechCrunch AI	14	Media
HackerNews	6	Community
The Verge AI	4	Media
MIT Tech Review	2	Media

VERIFIED INTELLIGENCE — 1 story

VERI

After the Attacker Leaves: Benchmarking Carryover Attacks on LLM Agents

ArXiv CS.AI +1 source 80%

arXiv:2610.28425v1 Announce Type: cross Abstract: Modern LLM agents persist state across sessions via two channels: long-lived memory files silently prepended to the system prompt, and scheduled tasks waking the agent without user input. A one-time indirect prompt injection...

https://arxiv.org/abs/2610.28425

CONFIRMED SIGNALS — 173 stories

CONF

Show HN: Penmentor – Claude marks up your handwritten math like a teacher

HackerNews 50% HN 61

No summary — see link for full article.

https://github.com/AbdullahAlhariri/penmentor

CONF

Show HN: Lights-on software factory boilerplate for Claude Code

HackerNews 50% HN 18

I often switch between Claude Code and Codex throughout the week, and between my laptop and an older machine I leave running at home. I built agent-archive to make it easier to pick up where I left off, especially when i hit usage limits. It lets you (or a coding agent) find...

https://github.com/gojko/lights-on-software-factory

CONF

Show HN: Worklicant – Lightweight ATS. Pay per Vacancy. AI Enabled

HackerNews 50% HN 7

I have noticed that a lot of job posts that do not use any ATS, and in order to apply, they put their emails and ask candidates to apply with “X” in email subject. That seemed to be very counter productive — imagine having 300+ emails with resumes. Where do you manage them? In...

https://worklicant.com/

CONF

Show HN: Standard Topic – An AI and RSS-powered news and resource platform

HackerNews 50% HN 4

Hi HN, I'm John, a knowledge management and AI enablement professional. I created Standard Topic, an AI and RSS-powered news and resource platform, with assistance from Claude Code. Standard Topic uses AI integrations and RSS feeds to curate news and resources across relevant...

https://www.standardtopic.com/

CONF

Show HN: Koody for Business – AI bookkeeping for people who aren't accountants

HackerNews 50% HN 2

Hi HN, I'm Hallie, founder of Koody. Today, I'm launching Koody for Business: AI-powered accounting, bookkeeping, and tax prep software for sole proprietors and small businesses. For years, I used accounting software for my business. I went into it to create invoices, categorize...

https://koody.com/business

CONF

Show HN: LongTerMemory, AI-RAG Study tool helping people to study everything

HackerNews 50% HN 2

No summary — see link for full article.

https://longtermemory.com

CONF

Anthropic pitches AI safety bill that may block a model if 50+ people could be killed

TechCrunch AI 50%

The proposed policy seems to offer protections against AI running amok but actually forbids federal agencies from blocking a model's release without the permission of a judge.

https://techcrunch.com/2026/10/20/anthropic-pitches-ai-safety-bill-that-may-block-a-mod...

CONF

Hugging Face CEO warns that Netflix’s OpenAI hack documentary isn’t accurate

TechCrunch AI 50%

Before you share the Netflix documentary "AI Gone Rogue," take note. Clem Delangue, Hugging Face's co-founder who is featured in the film, says it went "full doomer mode" and isn't accurate.

https://techcrunch.com/2026/10/20/hugging-face-ceo-warns-that-netflixs-openai-hack-docu...

0 CONF

Anthropic’s cloud partnerships are getting messy

TechCrunch AI 50%

Anthropic is reportedly struggling to secure enough compute from cloud providers that increasingly view it as a competitor, even as its infrastructure spending balloons ahead of a planned November IPO.

https://techcrunch.com/2026/10/20/anthropics-cloud-partnerships-are-getting-messy/

1 CONF

SpaceX’s AI business is beating expectations

TechCrunch AI 50%

SpaceX hit profitability in the third quarter, with net income of $4.4 billion. AI was the engine.

https://techcrunch.com/2026/10/20/spacexs-ai-business-is-beating-expectations/

2 CONF

OpenAI acquires startup Orchestra Bio to beef up its biotech business

TechCrunch AI 50%

OpenAI says it's adding Orchestra's team and technology to work on Rosalind, its AI model for life sciences research, and to its related Rosalind Workbench tool, a harness that aims to help researchers plan experiments and analyze results.

https://techcrunch.com/2026/10/20/openai-acquires-startup-orchestra-bio%e2%81%a0-to-bee...

3 CONF

Google has joined Amazon in attacking Nvidia’s stronghold with AI app developers

TechCrunch AI 50%

Google has joined Amazon in releasing a developer tool that makes it easy for PyTorch users to move their apps off Nvidia GPUs.

https://techcrunch.com/2026/10/20/google-has-joined-amazon-in-attacking-nvidias-strongh...

4 CONF

ChatGPT now lets you lock your chats

TechCrunch AI 50%

The company says the feature is designed for situations where users might be discussing something personal or planning a surprise and want to keep those conversations private when handing their device to friends or family to show them something in another chat.

https://techcrunch.com/2026/10/20/chatgpt-now-lets-you-lock-your-chats/

5 CONF

Eric Schmidt reportedly owns about half as much of Anthropic as CEO Dario Amodei

TechCrunch AI 50%

Eric Schmidt’s fortune is about to get even bigger.

https://techcrunch.com/2026/10/20/eric-schmidt-reportedly-owns-about-half-as-much-of-an...

6 CONF

Ex-Nvidia-turned-VC Amulya Vishwanath: ‘Physical AI is in its LEGO era’

TechCrunch AI 50%

It’s the moment everyone is waiting for — the ChatGPT moment for robotics, Amulya Vishwanath explained to TechCrunch’s Equity.

https://techcrunch.com/2026/10/20/ex-nvidia-turned-vc-amulya-vishwanath-physical-ai-is-...

7 CONF

Plants can speak using electricity, so this startup built an AI model to decipher their language

TechCrunch AI 50%

Electric Plant has built an AI-powered translator to help humans listen to what plants are saying with the subtle electricity coursing through their stems.

https://techcrunch.com/2026/10/20/plants-can-speak-using-electricity-so-this-startup-bu...

8 CONF

US orders federal agencies to remove China’s DeepSeek AI from their systems

TechCrunch AI 50%

The U.S. has ordered federal civilian agencies to remove DeepSeek products and third-party services built using its technology, citing national security concerns.

https://techcrunch.com/2026/10/20/us-orders-federal-agencies-to-remove-chinas-deepseek-...

9 CONF

Eka is worth $1.45B thanks to a physical AI model that has experts raving

TechCrunch AI 50%

Eka Robotics may be the first robotic arm that is actually good at picking up a wide range of objects, and it is so smooth and human-like, it is wowing the industry.

https://techcrunch.com/2026/10/20/eka-is-worth-1-45-billion-thanks-to-a-physical-ai-mod...

0 CONF

Yelp can now call on your behalf to check wait times at a restaurant

TechCrunch AI 50%

Yelp is embedding numerous new AI features into its app that can do everything from call to check on restaurant wait times to create personalized recommendations that remember your preferences.

https://techcrunch.com/2026/10/20/yelp-can-now-call-on-your-behalf-to-check-wait-times-...

1 CONF

Otter AI raises $320M from General Catalyst’s growth fund for its meeting tool

TechCrunch AI 50%

Otter.ai said that it will use these funds for enterprise growth, go-to-market strategy, international expansion, and product innovation.

https://techcrunch.com/2026/10/20/otter-ai-raises-320-million-from-general-catalysts-gr...

2 CONF

Melt it, spin it, use it again

MIT Tech Review 50%

The average American throws out around 81 pounds of clothing each year, and there are few options for recycling it. MIT engineers hope to cut down on that textile waste with a new type of yarn. The thermoplastic yarn mimics the properties of conventional elastic yarns, which...

https://www.technologyreview.com/2026/10/20/1145276/melt-it-spin-it-use-it-again/

3 CONF

A champion for brain injury patients

MIT Tech Review 50%

Alissa Totman ’13 was a sophomore when she joined MIT BrainTrust, a student-run organization that connects Institute undergraduates and people with brain injuries for support and socializing. “That group was a great way to learn about the human experience of what people go...

https://www.technologyreview.com/2026/10/20/1145297/a-champion-for-brain-injury-patients/

4 CONF

Google’s more personalized Gemini AI is heading to your car

The Verge AI 50%

Google is bringing Personal Intelligence to Gemini AI in your car. With this update, Gemini in Android Auto and cars with Google built-in can tap into your information across Google apps, including Gmail, Calendar, Maps, Photos, YouTube, and Search. As an example, Google says...

https://www.theverge.com/tech/1014999/google-gemini-ai-cars-android-auto

5 CONF

Meta pauses Muse sharing after researchers find AI chats on the web

The Verge AI 50%

Meta says it paused a Muse feature that lets you share conversations with the AI assistant after researchers found the URLs publicly available on the web, as reported by Ars Technica. In a report published this week, researchers at the security firm Claroc say they found more...

https://www.theverge.com/tech/1014627/meta-muse-ai-sharing-ai-chats

6 CONF

Spotify pulled 50 million AI slop and spam tracks from its recommendations

The Verge AI 50%

Spotify says it has removed more than 50 million songs considered AI-generated slop or spam from user recommendations over the past year. That's according to an announcement on Tuesday that says Spotify has also made changes to its recommendation system to highlight more music...

https://www.theverge.com/entertainment/1014284/spotify-ai-slop-spam-songs-removed

7 CONF

Navalia: Advancing Cowork Agents through Verifiable Task Synthesis and Long-Horizon Post-Training

ArXiv CS.AI 50%

arXiv:2610.26887v1 Announce Type: new Abstract: Large language model (LLM) agents are evolving from conversational assistants into Cowork Agents capable of autonomous planning, tool use, and complex task execution. Financial analysis requires these agents to integrate...

https://arxiv.org/abs/2610.26887

8 CONF

Tabular Foundation Models Can Learn Association Rules

ArXiv CS.AI 50%

arXiv:2602.14622v3 Announce Type: replace Abstract: Association Rule Mining (ARM) is a fundamental task for knowledge discovery in tabular data and is widely used in high-stakes decision-making. Classical ARM methods rely on frequent itemset mining, leading to rule explosion and...

https://arxiv.org/abs/2602.14622

9 CONF

ACE-Compression: An Ability-Centric Evaluation of Compressed Large Language Models

ArXiv CS.AI 50%

arXiv:2610.27913v1 Announce Type: new Abstract: Model compression makes large language models deployable, but today's evaluation tells an incomplete story. Standard practice measures retained task performance and stops there. This misses a critical fact: compression perturbs the...

https://arxiv.org/abs/2610.27913

0 CONF

MedPAO-Assist: Edge-Deployable, Modality-Aware Agentic AI for Radiology Report Structuring

ArXiv CS.AI 50%

arXiv:2610.26913v1 Announce Type: new Abstract: The adoption of Large Language Models for radiology report structuring has been largely dominated by either proprietary cloud-based models or large open models requiring high-end GPUs for deployment, which is a critical bottleneck...

https://arxiv.org/abs/2610.26913

1 CONF

Agentic Ensemble with Vision-Language Models for Visual Anomaly Detection

ArXiv CS.AI 50%

arXiv:2610.28560v1 Announce Type: new Abstract: Visual anomaly detection aims to detect abnormal objects, while anomaly samples are often scarce during model training. Assembling multiple pretrained detectors can help by leveraging their transferable image scores and anomaly...

https://arxiv.org/abs/2610.28560

2 CONF

Fix, Not Just Resample: Bounded Compiler-Guided Repair in Lean 4

ArXiv CS.AI 50%

arXiv:2610.26942v1 Announce Type: new Abstract: Automated theorem provers often rely on sampling language models, but proof assistants like Lean reject each failed step with a precise error message --- information that pure sampling discards. To overcome this, we introduce a...

https://arxiv.org/abs/2610.26942

3 CONF

MAMath-Bench: Process-Aware and Robust Evaluation of Multimodal Multi-Agent Mathematical Reasoning

ArXiv CS.AI 50%

arXiv:2610.26943v1 Announce Type: new Abstract: Mathematical reasoning is a fundamental capability for educational applications of Large Language Models (LLMs), where reliable problem solving requires not only correct answers but also coherent and verifiable reasoning processes....

https://arxiv.org/abs/2610.26943

4 CONF

LightCRS: Lightweight Multi-Domain Conversational Recommendation System

ArXiv CS.AI 50%

arXiv:2610.26948v1 Announce Type: new Abstract: Conversational recommender systems have recently adopted vision-language models to match user dialogue intents with multimodal product information. However, extending these methods to many product domains faces a dilemma: deploying...

https://arxiv.org/abs/2610.26948

5 CONF

When Planning Problems Become Hard for LLMs: Separating Structural Complexity from Semantic Interpretability

ArXiv CS.AI 50%

arXiv:2610.26964v1 Announce Type: new Abstract: Large language models (LLMs) struggle with classical planning, but benchmarks rarely distinguish structural difficulty from the difficulty of interpreting symbolic vocabulary. We examine seven STRIPS domains with BFS-optimal plan...

https://arxiv.org/abs/2610.26964

6 CONF

ClawMMU: Protection-Coherent Virtual Memory for Stateful LLM Agents

ArXiv CS.AI 50%

arXiv:2610.28093v1 Announce Type: cross Abstract: AI agents keep long-term memory, much of which comes from web pages and tool results. Agent harnesses, the software that runs the model, do not record who may act on this memory, so an instruction hidden in a fetched page can be...

https://arxiv.org/abs/2610.28093

7 CONF

Teaching AI Agent to Play Poker Strategically Through Preference Optimization

ArXiv CS.AI 50%

arXiv:2610.27028v1 Announce Type: new Abstract: A poker agent can make a legal move and still make a strategically poor one. We ask whether compact AI agents can exhibit strategic behavior under hidden information and whether preference optimization can improve beyond static and...

https://arxiv.org/abs/2610.27028

8 CONF

M-Plan: Comprehensive Planning For LLM Agents with Memory Arrangement

ArXiv CS.AI 50%

arXiv:2610.27032v1 Announce Type: new Abstract: Large language model (LLM)-based agents have recently demonstrated outstanding performance in single-turn tasks, yet they continue to struggle with long-horizon tasks, particularly in environments without prior training. A key...

https://arxiv.org/abs/2610.27032

9 CONF

Physical AI: Concepts, Techniques, and Challenges

ArXiv CS.AI 50%

arXiv:2610.27045v1 Announce Type: new Abstract: In recent years, physical artificial intelligence (physical AI) has experienced rapid development, capturing significant attention in academia and industry. However, the field has yet to reach consensus on its definition, technical...

https://arxiv.org/abs/2610.27045

10 CONF

ReuF2F: Benchmarking Coding Agents on Formalized Undergraduate Research Problems

ArXiv CS.AI 50%

arXiv:2610.27046v1 Announce Type: new Abstract: As AI systems begin to resolve open research problems, reliable verification becomes increasingly important. Formal mathematics provides a trusted framework for mathematical reasoning, enabling agents to produce machine-checkable...

https://arxiv.org/abs/2610.27046

1 CONF

Robustness of Internal Signals for Hallucination Detection in Vision-Language Models

ArXiv CS.AI 50%

arXiv:2610.27041v1 Announce Type: cross Abstract: When given an image and a text prompt, vision-language models (VLMs) can produce seemingly sophisticated text responses. However, they are also prone to hallucinate objects in their output, which can have detrimental consequences...

https://arxiv.org/abs/2610.27041

2 CONF

VISH-ASR: Viterbi-Guided Selection of Hotwords for Speech-LLM Contextual ASR

ArXiv CS.AI 50%

arXiv:2610.27867v1 Announce Type: cross Abstract: Prompt-based contextual ASR requires selecting a compact hotword subset from large dynamic inventories, yet existing pre-selection methods rely either on discrete ASR hypotheses that may discard acoustic evidence or on separately...

https://arxiv.org/abs/2610.27867

3 CONF

EDMA: Entropy-Driven Multimodal Answering

ArXiv CS.AI 50%

arXiv:2610.27120v1 Announce Type: new Abstract: Multimodal question answering (MMQA) is based on integrating heterogeneous data sources, selectively leveraging relevant modalities, and ignoring distractors. Existing approaches based on Multimodal Large Language Models (MLLMs)...

https://arxiv.org/abs/2610.27120

4 CONF

MoSAIK: Motion Search with Artificial Intelligence in K-space

ArXiv CS.AI 50%

arXiv:2610.27156v1 Announce Type: new Abstract: Object: Motion artefacts remain a major limitation of routine two-dimensional T2-weighted turbo spin-echo (TSE) brain MRI, reducing diagnostic confidence and often necessitating repeated acquisitions. MoSAIK (Motion Search with AI...

https://arxiv.org/abs/2610.27156

5 CONF

Sparse RL Relaxation for LLM Reasoning

ArXiv CS.AI 50%

arXiv:2610.27220v1 Announce Type: new Abstract: Recent work has explored continuous representations in place of discrete tokens during Chain-of-Thought (CoT) reasoning, often referred to as soft CoT. This is motivated by the idea that a mixture of token embeddings can represent...

https://arxiv.org/abs/2610.27220

6 CONF

EGI-BENCH: An Enterprise General Intelligence Benchmark Suite

ArXiv CS.AI 50%

arXiv:2610.27234v1 Announce Type: new Abstract: Enterprise adoption of LLMs in agentic workflows is gated by evaluations that span a wide arc of abilities: CRM operations, heterogeneous-document retrieval, personal data understanding, multi-turn planning, tool use, function...

https://arxiv.org/abs/2610.27234

7 CONF

CUA-Recovery: Benchmarking Error Recovery in Long-Horizon Computer-Use Agents

ArXiv CS.AI 50%

arXiv:2610.27645v1 Announce Type: new Abstract: As computer-use agents (CUAs) move to long-horizon workflows spanning multiple applications, undetected errors can silently corrupt persistent state and cause cascading failures in subsequent actions. Reliable error detection and...

https://arxiv.org/abs/2610.27645

8 CONF

An LLM-Based Agent for Legal Compliance Assessment: Architecture, Memory, and Evaluation in a Canadian and Quebec Context

ArXiv CS.AI 50%

arXiv:2610.27347v1 Announce Type: new Abstract: Checking whether a text complies with a body of law is slow when done by hand and fragile when done with keyword rules. This paper presents ComplianceAgent, the legal compliance sub-agent of COMPASS, a multi-agent framework that...

https://arxiv.org/abs/2610.27347

9 CONF

Runtime Control for AI Agents: Closing the Evaluation--Execution Gap in Operational Workflows

ArXiv CS.AI 50%

arXiv:2610.27480v1 Announce Type: new Abstract: Language-model agents increasingly participate in operational workflows where approvals, binds, and payments create commitments. An approval valid when issued may no longer authorize execution after relevant facts, evidence,...

https://arxiv.org/abs/2610.27480

0 CONF

Securing Agentic Commerce Through Behavior-Aware Fraud Detection and Cybersecurity for Trusted AI-Agent Payment Authorization

ArXiv CS.AI 50%

arXiv:2610.27483v1 Announce Type: new Abstract: The growing use of autonomous artificial intelligence agents in digital commerce creates new security concerns involving agent impersonation, unauthorized payments, compromised agents, and misuse of delegated authority. This...

https://arxiv.org/abs/2610.27483

1 CONF

Turning TS2Vec into a Foundation Model for Time Series Classification

ArXiv CS.AI 50%

arXiv:2610.28602v1 Announce Type: cross Abstract: TS2Vec is one of the strongest self-supervised methods for time series classification, introduced in 2022. It is designed to be trained anew on every dataset: self-supervised pre-training followed by linear probing. Since then,...

https://arxiv.org/abs/2610.28602

2 CONF

When Health Assistants Agree Too Readily: A Benchmark of Time-Critical Self-Diagnosis

ArXiv CS.AI 50%

arXiv:2610.27518v1 Announce Type: new Abstract: Every day, more than 40 million people ask ChatGPT a health question, such as whether laptop posture explains a stiff neck and days of pounding headache. Posture is plausible, but meningitis is a time-critical possibility. We...

https://arxiv.org/abs/2610.27518

3 CONF

MemDev-Bench: Does Memory Help Code Agents?Benchmarking Memory Systems over Real Repository Histories

ArXiv CS.AI 50%

arXiv:2610.27524v1 Announce Type: new Abstract: Code agents increasingly work on evolving real repositories, and memory systems aim to help them reuse earlier experience. However, such experience is diverse and evolving, so it remains unclear how memory systems organize it and...

https://arxiv.org/abs/2610.27524

4 CONF

Act on Your Behalf, Beyond Your Authorization: Benchmarking LLM Agent Authorization Alignment

ArXiv CS.AI 50%

arXiv:2610.27548v1 Announce Type: new Abstract: When an LLM agent acts on behalf of a user, it is expected to act within the authorization scope the user grants. Existing agent evaluations largely measure task completion or harmful consequences and can therefore overlook actions...

https://arxiv.org/abs/2610.27548

5 CONF

When LLMs Manipulate: Measuring Behavioral, Social, and Temporal Effects

ArXiv CS.AI 50%

arXiv:2610.27573v1 Announce Type: new Abstract: Large language models (LLMs) can influence user trust and decision-making through subtle linguistic cues, yet the behavioral effects of manipulative outputs remain poorly quantified. We introduce a behavioral computing framework...

https://arxiv.org/abs/2610.27573

6 CONF

DuplexLedger: Benchmarking Transactional Memory in Full-Duplex Speech Agents

ArXiv CS.AI 50%

arXiv:2610.27581v1 Announce Type: new Abstract: Full-duplex speech agents must update persistent memory while listening and speaking, yet it remains unclear which events should be stored, revised, or excluded. Existing benchmarks isolate interaction timing from memory outcomes,...

https://arxiv.org/abs/2610.27581

7 CONF

Meta Expert: Cross-Layer Expert Sharing for Storage- and Retrieval-Efficient MoE

ArXiv CS.AI 50%

arXiv:2610.27598v1 Announce Type: new Abstract: As model parameters scale up, sparsely activated Mixture-of-Experts (MoE) approaches have become essential for model scaling. However, mainstream models currently adopt hierarchical architectures, where experts in different layers,...

https://arxiv.org/abs/2610.27598

8 CONF

Inferring continuous cognitive traits from limited neuroimaging data using pairwise convolutional neural networks

ArXiv CS.AI 50%

arXiv:2610.27668v1 Announce Type: new Abstract: Individual differences in cognitive abilities vary widely, yet the structural brain features supporting these differences remain poorly understood. Traditional brain-behavior analyses rely on predefined metrics such as volume or...

https://arxiv.org/abs/2610.27668

9 CONF

Give the Model a Finger: Developmentally Aligned Evaluation of Counting in Vision-Language Models

ArXiv CS.AI 50%

arXiv:2610.27756v1 Announce Type: new Abstract: Vision-language models (VLMs) are exact on small sets and drift into estimation on larger ones, a profile reminiscent of children before they master counting. Children cross the barrier with epistemic actions: pointing at each item...

https://arxiv.org/abs/2610.27756

0 CONF

Pattern Intelligence: Unsupervised, LLM-Interpreted Discovery of Systematic Underpayment and Denial Patterns in Healthcare Revenue Cycle Management

ArXiv CS.AI 50%

arXiv:2610.27684v1 Announce Type: new Abstract: Healthcare providers lose substantial revenue to systematic payer underpayments and claim denials, yet identifying the recurring, correctable patterns behind them remains largely manual and does not scale to hospital claim volumes....

https://arxiv.org/abs/2610.27684

1 CONF

EASformer: Environment-Action-State Alignment for Industrial Generative Ranking

ArXiv CS.AI 50%

arXiv:2610.27691v1 Announce Type: new Abstract: Modern industrial ranking systems increasingly adopt generative recommendation (GR) paradigms, in which user behavior sequences and non-sequential (NS) features are tokenized and jointly modeled by Transformer-style backbones. This...

https://arxiv.org/abs/2610.27691

2 CONF

E8-QAT: Efficient 2-Bit Quantization-Aware Training with Implicit Lattice Codebooks

ArXiv CS.AI 50%

arXiv:2610.27699v1 Announce Type: new Abstract: Low-bit quantization reduces the memory footprint of large language models, but preserving accuracy with efficient training remains challenging. Scalar quantization encodes weights independently, while explicit-codebook vector...

https://arxiv.org/abs/2610.27699

3 CONF

How Fine-Tuning Objectives Shape Layer-Wise Information in LLM Hallucination Detection

ArXiv CS.AI 50%

arXiv:2610.27711v1 Announce Type: new Abstract: Under matched conditions, classifier-head fine-tuning (\textsc{cls}) paradigm consistently outperforms the LLM-as-Judge sequence-to-sequence (\textsc{s2s}) on binary hallucination detection. We trace this gap to the representations...

https://arxiv.org/abs/2610.27711

4 CONF

When Does Experience Memory Help Closed-Loop LLM Driving Agents? A Controlled Evaluation with Resampled Warmup Pools, Token-Matched Fillers, and Audited Baselines

ArXiv CS.AI 50%

arXiv:2610.27714v1 Announce Type: new Abstract: When does experience memory help a closed-loop LLM driving agent? Published gains cannot say, because the two factors we find to matter most, which warmup experiences the pool contains and what any injected tokens do to the prompt,...

https://arxiv.org/abs/2610.27714

5 CONF

Large Flow Language Models

ArXiv CS.AI 50%

arXiv:2610.28559v1 Announce Type: cross Abstract: Continuous flow language models offer a path to parallel generation with tools for control and acceleration unavailable to discrete diffusion, yet effective techniques for building them at the billion-parameter scale remain less...

https://arxiv.org/abs/2610.28559

6 CONF

How Intervention History Changes AI Agent Sabotage on Subsequent Tasks

ArXiv CS.AI 50%

arXiv:2610.26935v1 Announce Type: cross Abstract: AI control evaluations often reset agents' memory between tasks, although deployed agents may retain records of prior interventions. We ask whether learning that an earlier attack was caught changes an agent's ability to evade...

https://arxiv.org/abs/2610.26935

7 CONF

Toward Agentic AI for the 6G Physical Layer: From Algorithm Discovery to Verified Baseband Silicon

ArXiv CS.AI 50%

arXiv:2610.27797v1 Announce Type: new Abstract: 6G will be designed faster than it can be built: AI-driven search already proposes physical-layer algorithms at machine speed, while carrying a single one onto embedded baseband silicon remains specialist work. That silicon imposes...

https://arxiv.org/abs/2610.27797

8 CONF

Privacy-preserving inference on hosted models: a learned input-embedding transform for frozen Qwen3.8-27B

ArXiv CS.AI 50%

arXiv:2610.27817v1 Announce Type: new Abstract: Every prompt sent to a hosted language model is readable by whoever runs it. We study whether the prompt can remain on the client while the host receives transformed vectors that stand in for it. A language model converts text to...

https://arxiv.org/abs/2610.27817

9 CONF

StartLux-Decision: AutoThink Decision Models with Reinforcement Learning for Calibrated Deliberative Decisions

ArXiv CS.AI 50%

arXiv:2610.17309v2 Announce Type: replace-cross Abstract: We introduce StartLux-Decision, decision models from 0.8B to 27B parameters that combine efficient single-pass prediction with adaptive, confidence-guided reasoning. The Instant models use bidirectional attention in...

https://arxiv.org/abs/2610.17309

0 CONF

IndustryForge-27B: A Domain-Enhanced Multimodal Foundation Model for Industrial CAD

ArXiv CS.AI 50%

arXiv:2607.28050v2 Announce Type: replace Abstract: Automating industrial CAD design and manufacturing places distinctive demands on multimodal foundation models: the model must see engineering drawings and 3D geometry screenshots, write correct parametric-modelling scripts and...

https://arxiv.org/abs/2607.28050

1 CONF

From Comparison to Selection: Enhancing Cross-Scale Generalization of Pointer Networks Trained with Reinforcement Learning for Capacitated Drone Delivery Routing

ArXiv CS.AI 50%

arXiv:2610.27936v1 Announce Type: new Abstract: Unmanned aerial vehicles (UAVs) enable fast, flexible last-mile and emergency delivery, but their routing remains challenging as the number of clients varies. Classical approaches based on mixed-integer programming and heuristics...

https://arxiv.org/abs/2610.27936

2 CONF

PI-MLLM: Psychophysics-Inspired Multimodal Large Language Model for Oddly Satisfying Video Emotion Analysis

ArXiv CS.AI 50%

arXiv:2610.28264v1 Announce Type: cross Abstract: Oddly Satisfying Videos (OSVs) can evoke strong viewer responses through repetitive motion, visual tactility, and ASMR-like sounds despite containing few explicit semantic emotion cues. This makes OSVs a challenging setting for...

https://arxiv.org/abs/2610.28264

3 CONF

When Do Humans and Machines Truly Complement Each Other? Formal Conditions and Empirical Evidence for Human-AI Synergy

ArXiv CS.AI 50%

arXiv:2610.27965v1 Announce Type: new Abstract: Can humans and artificial intelligence cooperate such that their combination yields greater accuracy than either agent alone? This result, termed \emph{synergy} or \emph{complementarity}, is notoriously difficult to achieve, even...

https://arxiv.org/abs/2610.27965

4 CONF

Building Telecom Language Models with RSOD: Domain Data, Specialist Post-Training, Memory-Conscious Distillation, and Networking Evaluation

ArXiv CS.AI 50%

arXiv:2610.27993v1 Announce Type: new Abstract: Telecom language models must combine broad networking knowledge with specialist behavior across routing, broadband services, access technologies, and operational diagnostics while remaining practical to deploy as a single model. We...

https://arxiv.org/abs/2610.27993

5 CONF

TrajEvolve: Trajectory Evolution for Reinforcement Learning with Hindsight Credit Assignment

ArXiv CS.AI 50%

arXiv:2610.28060v1 Announce Type: new Abstract: The Reinforcement Learning (RL) paradigm has achieved remarkable success in enhancing the reasoning capabilities of Large Language Models (LLMs). However, when applied to long-horizon tasks, it faces severe challenges: i) Due to...

https://arxiv.org/abs/2610.28060

6 CONF

IECG: Weakly-Supervised Interpretability-Enhancing Foundation Model for Electrocardiogram

ArXiv CS.AI 50%

arXiv:2610.28083v1 Announce Type: new Abstract: Electrocardiography (ECG) is a cornerstone of cardiac diagnosis, yet most machine learning methods for ECG analysis lack interpretability, limiting their clinical adoption. We present IECG, a weakly-supervised ECG foundation model...

https://arxiv.org/abs/2610.28083

7 CONF

InsightRAG: Aggregating Distributed Scholarly Judgments for Scientific Survey Generation

ArXiv CS.AI 50%

arXiv:2610.28085v1 Announce Type: new Abstract: The rapid growth of scientific literature makes survey writing increasingly challenging, motivating automatic survey generation. Yet, existing systems must search an open space of papers and an open space of concepts with no trace...

https://arxiv.org/abs/2610.28085

8 CONF

GBClaw: An agentic AI framework for atomistic grain boundary research and mechanistic discovery

ArXiv CS.AI 50%

arXiv:2610.28629v1 Announce Type: cross Abstract: Agentic artificial intelligence (AI) systems hold immense potential for automating complex workflows in materials discovery and design, but extending them to domain-intensive mechanistic investigations remains challenging. Here,...

https://arxiv.org/abs/2610.28629

9 CONF

Robust Representation Learning for Spiking Neural Networks based on Conditional Information Bottleneck

ArXiv CS.AI 50%

arXiv:2610.28110v1 Announce Type: new Abstract: Spiking Neural Networks (SNNs) have shown great potential for low-power neuromorphic computing due to their event-driven processing and spatiotemporal sparsity, but they remain vulnerable to input perturbations, hardware-intrinsic...

https://arxiv.org/abs/2610.28110

0 CONF

Claims of emergence in AI should be grounded in information decomposition

ArXiv CS.AI 50%

arXiv:2610.28479v1 Announce Type: new Abstract: When a language model develops capabilities not traceable to its individual components, when a multi-agent AI system outperforms each agent on its own, or when a human-AI pair succeeds where either fails in isolation, AI...

https://arxiv.org/abs/2610.28479

1 CONF

Proof-Carrying Contracts: Commitments AI Agents Cannot Break

ArXiv CS.AI 50%

arXiv:2610.28484v1 Announce Type: new Abstract: AI agents increasingly act on behalf of people or other agents, purchasing services, exchanging information and delegating work. What an agent must respect is written in instructions, policies or agreements, but text alone cannot...

https://arxiv.org/abs/2610.28484

2 CONF

LoWAgent: A Low-Resource Multilingual Benchmark for Web Agents

ArXiv CS.AI 50%

arXiv:2610.27205v1 Announce Type: cross Abstract: Web agents are typically evaluated on English-language interfaces, leaving their ability to operate across the world's multilingual websites largely unexplored. This gap is especially significant for low-resource languages, where...

https://arxiv.org/abs/2610.27205

3 CONF

Humans Correct Their Judgments Through Debate, but Weaker AI Models Do Not

ArXiv CS.AI 50%

arXiv:2610.28539v1 Announce Type: new Abstract: How can we effectively oversee AI systems that surpass human intelligence? AI Safety via Debate proposes that two AI systems argue opposing positions and a judge, either a human or a weaker model, decides which is correct. By...

https://arxiv.org/abs/2610.28539

4 CONF

Joint Constraint Aggregation for Qualifier-Sensitive Retrieval-Augmented QA

ArXiv CS.AI 50%

arXiv:2610.27114v1 Announce Type: cross Abstract: Retrieval-augmented QA can fail even when the correct answer is in the retrieved evidence. This can happen when a competing answer satisfies some, but not all, of the question's requirements and is mentioned frequently in the...

https://arxiv.org/abs/2610.27114

5 CONF

Beyond the Sequentiality Bottleneck: A Hybrid Diffusion-Autoregressive Framework for Efficient Multimodal Reasoning

ArXiv CS.AI 50%

arXiv:2610.28584v1 Announce Type: new Abstract: Autoregressive models (ARMs) face a "Sequentiality Bottleneck" in reasoning, while diffusion language models (DLMs) offer parallelism but lack semantic coherence. To addresses both limitations, we propose Collaborative Reasoning...

https://arxiv.org/abs/2610.28584

6 CONF

What Do RTL Repair Benchmarks Actually Measure?

ArXiv CS.AI 50%

arXiv:2610.28595v1 Announce Type: new Abstract: RTL repair benchmarks should measure whether a model can fix broken RTL given a specification. To this end, we construct and hash-bind RTLRepairDataset, 5,784 (broken, fixed) training pairs; RTLRepairBench, 459 held-out cases with...

https://arxiv.org/abs/2610.28595

7 CONF

Value-Rich, Differently Organized: Measuring Value Expression and Organization in AI-Generated Debates

ArXiv CS.AI 50%

arXiv:2610.28604v1 Announce Type: new Abstract: Current evaluation of LLM-generated debate largely focuses on argumentative quality, leaving the value structure of generated arguments underexamined. We introduce a diagnostic metric framework for comparing how values are...

https://arxiv.org/abs/2610.28604

8 CONF

Language Guidance for Supervised Vision Training: An Empirical Study of Generalization

ArXiv CS.AI 50%

arXiv:2610.27208v1 Announce Type: cross Abstract: Deep neural networks have achieved remarkable success on vision benchmarks, yet they continue to struggle with many generalization challenges. Supervised vision training relies on one-hot labels, which provide limited information...

https://arxiv.org/abs/2610.27208

9 CONF

MOSS: A Production Framework for Monitoring and Diagnosing Semantic Failures in Search and Recommendation Systems

ArXiv CS.AI 50%

arXiv:2610.26902v1 Announce Type: cross Abstract: Detecting semantic failures in production recommendation and search systems is hard: behavioral metrics lag by days, manual review does not scale, and most LLM evaluation frameworks are designed for offline, fixed datasets rather...

https://arxiv.org/abs/2610.26902

0 CONF

Uncertainty Gates the Gradient: Adaptive Updates for Generalized Few-Shot 3D Segmentation

ArXiv CS.AI 50%

arXiv:2610.26909v1 Announce Type: cross Abstract: In generalized few-shot 3D point cloud segmentation, support annotations are often compromised by sparsity and occlusion. Blindly adapting to such low quality samples risks learning spurious geometric patterns rather than robust...

https://arxiv.org/abs/2610.26909

1 CONF

Steerable Pluralistic Policy Alignment from Anonymized Crowd Feedback

ArXiv CS.AI 50%

arXiv:2610.26914v1 Announce Type: cross Abstract: Pluralistic alignment requires AI systems to learn from diverse populations whose preferences may reflect heterogeneous or even conflicting objectives, and to personalize their behavior to individual users. Existing approaches in...

https://arxiv.org/abs/2610.26914

2 CONF

Enhancing analytical photon transport in turbid media through physics-guided neural network corrections

ArXiv CS.AI 50%

arXiv:2610.26917v1 Announce Type: cross Abstract: Analytical methods provide rapid and computationally efficient predictions of light transport in turbid media, making them attractive for real-time and inverse applications. However, their accuracy is limited by the...

https://arxiv.org/abs/2610.26917

3 CONF

Multilingual Brain Decoding Reveals Shared Cortical Semantic Geometry

ArXiv CS.AI 50%

arXiv:2610.26927v1 Announce Type: cross Abstract: Human languages differ markedly in lexical and syntactic form yet can convey similar semantic content. The neural basis of this cross-language semantic commonality remains unclear. Here we developed a multilingual brain decoding...

https://arxiv.org/abs/2610.26927

4 CONF

Expected Return Causes Outcome-Level Mode Collapse in Reinforcement Learning and How to Fix It with Inverse Probability Scaling

ArXiv CS.AI 50%

arXiv:2601.21669v2 Announce Type: replace-cross Abstract: Many reinforcement learning (RL) problems admit multiple terminal solutions of comparable quality, where the goal is not to identify a single optimum but to represent a diverse set of high-quality outcomes. Nevertheless,...

https://arxiv.org/abs/2601.21669

5 CONF

FoundPDE: A generative foundation model for data-driven symbolic discovery of partial differential equations

ArXiv CS.AI 50%

arXiv:2610.26963v1 Announce Type: cross Abstract: Discovering governing partial differential equations (PDEs) from observed data is a central inverse problem in computational science and engineering: the goal is not only to predict trajectories, but to identify interpretable...

https://arxiv.org/abs/2610.26963

6 CONF

CovNav: Conformal Prediction-Guided Adaptive Inference for Object Goal Navigation

ArXiv CS.AI 50%

arXiv:2610.27677v1 Announce Type: cross Abstract: In object goal navigation (ObjectNav), an embodied agent must find a target object (e.g., "find a bed") in a previously unseen environment, relying on spatial commonsense such as object co-occurrence. Large Language Models (LLMs)...

https://arxiv.org/abs/2610.27677

7 CONF

Cross-Lingual Reusability of LLM Pipelines: Financial Extraction, Multilingual Reasoning, and Semantic Screening

ArXiv CS.AI 50%

arXiv:2610.27043v1 Announce Type: cross Abstract: Financial institutions increasingly deploy large language models (LLMs) in multilingual markets, raising a practical question: can pipelines developed and validated in English be reused across languages, or must they be rebuilt...

https://arxiv.org/abs/2610.27043

8 CONF

BCT: Bayes-Consistent Tempering for Flow Language Models

ArXiv CS.AI 50%

arXiv:2610.27641v1 Announce Type: cross Abstract: Temperature scaling is typically applied as a post-hoc transformation of model probabilities. In posterior-induced flow language models, this creates two mismatches. First, posterior tempering implicitly changes both the endpoint...

https://arxiv.org/abs/2610.27641

9 CONF

Mind Your Boundaries: Boundary-Aware Model Obfuscation against Cross-node Attack

ArXiv CS.AI 50%

arXiv:2610.27135v1 Announce Type: cross Abstract: With the advancement of powerful AI chips, on-device machine learning is gaining traction for its low latency and privacy protection. However, when edge devices are compromised, attackers can obtain white-box access to the...

https://arxiv.org/abs/2610.27135

00 CONF

SLM-SS: Token-Based Speech Separation with Speech Language Models

ArXiv CS.AI 50%

arXiv:2610.27785v1 Announce Type: cross Abstract: Speech separation (SS) has witnessed substantial progress in recent years with the advent of neural network-based methods, achieving notable improvements on signal-level evaluation metrics. Existing speech separation systems are...

https://arxiv.org/abs/2610.27785

01 CONF

Model Exposure on One Device Endangers Others: Rethinking Edge Neural Network Security across Devices

ArXiv CS.AI 50%

arXiv:2610.27152v1 Announce Type: cross Abstract: Neural networks (NNs) are increasingly deployed on edge devices such as mobile and IoT platforms, offering low latency and improved privacy compared to cloud-based deployment. However, on-device models embedded in mobile...

https://arxiv.org/abs/2610.27152

02 CONF

CARLAR Influence: A Structured Hallucination Risk in Multimodal Cheque Extraction and an Exploratory Compressed-Image Countermeasure

ArXiv CS.AI 50%

arXiv:2610.27192v1 Announce Type: cross Abstract: Multimodal large language models (LLMs) are increasingly used for structured extraction from financial documents, but their behavior under visual ambiguity is poorly understood. We study CARLAR (Courtesy Amount Recognition and...

https://arxiv.org/abs/2610.27192

03 CONF

Profile-DP: Differential Privacy for User-Controlled Profile Release in Personalized LLM Inference

ArXiv CS.AI 50%

arXiv:2610.27213v1 Announce Type: cross Abstract: Personalized large language models (LLMs) increasingly rely on profile-conditioned inference, pairing public requests with rich, user-specific facts. This paradigm exposes the user profile itself, together with the user's...

https://arxiv.org/abs/2610.27213

04 CONF

MMedAgent-Plus: Scaling Multimodal Medical Agents across Modalities, Tasks and Workflows

ArXiv CS.AI 50%

arXiv:2610.27233v1 Announce Type: cross Abstract: Medical workflows often require multiple interdependent analyses, but existing specialist and generalist AI models are not designed to coordinate them. We introduce MMedAgent-Plus, a multimodal medical tool-use agent that...

https://arxiv.org/abs/2610.27233

05 CONF

ValiAssist: Scaling LLM-generated Programming Feedback Validation by Demonstration

ArXiv CS.AI 50%

arXiv:2610.27248v1 Announce Type: cross Abstract: Generative AI can create programming feedback at scale, but validating its alignment with instructors' pedagogical goals and strategies remains challenging. Instructors may struggle to fully specify validation criteria upfront,...

https://arxiv.org/abs/2610.27248

06 CONF

When Models Know but Can't Linearly Say: Relational Encoding Limits Linear Vulnerability Classification in Code LLMs

ArXiv CS.AI 50%

arXiv:2610.27257v1 Announce Type: cross Abstract: Large language models can detect vulnerable code, yet the form of vulnerability encoding in their representations remains unclear. We analyze 8 code models spanning 6.7B-15B parameters on C programs using three datasets...

https://arxiv.org/abs/2610.27257

07 CONF

LLaVA-CKD: Bottom-Up Cascaded Knowledge Distillation for Vision-Language Models

ArXiv CS.AI 50%

arXiv:2605.10641v2 Announce Type: replace-cross Abstract: Large Vision-Language Models (VLMs) are successful in addressing a multitude of vision-language understanding tasks, such as Visual Question Answering (VQA), but their memory and compute requirements remain a concern for...

https://arxiv.org/abs/2605.10641

08 CONF

Trail-Weighted Influence Scores for Approximate Outcome Prediction in Bayesian Networks

ArXiv CS.AI 50%

arXiv:2610.27366v1 Announce Type: cross Abstract: We study trail-weighted pruning of evidence for Bayesian-network prediction. A traversal enumerates the active trails from each evidence node to the outcome, scores each trail by the product of its edge strengths, and drops...

https://arxiv.org/abs/2610.27366

09 CONF

Fundamental Impossibility Results in AI Safety: Trading Off between Desiderata

ArXiv CS.AI 50%

arXiv:2610.27373v1 Announce Type: cross Abstract: Is there a fundamental tradeoff between desiderata for safe AI systems, such as harmlessness and helpfulness? We answer by formalizing the interaction between AI systems and users as a game with three players: a defender and an...

https://arxiv.org/abs/2610.27373

10 CONF

Beyond Scalar Leaderboards: Adaptive Sampling for Pareto Frontier Identification in Multi-Objective LLM Arenas

ArXiv CS.AI 50%

arXiv:2610.27447v1 Announce Type: cross Abstract: The evaluation of large language models (LLMs) is inherently multi-objective, as different models may offer different tradeoffs across performance dimensions such as math, code, and writing. Because such evaluations are often...

https://arxiv.org/abs/2610.27447

11 CONF

HealBench: A Fine-Grained Benchmark for Evaluating Psychological Comfort in Text-to-Image Generation

ArXiv CS.AI 50%

arXiv:2610.27516v1 Announce Type: cross Abstract: Despite advances in photorealism, semantic fidelity, and aesthetics, text-to-image generation and image editing remain understudied in a human-centered dimension: whether their outputs feel psychologically comforting. Grounded in...

https://arxiv.org/abs/2610.27516

12 CONF

Adversarial Benchmarks and BenchDoor Attacks: Exploiting Benchmark Incentives for Backdoor Attacks

ArXiv CS.AI 50%

arXiv:2610.27533v1 Announce Type: cross Abstract: Machine learning benchmarks act as guideposts for model development and spur the creation of training datasets intended to improve benchmark scores. We introduce BenchDoor, a family of data poisoning attacks that exploits this...

https://arxiv.org/abs/2610.27533

13 CONF

Can Native Safety Travel? Reusing Safety Pretraining Across Models via On-Policy Distillation

ArXiv CS.AI 50%

arXiv:2610.27555v1 Announce Type: cross Abstract: Safety pretraining has emerged as a promising paradigm for embedding safety deeply into a model during pretraining, yielding robustness to subsequent fine-tuning that conventional safety post-training often lacks. We refer to...

https://arxiv.org/abs/2610.27555

14 CONF

AnchorRM: Parallel Intra-Batch State Reconstruction with Anchor-Based Residual Memory for Temporal Graph Neural Networks

ArXiv CS.AI 50%

arXiv:2610.27558v1 Announce Type: cross Abstract: Memory-based temporal graph neural networks (TGN) rely on recurrent node memories to capture evolving interaction histories. However, temporal mini-batching introduces a trade-off between computational efficiency and temporal...

https://arxiv.org/abs/2610.27558

15 CONF

CityPaint: A Free Lunch from 2D Diffusion for City-Scale 3D Texturing

ArXiv CS.AI 50%

arXiv:2610.27564v1 Announce Type: cross Abstract: Generating high-fidelity, city-scale 3D environments plays a crucial role in applications such as virtual reality, gaming, and urban digital twins. However, the scarcity of real-world city-scale 3D training data forces existing...

https://arxiv.org/abs/2610.27564

16 CONF

AnomalyJev: Towards Evaluating Image Anomaly Explanations via Claim-Level Verification

ArXiv CS.AI 50%

arXiv:2610.27565v1 Announce Type: cross Abstract: Recent multimodal LLM (MLLM)-based anomaly detection (AD) methods can generate textual explanations that help interpret their predictions. However, reliably and efficiently evaluating these explanations remains challenging. While...

https://arxiv.org/abs/2610.27565

17 CONF

Learned Readout Tokens for Extracting Large Language Model Confidence

ArXiv CS.AI 50%

arXiv:2610.27566v1 Announce Type: cross Abstract: Large language models (LLMs) are increasingly used within everyday applications where their responses have significant downstream impacts. For responsible deployment of such systems, we desire insight into how much we can trust...

https://arxiv.org/abs/2610.27566

18 CONF

Factual Access States in Diffusion Language Models: From Mechanism to Knowledge Editing and Retrieval

ArXiv CS.AI 50%

arXiv:2610.27580v1 Announce Type: cross Abstract: Factual recall is a lookup: some representation inside the network serves as the key, and what that key is made of decides which queries can retrieve the fact, what an edit must cover, and what a retriever can read. We call it...

https://arxiv.org/abs/2610.27580

19 CONF

WORTH Benchmark: Evidence Discovery under Not-Fully-Cooperative Information -- A Two-Episode Pilot

ArXiv CS.AI 50%

arXiv:2610.27597v1 Announce Type: cross Abstract: Existing reasoning evaluations typically provide task-relevant information to models as available premises, rarely examining concurrently how models discover evidence autonomously and how information presentation within...

https://arxiv.org/abs/2610.27597

20 CONF

Auditing the Product, Not the Recursion: The Evaluation Evidence Behind Recursive Self-Improvement Claims

ArXiv CS.AI 50%

arXiv:2610.27610v1 Announce Type: cross Abstract: Recursive self-improvement (RSI) promises AI systems, such as self-evolving LLM agents, that become better at producing further improvements. Evaluating this promise requires separating product claims about the final system from...

https://arxiv.org/abs/2610.27610

21 CONF

Local Allow, Global Deny: Why Per-Action Authorization Does Not Compose in LLM Agents

ArXiv CS.AI 50%

arXiv:2610.27620v1 Announce Type: cross Abstract: Autonomous LLM agents act through tools under per-action authorization: a local guard screens each tool call in isolation. We show that local authorization does not compose into global authorization. A compositional authorization...

https://arxiv.org/abs/2610.27620

22 CONF

Beyond Calibration: Temporal LLM Confidence Assessment Across Languages and Local Settings

ArXiv CS.AI 50%

arXiv:2610.27702v1 Announce Type: cross Abstract: Large language models are expected to estimate their own uncertainty, with confidence signals used to guide retrieval, adaptive compute allocation, routing, and selective abstention. We investigate whether confidence signals...

https://arxiv.org/abs/2610.27702

23 CONF

Hearsay or Fact? How Framing and Elicitation Shape LLM Probability Updates

ArXiv CS.AI 50%

arXiv:2610.27745v1 Announce Type: cross Abstract: Large language models (LLMs) are increasingly used as judgment assistants and as stand-in participants in psychology experiments, yet little is known about how much their probability estimates move in response to a single new...

https://arxiv.org/abs/2610.27745

24 CONF

RELAY: Scaling Historical Build Restoration through Rule Reuse and Agentic Repair

ArXiv CS.AI 50%

arXiv:2610.27784v1 Announce Type: cross Abstract: Vulnerability benchmarks and software engineering research depend on rebuilding historical software. Yet builds rely on external resources, such as base images and packages, that change independently of the source code. In this...

https://arxiv.org/abs/2610.27784

25 CONF

Hallucinations of Large Language Models in Cross-Language Code Translation: Phenomena and Mitigation

ArXiv CS.AI 50%

arXiv:2610.27868v1 Announce Type: cross Abstract: Code translation converts source code from one programming language to another while preserving its functionality. Although Large Language Models (LLMs) have improved code translation, their outputs still contain hallucinations:...

https://arxiv.org/abs/2610.27868

26 CONF

Physical-Variable-Informed Deep Learning for Robust Diagnosis in Industrial Fluid Transport Systems

ArXiv CS.AI 50%

arXiv:2610.27891v1 Announce Type: cross Abstract: Industrial fluid transport systems are monitored through heterogeneous sensing streams, but robust fault diagnosis remains difficult because response signals vary with operating conditions and differ from physical variables in...

https://arxiv.org/abs/2610.27891

27 CONF

Polarity Blindness in LLM Safety: A Systematic Study of Negation, Antonym Substitution, and Adversarial Framing

ArXiv CS.AI 50%

arXiv:2610.27908v1 Announce Type: cross Abstract: Negation remains a persistent challenge for language models across NLP tasks and modalities. We show that this weakness can undermine LLM safety guardrails through a structural vulnerability we term polarity blindness: the...

https://arxiv.org/abs/2610.27908

28 CONF

Slots Are Not Speakers: Training-Free Speaker Linking for Frozen Streaming Diarizers

ArXiv CS.AI 50%

arXiv:2610.28053v1 Announce Type: cross Abstract: This paper presents a causal, training-free linker that allows a frozen streaming diarizer to track more speakers than it has output slots. Streaming end-to-end diarizers such as Streaming Sortformer emit a fixed number N of...

https://arxiv.org/abs/2610.28053

29 CONF

MoDDiT: Simple Token Routing in Diffusion Transformers

ArXiv CS.AI 50%

arXiv:2610.28086v1 Announce Type: cross Abstract: Real-time video generation, interactive world models, and on-device image synthesis are almost a reality. Diffusion Transformers (DiT) achieve excellent sample quality, shifting the bottleneck to the throughput of the models...

https://arxiv.org/abs/2610.28086

30 CONF

BAIT: Can LLMs Find What Biases a Reader? A Benchmark for Cognitive Bias Triggers in News

ArXiv CS.AI 50%

arXiv:2610.28092v1 Announce Type: cross Abstract: Persuasive writing exploits cognitive biases, recruiting a reader's mental shortcuts to shape belief, often without the reader noticing. We call the linguistic features exploiting such mental shortcuts cognitive bias triggers. As...

https://arxiv.org/abs/2610.28092

31 CONF

Causal Discovery for Linear Models with Latent Confounding via Multi-domain Identifiable Representation Learning

ArXiv CS.AI 50%

arXiv:2610.28134v1 Announce Type: cross Abstract: Causal discovery with latent confounding is particularly challenging, but a common setting in real-world data. In this work, we focus on linear causal models with latent confounding, represented by acyclic directed mixed graphs...

https://arxiv.org/abs/2610.28134

32 CONF

Temporal Evidence-Parameter Co-Alignment for LLM Reasoning over Temporal Knowledge Graphs

ArXiv CS.AI 50%

arXiv:2610.28176v1 Announce Type: cross Abstract: Large Language Models (LLMs) often struggle with temporally grounded reasoning because their static parametric memory is misaligned with the dynamic evolution of real-world knowledge. Although RAG and Parameter-Efficient...

https://arxiv.org/abs/2610.28176

33 CONF

JAXbounce: A Continuous-Control Pong-Like Benchmark for Active Inference Beyond Low Dimensional Environments

ArXiv CS.AI 50%

arXiv:2610.28203v1 Announce Type: cross Abstract: We introduce JAXbounce, a continuous control pong-like benchmark designed to evaluate active inference beyond discrete, low dimensional environments. JAXbounce combines continuous states and stochastic dynamics in discrete time...

https://arxiv.org/abs/2610.28203

34 CONF

Local Inference of LLMs on Long Contexts: A Data Systems Perspective

ArXiv CS.AI 50%

arXiv:2610.28223v1 Announce Type: cross Abstract: Large language models can solve complex problems across a variety of subjects, such as mathematics and coding. For such complex analytical tasks, models with a long context perform better. Serving models with long context is...

https://arxiv.org/abs/2610.28223

35 CONF

Local Work, Global Progress: A Convergence Theory of AI Agent Collaboration

ArXiv CS.AI 50%

arXiv:2610.28286v1 Announce Type: cross Abstract: Teams of large language model (LLM) agents are increasingly applied to complex tasks, but their collaboration protocols are mostly designed empirically, without convergence guarantees. We formalize collaborative problem solving...

https://arxiv.org/abs/2610.28286

36 CONF

Identifying Dependent Components from Multi-domain Linear Mixtures

ArXiv CS.AI 50%

arXiv:2610.28330v1 Announce Type: cross Abstract: We study a linear mixing model with dependent latent components, assuming multiple data domains. Most existing models assume that the components are independent or at least uncorrelated, in line with independent component...

https://arxiv.org/abs/2610.28330

37 CONF

CountVideoBench: A Benchmark to Evaluate Prediction Biases on the Object Counting task by Video-Language Models

ArXiv CS.AI 50%

arXiv:2610.28356v1 Announce Type: cross Abstract: Object counting in videos remains a poorly characterized capability of multimodal large language models. Counting questions are included in many existing VideoQA benchmarks, but the ground-truth count distributions in these...

https://arxiv.org/abs/2610.28356

38 CONF

MAS-Guard: Unified Guardrails from Individual Agents to Multi-Agent LLM Systems

ArXiv CS.AI 50%

arXiv:2610.28397v1 Announce Type: cross Abstract: Agentic AI extends large language models (LLMs) from generating responses to planning and executing complex workflows, substantially expanding their utility while exposing applications to unsafe actions, information leakage, and...

https://arxiv.org/abs/2610.28397

39 CONF

Rewards for Budget-Aware Multi-Turn Agents That Adapt to Arbitrary Test-Time Constraints

ArXiv CS.AI 50%

arXiv:2610.28409v1 Announce Type: cross Abstract: Large language model agents are often given an inference budget and asked to maximise success within it. A multi-turn agent has to allocate this budget across many environment interactions. An external harness can enforce the...

https://arxiv.org/abs/2610.28409

40 CONF

Code2Video-Compass: A Comprehensive Benchmark for General-Purpose Code-Based Video Generation across T2V, I2V, and V2V

ArXiv CS.AI 50%

arXiv:2610.28416v1 Announce Type: cross Abstract: Code-based video generation offers fine-grained control, targeted editing, and component reuse compared with direct video generation. This approach requires multimodal large language models (MLLMs) to translate visual and...

https://arxiv.org/abs/2610.28416

41 CONF

Every Model Leaves a Trace: Multi-Resolution LLM Fingerprinting

ArXiv CS.AI 50%

arXiv:2610.28434v1 Announce Type: cross Abstract: Large language models leave model-specific traces in their generated text, but it remains unclear how finely these fingerprints can distinguish related models and which signals remain informative as obvious cues are reduced. We...

https://arxiv.org/abs/2610.28434

42 CONF

VLM-Guided Contact Retargeting and Generative Partner Modeling for Humanoid-Human Interaction

ArXiv CS.AI 50%

arXiv:2610.28523v1 Announce Type: cross Abstract: Humanoid-human interaction requires robots to operate under severe partial observability: during close physical contact, the human partner is occluded, truncated, or outside the robot's field of view, causing pose estimation to...

https://arxiv.org/abs/2610.28523

43 CONF

Binary Discrete Diffusion: Candidate-Set Diffusion for Logic and Planning Tasks

ArXiv CS.AI 50%

arXiv:2610.28543v1 Announce Type: cross Abstract: Discrete diffusion models iteratively denoise a noisy sequence of categorical data such as text, enabling any-order generation with self-correction and in-filling capabilities. This makes them promising candidates for reasoning,...

https://arxiv.org/abs/2610.28543

44 CONF

When Do LLMs Help with Feature Selection? A Systematic Empirical Study

ArXiv CS.AI 50%

arXiv:2610.28556v1 Announce Type: cross Abstract: Large language models (LLMs) can leverage semantic feature names alongside summary statistics for tabular feature selection, yet it remains unclear when such information improves subset selection relative to established...

https://arxiv.org/abs/2610.28556

45 CONF

How Far Are LLMs from Symbolic Planners? An NLP-Based Perspective

ArXiv CS.AI 50%

arXiv:2508.01300v2 Announce Type: replace Abstract: AI planning provides agents the ability to act autonomously towards achieving a goal in a given environment. Recent advances in Large Language Models (LLMs) have introduced the prospect of using unstructured input for planning,...

https://arxiv.org/abs/2508.01300

46 CONF

LLM-Guided Evolution of Symbolic Acceleration Inequality Families for MILP

ArXiv CS.AI 50%

arXiv:2508.11850v3 Announce Type: replace Abstract: Integer programming (IP) is central to many combinatorial optimization tasks but remains challenging due to its NP-hard nature. A practical way to improve IP solvers is to manually design inequality families that exploit...

https://arxiv.org/abs/2508.11850

47 CONF

Mitigating Model Merging Conflicts via Knowledge-Aware Task Vector Purification

ArXiv CS.AI 50%

arXiv:2510.14697v2 Announce Type: replace Abstract: Model merging aims to integrate task-specific abilities from individually fine-tuned models into a single model without extra training. In recent model merging methods, task vector has become a fundamental building block, as it...

https://arxiv.org/abs/2510.14697

48 CONF

The Reward Model Selection Crisis in Personalized Alignment

ArXiv CS.AI 50%

arXiv:2512.23067v3 Announce Type: replace Abstract: Personalized alignment from preference data has focused primarily on improving personal reward model (RM) accuracy, with the implicit assumption that better preference ranking translates to better personalized behavior....

https://arxiv.org/abs/2512.23067

49 CONF

Repair the Core, Not the Symptom: Planning-Graph Repair for Long-Horizon Agents

ArXiv CS.AI 50%

arXiv:2607.01767v3 Announce Type: replace Abstract: Long-horizon language agents make interdependent decisions across multiple rounds, forming growing planning graphs in which later decisions depend on earlier states, observations, and tool outputs. Errors in these graphs can...

https://arxiv.org/abs/2607.01767

50 CONF

Diffusion Subgoal Planning for Long-Horizon Offline Goal-Conditioned Reinforcement Learning

ArXiv CS.AI 50%

arXiv:2609.34575v2 Announce Type: replace Abstract: Offline goal-conditioned reinforcement learning (GCRL) learns goal-directed policies from reward-free data, but in long-horizon tasks, goal-conditioned value functions often provide unstable guidance due to sparse rewards and...

https://arxiv.org/abs/2609.34575

51 CONF

Reasoning with Continuous Latent Diffusion

ArXiv CS.AI 50%

arXiv:2609.35694v3 Announce Type: replace Abstract: We introduce the Continuous Embedding Diffusion Reasoner (CEDR), a training and inference pipeline for continuous latent diffusion models that achieves strong performance on mathematical reasoning and code generation. We learn...

https://arxiv.org/abs/2609.35694

52 CONF

Not Self-Decidable: LLMs Cannot Draw the Boundary of What an Agent Verifier Can Check

ArXiv CS.AI 50%

arXiv:2610.04699v2 Announce Type: replace Abstract: A verifier for an agent faces rules of two kinds: the ones a fixed check can settle and the ones that require a judge. A team that derives its own checks fixes that split up front. Where the requirements come from outside, as...

https://arxiv.org/abs/2610.04699

53 CONF

Recognition Is Not Grounding: Benchmarking Multilingual Financial Evidence Extraction

ArXiv CS.AI 50%

arXiv:2610.19432v2 Announce Type: replace Abstract: Comparing financial disclosures across languages requires identifying shared accounting concepts and recovering all numerical facts that express them. Existing benchmarks evaluate aspects of these capabilities, but provide...

https://arxiv.org/abs/2610.19432

54 CONF

HSPR: Recovering Software-Agent Benchmark Scores via Hierarchical Posterior Inference

ArXiv CS.AI 50%

arXiv:2610.24611v2 Announce Type: replace Abstract: Evaluating software agents on a full benchmark is expensive. A small task subset can preserve agent rankings while yielding inaccurate scores. Historical responses provide useful structure, but tasks with identical source...

https://arxiv.org/abs/2610.24611

55 CONF

VibeTraining-Bench: Data-Trainer-Harness Co-Design for Iterative System Improvement

ArXiv CS.AI 50%

arXiv:2610.26342v2 Announce Type: replace Abstract: Recursive self-improvement (RSI) requires agents to diagnose system bottlenecks and coordinate improvements across training and inference. We refer to the agents' capability to jointly optimize training data, the trainer, and...

https://arxiv.org/abs/2610.26342

56 CONF

From Outcomes to Components: A Counterfactual Evaluation Framework for LLM-Proposed Repairs

ArXiv CS.AI 50%

arXiv:2610.26650v2 Announce Type: replace Abstract: A repair action proposed by a large language model (LLM) specifies which records to change and how to change their values. A failed action may still contain a useful choice of records or a useful update, depending on how the...

https://arxiv.org/abs/2610.26650

57 CONF

Entropic perspective on AI resilience, data-minimal learning and optimal control

ArXiv CS.AI 50%

arXiv:2310.14421v5 Announce Type: replace-cross Abstract: Behind the general terms like adversarial attacks and generative adversarial networks (GANs), such criteria as AI resilience and AI robustness gained a crucial importance, in trying to make the emergent AI tools reliable,...

https://arxiv.org/abs/2310.14421

58 CONF

Deep learning-based multi-level airway collapse site localization on obstructive sleep apnea patients based on snoring sounds

ArXiv CS.AI 50%

arXiv:2408.16030v3 Announce Type: replace-cross Abstract: Objective This study evaluated deep learning models, specifically ResNet-50 and Audio Spectrogram Transformer (AST), to identify multi-level upper airway collapses in obstructive sleep apnea (OSA) patients using snoring...

https://arxiv.org/abs/2408.16030

59 CONF

A Survey of Generative Categories and Techniques in Multimodal Generative Models

ArXiv CS.AI 50%

arXiv:2506.10016v4 Announce Type: replace-cross Abstract: Multimodal generative models (MGMs) have rapidly expanded beyond text generation to encompass images, music, video, human motion, and 3D objects. This survey categorises six primary text-conditioned generative modalities...

https://arxiv.org/abs/2506.10016

60 CONF

WoW-Bench: Evaluating Fine-Grained Acoustic Perception in Audio-Language Models via Marine Mammal Vocalizations

ArXiv CS.AI 50%

arXiv:2508.20976v2 Announce Type: replace-cross Abstract: Large audio-language models (LALMs) extend language understanding into the auditory domain, yet their ability to perform low-level listening, such as pitch and duration detection, remains underexplored. However, low-level...

https://arxiv.org/abs/2508.20976

61 CONF

Online Continual Learning on Intel Loihi 2 via a Co-designed Spiking Neural Network

ArXiv CS.AI 50%

arXiv:2511.01553v3 Announce Type: replace-cross Abstract: Edge AI must adapt to new classes and shifting data within a tight power budget, but online continual learning (learning from each sample before the next arrives) is where conventional processors are least efficient: each...

https://arxiv.org/abs/2511.01553

62 CONF

From Crawled to Published: A Publisher-Controlled Web Architecture for an AI-Native Internet

ArXiv CS.AI 50%

arXiv:2511.18354v2 Announce Type: replace-cross Abstract: AI agents, not humans, are becoming the web's primary consumers, yet the web still ships content structured for human browsing, with no native way for publishers to expose the semantic units within it. Access is therefore...

https://arxiv.org/abs/2511.18354

63 CONF

Activation Sensitivity as a Unifying Principle for Post-Training Quantization

ArXiv CS.AI 50%

arXiv:2601.11663v2 Announce Type: replace-cross Abstract: Post-training quantization (PTQ) methods for large language models compress pretrained weights to low bit-widths without retraining by optimizing layer-local proxy objectives. Activation-aware scaling methods such as AWQ...

https://arxiv.org/abs/2601.11663

64 CONF

Evaluation format, not only model capability, shapes measured triage failure in consumer health AI

ArXiv CS.AI 50%

arXiv:2603.11413v5 Announce Type: replace-cross Abstract: A recent Nature Medicine study reported that ChatGPT Health under-triages 51.6% of emergencies and concluded that consumer-facing AI triage poses safety risks. Its protocol, however, was an exam-style scaffold (forced...

https://arxiv.org/abs/2603.11413

65 CONF

Interpretable PM2.5 Forecasting for Urban Air Quality: A Comparative Study of Adaptive Time-Series Models

ArXiv CS.AI 50%

arXiv:2603.25495v2 Announce Type: replace-cross Abstract: Accurate short-term air-quality forecasting is essential for public health protection and urban management, yet many recent forecasting frameworks rely on complex, data-intensive, and computationally demanding models....

https://arxiv.org/abs/2603.25495

66 CONF

NVIDIA Spectrum-X: Hardware-Accelerated Multiplane Networking for Large-Scale AI Training

ArXiv CS.AI 50%

arXiv:2605.21187v2 Announce Type: replace-cross Abstract: As distributed model training scales to span hundreds of thousands of GPUs, scale-out networks face unprecedented performance and efficiency demands. NVIDIA Spectrum-X Ethernet has been designed from the ground up to...

https://arxiv.org/abs/2605.21187

67 CONF

What a One-Hour Interview Does Not Tell an LLM About You: Interviews Elicit Traits, Not Decision Policies

ArXiv CS.AI 50%

arXiv:2605.29458v2 Announce Type: replace-cross Abstract: Large language models are increasingly asked to stand in for particular people, and interviewing the person is the natural way to tell a model who they are. We test what a one-hour LLM-led adaptive interview tells a model...

https://arxiv.org/abs/2605.29458

68 CONF

EMERGE: Resolution-Agnostic Point Cloud Generation with Equivariant Graph-Based Diffusion

ArXiv CS.AI 50%

arXiv:2609.26039v2 Announce Type: replace-cross Abstract: Point cloud generation has emerged as a crucial task for accurately capturing and reproducing the complexity of the physical world. However, existing generative approaches, predominantly relying on Transformers and...

https://arxiv.org/abs/2609.26039

69 CONF

EDISCO: Equivariant DIScrete Diffusion for Euclidean Combinatorial Optimization

ArXiv CS.AI 50%

arXiv:2610.04953v2 Announce Type: replace-cross Abstract: Euclidean combinatorial optimization problems (ECOPs), such as the Traveling Salesman Problem (TSP) and Capacitated Vehicle Routing Problem (CVRP), possess inherent symmetries under the two-dimensional Euclidean group...

https://arxiv.org/abs/2610.04953

70 CONF

WeGR: Towards Unified Generative Retrieval via Behavior-aware Tokenization and Preference Alignment

ArXiv CS.AI 50%

arXiv:2610.16979v2 Announce Type: replace-cross Abstract: Generative retrieval (GR) offers a promising paradigm for industrial search by unifying candidate generation within an autoregressive framework. However, effectively leveraging user behaviors in industrial GR remains...

https://arxiv.org/abs/2610.16979

71 CONF

ELARSpeech: A 30K-Hour Dataset Across 675 Underrepresented Languages for Long-Tail Multilingual Speech Technologies

ArXiv CS.AI 50%

arXiv:2610.19388v2 Announce Type: replace-cross Abstract: Massively multilingual speech modeling has made remarkable progress in recent years, yet existing training resources and benchmarks still underrepresent much of the linguistic long tail. To address this gap, we introduce...

https://arxiv.org/abs/2610.19388

72 CONF

HumanSkill-4D: Training-Free Language Querying of Animatable Gaussian Avatars in Space and Time

ArXiv CS.AI 50%

arXiv:2610.24452v2 Announce Type: replace-cross Abstract: We introduce avatar referring segmentation, which selects regions of animatable Gaussian avatars from language queries. A query can also specify a pose or motion to select matching intervals. This lets users interact with...

https://arxiv.org/abs/2610.24452

73 CONF

TamedFlow: Trajectory-Aware Distillation for Teacher-Assisted Diffusion Sampling

ArXiv CS.AI 50%

arXiv:2610.26025v2 Announce Type: replace-cross Abstract: Diffusion Transformers (DiTs) deliver high-fidelity image and video generation, but inference requires many sequential model evaluations. Two acceleration strategies are increasingly important: model compression makes...

https://arxiv.org/abs/2610.26025

74 CONF

Rethinking LLM Fine-Tuning via Weight Space Reparameterization: Preserving Safety during Downstream Adaptation

ArXiv CS.AI 50%

arXiv:2610.26443v2 Announce Type: replace-cross Abstract: Fine-tuning large language models (LLMs) on downstream tasks often weakens their previously aligned safety behavior, creating an inherent trade-off between task adaptation and safety preservation. Existing approaches...

https://arxiv.org/abs/2610.26443