NeoSignal

AI Intelligence Daily · Multi-Source · Cross-Verified

03 November 2026

131 verified · 211 raw · 5 sources

131	3	128	0
TOTAL	VERIFIED	CONFIRMED	EMERGING

Pipeline

Scrape HackerNews (Show/Top/New), Reddit (r/artificial, r/MachineLearning, r/singularity, r/LocalLLaMA), TechCrunch AI, VentureBeat AI, MIT Tech Review, The Verge AI, Wired AI, ArXiv CS.AI

Filter 40+ AI keyword patterns — LLMs, alignment, safety, research, tooling

Dedup Title-similarity (45% threshold) merges cross-source variants

Score Authenticity = 0.5 base + 0.3 per extra source + diversity + HN score bonuses

Rank Sorted by authenticity. Below 0.25 threshold are dropped.

Authenticity Tiers

VERIFIED	**0.80 - 1.00**	3+ independent sources including media
CONFIRMED	**0.50 - 0.79**	2 sources or 1 high-quality media
EMERGING	**0.25 - 0.49**	Single-source; passes AI keyword filter

Source Breakdown

Source	Articles	Category
ArXiv CS.AI	111	Media
TechCrunch AI	11	Media
HackerNews	7	Community
The Verge AI	3	Media
MIT Tech Review	2	Media

VERIFIED INTELLIGENCE — 3 stories

VERI

Show HN: Arvre – A TUI for Claude Code sessions' forks

HackerNews +1 source 90% HN 4

arXiv:2610.41956v1 Announce Type: cross Abstract: Accurate forecasting with uncertainty quantification is critical in a variety of scientific applications ranging from epidemiology and economics to energy systems and earth sciences. Yet most forecasting models still need to be...

https://github.com/victorcarrico/arvre

VERI

OpenAI pitches data center power plants as a way to protect nearby areas

The Verge AI +1 source 80%

In an announcement on Monday, OpenAI says it will pilot its "Grid Protectors Program" at an upcoming data center in Effingham County, Georgia, where the company promises to free up to 1,000 megawatts of power during extreme weather or emergencies, enough to power air...

https://www.theverge.com/ai-artificial-intelligence/1024604/openai-data-center-grid-pro...

VERI

Does Recursive Knowledge Construction Help Agents Verify Consensus Claims in Science?

ArXiv CS.AI +1 source 80%

arXiv:2610.40906v1 Announce Type: new Abstract: Recent scientific agents build knowledge recursively by retrieving evidence, constructing an intermediate state, and judging whether that state contains sufficient information. These agents are evaluated end-to-end, usually without...

https://arxiv.org/abs/2610.40906

CONFIRMED SIGNALS — 128 stories

CONF

Show HN: Better Together – AI agents team up against spam calls and texts

HackerNews 50% HN 6

Launched https://better-together.fun this weekend to allow our personal AI agents to collaborate on problems that are tough to solve solo. First up is dealing with spam texts and calls.

https://better-together.fun/

CONF

Show HN: How Enigma worked and was cracked, explained with moving figures

HackerNews 50% HN 5

No summary — see link for full article.

https://www.readfp.com/chapters/how-enigma-was-cracked

CONF

Show HN: AgentTrafficCop – Stop AI agents from looping and burning money

HackerNews 50% HN 4

No summary — see link for full article.

https://agenttrafficcop.com

CONF

Show HN: ClickBench inspired leaderboard for multiple database benchmarks

HackerNews 50% HN 4

No summary — see link for full article.

https://benchmark.pivotlake.io/

CONF

Show HN: Wrapped – your neighborhood's year in complaints

HackerNews 50% HN 2

No summary — see link for full article.

https://311wrapped.com/

CONF

Show HN: Vaire, Self-Hosting Postgres Through the One Glorious CLI

HackerNews 50% HN 2

No summary — see link for full article.

https://github.com/mbvlabs/vaire

0 CONF

Apple Watch’s AI features for rewinding and recapping conversations begin beta testing

TechCrunch AI 50%

Now in beta: Apple's new Audio Intelligence features can help you remember what someone said or take notes on conversations.

https://techcrunch.com/2026/11/02/apple-watchs-ai-features-for-rewinding-and-recapping-...

1 CONF

Google takes Dreambeans to India in bid to bring AI-generated personal stories to the masses

TechCrunch AI 50%

Google's Dreambeans, its latest AI experiment, now supports 13 Indian languages.

https://techcrunch.com/2026/11/02/google-takes-dreambeans-to-india-in-bid-to-bring-ai-g...

2 CONF

Apple may try to increase revenue by doing…something with third-party AI apps

TechCrunch AI 50%

Apple hinted at ways that it could spur revenue through third-party "opportunities" during its Monday night earnings call.

https://techcrunch.com/2026/11/02/apple-may-try-to-increase-revenue-by-doing-something-...

3 CONF

Y Combinator’s Garry Tan uses AI agents so much, he spends up to $200K a year on tokens

TechCrunch AI 50%

Y Combinator Garry Tan has jokingly admitted that he's suffered from "cyber psychosis” and barely sleeps sometimes because he’s so excited to be working with his AI agents. On a new episode of Walter Isaacson’s podcast, The Builders, Tan put a price tag on his passion.

https://techcrunch.com/2026/11/02/y-combinators-garry-tan-uses-ai-agents-so-much-he-spe...

4 CONF

Trajectory raises $45M to make AI model training accessible to nontechnical experts

TechCrunch AI 50%

The one-year-old startup is now valued at $300 million.

https://techcrunch.com/2026/11/02/trajectory-raises-45m-to-make-ai-model-training-acces...

5 CONF

Anthropic warns that it’s very close to RSI capability, aka self-building AI

TechCrunch AI 50%

RSI is the point at which AI grows so good at training itself that it spawns a dramatic acceleration of AI capabilities. To the AI doomers, RSI represents the cataclysm from which there is no return.

https://techcrunch.com/2026/11/02/anthropic-warns-that-its-very-close-to-rsi-capability...

6 CONF

42AI comes out of stealth with $62.5M and a world model that can ‘predict human behavior’

TechCrunch AI 50%

Here's a question straight out of sci-fi: What if AI could predict what you were going to do before you decided to, even in a completely new situation?

https://techcrunch.com/2026/11/02/42ai-comes-out-of-stealth-with-62-5m-and-a-world-mode...

7 CONF

Elon Musk throttles Grok Bot limits due to ‘unsustainably high’ costs

TechCrunch AI 50%

Musk recently referred to Grok Bot as having "the fastest growth of a product that I've ever seen in my life."

https://techcrunch.com/2026/11/02/elon-musk-throttles-grok-bot-limits-due-to-unsustaina...

8 CONF

Omen AI adds liquid know-how in $16 million Aquatic Labs acquisition

TechCrunch AI 50%

Two startups tackling the data center water problem are joining forces in a $16 million deal.

https://techcrunch.com/2026/11/02/omen-ai-adds-liquid-know-how-in-16-million-aquatic-la...

9 CONF

OpenAI is finally merging ChatGPT’s Chat and Work tabs

TechCrunch AI 50%

OpenAI said that ChatGPT and Codex will draw usage from the same allocation pool after this change.

https://techcrunch.com/2026/11/02/openai-is-finally-merging-chatgpts-chat-and-work-tabs/

0 CONF

Raising the quality of insights in agentic analytics

MIT Tech Review 50%

In just a few years, generative AI has changed the face of enterprise analytics, notably by making analytics accessible to users across the organization. Agentic AI promises to do even more, by automating entire workflows and taking actions based on agent insights. But there is...

https://www.technologyreview.com/2026/11/02/1147660/raising-the-quality-of-insights-in-...

1 CONF

Anthropic clamps down on Claude’s AI video game clones

The Verge AI 50%

Anthropic has updated Claude Code's system prompt to prevent the AI tool from being used to re-create existing video games, as reported by Tom's Hardware. Retro gaming is currently being overrun with AI-made decompilations, recompilations, and ports, but while Anthropic will...

https://www.theverge.com/ai-artificial-intelligence/1024632/anthropic-claude-ai-video-g...

2 CONF

The New York Times sues Brave web browser for AI scraping and bypassing paywalls

The Verge AI 50%

The New York Times and a group of other publications have filed lawsuits against the company that makes the Brave web browser over alleged unlawful scraping to train AI and also letting users bypass their paywalls, as reported by Reuters. According to a complaint filed by the...

https://www.theverge.com/tech/1024588/brave-lawsuit-ai-scraping-new-york-times

3 CONF

FrontierMat: Benchmarking Language Models at the Frontier of Materials R&D

ArXiv CS.AI 50%

arXiv:2610.41162v1 Announce Type: new Abstract: To accelerate materials discovery, language models must be able to address problems at the research frontier. Yet textbook- and examination-derived benchmarks primarily assess established knowledge, leaving performance on frontier...

https://arxiv.org/abs/2610.41162

4 CONF

Circumventing the Computational Hardness of Computational Arbitrage

ArXiv CS.AI 50%

arXiv:2610.40831v1 Announce Type: new Abstract: AI model marketplaces host providers with heterogeneous costs and capabilities. These differences create an opportunity for computational arbitrage (Olmedo et al., 2026), in which an intermediary purchases inference from a...

https://arxiv.org/abs/2610.40831

5 CONF

GENSTRAT: Toward a Science of Strategic Reasoning in Large Language Models

ArXiv CS.AI 50%

arXiv:2605.23238v2 Announce Type: replace Abstract: Fixed game suites for evaluating strategic reasoning in large language models (LLMs) saturate and are hard to keep free of contamination. We introduce GENSTRAT, a system for evaluating the strategic capabilities of LLMs driven...

https://arxiv.org/abs/2605.23238

6 CONF

ChatGPT as a Surveillance Assistant? An Exploratory Case Study of AI-Assisted Surveillance Risks

ArXiv CS.AI 50%

arXiv:2610.40890v1 Announce Type: new Abstract: Large language models (LLMs) can generate detailed guidance, functional code, and persuasive text at scale. As one of the most widely used consumer language model products as of 2026, ChatGPT gives broad public access to these...

https://arxiv.org/abs/2610.40890

7 CONF

The First Few Tokens Matter: Understanding Chain-of-Thought Controllability

ArXiv CS.AI 50%

arXiv:2610.40939v1 Announce Type: new Abstract: Chain-of-thought (CoT) monitoring is a promising way to oversee increasingly capable agents. It succeeds in part because current models appear limited in their ability to control what they verbalize in their reasoning traces. We...

https://arxiv.org/abs/2610.40939

8 CONF

Opening the Box Changes the Cat: LLMs Detect Chain-of-Thought Monitoring - What now?

ArXiv CS.AI 50%

arXiv:2610.40946v1 Announce Type: new Abstract: Chain-of-thought (CoT) reasoning allows large language models (LLMs) to generate intermediate reasoning traces in natural language while solving complex tasks. These traces can support safety monitoring by exposing potentially...

https://arxiv.org/abs/2610.40946

9 CONF

Nedimo: An Evidence-Grounded Multilingual Pipeline for AI-Generated Sleep Stories

ArXiv CS.AI 50%

arXiv:2610.40970v1 Announce Type: new Abstract: Generative audio systems can produce large libraries of personalized bedtime content, but ordinary media objectives (retention, completion, and novelty) are poorly aligned with the goal of supporting a transition toward sleep....

https://arxiv.org/abs/2610.40970

0 CONF

Violet Teaming in Practice: Lessons from a Pilot Expert Workshop on Governing Complex AI Systems

ArXiv CS.AI 50%

arXiv:2610.41018v1 Announce Type: new Abstract: Violet teaming has been proposed as a method to integrate technical, policy, and societal considerations into the evaluation of emerging technologies. Here, we document a pilot expert workshop used to explore violet teaming as a...

https://arxiv.org/abs/2610.41018

1 CONF

ReplayRCA: Measuring Post-hoc Diagnosis and Live Oversight of Agent Failures by Counterfactual Replay

ArXiv CS.AI 50%

arXiv:2610.41025v1 Announce Type: new Abstract: When a language-model agent fails a multi-step task, can another model find the decisive mistake and fix it with a single action? We introduce ReplayRCA, a benchmark that scores such diagnoses by intervention rather than by...

https://arxiv.org/abs/2610.41025

2 CONF

Consensus Within, Competition Between: Decentralized LLM Teams for Perimeter Defense

ArXiv CS.AI 50%

arXiv:2610.41044v1 Announce Type: new Abstract: The use of large language models (LLMs) to coordinate multi-agent teams raises a fundamental architectural question: whether task allocation should be centralized in a single LLM controller or distributed across autonomous LLM...

https://arxiv.org/abs/2610.41044

3 CONF

LanG 2.0: Energy-Efficient Agentic AI for Semi-Automated Security Operations at Scale

ArXiv CS.AI 50%

arXiv:2610.41072v1 Announce Type: new Abstract: Security operations centers (SOCs) need to turn terabytes of alerts, logs and flows into trusted, affordable decisions to unveil hidden threats. We present LanG 2.0, an agentic system that detects threats, correlates evidence and...

https://arxiv.org/abs/2610.41072

4 CONF

Optimization Techniques for Solving the Minimum Red--Blue Separating Set Problem with an Application to Human--AI Text Separation

ArXiv CS.AI 50%

arXiv:2610.41081v1 Announce Type: new Abstract: We study the so-called Minimum Red''Blue Separating Set Problem (MRBSSP) which arises from computational geometry. In particular, we propose a compact Set-Cover ILP formulation, safe preprocessing rules, a Greedy Randomized...

https://arxiv.org/abs/2610.41081

5 CONF

Payroll Fraud Detection in Synthetic HR/ERP Graphs: An Inductive Comparison of Rules, Path Features, and Graph Neural Networks

ArXiv CS.AI 50%

arXiv:2610.41085v1 Announce Type: new Abstract: Payroll-fraud screening requires finding hidden employee--payee links while distinguishing suspicious relationships from legitimate ones. We formulate this problem as inductive link prediction and entity ranking on synthetic...

https://arxiv.org/abs/2610.41085

6 CONF

CIRCE Divines LLM Task Complexity from Constraint Structure

ArXiv CS.AI 50%

arXiv:2610.41089v1 Announce Type: new Abstract: Estimating whether a problem is too complex for a large language model (LLM) before the model attempts it can guide model routing, how to allocate test-time compute, and suggest the need for new tools to aid the agent. While...

https://arxiv.org/abs/2610.41089

7 CONF

ID2Pattern: Pretraining Generalizable Identity Behavior Patterns for Transaction Risk Foundation Models

ArXiv CS.AI 50%

arXiv:2610.41988v1 Announce Type: new Abstract: Large-scale behavioral pretraining offers a promising route to generalizable representations in online payment systems. However, high-cardinality identity fields such as card, device, and account IDs, though rich in behavioral...

https://arxiv.org/abs/2610.41988

8 CONF

Predicting Human-Gain Curves under Local Proxy Optimization from Repeated Ratings

ArXiv CS.AI 50%

arXiv:2610.41114v1 Announce Type: new Abstract: Optimizing a proxy objective can improve human-perceived quality, but the resulting gain can vary with optimization strength. Average proxy-human correlation alone does not reveal how human-perceived quality changes as optimization...

https://arxiv.org/abs/2610.41114

9 CONF

Confident Fools or Careful Searchers? A Behavioural Study of When LLMs Search Beyond Their Static Internal Memory

ArXiv CS.AI 50%

arXiv:2610.41124v1 Announce Type: new Abstract: Agentic LLM assistants must repeatedly decide whether to answer from memory or to call a tool such as web search. Unnecessary searches cost latency and money; missing ones yield confident but unsupported answers. Prior work mostly...

https://arxiv.org/abs/2610.41124

0 CONF

When Should AI Agents Ask? Clarification Requests Under Limited Human Attention

ArXiv CS.AI 50%

arXiv:2610.41129v1 Announce Type: new Abstract: AI agents increasingly carry out delegated tasks in parallel, with one person overseeing several of them at once. In practice, an agent often lacks information its task requires, such as an unstated preference, constraint, or...

https://arxiv.org/abs/2610.41129

1 CONF

Counterfactual Pairwise Augmentation Improves Small Pointwise LLM Judges

ArXiv CS.AI 50%

arXiv:2610.41149v1 Announce Type: new Abstract: Agentic systems increasingly gate individual steps with a pointwise judge that scores a response against a criterion. Small language models are attractive for this role because they can be served and specialized efficiently. Such a...

https://arxiv.org/abs/2610.41149

2 CONF

LLM Detoxification via Transition-Aware Reward-Guided Representation Sampling

ArXiv CS.AI 50%

arXiv:2610.41165v1 Announce Type: new Abstract: Large Language Models (LLMs) can generate toxic content, motivating effective test-time detoxification. Existing representation steering methods often rely on static or coarse interventions and provide imprecise guidance because...

https://arxiv.org/abs/2610.41165

3 CONF

RTL-Interact: Training EDA-Interactive Models for Multi-Task RTL Design

ArXiv CS.AI 50%

arXiv:2610.41225v1 Announce Type: new Abstract: Large language models offer a promising route to register-transfer-level (RTL) design, but reliable implementations require checking and revision based on electronic design automation (EDA) tools' feedback. Existing RTL-specialized...

https://arxiv.org/abs/2610.41225

4 CONF

Speech-DRAME: A Framework for Human-Aligned Benchmarks in Speech Role-Play

ArXiv CS.AI 50%

arXiv:2511.01261v2 Announce Type: replace-cross Abstract: Evaluating spoken role-play requires judging not only linguistic content but also prosody, emotional expression, character embodiment, and contextual fit. Existing automatic evaluation methods often collapse these aspects...

https://arxiv.org/abs/2511.01261

5 CONF

Experts Exhibit Structured Redundancy: Structure-Preserving Expert Pruning for Mixture-of-Experts Large Language Models

ArXiv CS.AI 50%

arXiv:2610.41236v1 Announce Type: new Abstract: Sparse MoE mechanism significantly improves the trade-off between model capacity and inference efficiency. However, practical deployment still requires storing all experts, resulting in substantial memory overhead. We show that...

https://arxiv.org/abs/2610.41236

6 CONF

From 1D Benchmarks to Complex 3D Geometries: Can Agents Reliably Specify Problems for Automated PDE Simulation?

ArXiv CS.AI 50%

arXiv:2610.41267v1 Announce Type: new Abstract: Turning an engineering request into a simulation requires consistent geometry, physics, boundary conditions, and numerical settings. Recent agent-assisted systems automate simulation setup, but successful execution alone does not...

https://arxiv.org/abs/2610.41267

7 CONF

Multimodal In-Context Learning with Explicit Rule Induction

ArXiv CS.AI 50%

arXiv:2610.41754v1 Announce Type: new Abstract: A central challenge in multimodal in-context learning (MICL) arises from tasks that are ill-defined without context and require uncovering the underlying rules from demonstrations. Existing methods predominantly treat MICL as...

https://arxiv.org/abs/2610.41754

8 CONF

Do Transaction Prices Reflect Visual Preference? A Diagnostic Study with Multimodal Language Models

ArXiv CS.AI 50%

arXiv:2610.41358v1 Announce Type: new Abstract: Existing visual preference evaluation relies on costly human annotations or preference reward models, whereas online marketplace transaction prices are readily available and reflect real purchasing behavior, offering potential...

https://arxiv.org/abs/2610.41358

9 CONF

LEAP: Efficient LLM Inference Scheduling with Generalizable Length Prediction

ArXiv CS.AI 50%

arXiv:2610.41359v1 Announce Type: new Abstract: Length-aware scheduling reduces request latency in LLM serving by prioritizing shorter requests. However, despite their large model sizes, length predictors can suffer degraded ranking performance under domain and task shifts, and...

https://arxiv.org/abs/2610.41359

0 CONF

From the Zoo to the BULLPEN: Sample-Efficient LLM Profiling via Multi-Channel Model Embeddings

ArXiv CS.AI 50%

arXiv:2610.41375v1 Announce Type: new Abstract: Choosing among the hundreds of thousands of available large language models (LLMs) requires a thorough understanding of each candidate model's properties. In practice, each property is measured by its own benchmark suite, so...

https://arxiv.org/abs/2610.41375

1 CONF

Online Evidence-Containment Prediction over Text Spans under Distinct Queries

ArXiv CS.AI 50%

arXiv:2610.41384v1 Announce Type: new Abstract: Evidence-grounded NLP systems often verify nested text regions sequentially, so verifying one region constrains others. We formalize this as Online Evidence-Containment Prediction (OECP): each candidate is predicted before exact...

https://arxiv.org/abs/2610.41384

2 CONF

ThinkSafe: Self-Generated Safety Alignment for Reasoning Models

ArXiv CS.AI 50%

arXiv:2601.23143v5 Announce Type: replace Abstract: Large reasoning models achieve strong performance through reinforcement learning but can suffer safety degradation. External teacher distillation can restore safety yet may compromise reasoning performance. We formalize safety...

https://arxiv.org/abs/2601.23143

3 CONF

Evidence-Guided Recovery for AI Agents with Ambiguous Tool Outcomes and Partial Execution

ArXiv CS.AI 50%

arXiv:2610.41453v1 Announce Type: new Abstract: Tool timeouts can leave AI agents facing ambiguous tool outcomes and partial execution: an action may have failed, committed or remained in flight while other workflow steps have already completed. We formulate evidence-guided task...

https://arxiv.org/abs/2610.41453

4 CONF

Steering Vectors as a Training Signal in LLM Post-Training

ArXiv CS.AI 50%

arXiv:2610.40998v1 Announce Type: cross Abstract: Steering vectors (SVs) are residual-stream directions that shift the behavior of LLMs when added to hidden states at inference time. While prior work has mainly used SVs as post-hoc controls, we ask whether the same directions...

https://arxiv.org/abs/2610.40998

5 CONF

Multi-Test Nation Bias Benchmarking of LLMs with Explicit Unbiased Baselines

ArXiv CS.AI 50%

arXiv:2610.41486v1 Announce Type: new Abstract: While prior work has highlighted that systematic nation-level bias in large language models (LLMs) can pose operational risks for international relations (IR) applications, many existing evaluations still lack a clearly specified...

https://arxiv.org/abs/2610.41486

6 CONF

From Representation to Readout: Mechanistic Analysis of Membership Signals in Language Models

ArXiv CS.AI 50%

arXiv:2610.41445v1 Announce Type: cross Abstract: Membership inference aims to determine whether a particular example was included in a model's training data. Such membership signals are often broadly described as memorization, while the underlying mechanisms can involve both...

https://arxiv.org/abs/2610.41445

7 CONF

Risk-Sensitive Mission Planning for Multi-Target On-Orbit Inspection via Distributional Reinforcement Learning

ArXiv CS.AI 50%

arXiv:2610.41647v1 Announce Type: new Abstract: Multi-target on-orbit servicing missions require planning tools that can adapt to evolving operational conditions while accounting for the outcome variability inherent to safety-critical spaceflight. This paper presents an adaptive...

https://arxiv.org/abs/2610.41647

8 CONF

Advancing Clinical Trial Outcome Prediction with Domain-Specific Large Language Models

ArXiv CS.AI 50%

arXiv:2610.41710v1 Announce Type: new Abstract: Clinical trial failures are a major barrier to efficient drug development, incurring substantial costs and delaying patient access to effective therapies. Structured approaches such as the Hierarchical Interaction Network (HINT)...

https://arxiv.org/abs/2610.41710

9 CONF

Clinical-Protocol-Aware Cyber Resilience for Connected Clinical Technologies Under AI-Enabled Adversarial Conditions

ArXiv CS.AI 50%

arXiv:2610.41784v1 Announce Type: new Abstract: Healthcare increasingly relies on connected medical devices, clinical information systems, cloud services, and distributed-care technologies, creating cybersecurity risks across clinical workflows. AI-enabled capabilities can...

https://arxiv.org/abs/2610.41784

0 CONF

Whose Values, Which Contexts, and What Signals? Grounding Cultural Value Alignment with Re3Culture

ArXiv CS.AI 50%

arXiv:2610.41793v1 Announce Type: new Abstract: Cultural value alignment requires not only model optimization but also a well-specified target grounded in real-human evidence. Yet how such targets should be grounded in human data remains largely unexplored, raising three...

https://arxiv.org/abs/2610.41793

1 CONF

RECAST: REconstruction of Chain-of-Thought via Auditable Structured Traces

ArXiv CS.AI 50%

arXiv:2610.41813v1 Announce Type: new Abstract: Large closed-source reasoning models expose only their final answers. The intermediate reasoning that produces those answers is hidden behind API surfaces, tool-call policies, and safety filters. Existing chain-of-thought (CoT)...

https://arxiv.org/abs/2610.41813

2 CONF

Vision Transformer Ensembles for Panoramic Street Segmentation

ArXiv CS.AI 50%

arXiv:2610.06063v2 Announce Type: replace-cross Abstract: Semantic segmentation of street panoramas can support detailed descriptions of urban environments, yet small datasets and unequal training costs make model selection difficult. This paper documents the two stages of a...

https://arxiv.org/abs/2610.06063

3 CONF

Automated Keyword Generation Using LLMs in a High-Volume Data Virtualization Service

ArXiv CS.AI 50%

arXiv:2610.41893v1 Announce Type: new Abstract: In modern data infrastructure, a data virtualization service (DVS) allows users to create many versions of source datasets for different processing tasks. For example, a multivariate or multi-modality dataset can be used for...

https://arxiv.org/abs/2610.41893

4 CONF

Using Machine Learning to Measure Self-Efficacy Belief Through Learners' Interaction Traces in Technology-Enhanced Learning

ArXiv CS.AI 50%

arXiv:2610.41900v1 Announce Type: new Abstract: Self-efficacy beliefs play a critical role in learners' performance, academic choices, and, more broadly, in their future career trajectories. As Technology-Enhanced Learning (TEL) environments have demonstrated strong potential...

https://arxiv.org/abs/2610.41900

5 CONF

ReX-GG: a LLM Ensemble Pipeline for Relation-extraction and Graph Generation

ArXiv CS.AI 50%

arXiv:2610.41901v1 Announce Type: new Abstract: Current LLM ensemble frameworks focus on multi-step setups with additional modules for answer ranking, often opting for token and span analysis rather than structured outputs, leading to heavyweight architectures with potential...

https://arxiv.org/abs/2610.41901

6 CONF

Sensorium: An Open-Source Multimodal Data Collection and Curation Library for Embodied Surgical AI

ArXiv CS.AI 50%

arXiv:2610.41946v1 Announce Type: new Abstract: Embodied surgical AI requires reliable multimodal data, yet surgical data collection remains costly, difficult to repeat, and strongly dependent on the hardware setup. We present Sensorium, an open-source Python library for...

https://arxiv.org/abs/2610.41946

7 CONF

Optimizing Stochastic Policy Geometry for Few-Step Flow Reinforcement Learning

ArXiv CS.AI 50%

arXiv:2610.41949v1 Announce Type: new Abstract: Few-step flow models generate samples through a handful of large denoising transitions. Applying GRPO to such models requires introducing stochasticity into the denoising transitions, and when a single transition spans a wide range...

https://arxiv.org/abs/2610.41949

8 CONF

ANGLER: Verifier-Grounded Benchmarking with an Adaptive Attacker for Web Agents

ArXiv CS.AI 50%

arXiv:2610.41272v1 Announce Type: cross Abstract: Web agents are increasingly deployed to complete tasks autonomously on real websites, where adversarially injected content can induce them to perform unauthorized actions. Existing evaluations primarily use fixed attacks or focus...

https://arxiv.org/abs/2610.41272

9 CONF

Same Question, Different Answers: Auditing Persona-Dependent Variation in Six LLMs on Smoking-Cessation Advice

ArXiv CS.AI 50%

arXiv:2610.42039v1 Announce Type: new Abstract: Hundreds of millions of people now ask large language model (LLM) chatbots for health advice, which raises a question that is simple to pose and hard to answer: does everyone get the same advice? We audit six widely deployed LLMs...

https://arxiv.org/abs/2610.42039

0 CONF

The Knowledge Layer Model (KLM): Evidence-Visible AI Output, Routing Diagnostics, and Negative Results

ArXiv CS.AI 50%

arXiv:2610.42066v1 Announce Type: new Abstract: AI answers require more than apparent correctness: reviewers need to inspect their recorded basis. We introduce the Knowledge Layer Model (KLM), an open, implementation-neutral specification for inference records with versioned...

https://arxiv.org/abs/2610.42066

1 CONF

ACCT: Asymmetric Cross-LLM Context Transfer

ArXiv CS.AI 50%

arXiv:2610.42116v1 Announce Type: new Abstract: In real-world deployments, large language model (LLM) systems are increasingly evolving from single-model invocation toward heterogeneous deployments in which different models are dynamically invoked for inference. When the same...

https://arxiv.org/abs/2610.42116

2 CONF

Leaner Training, Lower Leakage: Revisiting Memorization in LLM Fine-Tuning with LoRA

ArXiv CS.AI 50%

arXiv:2506.20856v1 Announce Type: cross Abstract: Memorization in large language models (LLMs) makes them vulnerable to data extraction attacks. While pre-training memorization has been extensively studied, fewer works have explored its impact in fine-tuning, particularly for...

https://arxiv.org/abs/2506.20856

3 CONF

PrivacyFlow: Privacy in AI Agents through Information Flow Analysis and Consequence-Aware Risk Management

ArXiv CS.AI 50%

arXiv:2610.40714v1 Announce Type: cross Abstract: Autonomous LLM agents executing multi-step workflows over personal data often misalign with user privacy expectations and leak sensitive, out-of-context information. Although Contextual Integrity (CI) formalizes this problem,...

https://arxiv.org/abs/2610.40714

4 CONF

Characterizing LLM Agent Behaviors in Module Shadowing Environments

ArXiv CS.AI 50%

arXiv:2610.40716v1 Announce Type: cross Abstract: LLM agents operating in untrusted workspaces face the risk of untrusted code execution during routine tasks, yet final reports and workspace states alone cannot reliably establish whether execution occurred. We introduce an...

https://arxiv.org/abs/2610.40716

5 CONF

RiskyPy: Toward Model-Calibrated Prompt Generation for Joint Security and Functionality Evaluation of LLM-Generated Code

ArXiv CS.AI 50%

arXiv:2610.40735v1 Announce Type: cross Abstract: Evaluating approaches that improve the security of LLM code generation requires datasets that jointly assess security and functionality and remain adapted to the capabilities of the models being studied. However, existing...

https://arxiv.org/abs/2610.40735

6 CONF

CLIC: Closed-Loop Intent Consistency for Securing LLM-Driven Control in Open RAN

ArXiv CS.AI 50%

arXiv:2610.40744v1 Announce Type: cross Abstract: With the progressive capabilities of large language models (LLMs), researchers are finding ways to integrate them into the control loops of Open Radio Access Network (O-RAN) to enable slicing and resource management through user...

https://arxiv.org/abs/2610.40744

7 CONF

AutoHebb: Self-Modifying Neural Networks that Zero-Shot Infer and Continually Learn

ArXiv CS.AI 50%

arXiv:2610.40757v1 Announce Type: cross Abstract: Humans and animals have a unique capacity to generalize and learn in novel circumstances, including "0-shot" inference (ZI) and continual learning (CL) -- two powerful cognitive abilities. Despite this importance, efforts to...

https://arxiv.org/abs/2610.40757

8 CONF

SUREON: A Benchmark and Vision-Language Model for Surgical Reasoning

ArXiv CS.AI 50%

arXiv:2603.06570v2 Announce Type: replace-cross Abstract: A capable surgical AI model should reason from visual evidence; yet, many existing surgical benchmarks can be partially solved without visual input, as models may exploit procedural priors or common anatomy-instrument...

https://arxiv.org/abs/2603.06570

9 CONF

A Theoretical Framework for Understanding and Building "Any-task inference" Capable Foundation Models

ArXiv CS.AI 50%

arXiv:2610.40934v1 Announce Type: cross Abstract: In this work, we provide a formal framework and mathematical definition for the subset of foundation models focused on enabling the property of "any-task inference" (ATI) (similar to zero-shot inference), rather than those...

https://arxiv.org/abs/2610.40934

0 CONF

CAMEL: Cross-Architecture Masked Embedding Learning for Ultra-Lightweight Retinal Foundation Models

ArXiv CS.AI 50%

arXiv:2610.40954v1 Announce Type: cross Abstract: Recent progress in deep learning has substantially advanced automated grading of ophthalmologic pathologies, supported by large annotated datasets and improved representation learning. However, a significant gap remains between...

https://arxiv.org/abs/2610.40954

1 CONF

ARK: Avoiding Routing Collisions for KV Cache Transfer in Disaggregated LLM Inference

ArXiv CS.AI 50%

arXiv:2610.41160v1 Announce Type: cross Abstract: Disaggregated LLM inference separates the prefill and decode phases across GPU pools, generating massive KV-cache transfers. Because these transfers last hundreds of milliseconds to seconds, they behave as mega elephant flows...

https://arxiv.org/abs/2610.41160

2 CONF

Towards Understanding Score-Seeking in LLMs

ArXiv CS.AI 50%

arXiv:2610.41014v1 Announce Type: cross Abstract: Production large language models sometimes reward-hack, exploiting flaws in how tasks are scored rather than performing the tasks as intended, sometimes in highly sophisticated and adversarial ways. We investigate the motivations...

https://arxiv.org/abs/2610.41014

3 CONF

Characterizing Recoverable Expert-Utilization Signatures in Fine-Tuned Mixture-of-Experts LLMs

ArXiv CS.AI 50%

arXiv:2610.41039v1 Announce Type: cross Abstract: As Mixture-of-Experts (MoE) large language models are increasingly deployed in distributed environments, from federated learning to edge-cloud systems, their architecture harbors an underexplored landscape of security...

https://arxiv.org/abs/2610.41039

4 CONF

Accept Changes, Reject Attacks: Robust Memory Management for LLM Agents

ArXiv CS.AI 50%

arXiv:2610.41056v1 Announce Type: cross Abstract: Since large language model (LLM) agents rely on long-term memory, what they store now shapes what they do later. A memory manager decides how each input changes this memory and which records the agent acts on. It can fail in two...

https://arxiv.org/abs/2610.41056

5 CONF

bf16 Rounding Silently Discards Most RL Policy Updates: A Hidden Training-Inference Mismatch and an Unbiased One-Line Fix

ArXiv CS.AI 50%

arXiv:2610.41073v1 Announce Type: cross Abstract: Reinforcement learning (RL) post-training of language models keeps fp32 master weights in the optimizer and serves rollouts from a bf16 copy produced by round-to-nearest conversion. At the learning rates in common use, most...

https://arxiv.org/abs/2610.41073

6 CONF

MUON-RT Reusing the Teacher's Trajectory for Momentum-Free Muon for LLM Self-Distillation

ArXiv CS.AI 50%

arXiv:2610.41104v1 Announce Type: cross Abstract: Self-distillation methods for large language models with an exponential moving average (EMA) teacher already retain a history of student updates. Muon nevertheless stores a separate momentum buffer, increasing persistent training...

https://arxiv.org/abs/2610.41104

7 CONF

When Disclosure Is Compulsory: Evaluating Ride-Hailing Rebalancing Policies with Self-Interested LLM Driver Agents

ArXiv CS.AI 50%

arXiv:2610.41132v1 Announce Type: cross Abstract: The EU Platform Work Directive, to be transposed by December 2026, requires ride-hailing platforms to state in plain language the main parameters of their automated decisions and how a worker's behaviour affects them. Such rules...

https://arxiv.org/abs/2610.41132

8 CONF

Lineage Is Memory: Parent Inheritance and Feedback Disclosure in Short-Budget LLM-Guided Optimization

ArXiv CS.AI 50%

arXiv:2610.41157v1 Announce Type: cross Abstract: Iterative language-model optimizers refine prompts and programs by evaluating a candidate, showing a proposer model a sample of failing cases, and keeping revisions that improve performance. Recent work attributes the limits of...

https://arxiv.org/abs/2610.41157

9 CONF

Coarse3D: Controllable and Faithful Sparse Structure Generation for Image-to-3D

ArXiv CS.AI 50%

arXiv:2610.41231v1 Announce Type: cross Abstract: Coarse-to-fine 3D-native generation relies heavily on the first-stage sparse structure, which determines the global orientation and overall geometry for subsequent refinement. However, existing coarse generators suffer from two...

https://arxiv.org/abs/2610.41231

0 CONF

KEEPER: Learning Control-Sufficient Textual Memory for Long-Horizon LLM Agents

ArXiv CS.AI 50%

arXiv:2610.41482v1 Announce Type: cross Abstract: Recursive textual memory can carry earlier errors into later updates, yet task performance alone does not establish memory reliability. We define self-consistency bias as the persistence of incorrect claims already present in the...

https://arxiv.org/abs/2610.41482

1 CONF

Erase the Injected Region: Multimodal Prompt-Injection Defense with On-Policy Self-Distillation

ArXiv CS.AI 50%

arXiv:2610.41307v1 Announce Type: cross Abstract: Multimodal indirect prompt injection embeds malicious instructions in external media that also contains information needed for the user's task. Existing defenses can block the attack yet impair the model's use of that...

https://arxiv.org/abs/2610.41307

2 CONF

Transferring Peptide-Target Interaction Patterns to Small Molecules by Joint Guidance for Diffusion and Flow Matching

ArXiv CS.AI 50%

arXiv:2610.41322v1 Announce Type: cross Abstract: Generating small molecules to target protein-protein interactions (PPIs) remains one of the most challenging yet high-reward frontiers in drug discovery. Unlike traditional small-molecule drugs that bind to deep, well-defined...

https://arxiv.org/abs/2610.41322

3 CONF

ProSearch: Benchmarking Multi-Constraint Protocol Retrieval in Experimental Science

ArXiv CS.AI 50%

arXiv:2610.41396v1 Announce Type: cross Abstract: In AI for Science scenarios, experimental design and method reproduction require retrieving protocols that satisfy multiple interdependent constraints, yet existing benchmarks lack systematic evaluation of this capability. To...

https://arxiv.org/abs/2610.41396

4 CONF

When Safety Checks Become Privacy Risks: A Privacy-Preserving Paradigm for LLM Agent Safety Auditing

ArXiv CS.AI 50%

arXiv:2610.41401v1 Announce Type: cross Abstract: Large language model agents interact with online services through tool calls that may access private data or perform sensitive actions. Specialized providers can supply and maintain pre-execution safety auditing capabilities for...

https://arxiv.org/abs/2610.41401

5 CONF

BlindToChange: AI Agents Can Find Changes When Asked But Do They Look When Needed?

ArXiv CS.AI 50%

arXiv:2610.41435v1 Announce Type: cross Abstract: Given that AI agents can search the web broadly and deeply in real time, it is tempting to conclude that their outputs account for recent world events. We show that this conclusion does not hold in practice. While agents can...

https://arxiv.org/abs/2610.41435

6 CONF

Sparse Text Diffusion under Dual Budgets: Context Connectivity and Expert Activation

ArXiv CS.AI 50%

arXiv:2610.41487v1 Announce Type: cross Abstract: Long-context diffusion repeatedly pays for both token interaction and feed-forward computation. We formulate these costs as two separate budgets: the edges available to an attention graph and the experts activated for each token....

https://arxiv.org/abs/2610.41487

7 CONF

ORION: An Outcome-Driven LLM Advisor for RL-Based Multi-Domain 6G Slice Placement

ArXiv CS.AI 50%

arXiv:2610.41563v1 Announce Type: cross Abstract: Deploying 6G network slices across administrative domains requires an online decision for each arriving request: which domain hosts each virtual network function, how traffic crosses domain boundaries, and whether the slice is...

https://arxiv.org/abs/2610.41563

8 CONF

Attention Maps Know When to Think: Training-Free Difficulty-Aware Chain-of-Thought for Reasoning Segmentation

ArXiv CS.AI 50%

arXiv:2610.41618v1 Announce Type: cross Abstract: Chain-of-Thought (CoT) prompting has become a standard reasoning strategy in Multi-modal Large Language Models (MLLMs), showing strong performance in complex vision-language tasks such as reasoning segmentation. However, our...

https://arxiv.org/abs/2610.41618

9 CONF

When Steering Shifts Discourse: Identifying and Intervening on Discourse-Level Changes due to Activation Steering in LLMs

ArXiv CS.AI 50%

arXiv:2610.41661v1 Announce Type: cross Abstract: Activation steering is an inference-time technique used to control or modify the behavior, tone, or safety properties of a large language model (LLM) without retraining the model's weights or editing its input prompt, but simply...

https://arxiv.org/abs/2610.41661

00 CONF

Simple Features Beat Most AI Control Monitors

ArXiv CS.AI 50%

arXiv:2610.41713v1 Announce Type: cross Abstract: AI control relies on monitors to catch a capable model that sabotages its work. These monitors are evaluated on their ability to differentiate honest from backdoored code. We show that on a standard evaluation dataset, simple...

https://arxiv.org/abs/2610.41713

01 CONF

Latent-Lens: Visual Perception in Small Language Models Through Latent Communication

ArXiv CS.AI 50%

arXiv:2610.41751v1 Announce Type: cross Abstract: Bridging independent vision-language models (VLMs) and small language models (SLMs) in a modular multi-agent system typically forces them to exchange information as discrete text, which creates a lossy bottleneck for spatial and...

https://arxiv.org/abs/2610.41751

02 CONF

Different Models, Shared Failures: Auditing Frozen-Encoder Pools for Medical Segmentation

ArXiv CS.AI 50%

arXiv:2610.41790v1 Announce Type: cross Abstract: Average segmentation accuracy and model count do not reveal whether models fail on the same cases. We present CoFailMed, an audit of correlated failures in pretrained-encoder pools for medical segmentation. Across five 2D tasks,...

https://arxiv.org/abs/2610.41790

03 CONF

Accurate and Auditable ECG Classification via Visibility Graph Neural Networks

ArXiv CS.AI 50%

arXiv:2610.41795v1 Announce Type: cross Abstract: Physicians read electrocardiograms (ECGs) from waveform shape and timing, yet accurate deep-learning classifiers rarely show which waveform regions drive their predictions. We introduce LYNX-ECG, a graph neural network that...

https://arxiv.org/abs/2610.41795

04 CONF

Backpropagation-free Deep Learning for Time-Series Classification

ArXiv CS.AI 50%

arXiv:2610.41805v1 Announce Type: cross Abstract: Deep neural networks for time series classification (TSC) are trained almost exclusively by error backpropagation, which imposes update locking and the weight-transport problem. Backpropagation-free learning rules such as Direct...

https://arxiv.org/abs/2610.41805

05 CONF

SimXAI: A Simple Drop-in Layer Increases Interaction Quality and Understanding in Conversational XAI

ArXiv CS.AI 50%

arXiv:2610.41856v1 Announce Type: cross Abstract: Conversational explainable AI (ConvXAI) agents often use GUS-style architectures with separate modules for intent recognition, dialogue management, and template-based response generation. While faithful to the underlying XAI...

https://arxiv.org/abs/2610.41856

06 CONF

AI evaluators favor job applications written by certain AI models, independent of candidate quality

ArXiv CS.AI 50%

arXiv:2610.41866v1 Announce Type: cross Abstract: Job applicants increasingly use large language models (LLMs) to write cover letters, while employers deploy LLMs to screen them. In this all-AI setting, we ask whether the \emph{choice of model} affects hiring outcomes...

https://arxiv.org/abs/2610.41866

07 CONF

General-purpose foundation models surpass specialized ones on chemical property prediction tasks

ArXiv CS.AI 50%

arXiv:2610.41899v1 Announce Type: cross Abstract: Foundation models (FMs) learn reusable representations from large collections of unlabeled data. In chemistry the corresponding data mainly consists of molecular structures, which are abundant, whereas experimental measurements...

https://arxiv.org/abs/2610.41899

08 CONF

Observable-Specific Validity Tests for Scientific AI: Controlled Approximations and Intervention Response

ArXiv CS.AI 50%

arXiv:2610.41939v1 Announce Type: cross Abstract: An approximation can reproduce an energy while missing its response, or satisfy an error tolerance without being certified by a given bound. We formulate observable-specific validity records for scientific artificial intelligence...

https://arxiv.org/abs/2610.41939

09 CONF

Aligning MLLMs with the Latent Structure of Human Cognition via Behavior-Derived Semantic Dimensions

ArXiv CS.AI 50%

arXiv:2610.41951v1 Announce Type: cross Abstract: Multimodal Large Language Models (MLLMs) have achieved impressive performance across a wide range of reasoning tasks, yet it remains unclear whether their internal representations and decision criteria align with the latent...

https://arxiv.org/abs/2610.41951

10 CONF

SecPO: Principled Adversarial Training for Prompt Injection Security

ArXiv CS.AI 50%

arXiv:2610.41998v1 Announce Type: cross Abstract: Recognized as a top threat to AI agents, prompt injection allows instructions from untrusted data (email, documents, websites) to manipulate the agent's operation. The existing best-defended LLM, Meta-SecAlign, is trained with...

https://arxiv.org/abs/2610.41998

11 CONF

AutoAnalysis: An automated, self-updating meta-analysis of human-AI collaboration

ArXiv CS.AI 50%

arXiv:2610.42001v1 Announce Type: cross Abstract: As generative artificial intelligence (AI) becomes more capable and widely used, understanding when and how humans should work with these systems is becoming increasingly important. However, the empirical evidence in this space...

https://arxiv.org/abs/2610.42001

12 CONF

Know When the Equation Is Wrong: Structural Uncertainty for LLM-Guided Symbolic Regression under Extrapolation

ArXiv CS.AI 50%

arXiv:2610.42024v1 Announce Type: cross Abstract: Large language models (LLMs) can help discover mathematical equations from data, but most LLM-guided symbolic regression methods focus on a single best equation without quantifying uncertainty over alternative functional forms....

https://arxiv.org/abs/2610.42024

13 CONF

There Is No Free Loop: When Does Looping a Trained Model Pay for Its Inference Compute?

ArXiv CS.AI 50%

arXiv:2610.42030v1 Announce Type: cross Abstract: Looping re-applies a block of layers so that each token passes through the block more than once. Adding a loop to a trained model is attractive because it leaves the parameter count, and hence the disk size, the memory footprint...

https://arxiv.org/abs/2610.42030

14 CONF

CRoS: Causality Reward on Scrambled CoTs Improves Accuracy and Reasoning Faithfulness

ArXiv CS.AI 50%

arXiv:2610.42054v1 Announce Type: cross Abstract: Reinforcement learning with verifiable rewards (RLVR) has become the standard method for training language models to reason. However, RLVR typically relies solely on outcome correctness, which does not guarantee that the CoT...

https://arxiv.org/abs/2610.42054

15 CONF

Teaching Large Language Models When Not to Know: Learning Temporal Critique for Ex-Ante Reasoning

ArXiv CS.AI 50%

arXiv:2605.14636v2 Announce Type: replace Abstract: Large language models (LLMs) often fail to reason under temporal cutoffs: when prompted to answer from the standpoint of an earlier time, they exploit knowledge that became available only later. We study this failure through...

https://arxiv.org/abs/2605.14636

16 CONF

Fine-Tuning VLM for Enhancing AI's Spatial Intelligence: Understanding 3D and 2D Rotations

ArXiv CS.AI 50%

arXiv:2610.04206v3 Announce Type: replace Abstract: Spatial intelligence is a fundamental skill in multiple domains, such as Science, Technology, Engineering, and Mathematics (STEM), Medicine, Architecture, and Construction. Recent studies indicate that Vision-Language Models...

https://arxiv.org/abs/2610.04206

17 CONF

From Stages to States: Unified Iterative Reasoning for MLLMs

ArXiv CS.AI 50%

arXiv:2610.15620v2 Announce Type: replace Abstract: Multimodal Chain-of-Thought (MCoT) substantially enhances the complex reasoning capabilities of Multimodal Large Language Models (MLLMs) by explicitly modeling intermediate reasoning processes. However, most learning-based MCoT...

https://arxiv.org/abs/2610.15620

18 CONF

WeFair: Fidelity-Aware Alignment from Human Feedback for Personalized Query Rewriting in Short-Video Search

ArXiv CS.AI 50%

arXiv:2610.16927v2 Announce Type: replace Abstract: Short-video search needs compact query rewriters that recover users' personalized intent from ambiguous queries under strict latency constraints. Existing LLM-based methods have improved rewriting by using synthetic reasoning...

https://arxiv.org/abs/2610.16927

19 CONF

SpectRAG: Weighted Chunk Graphs for Token-Budgeted Context Selection in Multi-Hop Retrieval-Augmented Generation

ArXiv CS.AI 50%

arXiv:2610.36991v3 Announce Type: replace Abstract: Retrieval-augmented generation (RAG) systems ground large language models (LLMs) by retrieving external evidence and conditioning generation on the retrieved context. Although dense retrieval is effective for local semantic...

https://arxiv.org/abs/2610.36991

20 CONF

MoLRSI: A Recursive Self-Improving AI agent for Molecular Discovery

ArXiv CS.AI 50%

arXiv:2610.39714v2 Announce Type: replace Abstract: Molecular discovery requires navigating vast combinatorial search spaces while balancing competing biological objectives. AI agents can automate expert-defined molecular design protocols, but automation alone does not address...

https://arxiv.org/abs/2610.39714

21 CONF

Integrating AI for Human-Centric Breast Cancer Diagnostics: A Multi-Scale and Multi-View Swin Transformer Framework

ArXiv CS.AI 50%

arXiv:2503.13309v3 Announce Type: replace-cross Abstract: Despite advancements in Computer-Aided Diagnosis (CAD) systems, breast cancer remains one of the leading causes of cancer-related deaths among women worldwide. Recent breakthroughs in Artificial Intelligence (AI) have...

https://arxiv.org/abs/2503.13309

22 CONF

Beyond Public Access in LLM Pre-Training Data

ArXiv CS.AI 50%

arXiv:2505.00020v3 Announce Type: replace-cross Abstract: Using a legally obtained dataset of 34 copyrighted O'Reilly Media books (13,962 paragraphs), we apply the DE-COP membership inference attack to test whether OpenAI models show recognition of non-public (pay-walled)...

https://arxiv.org/abs/2505.00020

23 CONF

LLINBO: Trustworthy LLM-in-the-Loop Bayesian Optimization

ArXiv CS.AI 50%

arXiv:2505.14756v3 Announce Type: replace-cross Abstract: Bayesian optimization (BO) is a sequential decision-making tool widely used for optimizing expensive black-box functions. Recently, Large Language Models (LLMs) have shown remarkable adaptability in low-data regimes,...

https://arxiv.org/abs/2505.14756

24 CONF

On the Faithfulness of Visual Thinking: Measurement and Enhancement

ArXiv CS.AI 50%

arXiv:2510.23482v2 Announce Type: replace-cross Abstract: Recent large vision-language models (LVLMs) can generate vision-text multimodal chain-of-thought (MCoT) traces after reinforcement fine-tuning (RFT). However, we observe that the visual information in MCoT is often...

https://arxiv.org/abs/2510.23482

25 CONF

DiTGaze: Geometry-Conditioned Diffusion Augmentation for Few-Shot Gaze Estimation

ArXiv CS.AI 50%

arXiv:2511.11231v2 Announce Type: replace-cross Abstract: Accurate person-specific gaze estimation benefits from labeled user data, but collecting images that densely cover gaze directions is burdensome. We present DiTGaze, a calibration-efficient augmentation system that...

https://arxiv.org/abs/2511.11231

26 CONF

Eroding the Truth-Default: A Causal Analysis of Human Susceptibility to Foundation Model Hallucinations and Disinformation in the Wild

ArXiv CS.AI 50%

arXiv:2601.22871v3 Announce Type: replace-cross Abstract: As foundation models (FMs) approach human-level fluency, distinguishing synthetic from organic content has become a key challenge for Trustworthy Web Intelligence. This paper presents JudgeGPT and RogueGPT, a dual-axis...

https://arxiv.org/abs/2601.22871

27 CONF

Beyond IID: How General Are Tabular Foundation Models, Really?

ArXiv CS.AI 50%

arXiv:2606.30410v2 Announce Type: replace-cross Abstract: Foundation models for predictive machine learning on tabular data have recently gained significant traction in academia and industry. Research communities across disciplines are increasingly evaluating tabular foundation...

https://arxiv.org/abs/2606.30410

28 CONF

What Does a Harness Repair? Three Preregistered Studies Around a Longevity-Tuned Language Model

ArXiv CS.AI 50%

arXiv:2610.05533v3 Announce Type: replace-cross Abstract: A harness search around a frozen longevity-tuned 1.7B model reported a rescue. An audit found that the gain came from rows the start left unparsed, that the caller sent each row's reference answer as an assistant turn,...

https://arxiv.org/abs/2610.05533

29 CONF

Self-improving data synthesis can scale embedding-model adaptation across domains and tasks

ArXiv CS.AI 50%

arXiv:2610.14730v3 Announce Type: replace-cross Abstract: AI agents require specialised retrieval across domains and tasks, but adapting embedding models is constrained by costly manual training-data design. Here we introduce SYNTRA, a self-improving agentic data synthesis...

https://arxiv.org/abs/2610.14730

30 CONF

DeFT-RAG: Decomposing Multi-Hop Questions into Self-Contained Sub-Questions with Reusable Answers

ArXiv CS.AI 50%

arXiv:2610.37826v2 Announce Type: replace-cross Abstract: Retrieval-augmented generation (RAG) lets a large language model (LLM) answer questions by retrieving relevant passages from a large corpus. However, RAG struggles with multi-hop questions, which require chaining facts...

https://arxiv.org/abs/2610.37826

31 CONF

Turing LLM Post-Training: Calibrated Distillation and Efficient Dynamic-MoE Execution

ArXiv CS.AI 50%

arXiv:2610.39876v2 Announce Type: replace-cross Abstract: We study post-training for dynamically routed mixture-of-experts (MoE) models, focusing on integrating independently optimized specialists while keeping consolidation efficient. Our approach combines calibrated...

https://arxiv.org/abs/2610.39876